

Page 1 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

# **Liquimate 7700 Mini Kartusche**

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive

## **Uses advised against:**

No information available at present.

# 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### 1.4 Emergency telephone number

# Emergency information services / official advisory body:

---

### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

# **SECTION 2: Hazards identification**

**Hazard statement** 

### 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard category

Acute Tox.	4	H302-Harmful if swallowed.
Skin Irrit.	2	H315-Causes skin irritation.

Eye Dam. 1 H318-Causes serious eye damage.

Skin Sens. 1 H317-May cause an allergic skin reaction.

Aquatic Chronic 3 H412-Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

Hazard class

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016 Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche



H302-Harmful if swallowed. H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P501-Dispose of contents / container to an approved waste disposal facility.

Glycerine propoxylate

4,4'-methylenebis(cyclohexylamine)

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

# n.a. 3.2 Mixtures

Polyether polyol	
Registration number (REACH)	01-2119471485-32-XXXX
Index	
EINECS, ELINCS, NLP	500-035-6 (NLP)
CAS	25214-63-5
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319

Glycerine propoxylate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	25791-96-2
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302

4,4'-methylenebis(cyclohexylamine)	
Registration number (REACH)	01-2119541673-38-XXXX
Index	
EINECS, ELINCS, NLP	217-168-8
CAS	1761-71-3
content %	1-<5
content %	1-<5



Page 3 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Corr. 1A. H314
	Aquatic Chronic 2, H411
	STOT RE 2, H373 (oral) Skin Sens. 1, H317
	Eye Dam. 1, H318

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP	220-449-8
CAS	2768-02-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Acute Tox. 4, H332
	Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

# Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Adapt to the nature and extent of fire.

### Unsuitable extinguishing media

None known

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

# 5.3 Advice for firefighters



Page 4 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

# 7.1.1 General recommendations

Avoid inhalation of the vapours.

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store in a well-ventilated place.

Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Polyether polyol						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,085	mg/l	
	Environment - marine		PNEC	0,0085	mg/l	



Page 5 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

	Environment - sporadic		PNEC	1,51	mg/l
	(intermittent) release Environment - sewage		PNEC	70	mg/l
	treatment plant		INLO	10	mg/i
	Environment - sediment, freshwater		PNEC	0,193	mg/kg dw
	Environment - sediment, marine		PNEC	0,0193	mg/kg dw
	Environment - soil		PNEC	0,0193	mg/kg dw
Consumer	Human - oral	Long term, systemic effects	DNEL	8,3	mg/kg bw/d
Consumer	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/d
Consumer	Human - inhalation	Long term, systemic effects	DNEL	29	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13,9	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entspreche ndes Silantriol (Hydrolysp odukt) ermittelt.
	Environment - marine		PNEC	0,04	mg/l	Für entspreche ndes Silantriol (Hydrolysp odukt) ermittelt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entspreche ndes Silantriol (Hydrolysp odukt) ermittelt.
	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprech ndes Silantriol (Hydrolysp odukt) ermittelt.
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprech ndes Silantriol (Hydrolysp odukt) ermittelt.



(B)

Page 6 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - soil		PNEC	0,06	mg/kg dw	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - marine		PNEC	0,0018	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - water		PNEC	0,18	mg/l	PNEC- Interval
	Environment - sediment, freshwater		PNEC	0,16	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,016	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	0,18	mg/l	
	Environment - soil		PNEC	0,09	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	5	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	8,3	mg/m3	

# 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.



Page 7 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves made of butyl (EN 374).

Protective gloves made of chloroprene (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Water solubility:

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

# 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

Not miscible

# 9.1 Information on basic physical and chemical properties

Physical state: Liauid

Colour: Black

Odour: Slightly, Characteristic

Odour threshold: Not determined pH-value: Not determined

Melting point/freezing point: Not determined

Initial boiling point and boiling range: Not determined

Flash point: >150 °C

Evaporation rate: Not determined Flammability (solid, gas): Not determined

Lower explosive limit: Not determined

Upper explosive limit: Not determined

Vapour pressure: Not determined

Vapour density (air = 1): Not determined Density: 1,02 g/cm3 (23°C)

Bulk density: Not determined Solubility(ies): Not determined

Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: >300 °C (Ignition temperature)



Page 8 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Explosive properties:

Not determined
1800 mPas (23°C)
Product is not explosive.

9.2 Other information

Oxidising properties:

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

# 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

None known

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis. Avoid contact with strong acids.

# 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1501,5	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value,
						Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value,
						Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.



Page 9 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Other information:			Classification
			according to
			calculation
			procedure.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	933-1072	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	Analogous
• •					Dermal Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Analogous
					Dermal	conclusion, Not
					Irritation/Corrosion)	irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
, ,					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Analogous
-					Irritation/Corrosion)	conclusion, Not
						irritant
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	(Analogous
						conclusion),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	No indications of
				typhimurium	Reverse Mutation Test)	such an effect.,
						Analogous
						conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro	Negative,
					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Analogous
					Mammalian	conclusion,
					Chromosome	Negative
					Aberration Test)	
Reproductive toxicity	NOAEL	1000	mg/kg	Rat	OECD 421	Analogous
(Developmental toxicity):					(Reproduction/Developm	conclusion,
					ental Toxicity Screening	Female
					Test)	
Reproductive toxicity (Effects	NOAEL	1000	mg/kg	Rat	OECD 421	Analogous
on fertility):					(Reproduction/Developm	conclusion
					ental Toxicity Screening	
					Test)	



Page 10 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Specific target organ toxicity -	NOAEL	1000	mg/kg	Rat	OECD 407 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose 28-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	

4,4'-methylenebis(cyclohexyla	4,4'-methylenebis(cyclohexylamine)											
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes						
Acute toxicity, by oral route:	LD50	625	mg/kg	Rat								
Acute toxicity, by dermal route:	LD50	2110	mg/kg	Rabbit								
Skin corrosion/irritation:						Intensively irritant						
Serious eye damage/irritation:						Intensively irritant						
Symptoms:						cramps,						
						paralysis,						
						trembling						

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Vapours
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visua disturbances

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Liquimate 7700 Mini Kart	tusche						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-				_		n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							



Page 11 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015 Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Polyether polyol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4600	mg/l	Leuciscus idus	DIN 38412 T.15	
12.1. Toxicity to fish:	LC50	96h	4870	mg/l	Brachydanio rerio	DIN 38412 T.15	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	ErC50	72h	150,67	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:		21d	9	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		<100				
Toxicity to bacteria:	NOEC/NOEL	3h	700	mg/l	activated sludge	ISO 8192	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l		Regulation (EC)	
•						440/2008 C.1	
						(ACUTE	
						TOXICITY FOR	
						FISH)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Leuciscus idus	OECD 203 (Fish,	Analogous
•						Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l		OEĆD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l		OECD 211	
, ,						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=10	mg/l	Daphnia magna	OECD 211	Analogous
					'	(Daphnia magna	conclusion
						Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	LC50	72h	>1000	mg/l		84/449/EEC C.3	
12.1. Toxicity to algae:	ErC50	72h	>100	mg/l	Desmodesmus	OECD 201 (Alga,	Analogous
					subspicatus	Growth Inhibition	conclusion
					,	Test)	
12.2. Persistence and		28d	1,9	%		OECD 301 A	
degradability:						(Ready	
- ·						Biodegradability -	
						DOC Die-Away	
						Test)	



Page 12 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

12.2. Persistence and degradability:		28d	40	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.2. Persistence and degradability:						·	Not readily biodegradable
Toxicity to bacteria:	EC10	3h	>10000	mg/l	activated sludge	Regulation (EC) 440/2008 C.11 (BIODEGRADATI ON - ACTIVATED SLUDGE RESPIRATION INHIBITION)	Analogous conclusion

4,4'-methylenebis(cyclohexylamine)												
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes					
12.1. Toxicity to fish:	LC50	96h	46-100	mg/l	Leuciscus idus							
12.1. Toxicity to daphnia:	EC50	48h	6,84	mg/l	Daphnia magna							
12.1. Toxicity to algae:	EC50	72h	140-200	mg/l								
12.2. Persistence and							Not					
degradability:							biodegradable					

Trimethoxyvinylsilane											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus	OECD 203 (Fish,					
-					mykiss	Acute Toxicity					
						Test)					
12.2. Persistence and		28d	51	%		OECD 301 F	Readily				
degradability:						(Ready	biodegradable				
						Biodegradability -					
						Manometric					
						Respirometry Test)					

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

# For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

# **SECTION 14: Transport information**

### **General statements**

14.1. UN number:

n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:



(GB)-

Page 13 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards:

Not applicable

**Transport by air (IATA)** 

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:
n.a.

14.5. Environmental hazards: Not applicable

# 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

~ 62 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

Revised sections:

2, 15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used		
(EC) No. 1272/2008 (CLP)			
Acute Tox. 4, H302	Classification according to calculation procedure.		
Skin Irrit. 2, H315	Classification according to calculation procedure.		
Eye Dam. 1, H318	Classification according to calculation procedure.		
Skin Sens. 1, H317	Classification according to calculation procedure.		
Aquatic Chronic 3, H412	Classification according to calculation procedure.		

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H226 Flammable liquid and vapour.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H317 May cause an allergic skin reaction.



Page 14 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

H302 Harmful if swallowed.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - oral

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Eye Irrit. — Eye irritation Skin Corr. — Skin corrosion

Skin Corr. — Skin corrosion STOT RE — Specific target organ toxicity - repeated exposure

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

# Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities



Page 15 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

# Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.



Page 16 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0016

Replacing version dated / version: 26.03.2018 / 0015

Valid from: 11.03.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

# Liquimate 7700 Mini Kartusche

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive

## **Uses advised against:**

No information available at present.

### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### 1.4 Emergency telephone number

# Emergency information services / official advisory body:

---

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or
		breathing difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
STOT RE	2	H373-May cause damage to organs through prolonged
		or repeated exposure by inhalation (respiratory system).

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 17 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche



H332-Harmful if inhaled. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH204-Contains isocyanates. May produce an allergic reaction.

Diphenylmethanediisocyanate, isomeres and homologues

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

2,2'-methylenediphenyl diisocyanate

# 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

# n.a. **3.2 Mixtures**

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	9016-87-9
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373 (respiratory system) (as inhalation)

4,4'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119457014-47-XXXX



Page 18 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Index	615-005-00-9
EINECS, ELINCS, NLP	202-966-0
CAS	101-68-8
content %	10-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373 (respiratory system) (as inhalation)

o-(p-isocyanatobenzyl)phenyl isocyanate	
Registration number (REACH)	01-2119480143-45-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP	227-534-9
CAS	5873-54-1
content %	1-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373 (respiratory system) (as inhalation)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
Registration number (REACH)	01-2119513212-58-XXXX
Index	
EINECS, ELINCS, NLP	219-784-2
CAS	2530-83-8
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318

2,2'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119927323-43-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP	219-799-4
CAS	2536-05-2
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373 (respiratory system) (as inhalation)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!



Page 19 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

# 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

## 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

# 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Allow to stand for a few days in an unclosed container until reaction no longer occurs. Keep moist.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**



(GB)-

Page 20 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect from direct sunlight and warming.

Store in a well-ventilated place.

Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Chemical Name Diphenylmethanediisocyanate, isomeres and homologues Content %:30-					
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) WEL-STEL: 0	all (as -NCO)) WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))				
Monitoring procedures:					
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the	e end of the Other information: Sen (Isocyanates, all (as -				
period of exposure)	NCO))				
Chemical Name 4,4'-methylenediphenyl diisocyanate	Content %:10-30				
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) WEL-STEL: 0	0,07 mg/m3 (Isocyanates, all (as -NCO))				
Monitoring procedures: ISO 16702 (Workp	place air quality – determination of total isocyanate groups in air using				
	ylpiperazine and liquid chromatography) - 2007				
MDHS 25/4 (Organ	nic isocyanates in air – Laboratory method using sampling either onto				
	ylpiperazine coated glass fibre filters followed by solvent desorption				
	and analysis using high performance liquid chromatography) - 2015 -				
	N/ENTR/000/2002-16 card 7-4 (2004)				
,	CYANATES, MONOMERIC) - 1994				
	CYANATES) - 1998				
- NIOSH 5525 (ISOCYANATES, TOTAL (MAP)) - 2003					
- OSHA 18 (Diisocyanates 2,4-TDI and MDI) - 1980					
	ene Bisphenyl Isocyanate (MDI)) - 1984				
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the	` ` ` ` `				
period of exposure)	NCO))				
Chemical Name o-(p-isocyanatobenzyl)phenyl isocya	nate Content %:1-20				
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) WEL-STEL: 0	0,07 mg/m3 (Isocyanates, all (as -NCO))				
Monitoring procedures:					
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the	e end of the Other information: Sen (Isocyanates, all (as -				
period of exposure)	NCO))				
Chemical Name 2,2'-methylenediphenyl diisocyanate	Content %:0,1-<1				
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) WEL-STEL: 0	0,07 mg/m3 (Isocyanates, all (as -NCO))				
Monitoring procedures:					



③B)·

Page 21 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the Other information: Sen (Isocyanates, all (as period of exposure) NCO))

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	

Area of application	henyl isocyanate Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental				J	
	compartment					
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage		PNEC	1	mg/l	
	treatment plant					
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sporadic		PNEC	10	mg/l	
	(intermittent) release					
Consumer	Human - oral	Short term, systemic	DNEL	20	mg/kg	
		effects			bw/day	
Consumer	Human - dermal	Short term, local	DNEL	17,2	mg/cm2	
		effects				
Consumer	Human - dermal	Short term, systemic	DNEL	25	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Short term, local	DNEL	0,05	mg/m3	
		effects				
Consumer	Human - inhalation	Short term, systemic	DNEL	0,05	mg/m3	-
		effects				
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	



Page 22 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sediment		PNEC	0,79	mg/kg dry weight	
	Environment - soil		PNEC	0,13	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	12,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	43,5	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,5	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	147	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	21	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	147	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	21	mg/kg bw/day	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
лись старриського	Environmental compartment		230311,		J	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	



(B)

Page 23 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Consumer	Human - inhalation	Long term, systemic	DNEL	0,025	mg/m3	
		effects				
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local	DNEL	28,7	mg/cm2	
		effects				
Workers / employees	Human - dermal	Short term, systemic	DNEL	50	mg/kg bw/d	
		effects				
Workers / employees	Human - inhalation	Short term, local	DNEL	0,1	mg/m3	
		effects				
Workers / employees	Human - inhalation	Short term, systemic	DNEL	0,1	mg/m3	
, ,		effects				
Workers / employees	Human - inhalation	Long term, systemic	DNEL	0.05	mg/m3	
. ,		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0.05	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW =
  "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

### 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves made of butyl (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,4

With short-term contact:

Permeation time (penetration time) in minutes:

> 120

With long-term contact:

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.



Page 24 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Brown

Odour: Slightly, Characteristic

Odour threshold:

pH-value:

Mot determined

Not determined

Not determined

Not determined

Not determined

Initial boiling point:

Initial boiling point and boiling range:

Flash point:

Evaporation rate:

Not determined
>300 °C
>200 °C

Not determined

Flammability (solid, gas): n.a.

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Density:

Not determined

Not determined

Not determined

1.16 g/cm3 (23°C)

Density: 1,16 g/cm3 (23°C)
Bulk density: n.a.
Solubility(ies): Not determined
Water solubility: Not miscible

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Not determined
400 °C (Ignition temperature)

Auto-ignition temperature: No

Decomposition temperature:

Viscosity:

Explosive properties:

Not determined
500 mPas (23°C)
Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

Not determined

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity



Page 25 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

# The product has not been tested. **10.2 Chemical stability**

Stable with proper storage and handling.

# 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

# 10.4 Conditions to avoid

See also section 7. Strong heat Moisture

# 10.5 Incompatible materials

See also section 7.

Water

Alcohols

Amines

Bases

Acids

Developement of:

Carbon dioxide

CO2 formation in closed tanks causes pressure to rise.

Pressure increase will result in danger of bursting.

# 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Liquimate 7700 Mini Kartusche	}					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	14,95	mg/l/4h			calculated value,
						Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification
						according to
						calculation
						procedure.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	0,31	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.	



Page 26 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Expert judgement.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact
Respiratory or skin sensitisation:				Rat		Yes (inhalation)
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Limited evidence of a carcinogenic effect.
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Aspiration hazard:						Negative
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, May cause respiratory irritation.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

4,4'-methylenediphenyl diisocyanate							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion	
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol, Expert judgement.	
Acute toxicity, by inhalation:	LC50	0,368	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.	



Page 27 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	,	Yes (inhalation)
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo Mammalian Alkaline Comet Assay)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Limited evidence of a carcinogenic effect., Aerosol, Analogous conclusion
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

o-(p-isocyanatobenzyl)phenyl isocyanate								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion		
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion		
Acute toxicity, by inhalation:	LC50	0,387	mg/l/4h	Rat		Aerosol, Does not conform with EU classification.		
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol, Expert judgement.		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2, Analogous conclusion		
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.		



(B)

Page 28 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion, Limited evidence of a carcinogenic effect.
Reproductive toxicity:	NOAEL	4	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Symptoms:						mucous membrane irritation, breathing difficulties, coughing, asthmatic symptoms
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	8025	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	5,3	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1



(B)

Page 29 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Respiratory or skin				Guinea pig	OECD 406 (Skin	Negative
sensitisation:					Sensitisation)	
Carcinogenicity:	NOAEL	>11,1	mg/kg	Mouse		Negative
Reproductive toxicity:		1500	mg/kg/d			
Aspiration hazard:						No
Symptoms:						acidosis, drop in blood pressure, vomiting, headaches, cramps, dizziness, visual disturbances, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,225	mg/kg	Rat	OECD 412 (Subacute Inhalation Toxicity - 28- Day Study)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation) Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Limited evidence of a carcinogenial effect., Analogous conclusion, Aerosol
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect., Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion



Page 30 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

C. manta man			
Symptoms:			respiratory
			distress,
			coughing,
			mucous
			membrane
			irritation
Specific target organ toxicity -			May cause
single exposure (STOT-SE),			respiratory
inhalative:			irritation.
Specific target organ toxicity -			Target organ(s):
repeated exposure (STOT-RE),			respiratory
inhalat.:			system

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Liquimate 7700 Mini Kar	tusche						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	OECD 208	
						(Terrestrial Plants,	
						Growth Test)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish,	
						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus	OECD 201 (Alga,	
					subspicatus	Growth Inhibition	
						Test)	



Page 31 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, According to experience available to date, polycarbamide is inert and non- degradable., With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide).
12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus carpio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.5. Results of PBT and vPvB assessment						,	Negative
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	
Toxicity to annelids:	NOEC/NOEL	14d	>1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	

4,4'-methylenediphenyl diisocyanate										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
Other information:	H (Henry)		0,0229							
Other information:							According to experience available to date, polycarbamide is inert and non-degradable., With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide).			
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion			



Page 32 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and nondegradable.
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		5,22			,	A notable biological accumulation potential has to be expected (LogPow > 3).
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.3. Bioaccumulative potential: 12.5. Results of PBT and vPvB assessment	BCF	28d	200		Cyprinus caprio	IUCLID Chem. Data Sheet (ESIS)	Not to be expected No PBT substance, No
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	vPvB substance Analogous conclusion
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Toxicity to annelids:	NOEC/NOEL	14d	> 1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

o-(p-isocyanatobenzyl)p	henyl isocyanate	)					
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



B.

Page 33 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through	Not to be expected, Analogous
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	Fish Test) OECD 208 (Terrestrial Plants, Growth Test)	conclusion Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other information: 12.5. Results of PBT and vPvB assessment	H (Henry)		0,0229				No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:	ECEO	28d	0	% mg/l	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, Analogous conclusion, According to experience available to dat polycarbamide inert and non-degradable., With water at the interface, transforms slowly with formation of CO2 into a firm insoluble reaction produce with a high melting point (polycarbamide Analogous).
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Toxicity to annelids:	NOEC/NOEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

# [3-(2,3-epoxypropoxy)propyl]trimethoxysilane



Page 34 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011 Valid from: 22.02.2019

PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	237	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	324	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	7d	119	mg/l	Anabaena flos- aquae	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	NOEC/NOEL	7d	<50	mg/l	Anabaena flos- aquae	U.S. EPA ECOTOX Database	
12.2. Persistence and degradability:		28d	37	%	activated sludge	Regulation (EC) 440/2008 C.4-A (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - DOC DIE- AWAY TEST)	Not readily biodegradable
12.2. Persistence and degradability:	DOC	28d	37	%		Regulation (EC) 440/2008 C.4-A (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - DOC DIE- AWAY TEST)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,5				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish,	Analogous
					-	Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Scenedesmus	OECD 201 (Alga,	Analogous
					subspicatus	Growth Inhibition	conclusion
						Test)	



Œ

Page 35 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

				1			
12.2. Persistence and		28d	0	%		OECD 302 C	With water at the
degradability:						(Inherent	interface,
						Biodegradability -	transforms
						Modified MITI	slowly with
						Test (II))	formation of
							CO2 into a firm,
							insoluble
							reaction product
							with a high
							melting point
							(polycarbamide).,
							According to
							experience
							available to date,
							polycarbamide is
							inert and non-
							degradable.,
							Analogous
							conclusion
12.3. Bioaccumulative	Log Pow		5,22				A notable
potential:							biological
							accumulation
							potential has to
							be expected
							(LogPow > 3).
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209	Analogous
						(Activated Sludge,	conclusion
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

# For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

# For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

# **SECTION 14: Transport information**

#### **General statements**

14.1. UN number:

n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:



-(GB)-

Page 36 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:
n.a.

14.5. Environmental hazards: Not applicable

# 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Revised sections:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Diphenylmethanediisocyanate, isomeres and homologues

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

2,2'-methylenediphenyl diisocyanate

 $Comply \ with \ national \ regulations/laws \ governing \ maternity \ protection \ (national \ implementation \ of \ the \ Directive \ 92/85/EEC)!$ 

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

2, 3, 8, 11, 12, 16

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.



Page 37 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure by inhalation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

STOT RE — Specific target organ toxicity - repeated exposure

Eye Dam. — Serious eye damage

# Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general



Page 38 of 38

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 21.08.2015 / 0011

Valid from: 22.02.2019 PDF print date: 02.03.2021 Liquimate 7700 Mini Kartusche

Globally Harmonized System of Classification and Labelling of Chemicals

**GWP** Global warming potential

IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive

**IUCLID International Uniform Chemical Information Database** IUPAC International Union for Pure Applied Chemistry Lethal Concentration to 50 % of a test population

Lethal Dose to 50% of a test population (Median Lethal Dose) LD50

LQ Limited Quantities

**MARPOL** International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PF Polyethylene

PNEC Predicted No Effect Concentration

parts per million mag **PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No.

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Tel. Telephone

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to quarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by

# Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.