

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Liquimate 7700 Mini Kartusche

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H302-Harmful if swallowed.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche



Danger

H302-Harmful if swallowed. H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P501-Dispose of contents / container to an approved waste disposal facility.

Glycerine propoxylate
 Trimethoxyvinylsilane
 4,4'-methylenebis(cyclohexylamine)

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Polyether polyol	
Registration number (REACH)	01-2119471485-32-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	500-035-6
CAS	25214-63-5
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Irrit. 2, H319
Glycerine propoxylate	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	25791-96-2
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
4,4'-methylenebis(cyclohexylamine)	
Registration number (REACH)	01-2119541673-38-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	217-168-8
CAS	1761-71-3
content %	1-<5

Page 3 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Skin Corr. 1A, H314 Aquatic Chronic 2, H411 STOT RE 2, H373 (oral) Skin Sens. 1, H317 Eye Dam. 1, H318
Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	220-449-8
CAS	2768-02-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
 Oxides of nitrogen
 Toxic gases

5.3 Advice for firefighters

GB

Page 4 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

In case of fire and/or explosion do not breathe fumes.
 Protective respirator with independent air supply.
 Full protection, if necessary.
 Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
 Avoid inhalation, and contact with eyes or skin.
 If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
 Resolve leaks if this possible without risk.
 Prevent from entering drainage system.
 Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid inhalation of the vapours.
 Ensure good ventilation.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Store in a well-ventilated place.
 Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Methanol	Content %:
WEL-TWA: 200 ppm (266 mg/m ³) (WEL), 200 ppm (260 mg/m ³) (EU)	WEL-STEL: 250 ppm (333 mg/m ³) (WEL)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Alcohol 25/a Methanol (81 01 631) - Compur - KITA-119 SA (549 640) - Compur - KITA-119 U (549 657) - DFG Meth. Nr. 6 (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 2013, - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004) 	

Page 5 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

- NIOSH 2000 (METHANOL) - 1998
- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016
- Draeger - Alcohol 100/a (CH 29 701)

BMGV: ---

Other information: Sk (WEL, EU)

Polyether polyol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,085	mg/l	
	Environment - marine		PNEC	0,0085	mg/l	
	Environment - sporadic (intermittent) release		PNEC	1,51	mg/l	
	Environment - sewage treatment plant		PNEC	70	mg/l	
	Environment - sediment, freshwater		PNEC	0,193	mg/kg dw	
	Environment - sediment, marine		PNEC	0,0193	mg/kg dw	
	Environment - soil		PNEC	0,0193	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	8,3	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	29	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13,9	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m ³	

Trimethoxyvinylsilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - marine		PNEC	0,04	mg/l	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.

Page 6 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - soil		PNEC	0,06	mg/kg dw	Für entsprechendes Silantriol (Hydrolyspr odukt) ermittelt.
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m ³	

Reaction mass of dimethyl adipate and dimethyl glutarate and dimethyl succinate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - marine		PNEC	0,0018	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - water		PNEC	0,18	mg/l	PNEC-Interval
	Environment - sediment, freshwater		PNEC	0,16	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,016	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	0,18	mg/l	
	Environment - soil		PNEC	0,09	mg/kg	

Page 7 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Consumer	Human - inhalation	Long term, local effects	DNEL	5	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	8,3	mg/m ³	

Methanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	50	mg/m ³	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m ³	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m ³	

CE WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause

Page 8 of 42
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0017
Replacing version dated / version: 11.03.2019 / 0016
Valid from: 10.03.2021
PDF print date: 15.06.2021
Liquimate 7700 Mini Kartusche

sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves made of butyl (EN 374).

Protective gloves made of chloroprene (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

Black

Page 9 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Odour:	Slightly, Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>150 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,02 g/cm ³ (23°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	>300 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	1800 mPas (23°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Liquimate 7700 Mini Kartusche						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1501,5	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours

Page 10 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Polyether polyol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing

Glycerine propoxylate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	933-1072	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing (Analogous conclusion), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	No indications of such an effect., Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion

Page 11 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Analogous conclusion, Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	1000	mg/kg	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Analogous conclusion, Female
Reproductive toxicity (Effects on fertility):	NOAEL	1000	mg/kg	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Analogous conclusion

4,4'-methylenebis(cyclohexylamine)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	625	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	2110	mg/kg	Rabbit		
Skin corrosion/irritation:						Intensively irritant
Serious eye damage/irritation:						Intensively irritant
Symptoms:						cramps, paralysis, trembling

Trimethoxyvinylsilane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	62,5	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	Target organ(s): bladder
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,058	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours

Polyether polyol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4600	mg/l	Leuciscus idus	DIN 38412 T.15	
12.1. Toxicity to fish:	LC50	96h	4870	mg/l	Brachydanio rerio	DIN 38412 T.15	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	ErC50	72h	150,67	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:		21d	9	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		<100				
Toxicity to bacteria:	NOEC/NOEL	3h	700	mg/l	activated sludge	ISO 8192	

Glycerine propoxylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l		Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Leuciscus idus	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l		OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	LC50	72h	>1000	mg/l		84/449/EEC C.3	
12.1. Toxicity to algae:	ErC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1,9	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	

Page 14 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.2. Persistence and degradability:		28d	40	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.2. Persistence and degradability:							Not readily biodegradable
Toxicity to bacteria:	EC10	3h	>10000	mg/l	activated sludge	Regulation (EC) 440/2008 C.11 (BIODEGRADATION - ACTIVATED SLUDGE RESPIRATION INHIBITION)	Analogous conclusion

4,4'-methylenebis(cyclohexylamine)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	46-100	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6,84	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	140-200	mg/l			
12.2. Persistence and degradability:							Not biodegradable

Trimethoxyvinylsilane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	169	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	25	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:	BOD	28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.2. Persistence and degradability:		28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Methanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 15 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		EPA-660/3-75-009
12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		Not to be expected
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		-0,77				
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

Page 16 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

14.5. Environmental hazards: Not applicable
 Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 62,49 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 11, 12, 15
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H302	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.
 H226 Flammable liquid and vapour.
 H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
 H317 May cause an allergic skin reaction.
 H302 Harmful if swallowed.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

Page 17 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0017
 Replacing version dated / version: 11.03.2019 / 0016
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

H332 Harmful if inhaled.
 H411 Toxic to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - oral
 Skin Irrit. — Skin irritation
 Eye Dam. — Serious eye damage
 Skin Sens. — Skin sensitization
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Eye Irrit. — Eye irritation
 Skin Corr. — Skin corrosion
 STOT RE — Specific target organ toxicity - repeated exposure
 Flam. Liq. — Flammable liquid
 Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available

Page 18 of 42

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.03.2021 / 0017

Replacing version dated / version: 11.03.2019 / 0016

Valid from: 10.03.2021

PDF print date: 15.06.2021

Liquimate 7700 Mini Kartusche

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Liquimate 7700 Mini Kartusche

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche



Danger

H332-Harmful if inhaled. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P201-Obtain special instructions before use. P260-Do not breathe vapours. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH204-Contains isocyanates. May produce an allergic reaction.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

As from 24 August 2023 adequate training is required before industrial or professional use.

Diphenylmethanediisocyanate, isomeres and homologues

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

2,2'-methylenediphenyl diisocyanate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	9016-87-9
content %	30-50

GB

Page 21 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
4,4'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119457014-47-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	202-966-0
CAS	101-68-8
content %	10-30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
o-(p-isocyanatobenzyl)phenyl isocyanate	
Registration number (REACH)	01-2119480143-45-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	227-534-9
CAS	5873-54-1
content %	1-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
Registration number (REACH)	01-2119513212-58-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	219-784-2
CAS	2530-83-8
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Dam. 1, H318
2,2'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119927323-43-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	219-799-4
CAS	2536-05-2
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

Page 22 of 42
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0013
Replacing version dated / version: 22.02.2019 / 0012
Valid from: 10.03.2021
PDF print date: 15.06.2021
Liquimate 7700 Mini Kartusche

The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Oxides of nitrogen
Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.

GB

Page 23 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.
 Allow to stand for a few days in an unclosed container until reaction no longer occurs.
 Keep moist.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid contact with eyes or skin.
 No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect from direct sunlight and warming.
 Store in a well-ventilated place.
 Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues		Content %:30-50
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))		

Chemical Name	4,4'-methylenediphenyl diisocyanate		Content %:10-30
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	
Monitoring procedures:	ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2007 MDHS 25/4 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 2015 - - EU project BC/CEN/ENTR/000/2002-16 card 7-4 (2004) - NIOSH 5521 (ISOCYANATES, MONOMERIC) - 1994 - NIOSH 5522 (ISOCYANATES) - 1998 - NIOSH 5525 (ISOCYANATES, TOTAL (MAP)) - 2003 - OSHA 18 (Diisocyanates 2,4-TDI and MDI) - 1980 - OSHA 47 (Methylene Bisphenyl Isocyanate (MDI)) - 1984		
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))		

Chemical Name	o-(p-isocyanatobenzyl)phenyl isocyanate		Content %:1-20

GB

Page 24 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---
Monitoring procedures: ---		
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	2,2'-methylenediphenyl diisocyanate		Content %:0,1-<1
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))		

4,4'-methylenediphenyl diisocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	

o-(p-isocyanatobenzyl)phenyl isocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	

Page 25 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sediment		PNEC	0,79	mg/kg dry weight	
	Environment - soil		PNEC	0,13	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	12,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	43,5	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,5	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	147	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	21	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	147	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	21	mg/kg bw/day	

2,2'-methylenediphenyl diisocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	

Page 26 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Page 27 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves made of butyl (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,4

With short-term contact:

Permeation time (penetration time) in minutes:

> 120

With long-term contact:

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Slightly, Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	>300 °C
Flash point:	>200 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,16 g/cm ³ (23°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	400 °C (Ignition temperature)

Page 28 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Auto-ignition temperature: No
 Decomposition temperature: Not determined
 Viscosity: 500 mPas (23°C)
 Explosive properties: Product is not explosive.
 Oxidising properties: No

9.2 Other information

Miscibility: Not determined
 Fat solubility / solvent: Not determined
 Conductivity: Not determined
 Surface tension: Not determined
 Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

Moisture

10.5 Incompatible materials

See also section 7.

Water

Alcohols

Amines

Bases

Acids

Development of:

Carbon dioxide

CO₂ formation in closed tanks causes pressure to rise.

Pressure increase will result in danger of bursting.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Liquimate 7700 Mini Kartusche						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	14,95	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.

Page 29 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Diphenylmethanediisocyanate, isomeres and homologues						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,31	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Expert judgement.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Respiratory or skin sensitisation:				Rat		Yes (inhalation)
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Limited evidence of a carcinogenic effect.
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Aspiration hazard:						Negative
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, May cause respiratory irritation.

Page 30 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive
---	--	--	--	--	--	---

4,4'-methylenediphenyl diisocyanate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol, Expert judgement.
Acute toxicity, by inhalation:	LC50	0,368	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation)
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo Mammalian Alkaline Comet Assay)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion, Carc. 2
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

o-(p-isocyanatobenzyl)phenyl isocyanate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion

Page 31 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Acute toxicity, by inhalation:	LC50	0,387	mg/l/4h	Rat		Aerosol, Does not conform with EU classification.
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol, Expert judgement.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion, Carc. 2
Reproductive toxicity:	NOAEL	4	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Symptoms:						mucous membrane irritation, breathing difficulties, coughing, asthmatic symptoms
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

Page 32 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Acute toxicity, by oral route:	LD50	8025	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	5,3	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Negative
Carcinogenicity:	NOAEL	>11,1	mg/kg	Mouse		Negative
Reproductive toxicity:		1500	mg/kg/d			
Aspiration hazard:						No
Symptoms:						acidosis, drop in blood pressure, vomiting, headaches, cramps, dizziness, visual disturbances, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,225	mg/kg	Rat	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	

2,2'-methylenediphenyl diisocyanate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	0,527	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Acute toxicity, by inhalation:	ATE	1,5	mg/l			Aerosol, Expert judgement
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Slightly irritant
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion

Page 33 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Limited evidence of a carcinogenic effect., Analogous conclusion, Aerosol
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect., Aerosol, Analogous conclusion
Symptoms:						respiratory distress, coughing, mucous membrane irritation
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,2	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Target organ(s): respiratory system, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Target organ(s): respiratory system, Analogous conclusion

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Liquimate 7700 Mini Kartusche							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 34 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, According to experience available to date, polycarbamide is inert and non-degradable., With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide).
12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus carpio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.5. Results of PBT and vPvB assessment							Negative
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	
Toxicity to annelids:	NOEC/NOEL	14d	>1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	

4,4'-methylenediphenyl diisocyanate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 35 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Other information:							According to experience available to date, polycarbamide is inert and non-degradable., With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide).
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and non-degradable., Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	IUCLID Chem. Data Sheet (ESIS)	Not to be expected

Page 36 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other information:	H (Henry)		0,0229				
Toxicity to annelids:	NOEC/NOEL	14d	> 1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

o-(p-isocyanatobenzyl)phenyl isocyanate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion

Page 37 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, Analogous conclusion, According to experience available to date, polycarbamide is inert and non-degradable., With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide).
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other information:	H (Henry)		0,0229				
Toxicity to annelids:	NOEC/NOEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	237	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	324	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	7d	119	mg/l	Anabaena flos-aquae	U.S. EPA ECOTOX Database	

Page 38 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.1. Toxicity to algae:	NOEC/NOEL	7d	<50	mg/l	Anabaena flos-aquae	U.S. EPA ECOTOX Database	
12.2. Persistence and degradability:		28d	37	%	activated sludge	Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable
12.2. Persistence and degradability:	DOC	28d	37	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,5				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2,2'-methylenediphenyl diisocyanate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	H (Henry)		0,0229				
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion

Page 39 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and non-degradable., Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected, Analogous conclusion
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Toxicity to annelids:	NOEC/NOEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Classification code: n.a.
 LQ: n.a.
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Regulation (EC) No 1907/2006, Annex XVII
 Diphenylmethanediisocyanate, isomeres and homologues
 4,4'-methylenediphenyl diisocyanate
 o-(p-isocyanatobenzyl)phenyl isocyanate
 2,2'-methylenediphenyl diisocyanate
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 15

These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Page 41 of 42
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0013
 Replacing version dated / version: 22.02.2019 / 0012
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Liquimate 7700 Mini Kartusche

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure by inhalation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

STOT RE — Specific target organ toxicity - repeated exposure

Eye Dam. — Serious eye damage

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

Page 42 of 42
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0013
Replacing version dated / version: 22.02.2019 / 0012
Valid from: 10.03.2021
PDF print date: 15.06.2021
Liquimate 7700 Mini Kartusche

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.