

Page 1 of 12  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.09.2019 / 0012  
Replacing version dated / version: 04.05.2018 / 0011  
Valid from: 11.09.2019  
PDF print date: 12.09.2019  
Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
Art.: 1182

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L**  
**Art.: 1182**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Gear lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

## Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Magnesium metaborate, Polysulfides, di-tert-Bu. May produce an allergic reaction.  
 EUH210-Safety data sheet available on request.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.  
 Endangerment of potable water possible.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>1-Decene, homopolymer, hydrogenated</b>	
<b>Registration number (REACH)</b>	01-2119486452-34-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	500-183-1 (NLP)
<b>CAS</b>	68037-01-4
<b>content %</b>	40-60
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304
<b>1-decene, trimers, hydrogenated</b>	
<b>Registration number (REACH)</b>	01-2119493949-12-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	500-393-3 (NLP)
<b>CAS</b>	157707-86-3
<b>content %</b>	40-60
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304
<b>Baseoil - unspecified *</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	---
<b>CAS</b>	---
<b>content %</b>	1-6
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304
<b>Polysulfides, di-tert-Bu</b>	<b>Substance with specific conc. limit(s) acc. to REACH-registration</b>
<b>Registration number (REACH)</b>	01-2119540515-43-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	273-103-3
<b>CAS</b>	68937-96-2
<b>content %</b>	1-5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1B, H317 Aquatic Chronic 3, H412

Page 3 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	Substance with specific conc. limit(s) acc. to REACH-registration
<b>Registration number (REACH)</b>	01-2119493620-38-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	931-384-6 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Eye Dam. 1, H318 Aquatic Chronic 2, H411 Skin Sens. 1B, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

\* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Drying of the skin.

Dermatitis (skin inflammation)

Irritation of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Page 4 of 12  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.09.2019 / 0012  
Replacing version dated / version: 04.05.2018 / 0011  
Valid from: 11.09.2019  
PDF print date: 12.09.2019  
Vollsynthetisches Hypoid Getriebeöl Truck (GL4/5) 75W-90 20 L  
Art.: 1182

CO2  
Foam  
Dry extinguisher  
Water jet spray

### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen  
Oxides of sulphur  
Flammable vapour/air mixtures

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

### **6.2 Environmental precautions**

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.  
Oil binder

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Avoid formation of oil mist.  
Ensure good ventilation.  
Do not heat to temperatures close to flash point.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Avoid long lasting or intensive contact with skin.  
Do not carry cleaning cloths soaked in product in trouser pockets.  
Observe directions on label and instructions for use.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.

GB

Page 5 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

Protect against moisture and store closed.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

GB Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Permeation time (penetration time) in minutes:

n.d.a.

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Page 6 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	210 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,87 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	106 mm <sup>2</sup> /s (40°C)
Viscosity:	15,6 mm <sup>2</sup> /s (100°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Page 7 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

No dangerous reactions are known.  
**10.4 Conditions to avoid**

See also section 7.  
 Heating, open flame, ignition sources

**10.5 Incompatible materials**

See also section 7.  
 Avoid contact with strong oxidizing agents.

**10.6 Hazardous decomposition products**

See also section 5.2  
 No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L Art.: 1182						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

1-Decene, homopolymer, hydrogenated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Aspiration hazard:						Asp. Tox. 1

1-decene, trimers, hydrogenated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing

Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin sensitisation:						Not sensitizing
Aspiration hazard:						Yes

GB

Page 8 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

**Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit		Corrosive
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

**SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

**Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

**1-Decene, homopolymer, hydrogenated**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Kow		>6,5				measured
12.1. Toxicity to algae:	LC50	72h	>1000	mg/l	Scenedesmus quadricauda		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	125	mg/l	Daphnia magna		
12.2. Persistence and degradability:		28d	2	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	

**1-decene, trimers, hydrogenated**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	125	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	



Page 9 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Mysidopsis bahia	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		>10				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	1000	mg/l	activated sludge		

**Baseoil - unspecified**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

**Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24	mg/l			
12.2. Persistence and degradability:	DOC	28d	3,6	%	activated sludge		
12.1. Toxicity to daphnia:	EC50	21d	0,66	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,12	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOEC/NOEL	96h	3,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	91,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	6,4	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	1,7	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	7,4	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

Page 10 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.09.2019 / 0012  
 Replacing version dated / version: 04.05.2018 / 0011  
 Valid from: 11.09.2019  
 PDF print date: 12.09.2019  
 Vollsynthetisches Hypoid Getriebeöl Truck (GL4/5) 75W-90 20 L  
 Art.: 1182

Toxicity to bacteria:	EC50	3h	~2433	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	----	-------	------	------------------	--	--

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

GB

Page 11 of 12  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.09.2019 / 0012  
Replacing version dated / version: 04.05.2018 / 0011  
Valid from: 11.09.2019  
PDF print date: 12.09.2019  
Vollsynthetisches Hypoid Getriebeoel Truck (GL4/5) 75W-90 20 L  
Art.: 1182

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 5 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Eye Dam. — Serious eye damage

## Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

Page 12 of 12  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.09.2019 / 0012  
Replacing version dated / version: 04.05.2018 / 0011  
Valid from: 11.09.2019  
PDF print date: 12.09.2019  
Vollsynthetisches Hypoid Getriebeöl Truck (GL4/5) 75W-90 20 L  
Art.: 1182

ECHA European Chemicals Agency  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.