

Page 1 of 23  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.08.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 01.08.2022  
PDF print date: 01.08.2022  
Brake Anti Squeal

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Brake Anti Squeal

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Lubricant

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

## Danger

H315-Causes skin irritation. H318-Causes serious eye damage.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

Calcium dihydroxide  
 Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

Calcium dihydroxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475151-45-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	215-137-3
CAS	1305-62-0
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	
Registration number (REACH)	01-2119948548-22-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	270-478-5
CAS	68442-22-8
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
Registration number (REACH)	01-0000015551-76-XXXX
Index	607-530-00-7
EINECS, ELINCS, NLP, REACH-IT List-No.	406-040-9
CAS	125643-61-0
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 4, H413

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Registration number (REACH)	01-2119491299-23-XXXX
Index	---

Page 3 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	270-128-1
<b>CAS</b>	68411-46-1
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Aquatic Chronic 3, H412

<b>Propylene carbonate</b>	
<b>Registration number (REACH)</b>	01-2119537232-48-XXXX
<b>Index</b>	607-194-00-1
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	203-572-1
<b>CAS</b>	108-32-7
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Eye Irrit. 2, H319

<b>Disodium sebacate</b>	
<b>Registration number (REACH)</b>	01-2120762063-61-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	241-300-3
<b>CAS</b>	17265-14-4
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Eye Irrit. 2, H319

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.  
 Protect uninjured eye.  
 Follow-up examination by an ophthalmologist.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.  
 eyes, reddened  
 watering eyes  
 Conjunctivitis  
 reddening of the skin

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Page 4 of 23  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.08.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 01.08.2022  
PDF print date: 01.08.2022  
Brake Anti Squeal

Water jet spray/foam/CO2/dry extinguisher  
**Unsuitable extinguishing media**  
High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of phosphorus  
Oxides of sulphur  
Oxides of nitrogen  
Toxic gases

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Keep unprotected persons away.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid contact with eyes or skin.  
Do not heat to temperatures close to flash point.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

GB

Page 5 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Do not store with oxidizing agents.  
 Store in a well ventilated place.  
 Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Calcium dihydroxide		
WEL-TWA: 1 mg/m3 (9) (WEL, EU)	WEL-STEL: 4 mg/m3 (9) (WEL, EU)	---	
Monitoring procedures:	ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 2004 (Part 3) - NIOSH 7020 (CALCIUM and compounds, as Ca) - 1994 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 42-4 (2004) - OSHA PV2121 (Gravimetric Determination) - 2003		
BMGV: ---	Other information: ---		
Chemical Name	Silicon dioxide		
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

Calcium dihydroxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,49	mg/l	
	Environment - soil		PNEC	1080	mg/kg dw	
	Environment - marine		PNEC	0,32	mg/l	
	Environment - sewage treatment plant		PNEC	3	mg/l	
	Environment - sporadic (intermittent) release		DMEL	0,49	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	4	µg/l	
	Environment - marine		PNEC	4,6	µg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	0,045	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,005	mg/kg dw	

Page 6 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

	Environment - soil		PNEC	0,007	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	10,67	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,71	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,98	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,24	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11,4	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,05	mg/m <sup>3</sup>	

**Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,37	mg/kg dw	
	Environment - sediment, marine		PNEC	0,037	mg/kg dw	
	Environment - soil		PNEC	10	mg/kg dw	
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - marine		PNEC	0,002	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,018	mg/l	
	Environment - oral (animal feed)		PNEC	41,33	mg/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,74	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,93	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,67	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,6	mg/m <sup>3</sup>	

**Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,51	mg/l	
	Environment - sediment, freshwater		PNEC	0,0246	mg/kg	
	Environment - sediment, marine		PNEC	0,00246	mg/kg	
	Environment - soil		PNEC	0,0193	mg/kg	
	Environment - sewage treatment plant		PNEC	0,187	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg	

Page 7 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,1	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,07	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,5	mg/m <sup>3</sup>	

Propylene carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sporadic (intermittent) release		PNEC	9	mg/l	
	Environment - marine		PNEC	0,09	mg/l	
	Environment - sediment, marine		PNEC	0,083	mg/l	
	Environment - soil		PNEC	0,81	mg/l	
	Environment - freshwater		PNEC	0,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,83	mg/l	
	Environment - sewage treatment plant		PNEC	7400	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	10	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	10	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	10	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,4	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	70,53	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	176	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	20	mg/m <sup>3</sup>	

Disodium sebacate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - marine		PNEC	0,002	mg/l	
	Environment - sediment, freshwater		PNEC	0,548	mg/kg	
	Environment - sediment, marine		PNEC	0,055	mg/kg	
	Environment - soil		PNEC	0,099	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,7	mg/m <sup>3</sup>	
Industrial / commercial	Human - inhalation	Long term, systemic effects	DNEL	35,26	mg/m <sup>3</sup>	
Industrial / commercial	Human - dermal	Long term, systemic effects	DNEL	10	mg/kg bw/day	

GB

Page 8 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Silicon dioxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

Zinc sulphide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	20,6	µg/l	
	Environment - marine		PNEC	6,1	µg/l	
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dry weight	
	Environment - sediment, marine		PNEC	56,5	mg/kg dry weight	
	Environment - soil		PNEC	35,5	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	100	µg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Page 9 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN ISO 374).  
 If applicable  
 Protective Neoprene® / polychloroprene gloves (EN ISO 374).  
 Protective nitrile gloves (EN ISO 374).  
 Protective PVC gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 >= 0,5  
 Permeation time (penetration time) in minutes:  
 >= 480  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	Blue
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	>63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.a.
Kinematic viscosity:	<=20,5 mm <sup>2</sup> /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,048 g/cm <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.

Page 10 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Particle characteristics:

Does not apply to liquids.

## 9.2 Other information

No information available at present.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

None known

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Brake Anti Squeal						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Calcium dihydroxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:					OECD 431 (In Vitro Skin Corrosion - Human Skin Model Test)	Non-caustic
Skin corrosion/irritation:				Rabbit		Irritant, in vivo
Serious eye damage/irritation:				Rabbit		Risk of serious damage to eyes., in vivo
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:						Not to be expected

Page 11 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat		Negative, administered as Ca-lactate
Reproductive toxicity:				Mouse		Negative, administered as Ca-carbonate
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract oral (UL by SCF)
Specific target organ toxicity - repeated exposure (STOT-RE):		36	mg/kg bw/d			
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative, dermal
Aspiration hazard:						No
Symptoms:						breathing difficulties, abdominal pain, drowsiness, thirst, fever, sore throat, cornea opacity, coughing, headaches, mucous membrane irritation, fatigue

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4358	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2002	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	160	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Negative, Analogous conclusion

Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	

Page 12 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative Chinese hamster
Reproductive toxicity:	NOAEL	150-600	mg/kg bw/d	Mouse	OECD 415 (One-Generation Reproduction Toxicity Study)	
Carcinogenicity:				Rat		Negative, Analogous conclusion
Aspiration hazard:						Negative

**Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:				Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Negative

**Propylene carbonate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Human being		No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative

Page 13 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Germ cell mutagenicity:					OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Aspiration hazard:						No
Symptoms:						breathing difficulties, headaches, gastrointestinal disturbances, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	>5000	mg/kg		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEC	100	mg/m3		OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Dust, Mist

#### Disodium sebacate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 492 (Reconstructed Human Cornea-like Epithelium ... Not Requir. C. + L. for Eye Irrit./Dam.)	Eye Irrit. 2

#### Silicon dioxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications of such an effect.

Page 14 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddened

## 11.2. Information on other hazards

Brake Anti Squeal						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Brake Anti Squeal							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: No
Other information:	AOX			%			According to the recipe, contains no AOX.

Calcium dihydroxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	50,6	mg/l			freshwater
12.1. Toxicity to fish:	LC50	96h	457	mg/l			marine water
12.1. Toxicity to fish:	LC50	96h	160	mg/l	Gambusia affinis	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	49,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	14d	32	mg/l			marine water
12.1. Toxicity to daphnia:	LC50	96h	158	mg/l			marine water

Page 15 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

12.1. Toxicity to algae:	EC50	72h	184,57	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	48	mg/l			freshwater
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Calcium dihydroxide, which is sparingly soluble, presents a low mobility in most soils.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.7. Other adverse effects:							pH-value of > 12 will rapidly decrease as result of dilution and carbonation., Even though this product can be used to neutralise over- acidified water, when 1g/l is exceeded organisms in the water may be affected adversely.
Toxicity to bacteria:							In high concentrations the product provokes an increase in temperature and of the pH-value. It is used to sanitise sewage sludge
Other organisms:	NOEC/NOEL		2000	mg/kg dw			soil macroorganisms
Other organisms:	NOEC/NOEL		12000	mg/kg dw			soil microorganisms
Other organisms:	NOEC/NOEL	21d	1080	mg/kg			terrestrial plants

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Page 16 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

12.1. Toxicity to fish:	LL50	96h	4,5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	46	mg/l	Cyprinodon variegatus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	23	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,4	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EL50	72h	21	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	1,5	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

**Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other organisms:	NOEC/NOEL	28d	31,6	mg/kg		OECD 217 (Soil Microorganisms - Carbon Transformation Test)	
12.1. Toxicity to fish:	LC50	96h	>74	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,001	mg/l	Brachydanio rerio	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	72h	>3	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	2-4	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.2. Persistence and degradability:							Mechanical precipitation possible. Possible @20°C
12.3. Bioaccumulative potential:	Log Pow		9,2				

Page 17 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

12.3. Bioaccumulative potential:	BCF	35d	260			OECD 305 (Bioconcentration - Flow-Through Fish Test)	Concentration in organisms possible. <i>Oncorhynchus mykiss</i>
12.4. Mobility in soil:							Adsorption in ground., To be expected
12.4. Mobility in soil:	Koc		7673-18432			OECD 106 (Adsorption/Desorption Using a Batch Equilibrium Method)	
Toxicity to bacteria:	IC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	EC50	19d	>100	mg/kg		OECD 208 (Terrestrial Plants, Growth Test)	Brassica rapa
Toxicity to annelids:	EC50	14d	>1000	mg/kg	<i>Eisenia foetida</i>	OECD 207 (Earthworm, Acute Toxicity Tests)	artificial soil
Toxicity to annelids:	NOEC/NOEL	56d	250	mg/kg	<i>Eisenia foetida</i>	OECD 222 (Earthworm Reproduction Test ( <i>Eisenia foetida</i> / <i>Eisenia andrei</i> ))	artificial soil
Water solubility:			0,5	µg/l			Insoluble

**Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>= 10	mg/l	<i>Pseudokirchneriella subcapitata</i>	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC20	3h	~ 100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.1. Toxicity to daphnia:	EC10	21d	1,69	mg/l	<i>Daphnia magna</i>	OECD 211 ( <i>Daphnia magna</i> Reproduction Test)	
Other organisms:	EC10	56d	259	mg/kg	<i>Eisenia foetida</i>	OECD 222 (Earthworm Reproduction Test ( <i>Eisenia foetida</i> / <i>Eisenia andrei</i> ))	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	<i>Brachydanio rerio</i>	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	51	mg/l	<i>Daphnia magna</i>	OECD 202 ( <i>Daphnia</i> sp. Acute Immobilisation Test)	

Page 18 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.2. Persistence and degradability:		28d	1	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		>6				A notable biological accumulation potential has to be expected (LogPow > 3).
Toxicity to bacteria:	IC50	3h	>100	mg/l		OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	EC50		>100	mg/l		OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Propylene carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Cyprinus caprio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>900	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			83,5-87-7	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable29 d
12.2. Persistence and degradability:	DOC	14d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	
12.3. Bioaccumulative potential:	Log Pow		-0,48				Bioaccumulation is unlikely (LogPow < 1)., calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Page 19 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

Toxicity to bacteria:	EC10	16h	7400	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	AOX		0	%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Disodium sebacate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to algae:	EL50	72h	38,7	mg/l	Skeletonema costatum	ISO 10253	
12.1. Toxicity to daphnia:	EC0	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	89	%		OECD 306 (Biodegradability in Seawater)	Readily biodegradable

Silicon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

12 01 12 spent waxes and fats

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Page 20 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.08.2022 / 0006  
 Replacing version dated / version: 01.11.2021 / 0005  
 Valid from: 01.08.2022  
 PDF print date: 01.08.2022  
 Brake Anti Squeal

E.g. dispose at suitable refuse site.

### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Classification code:

n.a.

LQ:

n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Marine Pollutant:

n.a.

14.5. Environmental hazards:

Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

14.5. Environmental hazards:

Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC):

0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

3, 8, 11, 12

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.08.2022 / 0006

Replacing version dated / version: 01.11.2021 / 0005

Valid from: 01.08.2022

PDF print date: 01.08.2022

Brake Anti Squeal

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Eye Irrit. — Eye irritation

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA	European Chemicals Agency
EC <sub>x</sub> , EL <sub>x</sub> (x = 0, 3, 5, 10, 20, 50, 80, 100)	Effect Concentration/Level for x % effect
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ErC <sub>x</sub> , E <sub>μ</sub> C <sub>x</sub> , ErL <sub>x</sub> (x = 10, 50)	Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc.	et cetera
EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
K <sub>oc</sub>	Adsorption coefficient of organic carbon in the soil
K <sub>ow</sub>	octanol-water partition coefficient
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC <sub>50</sub>	Lethal Concentration to 50 % of a test population
LD <sub>50</sub>	Lethal Dose to 50% of a test population (Median Lethal Dose)
Log K <sub>oc</sub>	Logarithm of adsorption coefficient of organic carbon in the soil
Log K <sub>ow</sub> , Log P <sub>ow</sub>	Logarithm of octanol-water partition coefficient
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute for Occupational Safety and Health (USA)
NLP	No-longer-Polymer
NOEC, NOEL	No Observed Effect Concentration/Level
OECD	Organisation for Economic Co-operation and Development
org.	organic
OSHA	Occupational Safety and Health Administration (USA)
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration
ppm	parts per million
PVC	Polyvinylchloride
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No.	9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC	Substances of Very High Concern
Tel.	Telephone
TOC	Total organic carbon
UN RTDG	United Nations Recommendations on the Transport of Dangerous Goods
VOC	Volatile organic compounds
vPvB	very persistent and very bioaccumulative
wwt	wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.08.2022 / 0006

Replacing version dated / version: 01.11.2021 / 0005

Valid from: 01.08.2022

PDF print date: 01.08.2022

Brake Anti Squeal

---

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax:  
+49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.