

(B)

Page 1 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1 Product identifier

# Steinschlagschutz schwarz Stoneguard, black

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection

# **Uses advised against:**

No information available at present.

# 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number

# Emergency information services / official advisory body:

---

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

nazaru ciass	nazaru calegory	nazaru Statement				
	_					

Flam. Liq. 2 H225-Highly flammable liquid and vapour.

Skin Irrit. 2 H315-Causes skin irritation.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz

Stoneguard, black



Danger

H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243-Take action to prevent static discharges. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Ethyl acetate

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

# n.a. **3.2 Mixtures**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119475515-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	927-510-4
CAS	
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	
content %	10-<25



Page 3 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Ethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475103-46-XXXX
Index	607-022-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	205-500-4
CAS	141-78-6
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3, H336

Hydrocarbons, C9, aromatics	
Registration number (REACH)	01-2119455851-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-668-5
CAS	(64742-95-6)
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 3, H226
	STOT SE 3, H335
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### **Skin contact**



Page 4 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Headaches

Dizziness

Nausea

Unconsciousness

Irritation of the respiratory tract

Product removes fat.

Dermatitis (skin inflammation)

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Sand

# Unsuitable extinguishing media

High volume water jet

# 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Possible build up of explosive/highly flammable vapour/air mixture.

# 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

# 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.



Œ

Page 5 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

# 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

# 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Do not wash away with water or watery cleaning agents.

# 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

# 7.1 Precautions for safe handling

# 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Keep away from food, drink and animal feedingstuffs.

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store cool.

Store in a dry place.

# 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3



Page 6 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025 Valid from: 19.09.2023

PDF print date: 19.09.2023 Steinschlagschutz schwarz

Stoneguard, black		
Chemical Name	Hydrocarbons, C7, n-alkanes, isoalkar	es, cyclics
WEL-TWA: 800 mg/m3	WEL-STEL:	
Monitoring procedures:	- Draeger - Hydrocarb - Draeger - Hydrocarb - Compur - KITA-187	
BMGV:	- Comput - KITA-107	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)
Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoa	kanes, cyclics
WEL-TWA: 1200 mg/m3	WEL-STEL:	
Monitoring procedures:	- Draeger - Hydrocarb - Draeger - Hydrocarb - Compur - KITA-187	
BMGV:		Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)
Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoa	kanes, cyclics, <5% n-hexane
WEL-TWA: 600 mg/m3	WEL-STEL:	
Monitoring procedures:	- Compur - KITA-187	
BMGV:		Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)
Chemical Name	Ethyl acetate	
WEL-TWA: 200 ppm (734 mg/	m3) (WEL, EU) WEL-STEL: 400	) ppm (1468 mg/m3) (WEL, EU)
ō,	- Compur - KITA-111 1 - Compur - KITA-111 1 - DFG Meth. Nr. 1 (D) - 2002 - DFG Meth. Nr. 2 (D) - 2002 - DFG Meth. Nr. 6 (D) - 2002 - NIOSH 1457 (ETHY)	J(C) (549 178) (Loesungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1993 (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014 (Loesungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2014  _ ACETATE) - 1994 FILE ORGANIC COMPOUNDS (SCREENING)) - 1996
BMGV:	·	Other information:
Chemical Name	Hydrocarbons, C9, aromatics	
WEL-TWA: 500 mg/m3 (Aroma		
Monitoring procedures:	- Draeger - Hydrocarb - Draeger - Hydrocarb - Compur - KITA-187	
BMGV:	,	Other information:
Chemical Name	Calcium carbonate	
WEL-TWA: 4 mg/m3 (respirab		
(total inhalable dust)		
Manitaria a mananduran		
Monitoring procedures: BMGV:	<del></del>	Other information:

Hydrocarbons, C7, n-alka	nes, isoalkanes, cyclics					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	447	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	149	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2085	mg/m3	



Page 7 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

Ethyl acetate  Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
7 a oa o appiloation	Environmental	Zilost on libaian	2000p.o.	Tuiuo	0	11010
	compartment					
	Environment - freshwater		PNEC	0,24	mg/l	
	Environment - marine		PNEC	0,024	mg/l	
	Environment - water,		PNEC	1,65	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sediment,		PNEC	1,15	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	0,115	mg/kg	
	marine					
	Environment - soil		PNEC	0,148	mg/kg	
	Environment - sewage		PNEC	650	mg/l	
	treatment plant					
	Environment - oral (animal		PNEC	200	mg/kg	
	feed)					
Consumer	Human - oral	Long term, systemic	DNEL	4,5	mg/kg	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	37	mg/kg	
		effects				
Consumer	Human - inhalation	Long term, systemic	DNEL	367	mg/m3	
		effects				
Consumer	Human - inhalation	Long term, local effects	DNEL	367	mg/m3	
Consumer	Human - inhalation	Short term, systemic	DNEL	734	mg/m3	
		effects				



(B)

Page 8 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Consumer	Human - inhalation	Short term, local effects	DNEL	734	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	63	mg/kg
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	734	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	734	mg/m3
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m3

Hydrocarbons, C9, arom		Effect on books	December	Value	I Imit	Mata
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m3	

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

#### 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls

<sup>(8) =</sup> Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

<sup>(8) =</sup> Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

<sup>\*\* =</sup> The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

<sup>(13) =</sup> The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).



(B)

Page 9 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,12

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Black



Page 10 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Odour:

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

pH:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density:

Relative vapour density: Particle characteristics:

9.2 Other information

Solvents content:

Characteristic

There is no information available on this parameter.

94-99 °C (Solvent)

There is no information available on this parameter.

0,9 Vol-% (Solvent)
7 Vol-% (Solvent)
-9 °C (Solvent)
>200 °C (Solvent)

There is no information available on this parameter.

Mixture is non-soluble (in water).

285,4 mm2/s (40°C)

Insoluble

Does not apply to mixtures.

306 hPa (50°C)

1,04 g/cm3 (20°C, DIN 51757)

There is no information available on this parameter.

Does not apply to liquids.

50,8 % (Organic solvents)

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

## 10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

# 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Steinschlagschutz schwarz						
Stoneguard, black						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						



Page 11 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025 Valid from: 19.09.2023

PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
Acute toxicity, by dermal route:	I DEO	. 2020		Rat	Toxicity) OECD 402 (Acute	conclusion
Acute toxicity, by dermai route:	LD50	>2920	mg/kg	Rat		Analogous
A suite terrisite. In clinical state of	1.050	00.0		D-4	Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Analogous
Obia				D-b-b-it	Inhalation Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	,	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	9000	ppm	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Aspiration hazard:					7,	Yes
Symptoms:						diarrhoea, headaches, dizziness, nausea and vomiting.
Symptoms:						drowsiness, unconsciousnes, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting., diarrhoea

Hydrocarbons, C7-C9, n-alkane	, ,	· •	1			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.



Page 12 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025 Valid from: 19.09.2023

PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousnes , heart/circulatory disorders, headaches, cramps, drowsiness,
						mucous membrane irritation, dizziness, nausea and vomiting.

Hydrocarbons, C6-C7, n-alkan	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral		
					Toxicity)		
Acute toxicity, by dermal route:	LD50	>2800-3100	mg/kg	Rat	OECD 402 (Acute		
					Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute	Vapours	
					Inhalation Toxicity)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2	
					Dermal		
					Irritation/Corrosion)		
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Mild irritant	
					Irritation/Corrosion)	(Analogous	
						conclusion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)	
sensitisation:					Sensitisation)		
Germ cell mutagenicity:					OECD 471 (Bacterial	Analogous	
					Reverse Mutation Test)	conclusion,	
						Negative	
Carcinogenicity:						Negative	



Page 13 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Reproductive toxicity:	OECD 414 (Prenatal	Analogous
	Developmental Toxicity	conclusion,
	Study)	Negative
Specific target organ toxicity -		May cause
single exposure (STOT-SE):		drowsiness or
singic exposure (OTOT GE).		
		dizziness.,
		STOT SE 3,
		H336
Aspiration hazard:		Yes
Symptoms:		drowsiness,
		unconsciousness
		heart/circulatory
		disorders,
		,
		headaches,
		cramps,
		drowsiness,
		mucous
		membrane
		irritation,
		dizziness,
		·
		nausea and
		vomiting.

Ethyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit	TOXICITY)	
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:	LCU	29,3	1119/1/411	Rabbit	OECD 404 (Acute	Not irritant,
Skin corrosion/irritation.				Rabbit	Dermal	'
						Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Eye Irrit. 2
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian	Negative
0 ,					Erythrocyte `	
					Micronucleus Test)	
Carcinogenicity:					,	Negative
Reproductive toxicity:						Negative
Specific target organ toxicity -						STOT SE 3.
single exposure (STOT-SE):						H336, May
3 (						cause
						drowsiness or
						dizziness.
Aspiration hazard:						No
7 opiration nazara.						110



Page 14 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Symptoms:						lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting., fatigue
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,002	mg/kg	Rat	Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS))	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>6,193	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative



Page 15 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Germ cell mutagenicity:		OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:		OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Germ cell mutagenicity:	Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:			Negative
Reproductive toxicity:	Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:		OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:		OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):			STOT SE 3, H335, STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):		OECD 452 (Chronic Toxicity Studies)	Negative
Aspiration hazard:			Yes
Symptoms:			respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness, fever, ear noises, drying of the skin.

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral	
					toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	



③B)·

Page 16 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local	No (skin contact)
Sensitisation.					Lymph Node Assay)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
3 ,					Reverse Mutation Test)	3
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Carcinogenicity:						No indications of
						such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg	Rat	OECD 422 (Combined	
			bw/d		Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Specific target organ toxicity -						No indications of
single exposure (STOT-SE):						such an effect.
Specific target organ toxicity -						No indications of
repeated exposure (STOT-RE):						such an effect.
Aspiration hazard:						No
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),			bw/d		Repeated Dose Tox.	
oral:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Specific target organ toxicity -	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic	
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	
inhalat.:					Day Study)	

# 11.2. Information on other hazards

Steinschlagschutz schwarz Stoneguard, black										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Endocrine disrupting properties:						Does not apply				
						to mixtures.				
Other information:						No other				
						relevant				
						information				
						available on				
						adverse effects				
						on health.				

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Steinschlagschutz schw	arz			•							
Stoneguard, black											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:	-						n.d.a.				
12.1. Toxicity to daphnia:							n.d.a.				
12.1. Toxicity to algae:							n.d.a.				
12.2. Persistence and							n.d.a.				
degradability:											
12.3. Bioaccumulative							n.d.a.				
potential:											
12.4. Mobility in soil:							n.d.a.				



Page 17 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

12.5. Results of PBT			n.d.a.	
and vPvB assessment				
12.6. Endocrine			Does not apply	y
disrupting properties:			to mixtures.	
12.7. Other adverse			No information	1
effects:			available on	
			other adverse	
			effects on the	
			environment.	
Other information:			DOC-elimination	on
			degree(comple	exi
			ng organic	
			substance)>=	
			80%/28d: n.a.	
Other information:	AOX	%	Does not conta	ain
			any organically	
			bound haloger	ns
			which can	
			contribute to the	ne
			AOX value in	
			waste water.	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13,4	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>13,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	1,53	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	NOELR	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	10 - 30	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	10	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	ErL50	72h	10-30	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	6,3	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	NOELR	28d	0,574	mg/kg	Oncorhynchus mykiss					
12.1. Toxicity to fish:	LC50	96h	3 -10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)				
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna					



Page 18 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025 Valid from: 19.09.2023

PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	98	%		OECD 301 F	Completely
degradability:						(Ready	biodegradable.
						Biodegradability -	-
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative							Not to be
potential:							expected(evapor
							ation)
12.4. Mobility in soil:							Product is
-							slightly volatile.
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.7. Other adverse							Product floats on
effects:							the water
							surface.
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish,	
						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	30-100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	81	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative							Concentration i
potential:							organisms
							possible.



Page 19 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

12.3. Bioaccumulative potential:	BCF	242-253			
12.4. Mobility in soil:					Adsorption in ground., Product is slightly volatile.
12.5. Results of PBT and vPvB assessment					No PBT substance, No vPvB substance
Other information:	AOX	0	%		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	32d	<9.65	mg/l	Pimephales	1 oot mounou	110100
12.11. Toxicity to lish.	NOLO/NOLL	32u	\\ \0,00	1119/1	promelas		
12.1. Toxicity to fish:	LC50	96h	230	mg/l	Pimephales		
12.1. Toxicity to fish.	L030	3011	230	1119/1	promelas		
12.1. Toxicity to fish:	LC50	48h	333	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	610	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,4	mg/l	Daphnia magna	OECD 211	
12.11. Toxicity to daprillia.	NOLO/NOLL	210	2,4	1119/1	Dapririla magna	(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	165	mg/l		reproduction resty	Daphnia
12.1. Toxiony to daprima.	2000	4011	100	1119/1			cucullata
12.1. Toxicity to algae:	EC50	48h	5600	mg/l	Desmodesmus	DIN 38412 T.9	ododilata
12.11 Toxiony to diguo.	2000	1011	0000	1119/1	subspicatus	DII 00 112 1.0	
12.1. Toxicity to algae:	NOEC/NOEL	96h	2000	mg/l	Scenedesmus	OECD 201 (Alga,	
12.11 Toxiony to diguo.	11020/11022	0011	2000	1119/1	subspicatus	Growth Inhibition	
					Japopioatas	Test)	
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
12.11 Toxiony to diguo.	2000	0011	72000	1119/1	a subcapitata	Growth Inhibition	
					a outoup.tata	Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Desmodesmus	OECD 201 (Alga,	
romeny to algue.					subspicatus	Growth Inhibition	
					Cabopidatao	Test)	
12.1. Toxicity to algae:	EC50	48h	3300	mg/l	Scenedesmus		
comercial to engage		1011			subspicatus		
12.2. Persistence and		20d	79	%		OECD 301 D	Readily
degradability:						(Ready	biodegradable
,						Biodegradability -	3
						Closed Bottle Test)	
12.3. Bioaccumulative	BCF	72h	30			,	(Fish)
potential:							,
12.3. Bioaccumulative	Log Kow		0,68			OECD 107	Bioaccumulatio
potential:			,			(Partition	is unlikely
•						Coefficient (n-	(LogPow < 1).2
						octanol/water) -	°C ´
						Shake Flask	
						Method)	
12.4. Mobility in soil:	H (Henry)		0,00012	atm*m3/m		,	
•	' '			ol			
12.4. Mobility in soil:	Koc		3				
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EC10	16h	2900	mg/l	Escherichia coli		
Toxicity to bacteria:	EC50	15min	5870	mg/l	Photobacterium		
					phosphoreum		
Toxicity to bacteria:	EC10	18h	2900	mg/l	Pseudomonas	DIN 38412 T.8	
					putida		

Hydrocarbons, C9, aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 20 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	54-56	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.2. Persistence and degradability:		28d	78	%	activated sludge	OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	78	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		3,7 - 4,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	10min	>99	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	No observation with saturated solution of test material.
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OEĆD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						,	Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.



Page 21 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

12.5. Results of PBT and vPvB assessment							No PBT substance, No
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge,	vPvB substance
						Respiration Inhibition Test (Carbon and	
						Ammonium Oxidation))	
Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209	
					_	(Activated Sludge, Respiration	
						Inhibition Test (Carbon and	
						Ammonium Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Glycine max
-						(Terrestrial Plants, Growth Test)	,
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants,	Lycopersicon esculentum
Other organisms:	EC50	21d	>1000	mg/kg dw		Growth Test) OECD 208	Avena sativa
Other organisms.	L030	210	>1000	mg/kg dw		(Terrestrial Plants, Growth Test)	Averia Saliva
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants,	Glycine max
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		Growth Test) OECD 208	Lycopersicon
Other organisms.	NOLO/NOLL	210	1000	mg/kg uw		(Terrestrial Plants, Growth Test)	esculentum
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm,	
						Acute Toxicity Tests)	
Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm,	
						Acute Toxicity Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil	
						Microorganisms - Nitrogen	
						Transformation Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OEĆD 216 (Soil Microorganisms -	
						Nitrogen Transformation	
Water solubility:			0,0166	g/I		Test) OECD 105 (Water Solubility)	20°C

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:



Page 22 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND

VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 wastes from MFSU and removal of paint and varnish

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

# For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

# **SECTION 14: Transport information**

3

#### **General statements**

# Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:
14.2. UN proper shipping name:
UN 1139 COATING SOLUTION
14.3. Transport hazard class(es):
14.4. Packing group:

1139

3
14.5. Packing group:

14.5. Environmental hazards: environmentally hazardous
Tunnel restriction code: D/E

Tunnel restriction code: D/E
Classification code: F1
LQ: 5 L
Transport category: 2

Transport by sea (IMDG-code)

14.1. UN number or ID number:

14.2. UN proper shipping name:

UN 1139 COATING SOLUTION (NAPHTHA (PETROLEUM))
14.3. Transport hazard class(es):
3

14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

Marine Pollutant: Yes
EmS: F-E, S-E

Transport by air (IATA)

14.1. UN number or ID number: 1139
14.2. UN proper shipping name:

UN 1139 Coating solution 14.3. Transport hazard class(es):

14.4. Packing group:14.5. Environmental hazards:Not applicable

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

# 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.









Page 23 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

50,82 %

Directive 2004/42/CE (VOC):

840 g/l (B/e)

VOC EU limit value for this product is: Maximum VOC content of this product is:

a/l

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

# 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections:

3, 6, 7, 9, 15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.



Page 24 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz

Stoneguard, black

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid
Skin Irrit. — Skin irritation
STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Asp. Tox. — Aspiration hazard Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

# **Key literature references and sources for data:**

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

# Any abbreviations and acronyms used in this document:

according, according to

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA

BCF Bioconcentration factor

BSEF The International Bromine Council

body weight bw

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

carcinogenic, mutagenic, reproductive toxic CMR

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

**European Community** FC ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

**European Economic Community** EEC

**EINECS** European Inventory of Existing Commercial Chemical Substances

**ELINCS** European List of Notified Chemical Substances

ΕN **European Norms** 

**EPA** United States Environmental Protection Agency (United States of America)



Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.09.2023 / 0026

Replacing version dated / version: 01.11.2021 / 0025

Valid from: 19.09.2023 PDF print date: 19.09.2023 Steinschlagschutz schwarz Stoneguard, black

ErCx,  $E\mu Cx$ , ErLx (x = 10, 50)

Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

# Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.