# Safety data sheet
# according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

## Tire Repair Spray

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

See definition of the substance or mixture.
Sealant

**Uses advised against:**

No information available at present.

### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

| Hazard class | Hazard category | Hazard statement |
|---|---|---|
| Eye Irrit. | 2 | H319-Causes serious eye irritation. |
| STOT SE | 3 | H336-May cause drowsiness or dizziness. |
| Aerosol | 1 | H222-Extremely flammable aerosol. |
| Aerosol | 1 | H229-Pressurised container: May burst if heated. |

### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear eye protection / face protection.
P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.
P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.
n-butyl acetate
Acetone
Butanone

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# SECTION 3: Composition/information on ingredients

## 3.1 Substances

n.a.

## 3.2 Mixtures

| **Dimethyl ether** | **Substance for which an EU exposure limit value applies.** |
|---|---|
| **Registration number (REACH)** | 01-2119472128-37-XXXX |
| **Index** | 603-019-00-8 |
| **EINECS, ELINCS, NLP, REACH-IT List-No.** | 204-065-8 |
| **CAS** | 115-10-6 |
| **content %** | 30-50 |
| **Classification according to Regulation (EC) 1272/2008 (CLP), M-factors** | Flam. Gas 1A, H220 |

| **n-butyl acetate** | **Substance for which an EU exposure limit value applies.** |
|---|---|
| **Registration number (REACH)** | 01-2119485493-29-XXXX |
| **Index** | 607-025-00-1 |
| **EINECS, ELINCS, NLP, REACH-IT List-No.** | 204-658-1 |
| **CAS** | 123-86-4 |
| **content %** | 20-30 |
| **Classification according to Regulation (EC) 1272/2008 (CLP), M-factors** | EUH066<br>Flam. Liq. 3, H226<br>STOT SE 3, H336 |

| Acetone | Substance for which an EU exposure limit value applies. |
|---|---|
| **Registration number (REACH)** | 01-2119471330-49-XXXX |
| **Index** | 606-001-00-8 |
| **EINECS, ELINCS, NLP, REACH-IT List-No.** | 200-662-2 |
| **CAS** | 67-64-1 |
| **content %** | 10-20 |
| **Classification according to Regulation (EC) 1272/2008 (CLP), M-factors** | EUH066<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336 |

| Butanone | Substance for which an EU exposure limit value applies. |
|---|---|
| **Registration number (REACH)** | 01-2119457290-43-XXXX |
| **Index** | 606-002-00-3 |
| **EINECS, ELINCS, NLP, REACH-IT List-No.** | 201-159-0 |
| **CAS** | 78-93-3 |
| **content %** | 10-20 |
| **Classification according to Regulation (EC) 1272/2008 (CLP), M-factors** | EUH066<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336 |

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures
First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

### Inhalation
Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

### Skin contact
Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

### Eye contact
Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### Ingestion
Typically no exposure pathway.
Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed
If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
eyes, reddened
watering eyes
drying of the skin.
headaches
dizziness
Coordination disorders
mental confusion

### 4.3 Indication of any immediate medical attention and special treatment needed
Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media
### Suitable extinguishing media
Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.
### Unsuitable extinguishing media
High volume water jet
### 5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Hydrogen chloride
Oxides of nitrogen
Toxic gases
Danger of bursting (explosion) when heated
Possible build up of explosive/highly flammable vapour/air mixture.
### 5.3 Advice for firefighters
For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures
### 6.1.1 For non-emergency personnel
In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Avoid contact with eyes or skin.
### 6.1.2 For emergency responders
See section 8 for suitable protective equipment and material specifications.
### 6.2 Environmental precautions
If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.
### 6.3 Methods and material for containment and cleaning up
If spray or gas escapes, ensure ample fresh air is available.
Active substance:
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
### 6.4 Reference to other sections
For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.
### 7.1 Precautions for safe handling
### 7.1.1 General recommendations
Ensure good ventilation.
Avoid breathing vapours or spray.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Do not use on hot surfaces.

Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Observe special regulations for aerosols!
Do not store with flammable or self-igniting materials.
Keep protected from direct sunlight and temperatures over 50°C.
Store in a dry place.
Store cool.
Observe special storage conditions.

### 7.3 Specific end use(s)

No information available at present.
Observe the instructions for good working practice and the recommendations for risk assessment.
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

| GB | **Chemical Name** | Dimethyl ether | |
|---|---|---|---|
| WEL-TWA: 400 ppm (766 mg/m3) (WEL-TWA), 1000 ppm (1920 mg/m3) (EU) | WEL-STEL: 500 ppm (958 mg/m3) (WEL-STEL) | --- | |
| Monitoring procedures: | - Compur - KITA-123 S (549 129) | | |
| BMGV: --- | Other information: --- | | |

| GB | **Chemical Name** | n-butyl acetate | |
|---|---|---|---|
| WEL-TWA: 150 ppm (724 mg/m3) (WEL-TWA), 50 ppm (241 mg/m3) (EU) | WEL-STEL: 200 ppm (966 mg/m3) (WEL-STEL), 150 ppm (723 mg/m3) (EU) | --- | |
| Monitoring procedures: | - Compur - KITA-138 U (548 857)<br>- Compur - KITA-139 SB(C) (549 731)<br>- NIOSH 1450 (ESTERS 1) - 2003<br>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996<br>- OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007 | | |
| BMGV: --- | Other information: --- | | |

| GB | **Chemical Name** | Acetone | |
|---|---|---|---|
| WEL-TWA: 500 ppm (1210 mg/m3) (WEL-TWA, EU) | WEL-STEL: 1500 ppm (3620 mg/m3) (WEL-STEL) | --- | |
| Monitoring procedures: | - Draeger - Acetone 100/b (CH 22 901)<br>- Draeger - Acetone 40/a (5) (81 03 381)<br>- Compur - KITA-102 SA (548 534)<br>- Compur - KITA-102 SC (548 550)<br>- Compur - KITA-102 SD (551 109)<br>- INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 -<br>- EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004)<br>- MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993<br>- NIOSH 1300 (KETONES I) - 1994<br>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996<br>- NIOSH 2555 (KETONES I) - 2003<br>- NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 | | |

| | |
|---|---|
| - OSHA 69 (Acetone) - 1988 | |
| BMGV: --- | Other information: --- |

| **Chemical Name** | Butanone | |
|---|---|---|
| WEL-TWA: 200 ppm (600 mg/m3) (WEL-TWA, EU) | WEL-STEL: 300 ppm (899 mg/m3) (WEL-STEL), 300 ppm (900 mg/m3) (EU) | --- |
| Monitoring procedures: | - Compur - KITA-122 SA(C) (549 277)<br>- Compur - KITA-139 SB (549 731)<br>- Compur - KITA-139 U (549 749)<br>- DFG Meth.-Nr. 4 (D) (Loesungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2015, 2002<br>- INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 -<br>- EU project BC/CEN/ENTR/000/2002-16 card 105-1 (2004)<br>- MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993<br>- NIOSH 2500 (METHYL ETHYL KETONE) - 1996<br>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996<br>- NIOSH 2555 (KETONES I) - 2003<br>- NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016<br>- OSHA 1004 (2-Butanone (MEK) Hexone (MIBK)) - 2000 | |
| BMGV: 70 µmol butan-2-one/l in urine, post shift (BMGV) | | Other information: Sk |

**Dimethyl ether**

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---|---|---|---|---|---|---|
| | Environment - freshwater | | PNEC | 0,155 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,681 | mg/kg | |
| | Environment - soil | | PNEC | 0,045 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 160 | mg/l | |
| | Environment - marine | | PNEC | 0,016 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 1,549 | mg/l | |
| | Environment - sediment, marine | | PNEC | 0,069 | mg/kg | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 471 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 1894 | mg/m3 | |

**n-butyl acetate**

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---|---|---|---|---|---|---|
| | Environment - freshwater | | PNEC | 0,18 | mg/l | |
| | Environment - marine | | PNEC | 0,018 | mg/l | |
| | Environment - periodic release | | PNEC | 0,36 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,981 | mg/kg | |
| | Environment - sediment, marine | | PNEC | 0,0981 | mg/kg | |
| | Environment - soil | | PNEC | 0,0903 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 35,6 | mg/l | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 3,4 | mg/kg | |

| | | | | | | |
|---|---|---|---|---|---|---|
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 300 | mg/m3 | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 35,7 | mg/m3 | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 300 | mg/m3 | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 35,7 | mg/m3 | |
| Consumer | Human - dermal | Short term, systemic effects | DNEL | 6 | mg/kg bw/day | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 2 | mg/kg bw/day | |
| Consumer | Human - oral | Short term, systemic effects | DNEL | 2 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 600 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 300 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 7 | mg/kg bw/d | |
| Workers / employees | Human - dermal | Short term, systemic effects | DNEL | 11 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 600 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 300 | mg/m3 | |

| **Acetone** | | | | | | |
|---|---|---|---|---|---|---|
| **Area of application** | **Exposure route / Environmental compartment** | **Effect on health** | **Descriptor** | **Value** | **Unit** | **Note** |
| | Environment - marine | | PNEC | 1,06 | mg/l | Assesment factor 500 |
| | Environment - freshwater | | PNEC | 10,6 | mg/l | Assesment factor 50 |
| | Environment - sediment, freshwater | | PNEC | 30,4 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 3,04 | mg/kg dw | |
| | Environment - soil | | PNEC | 29,5 | mg/kg dw | |
| | Environment - sewage treatment plant | | PNEC | 19,5 | mg/l | |
| | Environment - sporadic (intermittent) release | | PNEC | 21 | mg/l | Assesment factor 100 |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 62 | mg/kg bw/day | Overall assesment factor 2 |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 62 | mg/kg bw/day | Overall assesment factor 20 |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 200 | mg/m3 | Overall assesment factor 5 |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 186 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 2420 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 1210 | mg/m3 | |

| **Butanone** | | | | | | |
|---|---|---|---|---|---|---|
| **Area of application** | **Exposure route / Environmental compartment** | **Effect on health** | **Descriptor** | **Value** | **Unit** | **Note** |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Environment - freshwater | | PNEC | 55,8 | mg/l | |
| | Environment - marine | | PNEC | 55,8 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 284,74 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 284,7 | mg/kg dw | |
| | Environment - soil | | PNEC | 22,5 | mg/kg dw | |
| | Environment - sewage treatment plant | | PNEC | 709 | mg/l | |
| | Environment - sporadic (intermittent) release | | PNEC | 55,8 | mg/l | |
| | Environment - oral (animal feed) | | PNEC | 1000 | mg/kg | |
| Consumer | Human - dermal | Long term | DNEL | 412 | mg/kg bw/day | Overall assesment factor 2 |
| Consumer | Human - inhalation | Long term | DNEL | 106 | mg/m3 | Overall assesment factor 2 |
| Consumer | Human - oral | Long term | DNEL | 31 | mg/kg bw/day | Overall assesment factor 2 |
| Workers / employees | Human - dermal | Long term | DNEL | 1161 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term | DNEL | 600 | mg/m3 | |

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

## 8.2 Exposure controls
## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Chemical resistant protective gloves (EN ISO 374).
Recommended
Protective gloves made of butyl (EN ISO 374).
Minimum layer thickness in mm:
0,7
Permeation time (penetration time) in minutes:
480
Protective hand cream recommended.
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Filter A2 P2 (EN 14387), code colour brown, white
At high concentrations:
Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls
No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

| | |
|---|---|
| Physical state: | Aerosol. Active substance: liquid. |
| Colour: | Light yellow |
| Odour: | Characteristic |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | There is no information available on this parameter. |
| Flammability: | Does not apply to aerosols. |
| Lower explosion limit: | There is no information available on this parameter. |
| Upper explosion limit: | There is no information available on this parameter. |
| Flash point: | -41 °C (The flash-point of the mixture was not tested, but complies with the ingredient with the lowest value. ) |
| Auto-ignition temperature: | Does not apply to aerosols. |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | Mixture is non-soluble (in water). |
| Kinematic viscosity: | Does not apply to aerosols. |
| Solubility: | There is no information available on this parameter. |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | 4000 hPa (20°C) |
| Density and/or relative density: | ~0,76 g/cm3 |
| Density and/or relative density: | 0,86 g/ml (Active substance ) |
| Relative vapour density: | Does not apply to aerosols. |

Particle characteristics: Does not apply to aerosols.

### 9.2 Other information
No information available at present.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity
The product has not been tested.

### 10.2 Chemical stability
Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions
No dangerous reactions are known.

### 10.4 Conditions to avoid
See also section 7.
Heating, open flame, ignition sources
Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials
See also section 7.
Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Possibly more information on health effects, see Section 2.1 (classification).

| **Tire Repair Spray** | | | | | | |
|---|---|---|---|---|---|---|
| **Toxicity / effect** | **Endpoint** | **Value** | **Unit** | **Organism** | **Test method** | **Notes** |
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| **Dimethyl ether** | | | | | | |
|---|---|---|---|---|---|---|
| **Toxicity / effect** | **Endpoint** | **Value** | **Unit** | **Organism** | **Test method** | **Notes** |
| Acute toxicity, by inhalation: | LC50 | 164 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Respiratory or skin sensitisation: | | | | | | No (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |

| | | | | | | |
|---|---|---|---|---|---|---|
| Germ cell mutagenicity: | | | | | OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophilia melanogaster) | Negative |
| Carcinogenicity: | NOAEC | 47000 | mg/m3 | Rat | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative |
| Reproductive toxicity: | NOAEL | 5000 | ppm | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEC | 47106 | mg/kg | Rat | OECD 452 (Chronic Toxicity Studies) | Negative(2 a) |
| Aspiration hazard: | | | | | | No |

**n-butyl acetate**

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|
| Acute toxicity, by oral route: | LD50 | 10760-13100 | mg/kg | Rat | OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method) | |
| Acute toxicity, by dermal route: | LD50 | >14112 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >21,1 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity: | NOAEC | 9640 | mg/m3 | | OECD 416 (Two-generation Reproduction Toxicity Study) | Negative |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Vapours may cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | Negative |
| Symptoms: | | | | | | drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting. |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 500 | ppm | Rat | | |

**Acetone**

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|

| | | | | | | |
|---|---|---|---|---|---|---|
| Acute toxicity, by oral route: | LD50 | 5800 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >15800 | mg/kg | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 76 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | Guinea pig | | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitizising |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mammalian | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Carcinogenicity: | | | | Mouse | | Negative, References |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | STOT SE 3, H336 |
| Reproductive toxicity (Developmental toxicity): | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative |
| Symptoms: | | | | | | unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 900 | mg/kg bw/d | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | |

**Butanone**

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method) | |
| Acute toxicity, by dermal route: | LD50 | 5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | 34-34,5 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitizising |

| | | | | | | |
|---|---|---|---|---|---|---|
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | STOT SE 3, H336, May cause drowsiness or dizziness. |
| Reproductive toxicity (Developmental toxicity): | NOAEC | 1002 | ppm | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative |
| Symptoms: | | | | | | respiratory distress, drowsiness, unconsciousness, drop in blood pressure, coughing, headaches, cramps, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting., mental confusion, fatigue |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 5041 | ppm/6h/d | Rat | OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) | Vapours, Negative |

## 11.2. Information on other hazards

| Tire Repair Spray | | | | | | |
|---|---|---|---|---|---|---|
| **Toxicity / effect** | **Endpoint** | **Value** | **Unit** | **Organism** | **Test method** | **Notes** |
| Endocrine disrupting properties: | | | | | | Does not apply to mixtures. |
| Other information: | | | | | | No other relevant information available on adverse effects on health. |

# SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Tire Repair Spray | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Toxicity / effect** | **Endpoint** | **Time** | **Value** | **Unit** | **Organism** | **Test method** | **Notes** |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |
| Other information: | | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: No |
| Other information: | AOX | | 0 | % | | | According to the recipe, contains no AOX. |

**Dimethyl ether**

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|---|
| 12.1. Toxicity to fish: | LC0 | 96h | 2695 | mg/l | Pimephales promelas | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 3082 | mg/l | Salmo gairdneri | | |
| 12.1. Toxicity to fish: | LC50 | 96h | >4,1 | mg/l | Poecilia reticulata | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >4,4 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to algae: | EC50 | 96h | 154,9 | mg/l | Chlorella vulgaris | | |
| 12.2. Persistence and degradability: | | 28d | 5 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Not readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | -0,07 | | | | Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7) |
| 12.4. Mobility in soil: | H (Henry) | | 518,6 | Pa*m3/mol | | | No adsorption in soil. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC10 | | >1600 | mg/l | Pseudomonas putida | | |
| Water solubility: | | | 45,60 | mg/l | | | 25°C |

**n-butyl acetate**

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 18 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 44 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 23 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 397 | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 200 | mg/l | Desmodesmus subspicatus | | |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 12.2. Persistence and degradability: | | 28d | 98 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 1,78 - 2,3 | | | | Low |
| 12.3. Bioaccumulative potential: | BCF | | 15,3 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC10 | | 959 | mg/l | Pseudomonas putida | | |

**Acetone**

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 5540 | mg/l | Oncorhynchus mykiss | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 7500 | mg/l | Leuciscus idus | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 8300 | mg/l | Lepomis macrochirus | | |
| 12.1. Toxicity to fish: | EC50 | 96h | 8300 | mg/l | Lepomis macrochirus | | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 28d | 2212 | mg/l | Daphnia pulex | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 6100-12700 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 8800 | mg/l | Daphnia pulex | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 48h | 4740 | mg/l | Pseudokirchneriella subcapitata | | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 48h | 3400 | mg/l | Pseudokirchneriella subcapitata | | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 8d | 530 | mg/l | | DIN 38412 T.9 | Test organism: M. aeruginosa |
| 12.2. Persistence and degradability: | | 30d | 81-92 | % | | Regulation (EC) 440/2008 C.4-E (DETERMINATION OF 'READY' BIODEGRADABILITY - CLOSED BOTTLE TEST) | Readily biodegradable |
| 12.2. Persistence and degradability: | | 28d | 91 | % | | OECD 301 A (Ready Biodegradability - DOC Die-Away Test) | Readily biodegradable |
| 12.2. Persistence and degradability: | | 28d | 91 | % | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | -0,24 | | | OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method) | |
| 12.3. Bioaccumulative potential: | BCF | | 0,19 | | | | Low |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 12.4. Mobility in soil: | | | | | | | No adsorption in soil. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC10 | 30min | 1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Toxicity to bacteria: | BOD/COD | 16h | 1700 | mg/l | Pseudomonas putida | | |
| Other organisms: | EC5 | 72h | 28 | mg/l | Entosiphon sulcatum | | |
| Other information: | BOD5 | | 1760-1900 | mg/g | | | |
| Other information: | AOX | | 0 | % | | | |
| Other information: | COD | | 2070-2100 | mg/g | | | |

**Butanone**

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|---|---|---|---|---|---|---|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 1690 | mg/l | Lepomis macrochirus | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 2993 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 308 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 1972 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | EC50 | 96h | 2029 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 98 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 0,29-0,3 | | | OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method) | Bioaccumulation is unlikely (LogPow < 1). |
| 12.4. Mobility in soil: | H (Henry) | | 0,0000244 | | | | 25°C |
| 12.4. Mobility in soil: | Log Koc | | 3,8 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No vPvB substance, No PBT substance |
| Toxicity to bacteria: | EC0 | 16h | 1150 | mg/l | Pseudomonas putida | DIN 38412 T.8 | |
| Other information: | DOC | | >70 | % | | | |
| Other information: | BOD/COD | | >50 | % | | | |

## SECTION 13: Disposal considerations

## 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:
The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
16 05 04 gases in pressure containers (including halons) containing hazardous substances
Recommendation:
Sewage disposal shall be discouraged.
E.g. dispose at suitable refuse site.
Take full aerosol cans to problem waste collection.
Take emptied aerosol cans to valuable material collection.

### For contaminated packing material

Pay attention to local and national official regulations.
15 01 04 metallic packaging
15 01 10 packaging containing residues of or contaminated by hazardous substances
Recycling
Do not perforate, cut up or weld uncleaned container.
Residues may present a risk of explosion.

## SECTION 14: Transport information

### General statements

### Transport by road/by rail (ADR/RID)

| | |
|---|---|
| 14.1. UN number or ID number: | 1950 |
| 14.2. UN proper shipping name: | |
| UN 1950 AEROSOLS | |
| 14.3. Transport hazard class(es): | 2.1 |
| 14.4. Packing group: | - |
| 14.5. Environmental hazards: | Not applicable |
| Tunnel restriction code: | D |
| Classification code: | 5F |
| LQ: | 1 L |
| Transport category: | 2 |



### Transport by sea (IMDG-code)

| | |
|---|---|
| 14.1. UN number or ID number: | 1950 |
| 14.2. UN proper shipping name: | |
| UN 1950 AEROSOLS | |
| 14.3. Transport hazard class(es): | 2.1 |
| 14.4. Packing group: | - |
| 14.5. Environmental hazards: | Not applicable |
| Marine Pollutant: | Not applicable |
| EmS: | F-D, S-U |



### Transport by air (IATA)

| | |
|---|---|
| 14.1. UN number or ID number: | 1950 |
| 14.2. UN proper shipping name: | |
| UN 1950 Aerosols, flammable | |
| 14.3. Transport hazard class(es): | 2.1 |
| 14.4. Packing group: | - |
| 14.5. Environmental hazards: | Not applicable |



### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.
For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.
Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|---|---|---|---|
| P3a | 11.1 | 150 (netto) | 500 (netto) |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 93,6 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

### 15.2 Chemical safety assessment
A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|---|
| Eye Irrit. 2, H319 | Classification according to calculation procedure. |
| STOT SE 3, H336 | Classification according to calculation procedure. |
| Aerosol 1, H222 | Classification according to calculation procedure. |
| Aerosol 1, H229 | Classification based on the form or physical state. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H220 Extremely flammable gas.
EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. — Eye irritation
STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aerosol — Aerosols
Flam. Gas — Flammable gases - Flammable gas
Flam. Liq. — Flammable liquid

## Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

## Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.