

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1 Product identifier** 

Kaeltespray Cold Spray

# **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Refrigerant spray Uses advised against: No information available at present.

# 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number

Emergency information services / official advisory body:

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)							
Hazard class	Hazard category	Hazard statement					
Aerosol	1	H222-Extremely flammable aerosol.					
Aerosol	1	H229-Pressurised container: May burst if heated.					

# 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P410+P412-P10tect from sunlight. Do not expose to temperatures exceeding 50°C

Without adequate ventilation, formation of explosive mixtures may be possible.

# 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

### <sup>n.a.</sup> 3.2 Mixtures

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

### First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

# Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Respiratory arrest - Artificial respiration apparatus necessary.

# Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Cover frostbite aseptically.

Eye contact



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

### Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

# Ingestion

ആ

Typically no exposure pathway.

# 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

# Unsuitable extinguishing media

High volume water jet

# 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Toxic gases

### Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

# 5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

# 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

# 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

# 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

# 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

# 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

# 7.1 Precautions for safe handling

### 7.1.1 General recommendations Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

# 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

ആ

Store cool.

# Observe special storage conditions. 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

### ipplication (building materials, wood, chemistry, laboratory, leather, metal).

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Chemical Name	Propane			
WEL-TWA: 1000 ppm (ACGIH)		WEL-STEL:		
Monitoring procedures:	-	Compur - KITA-125 SA (549 954)		
	-	OSHA PV2077 (Propane) - 1990		
BMGV:			Other information:	
Chemical Name	Isobutane			
WEL-TWA: 1000 ppm (EX) (ACGI	H)	WEL-STEL:		
Monitoring procedures:	-	Compur - KITA-113 SB(C) (549 368	3)	
BMGV:			Other information:	

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction

(2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE).

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

# 8.2 Exposure controls

ആ

# 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,45 Permeation time (penetration time) in minutes: 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter AX (EN 14387), code colour brown. Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

# 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state: Colour: Aerosol. Active substance: gaseous. Colourless



Page 6 of 13

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

### Odour:

Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

# 9.2 Other information

No information available at present.

Characteristic There is no information available on this parameter. -42 °C Does not apply to aerosols. 1,5 Vol-% 10,8 Vol-% Does not apply to aerosols. Does not apply to aerosols. There is no information available on this parameter. Not determined >20,5 mm2/s (40°C) There is no information available on this parameter. Does not apply to mixtures. There is no information available on this parameter. 0,54 g/cm3 (20°C, DIN 51757) Does not apply to aerosols. Does not apply to aerosols.

# SECTION 10: Stability and reactivity

# 10.1 Reactivity

# The product has not been tested.

**10.2 Chemical stability** 

# Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

# No dangerous reactions are known.

10.4 Conditions to avoid See also section 7.

Heating, open flame, ignition sources Pressure increase will result in danger of bursting. Electrostatic charge

# **10.5 Incompatible materials**

See also section 7. Avoid contact with strong oxidizing agents.

# **10.6 Hazardous decomposition products**

See also section 5.2

No decomposition when used as directed.

**SECTION 11: Toxicological information** 

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification). Kaoltesnrav

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						



headaches, cramps, dizziness, nausea and vomiting.

Page 7 of 13 Safety data sheet according to Revision date / version: 04.03.20 Replacing version dated / versior Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray	24 / 0011		, Annex II			
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation: Acute toxicity, by inhalation:	LC50 LC50	658 260000	mg/l/4h ppmV/4h	Rat Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation: Serious eye damage/irritation:						Not irritant Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard: Symptoms:						No breathing difficulties, unconsciousness , frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation: Acute toxicity, by inhalation:	LC50 LC50	658 260000	mg/l/4h ppmV/4h	Rat Rat		Gasses, Male
Serious eye damage/irritation: Germ cell mutagenicity:				Rabbit Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Not irritant Negative
Aspiration hazard: Symptoms:						No unconsciousness
Symptoms.						, frostbite,



Page 8 of 13	
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II	
Revision date / version: 04.03.2024 / 0011	
Replacing version dated / version: 22.09.2023 / 0010	
Valid from: 04.03.2024	
PDF print date: 08.03.2024	
Kaeltespray	
Cold Spray	
	_

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the
					Reproduction/Developm.
					Tox. Screening Test)

# 11.2. Information on other hazards

- @B-

Kaeltespray						
Cold Spray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

# **SECTION 12: Ecological information**

Kaeltespray							
Cold Spray Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	Епаропп	Time	value	Unit	Organishi	Test method	n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.1. Persistence and							n.d.a.
degradability:							n.u.a.
12.3. Bioaccumulative							n.d.a.
potential:							n.u.a.
12.4. Mobility in soil:							Product is
-							slightly volatile.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-elimination
							degree(complex
							ng organic
							substance)>=
							80%/28d: n.a.
Other information:	AOX			%			Does not contai
							any organically
							bound halogens
							which can
							contribute to the
							AOX value in
							waste water.
Other information:							According to the
							recipe, contains
							no AOX.
Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



### Page 9 of 13 Safety data sh

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

12.3. Bioaccumulative potential:	Log Pow	2,28	A notable biological accumulation potential is not to be expected
12.5. Results of PBT and vPvB assessment			(LogPow 1-3). No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

# For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

**For contaminated packing material** Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 04 metallic packaging

# **SECTION 14: Transport information**

# **General statements**

# Transport by road/by rail (ADR/RID)14.1. UN number or ID number:195014.2. UN proper shipping name:1950UN 1950 AEROSOLS2.114.3. Transport hazard class(es):2.114.4. Packing group:-14.5. Environmental hazards:Not applicableTunnel restriction code:DClassification code:5F





Page 10 of 13

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

LQ: Transport category:	1 L 2	
Transport by sea (IMDG-code)	2	
14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	-
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-D, S-U	
Transport by air (IATA)		
14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	•
14.5. Environmental hazards:	Not applicable	
14.6 Special precautions for user		

# 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

### Precautions must be taken to prevent damage.

# 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account. Danger code and packing code on request.

Comply with special provisions.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

### Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			
The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when				

assigning categories and qualifying quantities.



Page 11 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

# 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

**Revised sections:** 

അ

2

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

Aerosol — Aerosols

# Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

# Any abbreviations and acronyms used in this document:

acc., acc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSFF The International Bromine Council **Chemical Abstracts Service** CAS CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic



ആ Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon e.g. for example (abbreviation of Latin 'exempli gratia'), for instance EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN **European Norms** United States Environmental Protection Agency (United States of America) EPA  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. gen. deneral Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow International Agency for Research on Cancer IARC ΙΑΤΑ International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dw ma/ka dry weight mg/kg wet weight mg/kg wwt not applicable n.a. not available n.av. not checked n.c. no data available n.d.a. NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic Polyethylene PF PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern



Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0011 Replacing version dated / version: 22.09.2023 / 0010 Valid from: 04.03.2024 PDF print date: 08.03.2024 Kaeltespray Cold Spray

Telephone Tel.

œ

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

# These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.