

Page 1 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009
 Replacing version dated / version: 31.07.2023 / 0008
 Valid from: 04.03.2024
 PDF print date: 08.03.2024
 Motorbike Multispray

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

## **Motorbike Multispray**

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
 Grease
 Uses advised against:
 No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number Emergency information services / official advisory body:

**Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)							
Hazard class	Hazard category	Hazard statement					
Skin Irrit.	2	H315-Causes skin irritation.					
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.					
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.					
Aerosol	1	H222-Extremely flammable aerosol.					
Aerosol	1	H229-Pressurised container: May burst if heated.					

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 16

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray



#### Danger

H315-Causes skin irritation. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P273-Avoid release to the environment. P280-Wear protective gloves. P332+P313-If skin irritation occurs: Get medical advice / attention. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

Aerosol

## 3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304



Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here. The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the respiratory tract Coughing Headaches Dizziness Effects/damages the central nervous system With long-term contact: drying of the skin. Dermatitis (skin inflammation) Ingestion: Nausea Vomiting Danger of aspiration. Chemical pneumonitis (condition similar to pneumonia)

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

#### High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:



Page 4 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

Oxides of carbon Oxides of sulphur Oxides of nitrogen Toxic gases Danger of bursting (explosion) when heated Explosive vapour/air or gas/air mixtures.

## 5.3 Advice for firefighters

ആ

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance: Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use. Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 5 of 16

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Observe special regulations for aerosols! Observe special storage conditions. Do not store with flammable or self-igniting materials. Keep protected from direct sunlight and temperatures over 50°C. Store in a well-ventilated place. Store cool.

## 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name		7, n-alkanes, isoalkanes, cyc	ics, <5% n-hexa	ane						
WEL-TWA: 800 mg/m3		WEL-STEL:								
Monitoring procedures:	- Co									
BMGV:			Other infor	· · · · · · · · · · · · · · · · · · ·	OEL acc. to R	CP-method,				
			paragraphs	s 84-87, E⊦	140)					
Chemical Name	Hydrocarbons C10-	C13, n-alkanes, isoalkanes, c	velies <2% aror	natics						
WEL-TWA: 800 mg/m3		WEL-STEL:	jeee, 4 <u>−</u> ,e a.e.							
Monitoring procedures:	- Dr	aeger - Hydrocarbons 0,1%/c	(81 03 571)							
		aeger - Hydrocarbons 2/a (81								
		mpur - KÍTA-187 S (551 174)								
BMGV:			Other infor	mation: (0	OEL acc. to R	CP-method,				
			paragraphs	s 84-87, E⊢	40)					
Chemical Name	Hydrocarbons, C3-4									
WEL-TWA: 1000 ppm (AC	GIH)	WEL-STEL: 1250 ppm (218	30 mg/m3) (Liqu	efied						
		petroleum gas (LPG))								
Monitoring procedures:										
BMGV:			Other infor	mation:	-					
Chemical Name	Oil mist, mineral									
WEL-TWA: 5 mg/m3 (Mine		WEL-STEL:								
working fluids, ACGIH)	, C									
Monitoring procedures:	- Dr	aeger - Oil Mist 1/a (67 33 03	1)							
BMGV:			Other infor	mation:						
Hvdrocarbons, C6-C7, n-al	kanes, isoalkanes, cyclics, <	5% n-hexane								
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note				
	Environmental									
	compartment									
Consumer	Human - dermal	Long term, systemic	DNEL	699	mg/kg					
		effects			bw/day					
Consumer	Human - inhalation	Long term, systemic	DNEL	608	mg/m3					
		effects								
Consumer	Human - oral	Long term, systemic	DNEL	699	mg/kg					
		effects			bw/day					
Workers / employees	Human - dermal	Long term, systemic	DNEL	773	mg/kg					
		effects			bw/day					



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

Workers / employees	Human - inhalation	Lona term. systemic	DNEL	2035	ma/m3	
Werkere, employeee			BITLE	2000	ing/ino	
		effects				
		010010				

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

## 8.2 Exposure controls

ആ

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,7 Permeation time (penetration time) in minutes: 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended. Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.



Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

#### 9.2 Other information

No information available at present.

#### Aerosol. Active substance: liquid. Light brown Coconut scent There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. Does not apply to aerosols. There is no information available on this parameter. Not determined <=20,5 mm2/s (40°C) There is no information available on this parameter. Does not apply to mixtures. There is no information available on this parameter. 0,817 g/ml (Active substance) Does not apply to aerosols. Does not apply to aerosols.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
Heating, open flame, ignition sources
Pressure increase will result in danger of bursting.
10.5 Incompatible materials
Avoid contact with strong oxidizing agents.
10.6 Hazardous decomposition products
No decomposition when used as directed.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



Page 8 of 16						
Safety data sheet according to Re		No 1907/2006	6, Annex II			
Revision date / version: 04.03.20						
Replacing version dated / version	n: 31.07.2023	/ 0008				
Valid from: 04.03.2024						
PDF print date: 08.03.2024						
Motorbike Multispray						
Possibly more information on hea	alth effects, see	e Section 2.1 (	classification).			
Motorbike Multispray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Hydrocarbons, C6-C7, n-alkane	es, isoalkanes	, cyclics, <5%	6 n-hexane			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute	Vapours
		,_			Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute	Irritant
					Dermal	lintant
					Irritation/Corrosion)	
Serious eye damage/irritation:					OECD 405 (Acute Eye	Mild irritant
conous eye damage/imation.					Irritation/Corrosion)	(Analogous
					Initiation/Contosion)	conclusion)
Respiratory or skin					OECD 406 (Skin	Analogous
sensitisation:					Sensitisation)	conclusion, No
					Ocholioau011	(inhalation and
						skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial	Analogous
					Reverse Mutation Test)	conclusion,
						Negative
Carcinogenicity:						Analogous
Caromogenicity.						conclusion,
					OECD 414 (Prenatal	Negative
Poproductivo toviciti "			1			Analogous
Reproductive toxicity:						
Reproductive toxicity:					Developmental Toxicity	conclusion,
Reproductive toxicity:					Study)	Negative
Specific target organ toxicity -						Negative May cause
Specific target organ toxicity -						Negative May cause drowsiness or
Specific target organ toxicity - single exposure (STOT-SE):						Negative May cause drowsiness or dizziness.
Specific target organ toxicity -						Negative May cause drowsiness or



Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

œ.

Symptoms:		drowsiness,
		unconsciousness
		,
		heart/circulatory
		disorders,
		headaches,
		cramps,
		drowsiness,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.
Specific target organ toxicity -		Not irritant
single exposure (STOT-SE),		(respiratory tract).
inhalative:		

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
	2000	20000	ing/ing	Rabbit	Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous
Acute toxicity, by initialation.	L030	24351	mg/ms/+m	Ναι	Inhalation Toxicity)	conclusion,
					initialation roxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant.
Skin corrosion/imitation:						
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin					OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	liogaaro
Carcinogenicity:				typhilliana	OECD 453 (Combined	Negative,
ouromogeniony.					Chronic	Analogous
					Toxicity/Carcinogenicity	conclusion
					Studies)	conclusion
Reproductive toxicity:					OECD 414 (Prenatal	Negative,
					Developmental Toxicity	Analogous
					Study)	conclusion
Openifie townet owner towicity						
Specific target organ toxicity -					OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):					Dose 90-Day Oral	Analogous
					Toxicity Study in	conclusion
					Rodents)	
Aspiration hazard:						Yes
Symptoms:						unconsciousnes
						, headaches,
						dizziness,
						mucous
						membrane
						irritation



#### Page 10 of 16

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

#### Hydrocarbons, C3-4 Toxicity / effect Endpoint Value Unit Organism Test method Notes OECD 474 (Mammalian Germ cell mutagenicity: Negative Rat Erythrocyte Micronucleus Test) NOAEC 10000 OECD 413 (Subchronic Specific target organ toxicity ppm Rat repeated exposure (STOT-RE): Inhalation Toxicity - 90-Day Study) Symptoms: malaise, nausea, dizziness. mucous membrane irritation, drowsiness, unconsciousness

## 11.2. Information on other hazards

Endpoint	Value	Unit	Organism	Test method	Notes
					Does not apply
					to mixtures.
					No other
					relevant
					information
					available on
					adverse effects
					on health.
	Endpoint	Endpoint Value	Endpoint Value Unit	Endpoint Value Unit Organism	Endpoint     Value     Unit     Organism     Test method       Image: Imag

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Other information:						Repeated	
						exposure may	
						cause skin	
						dryness or	
						cracking.	

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification). Motorbike Multispray Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: 12.1. Toxicity to algae: n.d.a. n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a. 12.5. Results of PBT n.d.a. and vPvB assessment Does not apply 12.6. Endocrine disrupting properties: to mixtures. No information 12.7. Other adverse effects: available on other adverse effects on the environment.



Revision date / version: 04 Replacing version dated /		23 / 0008					
Valid from: 04.03.2024 PDF print date: 08.03.202 Motorbike Multispray		23 / 0000					
Other information:		I					DOC-elimination
				24			degree(complex ng organic substance)>= 80%/28d: n.a.
Other information:	AOX		0	%			According to the recipe, contains no AOX.
Hydrocarbons, C6-C7, n	-alkanes, isoalka	nes. cvcli	cs. <5% n-he	xane			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	EL50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EL50	72h	30-100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	81	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion, Readily biodegradable
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Hydrocarbons, C10-C13, Toxicity / effect	, n-alkanes, isoa Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		Notes
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia: 12.1. Toxicity to algae:	NOELR EL50	21d 72h	0,176 >1000	mg/l mg/l	Daphnia magna Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OEĆD 301 F (Ready Biodegradability - Manometric	Readily biodegradable
						Respirometry Test)	



#### Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray 12.5. Results of PBT No PBT and vPvB assessment substance, No vPvB substance Other organisms: **EL50** 48h >1000 mg/l Tetrahymen pyriformis Water solubility: Product floats on the water surface. Hydrocarbons, C3-4 Toxicity / effect Time Value Unit Endpoint Organism Test method Notes 12.2. Persistence and Biodegradable degradability: 12.3. Bioaccumulative A notable potential: biological accumulation potential is not to be expected (LogPow 1-3). 12.4. Mobility in soil: Product is slightly volatile. 12.5. Results of PBT No PBT and vPvB assessment substance, No

## **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

œ

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations. Recommendation: Do not perforate, cut up or weld uncleaned container. Recycling

15 01 04 metallic packaging

## **SECTION 14: Transport information**

# General statements

Transport by road/by rall (ADR/RID)		
14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Classification code:	5F	
LQ:	1 L	



vPvB substance



ആ Page 13 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray 2 Transport category: Transport by sea (IMDG-code) 14.1. UN number or ID number: 1950 14.2. UN proper shipping name: UN 1950 AEROSOLS 14.3. Transport hazard class(es): 2.1 14.4. Packing group: 14.5. Environmental hazards: Not applicable Marine Pollutant: Not applicable F-D, S-U EmS: Transport by air (IATA) 14.1. UN number or ID number: 1950 14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 2.1 14.4. Packing group: 14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage. 14.7. Maritime transport in bulk according to IMO instruments Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

76 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**



Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

അ

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Skin Irrit. — Skin irritation Asp. Tox. — Aspiration hazard Aquatic Chronic - Hazardous to the aquatic environment - chronic Aerosol — Aerosols Flam. Liq. — Flammable liquid STOT SE — Specific target organ toxicity - single exposure - narcotic effects

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council CAS Chemical Abstracts Service



Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMFI Derived Minimum Effect Level DNEL Derived No Effect Level Dissolved organic carbon DOC for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community FC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. **European Union** EU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals Global warming potential GWP Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dry weight mg/kg dw mg/kg wet weight mg/kg wwt not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic orq. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic Polyethylene PF PNEC Predicted No Effect Concentration ppm parts per million **PVC** Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

ആ



Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0009 Replacing version dated / version: 31.07.2023 / 0008 Valid from: 04.03.2024 PDF print date: 08.03.2024 Motorbike Multispray

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Tel. Telephone

GB

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.