

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Grinding Paste

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Abrasive paste

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Page 2 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119456620-43-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	926-141-6
CAS	---
content %	10-15
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	
Registration number (REACH)	01-2120764691-48-XXXX
Index	613-167-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	55965-84-9
content %	0,00015-<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH071 Acute Tox. 2, H310 Acute Tox. 2, H330 Acute Tox. 3, H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
Specific Concentration Limits and ATE	Skin Corr. 1C, H314: >=0,6 % Skin Irrit. 2, H315: >=0,06 % Eye Dam. 1, H318: >=0,6 % Eye Irrit. 2, H319: >=0,06 % Skin Sens. 1A, H317: >=0,0015 % ATE (oral): 53 mg/kg ATE (dermal): 50 mg/kg ATE (as inhalation, Aerosol): 0,17 mg/l/4h ATE (as inhalation, Vapours): 0,5 mg/l/4h

2-methylisothiazol-3(2H)-one	
Registration number (REACH)	01-2120764690-50-XXXX
Index	613-326-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	220-239-6
CAS	2682-20-4
content %	0,00015-<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH071 Acute Tox. 2, H330 Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)

Page 3 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 03.06.2024 / 0016  
Replacing version dated / version: 05.07.2022 / 0015  
Valid from: 03.06.2024  
PDF print date: 04.06.2024  
Grinding Paste

**Specific Concentration Limits and ATE**

Skin Sens. 1A, H317:  $\geq 0,0015\%$   
ATE (oral): 120 mg/kg  
ATE (dermal): 242 mg/kg  
ATE (as inhalation, Dusts or mist): 0,11 mg/l/4h  
ATE (as inhalation, Vapours): 0,5 mg/l/4h

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

**Inhalation**

Supply person with fresh air and consult doctor according to symptoms.

**Skin contact**

Wash thoroughly using copious water - remove contaminated clothing immediately.

**Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

**Ingestion**

Rinse the mouth thoroughly with water.  
Give copious water to drink - consult doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

**4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

CO<sub>2</sub>  
Extinction powder  
Water jet spray  
Large fire:

Water jet spray / alcohol resistant foam

**Unsuitable extinguishing media**

High volume water jet

**5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:  
Oxides of carbon  
Oxides of nitrogen  
Toxic gases

**5.3 Advice for firefighters**

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
Dispose of contaminated extinction water according to official regulations.

**SECTION 6: Accidental release measures**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

## 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
 Ensure sufficient ventilation, remove sources of ignition.  
 Avoid dust formation with solid or powder products.  
 Leave the danger zone if possible, use existing emergency plans if necessary.  
 No special measures required.  
 Avoid contact with eyes or skin.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.

## 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Avoid contact with eyes.  
 Avoid long lasting or intensive contact with skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Store at room temperature.  
 Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 1200 mg/m<sup>3</sup>

GB	Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
	WEL-TWA: 1200 mg/m <sup>3</sup> (>=C7 normal and branched chain alkanes)	WEL-STEL: ---	---
	Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
	BMGV: ---	Other information: ---	

GB	Chemical Name	Aluminium oxide
----	---------------	-----------------

Page 5 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

WEL-TWA: 10 mg/m <sup>3</sup> (total inhal. dust), 4 mg/m <sup>3</sup> (resp. dust) (aluminium oxides)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,00339	mg/l	
	Environment - marine		PNEC	0,00339	mg/l	
	Environment - sediment, freshwater		PNEC	0,027	mg/kg dw	
	Environment - sediment, marine		PNEC	0,027	mg/kg dw	
	Environment - soil		PNEC	0,01	mg/kg dw	
	Environment - sewage treatment plant		PNEC	0,23	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,00339	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,11	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,02	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,04	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,09	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,02	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,04	mg/m <sup>3</sup>	

2-methylisothiazol-3(2H)-one						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	3,39	µg/l	
	Environment - marine		PNEC	3,39	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,39	µg/l	
	Environment - sewage treatment plant		PNEC	0,23	mg/l	
	Environment - soil		PNEC	0,0471	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,027	mg/kg body weight/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,053	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m <sup>3</sup>	

Aluminium oxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note

GB

Page 6 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

	Environment - sewage treatment plant		PNEC	20	mg/l	
Industrial	Human - inhalation	Long term	DNEL	3	mg/m3	
Commercial	Human - inhalation	Long term	DNEL	3	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,75	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,32	mg/kg bw/day	
Consumer	Human - oral	Long term	DNEL	6,22	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	3	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |  
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |  
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 With danger of contact with eyes.  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Protective latex rubber gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 0,25  
 Permeation time (penetration time) in minutes:  
 240  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Page 7 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 03.06.2024 / 0016  
Replacing version dated / version: 05.07.2022 / 0015  
Valid from: 03.06.2024  
PDF print date: 04.06.2024  
Grinding Paste

Skin protection - Other:  
Usual protective working garments

Respiratory protection:  
Normally not necessary.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	White
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	100 °C
Flammability:	Flammable
Lower explosion limit:	0,6 Vol-%
Upper explosion limit:	7 Vol-%
Flash point:	>90 °C (ASTM D 93 (Pensky-Martens, closed cup))
Auto-ignition temperature:	>200 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	7,8
Kinematic viscosity:	24000-28000 mPas (20°C, Dynamic viscosity )
Kinematic viscosity:	>20,5 mm <sup>2</sup> /s (40°C)
Solubility:	Mixable
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	0,4 hPa (20°C)
Density and/or relative density:	1,10 g/cm <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

### 9.2 Other information

Explosives:	Product is not explosive.
Oxidising liquids:	No
Bulk density:	n.a.
Solvents content:	20,20 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not to be expected

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

None known

### 10.5 Incompatible materials

Page 8 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

None known

## 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Grinding Paste						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m <sup>3</sup> /8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	in vivo	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative

Page 9 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

**Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	53-64	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	53	mg/kg			
Acute toxicity, by dermal route:	ATE	50	mg/kg			
Acute toxicity, by dermal route:	LD50	87	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,17-0,33	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	ATE	0,17	mg/l/4h			Aerosol
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1C
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1A
Germ cell mutagenicity:				Mouse	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells In Vivo)	Negative
Aspiration hazard:						No
Symptoms:						diarrhoea, mucous membrane irritation, watering eyes, eyes, reddened

**2-methylisothiazol-3(2H)-one**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	120	mg/kg	Rat	U.S. EPA Guideline OPPTS 870.1100	Female
Acute toxicity, by oral route:	LD50	183	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	120	mg/kg			
Acute toxicity, by dermal route:	ATE	242	mg/kg			
Acute toxicity, by dermal route:	LD50	242	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	0,11	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours

Page 10 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

Acute toxicity, by inhalation:	ATE	0,11	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive
Serious eye damage/irritation:				Rabbit		Risk of serious damage to eyes.
Serious eye damage/irritation:						Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	200	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	60	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Symptoms:						mucous membrane irritation, watering eyes

Aluminium oxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	NOAEL	30	mg/kg	Rat		Analogous conclusion
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	NOAEC	70	mg/m3	Rat		subchronic
Acute toxicity, by inhalation:	LC50	7,6	mg/l/4h	Rat		Aerosol, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:					in vivo	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	70	mg/m3	Rat		Lung damage
Symptoms:						constipation

## 11.2. Information on other hazards

Grinding Paste						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

Page 11 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

### SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Grinding Paste							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Page 12 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		6-8				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

**Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,19-0,22	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,098	mg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,004	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,1-0,16	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	0,048	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,0012	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	48h	0,49	µg/l	Skeletonema costatum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			>60	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Biodegradable
12.3. Bioaccumulative potential:	BCF		3,6				calculated value
12.3. Bioaccumulative potential:	Log Pow		-0,486-0,401			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Page 13 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

Toxicity to bacteria:	EC50	3h	7,92	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	----	------	------	------------------	--	--

**2-methylisothiazol-3(2H)-one**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,38	mg/l	Pimephales promelas	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	4,77	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,55	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,359	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,445	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,03	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	120h	0,05	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		48h	97	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	Readily biodegradable
12.2. Persistence and degradability:			< 0,08	d		OECD 307 (Aerobic and Anaerobic Transformation in Soil)	
12.2. Persistence and degradability:			1,28-2,1	d		OECD 308 (Aerobic and Anaerobic Transformation in Aquatic Sediment Systems)	
12.2. Persistence and degradability:			4,1	d		OECD 309 (Aerobic Mineralisation in Surface Water - Simulation Biodegradation Test)	
12.2. Persistence and degradability:		28d	0,32	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

Page 14 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

12.3. Bioaccumulative potential:	Log Pow		-0,32			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	Slight
12.3. Bioaccumulative potential:	BCF		3,16				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	34,6	mg/l	activated sludge		DIN 38412-3 (TTC-Test)
Toxicity to bacteria:	EC20	3h	2,8	mg/l	activated sludge		DIN 38412-3 (TTC-Test)

Aluminium oxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	218,6	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	>0,135	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50		>100	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50		>100	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=0,052	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 03 06 organic wastes other than those mentioned in 16 03 05

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Page 15 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 03.06.2024 / 0016  
 Replacing version dated / version: 05.07.2022 / 0015  
 Valid from: 03.06.2024  
 PDF print date: 04.06.2024  
 Grinding Paste

Recommended cleaner:  
 Water

## SECTION 14: Transport information

### General statements

#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable

#### Transport by air (IATA)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
 General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 14,18 %

#### REGULATION (EC) No 648/2004

15 % or over but less than 30 %  
 aliphatic hydrocarbons  
 less than 5 %  
 non-ionic surfactants

FORMALDEHYDE  
 BENZISOTHIAZOLINONE  
 METHYLISOTHIAZOLINONE  
 METHYLCHLOROISOTHIAZOLINONE/ METHYLISOTHIAZOLINONE  
 TETRAMETHYLOLGLYCOLURIL

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label.  
 Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012.

Page 16 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 03.06.2024 / 0016  
Replacing version dated / version: 05.07.2022 / 0015  
Valid from: 03.06.2024  
PDF print date: 04.06.2024  
Grinding Paste

Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods. These are indicated in the approval of the active substance.

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 15

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H330 Fatal if inhaled.  
H310 Fatal in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H318 Causes serious eye damage.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH071 Corrosive to the respiratory tract.

Asp. Tox. — Aspiration hazard  
Acute Tox. — Acute toxicity - dermal  
Acute Tox. — Acute toxicity - inhalation  
Acute Tox. — Acute toxicity - oral  
Skin Corr. — Skin corrosion  
Eye Dam. — Serious eye damage  
Skin Sens. — Skin sensitization  
Aquatic Acute — Hazardous to the aquatic environment - acute  
Aquatic Chronic — Hazardous to the aquatic environment - chronic

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately

Art., Art. no.	Article number
ASTM	ASTM International (American Society for Testing and Materials)
ATE	Acute Toxicity Estimate
BAM	Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF	Bioconcentration factor
BSEF	The International Bromine Council
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50)	Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC	European Community
ECHA	European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)	Effect Concentration/Level for x % effect
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50)	Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc.	et cetera
EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
Koc	Adsorption coefficient of organic carbon in the soil
Kow	octanol-water partition coefficient
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc	Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow	Logarithm of octanol-water partition coefficient
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw	mg/kg body weight
mg/kg bw/d, mg/kg bw/day	mg/kg body weight/day
mg/kg dw	mg/kg dry weight
mg/kg wwt	mg/kg wet weight
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute for Occupational Safety and Health (USA)
NLP	No-longer-Polymer
NOEC, NOEL	No Observed Effect Concentration/Level
OECD	Organisation for Economic Co-operation and Development
org.	organic
OSHA	Occupational Safety and Health Administration (USA)
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration

Page 18 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.06.2024 / 0016

Replacing version dated / version: 05.07.2022 / 0015

Valid from: 03.06.2024

PDF print date: 04.06.2024

Grinding Paste

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax:**

**+49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.