

Page 1 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SUPER LEICHTLAUF 10W40 20 L

Art.: 1304

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

(GB)

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet $\overline{}$

œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

(GB)

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

Hazardous to drinking water, on escape of even small quantities.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	64742-55-8
content %	0-26
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Substance with specific conc. limit(s) acc. to REACh-
	registration
Registration number (REACH)	01-2119543726-33-XXXX
Index	
EINECS, ELINCS, NLP	298-577-9
CAS	93819-94-4
content %	0,1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.



Page 3 of 12

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

Ingestion

Rinse the mouth thoroughly with water. Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Irritation of the eyes With long-term contact: Drying of the skin. Dermatitis (skin inflammation) With oil mist formation: Irritation of the respiratory tract

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Foam Dry extinguisher Large fire: Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Oxides of phosphorus Toxic gases Hot product gives off combustible vapours. **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist. Remove possible causes of ignition - do not smoke. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Oil binder

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.



Page 4 of 12

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid contact with eyes.

Avoid formation of oil mist. Avoid long lasting or intensive contact with skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Do not heat to temperatures close to flash point. Do not carry cleaning cloths soaked in product in trouser pockets.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Protect against moisture and store closed.

Store at room temperature. 7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	
Monitoring procedures:	 Draeger - Oil 10/a-P (67 28 371) 	
	- Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Zinc bis[O-(6-methylhepty)] bis[O-(sec-butyl)] bis(dithiop	hosphate)				
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,004	mg/l	
	Environment - marine		PNEC	0,0046	mg/l	
	Environment - sediment,		PNEC	0,0116	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	0,00116	mg/kg	
	marine					
	Environment - sewage		PNEC	100	mg/l	
	treatment plant					
	Environment - soil		PNEC	0,00528	mg/kg	
	Environment - oral (animal		PNEC	10,67	mg/kg	
	feed)					



Page 5 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,11	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,29	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,24	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,31	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,58	mg/kg	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

(GB)

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) If applicable Protective nitrile gloves (EN 374) Protective Neoprene® / polychloroprene gloves (EN 374). Protective PVC gloves (EN 374) Minimum layer thickness in mm: 0,35 Permeation time (penetration time) in minutes: >= 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.



Page 6 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties:

(GB)

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Liquid Brown Characteristic Not determined Not determined Not determined Not determined 222 °C Not determined n.a. Not determined Not determined Not determined Not determined 0,871 g/ml n.a. Not determined Insoluble Not determined Not determined Not determined 94,7 mm2/s (40°C) 13,83 mm2/s (100°C) Product is not explosive. No

Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling.

10.3 Possibility of hazardous reactions No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7. Protect from humidity. Open flame, ignition sources

10.5 Incompatible materials

See also section 7. Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).



Page 7 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

SUPER LEICHTLAUF 10W40 20 L

œ

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotreated light paraffinic									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat					
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral				
					Toxicity)				
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	OECD 402 (Acute				
					Dermal Toxicity)				
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat	OECD 403 (Acute	Aerosol			
					Inhalation Toxicity)				
Specific target organ toxicity -	LOAEL	125	mg/kg/d	Rat	OECD 408 (Repeated				
repeated exposure (STOT-RE):					Dose 90-Day Oral				
					Toxicity Study in				
					Rodents)				
Aspiration hazard:						Yes			

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2600	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>2	mg/l/1h	Rat	OECD 403 (Acute	Male
					Inhalation Toxicity)	
Skin corrosion/irritation:		>=6,25	%	Rabbit	OECD 404 (Acute	Analogous
					Dermal	conclusion,
					Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit		Eye Dam. 1,
						Analogous
						conclusion16
						CFR 1500.42
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin	Not sensitizising
					Sensitisation)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Reproductive toxicity	NOAEL	160	mg/kg	Rat	OECD 422 (Combined	Analogous
(Developmental toxicity):					Repeated Dose Tox.	conclusion,
					Study with the	Negative
					Reproduction/Developm.	
					Tox. Screening Test)	

SECTION 12: Ecological information



Page 8 of 12

B

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

Possibly more in	formation on environmental effects, se	ee Section 2.1 (classification).
SUPER LEICH	[LAUF 10W40 20 L		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Not totally
degradability:							biodegradable.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Distillates (petroleum), h	Distillates (petroleum), hydrotreated light paraffinic										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:	LC50		>100	mg/l							
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l		OECD 202					
						(Daphnia sp.					
						Acute					
						Immobilisation					
						Test)					

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	5,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	2,1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1,5	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,59-1,2			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			10	mg/l	activated sludge		

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts



Page 9 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. Implement substance recycling. E.g. suitable incineration plant. Observe regulations for disposal of old oil/waste. For contaminated packing material

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 01 paper and cardboard packaging 15 01 02 plastic packaging

15 01 04 metallic packaging

(GB)

SECTION 14: Transport information

General statements

14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ (ADR 2015):	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.



Page 10 of 12

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304

SECTION 16: Other information

Revised sections:

3, 9, 11, 12

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

AC Article Categories according, according to acc., acc. to ACGIH American Conference of Governmental Industrial Hygienists Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight CAS **Chemical Abstracts Service** CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level Dissolved organic carbon DOC DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw drv weight e.g. for example (abbreviation of Latin 'exempli gratia'), for instance ЕČ European Community ECHA European Chemicals Agency



Page 11 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304 European Economic Area FFA EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario et cetera etc. EU **European Union** EWC European Waste Catalogue Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) Inhibitory concentration IC IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLID International Uniform ChemicaL Information Database LC lethal concentration LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration Lethal Dose of a chemical 1 D LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) No Observed Adverse Effective Concentration NOAEC NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP **Ozone Depletion Potential** OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic Chemical product category PC ΡE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential ppm parts per million PROC Process category PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature

(GB)



Page 12 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 27.09.2016 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 27.09.2016 PDF print date: 28.09.2016 SUPER LEICHTLAUF 10W40 20 L Art.: 1304 Structure Activity Relationship SAR SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

(GB)