

Page 1 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Motorbike 2T-Additiv 250 mL

Art.: 1582

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives

അ

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet $(\ensuremath{\mathbb{R}})$

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC)Hazard classHazard categoryHazard statementAsp. Tox.1H304-May be fatal if swallowed and enters airways.Aquatic Chronic3H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10, aromatics, >1% naphthalene Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

ആ

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	919-284-0 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411
Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP	202-049-5
CAS	91-20-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351
	Acute Tox. 4, H302
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.



Page 3 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Protective hand cream recommended.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Irritation of the eyes Irritation of the respiratory tract

Headaches Dizziness Effects/damages the central nervous system Coordination disorders Unconsciousness Liver and kidney damage Blood count modifications Nausea Vomiting Danger of aspiration. Oedema of the lungs

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion: Activated carbon

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2 Extinction powder Foam Water jet spray Unsuitable extinguishing media



Page 4 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

High volume water jet 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Hydrocarbons Toxic pyrolysis products. Explosive vapour/air or gas/air mixtures. Dangerous vapours heavier than air. In case of spreading near the ground, flashback to distance sources of ignition is possible. **5.3** Advice for firefighters

5.3 Advice for firefighters

ആ

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Ensure sufficient ventilation. 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells.



Page 5 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

Solvent resistant floor Do not store with oxidizing agents. Store in a well ventilated place. Protect from direct sunlight and warming.

7.3 Specific end use(s)

œ

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

GB Chemical Name	Hydrocarbons, C1	0-C13, n-alkanes, isoalkanes, cyclid	cs, <2% aromatics	Content %:80- <100
WEL-TWA: 800 mg/m3		WEL-STEL:		 (100
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03	581)	
		Draeger - Hydrocarbons 0,1%/c (81		
	- (Compur - KITA-187 S (551 174)		
BMGV:			Other information: (O paragraphs 84-87, EH4	o RCP-method,
Chemical Name	Hydrocarbons, C1	0, aromatics, >1% naphthalene		 Content %:1-<2,5
WEL-TWA: 500 mg/m3 (Aromatics	;) ·	WEL-STEL:		
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03	581)	
	- 1	Draeger - Hydrocarbons 0,1%/c (81	03 571)	
	- (Compur - KITA-187 S (551 174)		
BMGV:			Other information:	
⁽³⁸⁾ Chemical Name	Naphthalene			Content %:0,1- <0,25
WEL-TWA: 500 mg/m3 (Aromatics (50 mg/m3) (EU)	s) (WEL), 10 ppm	WEL-STEL:		
Monitoring procedures:	- (Compur - KITA-153 U(C) (551 182)		
BMGV:			Other information:	
Chemical Name	Hydrocarbons, C1	1-C14, n-alkanes, isoalkanes, cyclic	cs, <2% aromatics	Content %:
WEL-TWA: 1200 mg/m3 (>=C7 nc			,	
chain alkanes)				
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03	581)	
		Draeger - Hydrocarbons 0,1%/c (81	03 571)	
	- (Compur - KITA-187 S (551 174)		
BMGV:			Other information:	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,24	µg/l	
	Environment - sewage		PNEC	2,9	mg/l	
	treatment plant				_	
	Environment - sediment,		PNEC	0,0672	mg/kg dry	
	freshwater				weight	
	Environment - sediment,		PNEC	0,0672	mg/kg dry	
	marine				weight	
	Environment - soil		PNEC	0,0533	mg/kg dry	
					weight	
Workers / employees	Human - dermal	Long term, systemic	DNEL	3,57	mg/kg	
		effects			bw/day	



Page 6 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

ആ

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective Viton® / fluoroelastomer gloves (EN 374) Permeation time (penetration time) in minutes: >480 Minimum layer thickness in mm: 0,4 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.



Page 7 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

ആ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Physical state: Liquid

Physical state: Colour: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties:

Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

Light yellow Clear Characteristic Not determined n.a. Not determined 145 °C >61 °C Not determined n.a. Not determined Not determined Not determined Vapours heavier than air. 0,765 g/ml (20°C) n.a. Not determined Insoluble Not determined Not determined Not determined <7 mm2/s (40°C) Product is not explosive. When using: development of explosive vapour/air mixture possible. No

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Heating, open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** No decomposition when used as directed.



Page 8 of 15

œ)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

SECTION 11: Toxicological information

11.1 Information on toxicological effects Possibly more information on health effects, see Section 2.1 (classification). Motorbike 2T-Additiv 250 mL

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the
						real
						Naphthalene
						content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous
					Inhalation Toxicity)	conclusion,
						Vapours
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin					OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Analogous
-						conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative,
					Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Carcinogenicity:					OECD 453 (Combined	Negative,
					Chronic	Analogous
					Toxicity/Carcinogenicity	conclusion
					Studies)	



Page 9 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

œ.

Reproductive toxicity:		OECD 414 (Prenatal	Negative,
		Developmental Toxicity	Analogous
		Study)	conclusion
Specific target organ toxicity -		OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):		Dose 90-Day Oral	Analogous
		Toxicity Study in	conclusion
		Rodents)	
Aspiration hazard:			Yes
Symptoms:			unconsciousness
			, headaches,
			dizziness
Other information:			Repeated
			exposure may
			cause skin
			dryness or
			cracking.

Hydrocarbons, C10, aromatics	, >1% naphtha	alene				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	~7093	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute	
			-		Inhalation Toxicity)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Rat		Not sensitizising
Germ cell mutagenicity:				Salmonella typhimurium	in vivo	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.



B Page 10 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

Specific target organ toxicity -		OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE):		Dose 90-Day Oral	conclusion, Not
		Toxicity Study in	to be expected
		Rodents)	
Aspiration hazard:			Yes
Symptoms:			drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

SECTION 12: Ecological information

Motorbike 2T-Additiv 250) mL						
Art.: 1582							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment	•						No PBT substance, No vPvB substance
Water solubility:							Product floats on the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna	,	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable



Page 11 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

œ

12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

Hydrocarbons, C10, aromatics, >1% naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EL50	48h	10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>1-<3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		6-8				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements



-(B)					
Page 12 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582	1				
14.1. UN number:	n.a.				
Transport by road/by rail (ADR/RID)					
14.2. UN proper shipping name:					
14.3. Transport hazard class(es):	n.a.				
14.4. Packing group:	n.a.				
Classification code:	n.a.				
LQ:	n.a.				
14.5. Environmental hazards:	Not applicable				
Tunnel restriction code:					
Transport by sea (IMDG-code)					
14.2. UN proper shipping name:					
14.3. Transport hazard class(es):	n.a.				
14.4. Packing group:	n.a.				
Marine Pollutant:	n.a				
14.5. Environmental hazards:	Not applicable				
Transport by air (IATA)					
14.2. UN proper shipping name:					
14.3. Transport hazard class(es):	n.a.				
14.4. Packing group:	n.a.				
14.5. Environmental hazards:	Not applicable				
14.6. Special precautions for user					
Unless specified otherwise, general measures for safe transport must be followed.					
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code					
Non-dangerous material according to Transport Regulations.					

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

.

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

1, 2, 15

~ 96 %

~ 764,1 g/l



Page 13 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582 H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. Asp. Tox. — Aspiration hazard Aquatic Chronic - Hazardous to the aquatic environment - chronic STOT SE - Specific target organ toxicity - single exposure - narcotic effects Carc. — Carcinogenicity Acute Tox. - Acute toxicity - oral Aquatic Acute - Hazardous to the aquatic environment - acute Any abbreviations and acronyms used in this document: AC **Article Categories** according, according to acc., acc. to ACGIH American Conference of Governmental Industrial Hygienists Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight Chemical Abstracts Service CAS Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CEC CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic Chemical oxygen demand COD CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. European Community EC ECHA European Chemicals Agency EEA European Economic Area European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) **Environmental Release Categories** ERC ES Exposure scenario et cetera etc. EU **European Union**

ആ



Page 14 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582 EWC European Waste Catalogue Fax. Fax number general aen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform ChemicaL Information Database LC lethal concentration lethal concentration 50 percent kill LC50 LCLo lowest published lethal concentration Lethal Dose of a chemical LD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. no data available n.d.a. NIOSH National Institute of Occupational Safety and Health (United States of America) NOAECNo Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP **Ozone Depletion Potential** OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon persistent, bioaccumulative and toxic PBT PC Chemical product category Polyethylene ΡE PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential ppm parts per million Process category PROC PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature Structure Activity Relationship SAR SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF

ദ്ര



Page 15 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.03.2019 / 0028 Replacing version dated / version: 09.07.2018 / 0027 Valid from: 21.03.2019 PDF print date: 21.03.2019 Motorbike 2T-Additiv 250 mL Art.: 1582

VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.