

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Motorbike Luft-Filter-Oel 500 mL Art.: 1625

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Sector of use [SU]:

അ

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC24 - Lubricants, greases, release products Process category [PROC]: PROC 7 - Industrial spraying PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC10 - Roller application or brushing PROC11 - Non industrial spraying PROC13 - Treatment of articles by dipping and pouring PROC17 - Lubrication at high energy conditions in metal working operation PROC18 - General greasing/lubrication at high kinetic energy conditions PROC19 - Manual activities involving hand contact Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 2 - Formulation into mixture ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 5 - Use at industrial site leading to inclusion into/onto article ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8c - Widespread use leading to inclusion into/onto article (indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) Hazard class Hazard category Hazard statement

nazaru calegory	
2	H225-Highly flammable liquid and vapour.
2	H315-Causes skin irritation.
3	H336-May cause drowsiness or dizziness.
2	H411-Toxic to aquatic life with long lasting effects.
	2 2 3 2

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Dangei

H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves. P312-Call a POISON CENTRE / doctor if you feel unwell. P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	
content %	50-60



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

Classification according to Regulation (EC) 1272/2008 (CLP)

Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

œ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration. 4.2 Most important symptoms and effects, both acute and delayed

Irritation of the respiratory tract Coughing Headaches Respiratory distress Effects/damages the central nervous system With long-term contact: Dermatitis (skin inflammation) Product removes fat. In certain cases, the symptoms of poisoning r

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

ECO2 Extinction powder Foam Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Toxic gases Explosive vapour/air or gas/air mixtures. In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

അ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling 7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special storage conditions.

Solvent resistant floor

Do not store with oxidizing agents.

Store in a well ventilated place.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

ആ

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 600 mg/m3

Chemical Name	Hydrocarbons, C	6-C7, n-alkanes, isoalkanes, cyclics	, <5% n-hexane		Content %:50-60
WEL-TWA: 600 mg/m3		WEL-STEL:			
Monitoring procedures:	-	Compur - KITA-187 S (551 174)		•	
BMGV:			Other information: (C	DEL acc. t	o RCP-method,
			paragraphs 84-87, EH	40)	
Chemical Name	Oil mist, mineral				Content %:
				-	Content 76.
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:			
working fluids, ACGIH)	-				
Monitoring procedures:	-	Draeger - Oil 10/a-P (67 28 371)		•	
	-	Draeger - Oil Mist 1/a (67 33 031)			
BMGV:			Other information:		

	alkanes, isoalkanes, cyclics,					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
Consumer	Human - dermal	Long term, systemic	DNEL	699	mg/kg	
		effects			bw/day	
Consumer	Human - inhalation	Long term, systemic	DNEL	608	mg/m3	
		effects				
Consumer	Human - oral	Long term, systemic	DNEL	699	mg/kg	
		effects			bw/day	
Workers / employees	Human - dermal	Long term, systemic	DNEL	773	mg/kg	
		effects			bw/day	
Workers / employees	Human - dermal	Long term, systemic	DNEL	300	mg/kg	
		effects			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2035	mg/m3	
		effects				

B WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective nitrile gloves (EN 374). Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: >= 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective Viton® / fluoroelastomer gloves (EN 374) Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

3.1 mormation on basic physical and chemis	
Physical state:	Liquid
Colour:	8 (Blue)
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	-9 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,8 Vol-% (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%
	n-hexane)
Upper explosive limit:	7,7 Vol-% (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%
	n-hexane)
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,786 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined



Page 7 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

Water solubility:

œ

Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties: Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Insoluble Not determined Not determined 48 mm2/s (40°C) n.a. No

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7. Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

oxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification
						according to
						calculation
						procedure.



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

œ)

Hydrocarbons, C6-C7, n-alkane				1		
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity -						STOT SE 3,
single exposure (STOT-SE): Specific target organ toxicity -						H336
repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness
						, heart/circulatory disorders, headaches, cramps,
						drowsiness, mucous membrane
						irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract)

SECTION 12: Ecological information

Motorbike Luft-Filter-Oel 500 mL							
Art.: 1625							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
2.2. Persistence and							Mechanical
egradability:							precipitation
							possible.
2.3. Bioaccumulative							n.d.a.
otential:							
2.4. Mobility in soil:							n.d.a.



Page 9 of 13 Safety data sheet accordin Revision date / version: 18 Replacing version dated / Valid from: 18.07.2019 PDF print date: 19.07.201	3.07.2019 / 0012 version: 25.06.20 9			ex II			
Motorbike Luft-Filter-Oel 5 Art.: 1625	600 mL						
Art.: 1625							
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.
Hudrooarbone C6 C7 n	alkanas isaalk	noc ovoli	oc - 50/ n ha	vana			
Hydrocarbons, C6-C7, n Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	DOC				Organisti		DOC-elimination degree(complexi ng organic substance)>= 80%/28d:
12.3. Bioaccumulative potential:							Concentration in organisms possible.
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna		•
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,32	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	BCF		242-253				
12.4. Mobility in soil:							Adsorption in ground., Product is slightly volatile
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

œ

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

allocated under certain circumstances. (2014/955/EU) 07 06 04 other organic solvents, washing liquids and mother liquors Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material Pay attention to local and national official regulations.

Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. Residues may present a risk of explosion.

SECTION 14: Transport information

General statements

അ

14.1. UN number: 1993 Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name: UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM)) 14.3. Transport hazard class(es): 3 14.4. Packing group: Ш Classification code: F1 LQ: 1 L 14.5. Environmental hazards: environmentally hazardous Tunnel restriction code: D/F Transport by sea (IMDG-code) 14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM)) 14.3. Transport hazard class(es): 3 14.4. Packing group: Ш EmS: F-E, S-E Marine Pollutant: Yes 14.5. Environmental hazards: environmentally hazardous Transport by air (IATA) 14.2. UN proper shipping name: Flammable liquid, n.o.s. (NAPHTHA (PETROLEUM)) 14.3. Transport hazard class(es): 3 14.4. Packing group: Ш 14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage. 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.



Page 11 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

	Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
			dangerous substances as	dangerous substances as
			referred to in Article 3(10) for the	referred to in Article 3(10) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
[P5c		5000	50000
	E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 55 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

2

Revised sections:

അ

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid Skin Irrit. — Skin irritation STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aquatic Chronic — Hazardous to the aquatic environment - chronic Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials)



ആ Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625 Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) The International Bromine Council BSFF body weight bw CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight e.g. EC for example (abbreviation of Latin 'exempli gratia'), for instance European Community ECHA European Chemicals Agency European Economic Community FFC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) etc. et cetera EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer International Air Transport Association ΙΑΤΑ IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic persistent, bioaccumulative and toxic PBT ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility. These statements were made by:



Page 13 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0012 Replacing version dated / version: 25.06.2018 / 0011 Valid from: 18.07.2019 PDF print date: 19.07.2019 Motorbike Luft-Filter-Oel 500 mL Art.: 1625

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.