

Page 1 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Leichtlauf Performance 10W-40 1 L

Art.: 2338

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

അ

Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



Page 2 of 12

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange. Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Substance with specific conc. limit(s) acc. to REACh- registration
Registration number (REACH)	01-2119543726-33-XXXX
Index	
EINECS, ELINCS, NLP	298-577-9
CAS	93819-94-4
content %	0,5-1,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately.



Page 3 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Danger of aspiration 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. With long-term contact:

Drying of the skin.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Foam

ആ

Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Oxides of phosphorus Hydrocarbons Toxic gases Flammable vapour/air mixtures

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Oil binder

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.



Page 4 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Avoid contact with eyes.

ആ

Avoid long lasting or intensive contact with skin. Do not carry cleaning cloths soaked in product in trouser pockets. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Protect against moisture and store closed. Do not store over 50°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH) -	
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371)	
	- Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,004	mg/l	
	Environment - marine		PNEC	0,0046	mg/l	
	Environment - sediment, freshwater		PNEC	0,0116	mg/kg	
	Environment - sediment, marine		PNEC	0,00116	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - soil		PNEC	0,00528	mg/kg	
	Environment - oral (animal feed)		PNEC	10,67	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	21	µg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,11	mg/m3	



Page 5 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Consumer	Human - dermal	Long term, systemic effects	DNEL	0,29	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,24	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,31	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,58	mg/kg	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

ആ

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) If applicable Protective nitrile gloves (EN 374) Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls



Page 6 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

No information available at present.

œ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties: 9.2 Other information Miscibility: Fat solubility / solvent:

Conductivity: Surface tension: Solvents content:

Liquid Brown Characteristic Not determined Not determined Not determined Not determined 225 °C Not determined n.a. Not determined Not determined Not determined Not determined 0,865 g/ml n.a. Not determined Insoluble Not determined Not determined Not determined 90 mm2/s (40°C) 14,0 mm2/s (100°C) Product is not explosive. No

Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. 10.4 Conditions to avoid See also section 7. Open flame, ignition sources **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed. **SECTION 11: Toxicological information**

11.1 Information on toxicological effects



Revision date / version: 17.05.20 Replacing version dated / version Valid from: 17.05.2018 PDF print date: 01.06.2018	n: 23.03.2018		, Annex II			
Leichtlauf Performance 10W-40	1 L					
Art.: 2338						
Possibly more information on hea	alth effects see	Section 2.1 (classification)			
Leichtlauf Performance 10W-4	0 1 L					
Art.: 2338						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
7 :	-10 (
Zinc bis[O-(6-methylheptyl)] bi				Organiam	To at math ad	Nataa
Tavialty / affect	Endpoint	Value	Unit	Organism	Test method	Notes
			malle			
Acute toxicity, by oral route:	LD50	2600	mg/kg	Rat		
Acute toxicity, by oral route:		>3160	mg/kg mg/kg	Rabbit	OECD 402 (Acute	
Acute toxicity, by oral route: Acute toxicity, by dermal route:	LD50 LD50	>3160	mg/kg	Rabbit	Dermal Toxicity)	Molo
Acute toxicity, by oral route: Acute toxicity, by dermal route:	LD50				Dermal Toxicity) OECD 403 (Acute	Male
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation:	LD50 LD50	>3160 >2	mg/kg mg/l/1h	Rabbit Rat	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity)	
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation:	LD50 LD50	>3160	mg/kg	Rabbit	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute	Skin Irrit. 2,
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation:	LD50 LD50	>3160 >2	mg/kg mg/l/1h	Rabbit Rat	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal	Skin Irrit. 2, Analogous
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute	Skin Irrit. 2, Analogous conclusion
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation:	LD50 LD50	>3160 >2	mg/kg mg/l/1h	Rabbit Rat	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal	Skin Irrit. 2, Analogous conclusion Eye Dam. 1,
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16
Toxicity / effect Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit Guinea pig Guinea pig	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation)	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative,
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit Guinea pig Guinea pig	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative, Analogous
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation: Germ cell mutagenicity:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative, Analogous conclusion
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse Salmonella	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test) OECD 471 (Bacterial	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative, Analogous conclusion Negative,
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation: Germ cell mutagenicity:	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative, Analogous conclusion Negative, Analogous
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation: Germ cell mutagenicity: Germ cell mutagenicity:	LD50 LD50 LC50	>3160 >2 >=6,25 504	mg/kg mg/l/1h % h	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse Salmonella typhimurium	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test) OECD 471 (Bacterial Reverse Mutation Test)	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contac Negative, Analogous conclusion Negative, Analogous conclusion
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation: Germ cell mutagenicity: Germ cell mutagenicity: Reproductive toxicity	LD50 LD50	>3160 >2 >=6,25	mg/kg mg/l/1h %	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse Salmonella	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test) OECD 471 (Bacterial Reverse Mutation Test) OECD 422 (Combined	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative, Analogous conclusion Negative, Analogous conclusion Analogous
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation: Germ cell mutagenicity: Germ cell mutagenicity:	LD50 LD50 LC50	>3160 >2 >=6,25 504	mg/kg mg/l/1h % h	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse Salmonella typhimurium	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test) OECD 471 (Bacterial Reverse Mutation Test) OECD 422 (Combined Repeated Dose Tox.	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contact Negative, Analogous conclusion Negative, Analogous conclusion Analogous conclusion
Acute toxicity, by oral route: Acute toxicity, by dermal route: Acute toxicity, by inhalation: Skin corrosion/irritation: Serious eye damage/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation: Germ cell mutagenicity: Germ cell mutagenicity: Reproductive toxicity	LD50 LD50 LC50	>3160 >2 >=6,25 504	mg/kg mg/l/1h % h	Rabbit Rat Guinea pig Rabbit Guinea pig Mouse Salmonella typhimurium	Dermal Toxicity) OECD 403 (Acute Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion) OECD 406 (Skin Sensitisation) OECD 474 (Mammalian Erythrocyte Micronucleus Test) OECD 471 (Bacterial Reverse Mutation Test) OECD 422 (Combined	Skin Irrit. 2, Analogous conclusion Eye Dam. 1, Analogous conclusion16 CFR 1500.42 No (skin contac Negative, Analogous conclusion Negative, Analogous conclusion Analogous

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).								
Leichtlauf Performance 10W-40 1 L								
Art.: 2338								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	
12.1. Toxicity to daphnia:							n.d.a.	
12.1. Toxicity to algae:							n.d.a.	
12.2. Persistence and							Isolate as much	
degradability:							as possible with	
							an oil separator.	



Page 8 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

œ

 12.3. Bioaccumulative potential:
 n.d.a.

 12.4. Mobility in soil:
 n.d.a.

 12.5. Results of PBT and vPvB assessment
 n.d.a.

 12.6. Other adverse effects:
 n.d.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,5	mg/l	Oncorhynchus	OECD 203 (Fish,	Analogous
					mykiss	Acute Toxicity Test)	conclusion
12.1. Toxicity to daphnia:	EL50	48h	5,4	mg/l	Daphnia magna	OECD 202	Analogous
, ,				Ū		(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EbC50	96h	2,1	mg/l	Selenastrum	OECD 201 (Alga,	Analogous
					capricornutum	Growth Inhibition	conclusion
						Test)	
12.2. Persistence and		28d	1,5	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability - Co2 Evolution	
						Test)	
12.3. Bioaccumulative	Log Pow		0,59-1,2			OECD 107	
potential:	Logion		0,00 1,2			(Partition	
						Coefficient (n-	
						octanol/water) -	
						Shake Flask	
						Method)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No vPvB substanc
Toxicity to bacteria:			10	mg/l	activated sludge		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

Observe regulations for disposal of old oil/waste.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information



Page 9 of 12

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

General statements

14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
116 Spacial processions for user	

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2, 3, 8, 9, 11, 12

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H315 Causes skin irritation. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage Aquatic Chronic — Hazardous to the aquatic environment - chronic

0 %



Page 10 of 12

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Any abbreviations and acronyms used in this document:

AC **Article Categories** acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) **Bioconcentration factor** BCF Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BGV Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum body weight bw **Chemical Abstracts Service** CAS Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CEC CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level Dissolved organic carbon DOC DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw dry weight e.g. EC for example (abbreviation of Latin 'exempli gratia'), for instance European Community ECHA European Chemicals Agency EEA European Economic Area EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN **European Norms** United States Environmental Protection Agency (United States of America) FPA ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera EU **European Union** EWC European Waste Catalogue Fax. Fax number general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS Global warming potential GWP Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWP Halocarbon Global Warming Potential International Agency for Research on Cancer IARC IATA International Air Transport Association Intermediate Bulk Container IBC International Bulk Chemical (Code) IBC (Code)



ആ Page 11 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338 Inhibitory concentration IC IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLID International Uniform ChemicaL Information Database** lethal concentration LC LC50 lethal concentration 50 percent kill lowest published lethal concentration LCLo Lethal Dose of a chemical I D LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. no data available n.d.a. NIOSH National Institute of Occupational Safety and Health (United States of America) NOAECNo Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level **Ozone Depletion Potential** ODP OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic Chemical product category PC ΡE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List **REACH-IT List-No.** Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature Structure Activity Relationship SAR SU Sector of use SVHC Substances of Very High Concern Telephone Tel. ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VhF VOC Volatile organic compounds very persistent and very bioaccumulative vPvB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility. These statements were made by:



Page 12 of 12

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 17.05.2018 / 0007 Replacing version dated / version: 23.03.2018 / 0006 Valid from: 17.05.2018 PDF print date: 01.06.2018 Leichtlauf Performance 10W-40 1 L Art.: 2338

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.