

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Wartungsspray weiss

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

അ

Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC24 - Lubricants, greases, release products Process category [PROC]: PROC 7 - Industrial spraying PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC10 - Roller application or brushing PROC11 - Non industrial spraying Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) Uses advised against: No information available at present. 1.3 Details of the supplier of the safety data sheet LIQUI MOLY GmbH Jerg-Wieland-Str. 4

89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 18

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Hazard class	Hazard category	Hazard statement
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.
Aquatic Chronic Aerosol	3 2 1 1	H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the

environment. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Pentane

 $Hydrocarbons, \, C6\text{-}C7, \, n\text{-}alkanes, \, isoalkanes, \, cyclics, \, <\!5\% \, n\text{-}hexane$

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

In case of spreading near the ground, flashback to distance sources of ignition is possible.

SECTION 3: Composition/information on ingredients

Aerosol	
3.1 Substance	
^{n.a.} 3.2 Mixture	
Pentane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-006-00-1
EINECS, ELINCS, NLP	203-692-4
CAS	109-66-0
content %	30-40



Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

ആ

Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Classification according to Regulation (EC) 1272/2008 (CLP)	
---	--

Aquatic Chronic 2, H411
Asp. Tox. 1, H304
STOT SE 3, H336
Flam. Liq. 2, H225

Undersontheme CC CZ is allowed inselling available (50/ is however	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Dizinc pyrophosphate	
Registration number (REACH)	01-2120768152-56-XXXX
Index	
EINECS, ELINCS, NLP	231-203-4
CAS	7446-26-6
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Titanium dioxide (in powder form containing 1 % or more of particles	
with aerodynamic diameter <= 10 μm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP	236-675-5
CAS	13463-67-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351 (as inhalation)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Call doctor immediately - have Data Sheet available. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

The following may occur: Irritation of the respiratory tract Coughing Headaches Effects/damages the central nervous system With long-term contact: Dermatitis (skin inflammation) Product removes fat. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

œ

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray CO2 Extinction powder Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of phosphorus Oxides of sulphur

Toxic pyrolysis products. Danger of explosion by prolonged heating. Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling



Page 5 of 18

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

7.1.1 General recommendations

Ensure good ventilation. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Do not store with oxidizing agents.

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1000 mg/m3

Chemical Name	Pentane				Content %:30-40
WEL-TWA: 1800 mg/m3 (600 ppm) (WEL), 3000	WEL-STEL:			
mg/m3 (1000 ppm) (EU)					
Monitoring procedures:		0raeger - Pentane 100/a (67 24 70			
		Compur - KITA-113 SB(C) (549 368			
	C	OFG (D) (Loesungsmittelgemische	Meth. Nr. 1), DFG (E) (S	olvent mi	xtures 1) - 1998,
	- 2	002			
	- N	IIOSH 1500 (HYDROCARBONS, E	3P 36°-216 °C) - 2003		
	- N	IOSH 2549 (VOLATILE ORGANIC	COMPOUNDS (SCREI	ENING))	- 1996
BMGV:			Other information:		
Chemical Name	Hydrocarbons, C6-	C7, n-alkanes, isoalkanes, cyclics,	<5% n-hexane		Content %:1-<10
WEL-TWA: 1000 mg/m3	•	WEL-STEL:			
Monitoring procedures:	- (Compur - KITA-187 S (551 174)			
BMGV:			Other information: (O	EL acc. to	o RCP-method,
			paragraphs 84-87, EH4	10)	
⁶⁸	Titanium dioxide (ir	powder form containing 1 % or m	ore of particles with		Content %:0,1-<1
Chemical Name	aerodynamic diame				00110111 /0.0,1 11
WEL-TWA: 10 mg/m3 (total inhala					
(respirable dust)	bio adoty, Ting/ino				
Monitoring procedures:					
BMGV:			Other information:		
Chemical Name	Butane				Content %:
WEL-TWA: 600 ppm (1450 mg/m3	3)	WEL-STEL: 750 ppm (1810 mg	g/m3)		
Monitoring procedures:		Compur - KITA-221 SA (549 459)			
		OSHA PV2010 (n-Butane) - 1993			
BMGV:			Other information:		
Chemical Name	Propane				Content %:
	•				



Consumer Consumer Consumer Workers / employees Workers / employees	sporadic (intermittent) release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, marine Environment - soil Human - oral Human - dermal Human - inhalation Human - dermal	Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects	PNEC PNEC PNEC PNEC PNEC PNEC DNEL DNEL DNEL DNEL DNEL	230 230 3600 1,2 1,2 1,2 0,55 214 214 643 3000 432	µg/l µg/l µg/l mg/kg dw mg/kg dw mg/kg bw/d mg/kg bw/d mg/m3 mg/kg bw/d	
Consumer Consumer Workers / employees	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, freshwater Environment - sediment, marine Environment - soil Human - oral Human - dermal Human - inhalation Human - inhalation	Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic	PNEC PNEC PNEC PNEC PNEC DNEL DNEL DNEL DNEL	230 3600 1,2 1,2 0,55 214 214 643 3000	μg/l μg/l mg/kg dw mg/kg dw mg/kg bw/d mg/kg bw/d mg/m3 mg/m3	
Consumer Consumer Workers / employees	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, freshwater Environment - sediment, marine Environment - soil Human - oral Human - dermal Human - inhalation Human - inhalation	Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects	PNEC PNEC PNEC PNEC PNEC DNEL DNEL DNEL DNEL	230 3600 1,2 1,2 0,55 214 214 643 3000	μg/l μg/l mg/kg dw mg/kg dw mg/kg bw/d mg/kg bw/d mg/m3 mg/m3	
Consumer	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, marine Environment - soil Human - oral Human - dermal	Long term, systemic effects Long term, systemic effects Long term, systemic	PNEC PNEC PNEC PNEC PNEC DNEL DNEL	230 3600 1,2 1,2 0,55 214 214	μg/l μg/l mg/kg dw mg/kg dw mg/kg dw mg/kg bw/d mg/kg bw/d	
	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, marine Environment - soil Human - oral	Long term, systemic effects Long term, systemic	PNEC PNEC PNEC PNEC PNEC PNEC DNEL	230 3600 1,2 1,2 0,55 214	μg/l μg/l mg/kg dw mg/kg dw mg/kg dw mg/kg bw/d	
Consumer	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, marine Environment - soil	Long term, systemic	PNEC PNEC PNEC PNEC PNEC PNEC	230 3600 1,2 1,2 0,55	μg/l μg/l mg/kg dw mg/kg dw mg/kg dw	
ancumor	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, marine Environment - soil		PNEC PNEC PNEC PNEC PNEC PNEC	230 3600 1,2 1,2 0,55	μg/l μg/l mg/kg dw mg/kg dw mg/kg dw	
	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater Environment - sediment, marine		PNEC PNEC PNEC PNEC PNEC	230 3600 1,2 1,2	μg/l μg/l mg/kg dw mg/kg dw	
	release Environment - freshwater Environment - marine Environment - sewage treatment plant Environment - sediment, freshwater		PNEC PNEC PNEC	230 3600 1,2	μg/l μg/l mg/kg dw	
	release Environment - freshwater Environment - marine Environment - sewage treatment plant		PNEC PNEC	230 3600	µg/l µg/l	
	release Environment - freshwater Environment - marine		PNEC	230	µg/l	
	release Environment - freshwater					
	release					
	Environment - water,		PNEC	880	µg/l	
	Environmental compartment					
Pentane Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
VEL-TWA: 5 mg/m3 (Mi vorking fluids, ACGIH) Monitoring procedures: 3MGV:	neral oil, excluding metal - Dr	WEL-STEL: raeger - Oil Mist 1/a (67 33 03	1) Other inforr	nation:		
Chemical Name	Oil mist, mineral	WEL STEL:				Content %:
MGV:			Other inform	mation:	-	
	- NI - NI - NI	C/CEN/ENTR/000/2002-16 ca IOSH 7601 (SILICA, CRYSTA IOSH 7602 (Crystalline Silica, IOSH 7603 (QUARTZ in coal SHA ID-142 (Quartz and Crist	LLINE, by VIS) - by IR (KBr pelle mine dust, by IR	t)) - 2003 (redepositi		
	inf - BC	DHS 101/2 (Crystalline silica frared spectroscopy and X-ray C/CEN/ENTR/000/2002-16 ca IOSH 7500 (Crystalline Silica,	/ diffraction) - 20 ard 52-1 (2004)	15 - EU pro	oject	
Aonitoring procedures:	IN - Xr	SHT MTA/MA-036/A00 (Dete ay Diffraction) - 2000, 2004				
Chemical Name	Quartz silica, respirable, crystalline)	WEL-STEL:			(Content %:
BMGV:	C(5 (0) (349 (0) (349	Other inforr	mation:	-	
VEL-TWA: 1000 ppm (E Ionitoring procedures:		WEL-STEL: ompur - KITA-113 SB(C) (549	368)			
Chemical Name	Isobutane				(Content %:
MGV:	- 09	SHA PV2077 (Propane) - 199	0 Other inforr	mation:		
ionitoring procedures.		WEL-STEL: ompur - KITA-125 SA (549 95	(4)			
	0.011.11					
VE print date: 02.10.2020 Vartungsspray weiss VEL-TWA: 1000 ppm (A fonitoring procedures:	J					
alid from: 30.09.2020 DF print date: 02.10.2020 Vartungsspray weiss VEL-TWA: 1000 ppm (A	version: 22.02.2019 / 0024					



Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

œ.

Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	733	mg/kg bw/d	

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	0,233	µg/l	
	Environment - marine		PNEC	0,023	µg/l	
	Environment - sediment, freshwater		PNEC	2560	µg/l	
	Environment - sediment, marine		PNEC	2560	µg/l	
	Environment - sewage treatment plant		PNEC	52	µg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,93	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	193	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	6,76	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	13,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	193	mg/kg bw/d	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental		-			
	compartment					
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Zinc sulphide										
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note				
	Environment - freshwater		PNEC	20,6	µg/l					



Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

	Environment - marine		PNEC	6,1	µg/l
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dry weight
	Environment - sediment, marine		PNEC	56,5	mg/kg dry weight
	Environment - soil		PNEC	35,5	mg/kg dry weight
	Environment - sewage treatment plant		PNEC	100	µg/l
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,3

ആ

Permeation time (penetration time) in minutes: >120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).



Page 9 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

œ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	n.a.
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,4 Vol-%
Upper explosive limit:	10,9 Vol-%
Vapour pressure:	2400 hPa (20°C)
Vapour density (air = 1):	Not determined
Density:	0,64 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	285 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. When using: development of explosive
	vapour/air mixture possible.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	80.7

SECTION 10: Stability and reactivity

10.1 ReactivityThe product has not been tested.10.2 Chemical stability



Page 10 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

œ

10.4 Conditions to avoid

Pressure increase will result in danger of bursting. Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Pentane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	5000	mg/kg	Mouse		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>100	mg/l/4h	Rat		
Skin corrosion/irritation:						Mild irritant, Repeated exposure may cause skin dryness or erroeking
Serious eye damage/irritation:						cracking. Mild irritant
Respiratory or skin sensitisation:						Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, vomiting, cramps, drowsiness, mucous membrane irritation
Hydrocarbons, C6-C7, n-alkane Toxicity / effect	es, isoalkanes Endpoint	, cyclics, <5% Value	n-hexane Unit	Organism	Test method	Notes



Page 11 of 18

œ.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	25,2	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:						Slightly irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Aspiration hazard:						Yes
Symptoms:						may cause headaches and vertigo.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications o such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		90d



GB						
Page 12 of 18 Safety data sheet according to R		No 1907/2006	6, Annex II			
Revision date / version: 30.09.20	20 / 0025					
Replacing version dated / version	n: 22.02.2019	/ 0024				
Valid from: 30.09.2020						
PDF print date: 02.10.2020						
Wartungsspray weiss						
Waltangoophay Weloo						
Specific target organ toxicity -	NOAEC	10	mg/m3	Rat		90d
repeated exposure (STOT-RE),						
inhalat.:						
Butane						_
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Aspiration hazard:						No
Symptoms:						ataxia, breathing
						difficulties,
						drowsiness,
						unconsciousness
						, frostbite,
						disturbed heart
						rhythm,
						headaches,
						cramps,
						intoxication,
						dizziness,
						nausea and
						vomiting.
Propane		1				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Reproductive toxicity	NOAEC	21,641	mg/l		OECD 422 (Combined	
(Developmental toxicity):					Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
A surface the surface surface	1	1		1	1	1 61

					Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing
						difficulties,
						unconsciousness
						, frostbite,
						headaches,
						cramps, mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.
Isobutane						
	E I I I		11.14		T ()	
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Toxicity / effect Acute toxicity, by inhalation:	Endpoint LC50	Value 658	Unit mg/l/4h	Rat	Test method	
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation:						Not irritant
Toxicity / effect Acute toxicity, by inhalation:				Rat	OECD 471 (Bacterial	
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity:				Rat		Not irritant Negative
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity: Aspiration hazard:				Rat	OECD 471 (Bacterial	Not irritant
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity:				Rat	OECD 471 (Bacterial	Not irritant Negative No unconsciousness
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity: Aspiration hazard:				Rat	OECD 471 (Bacterial	Not irritant Negative No
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity: Aspiration hazard:				Rat	OECD 471 (Bacterial	Not irritant Negative No unconsciousness
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity: Aspiration hazard:				Rat	OECD 471 (Bacterial	Not irritant Negative No unconsciousness , frostbite,
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity: Aspiration hazard:				Rat	OECD 471 (Bacterial	Not irritant Negative No unconsciousness , frostbite, headaches,
Toxicity / effect Acute toxicity, by inhalation: Serious eye damage/irritation: Germ cell mutagenicity: Aspiration hazard:				Rat	OECD 471 (Bacterial	Not irritant Negative No unconsciousness , frostbite, headaches, cramps,



B Page 13 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Quartz

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						respiratory
						distress,
						coughing,
						mucous
						membrane
						irritation

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Wartungsspray weiss Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Pentane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.1. Toxicity to fish:	LC50	96h	9,87	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	9,87	mg/l	Oncorhynchus		
-				_	mykiss		
12.1. Toxicity to fish:	LC50	96h	9,99	mg/l	Lepomis		
					macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	9,74	mg/l	Daphnia magna		
12.2. Persistence and		8d	70	%			
degradability:							
12.3. Bioaccumulative	Log Pow		3,39				calculated value
potential:							

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.6. Other adverse							Product floats or
effects:							the water
							surface.
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus	OECD 203 (Fish,	Goldforelle
-					mykiss	Acute Toxicity	(Oncorhynchus
						Test)	aguabonita)
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus	QSÁR	
-				_	mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	



B Page 14 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	100	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriell a subcapitata	U.S. EPA-600/9- 78-018	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:				~ ~			Insoluble20°C

Butane Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).



Page 15 of 18 Safety data sheet accord Revision date / version: 3 Replacing version dated / Valid from: 30.09.2020 PDF print date: 02.10.202 Wartungsspray weiss	80.09.2020 / 002 / version: 22.02.2	25		nex II			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
lashutana							
Isobutane Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae: 12.2. Persistence and degradability: 12.5. Results of PBT and vPvB assessment	EC50	96h	7,71	mg/l			Readily biodegradable No PBT substance, No vPvB substance
Our and a							
Quartz Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	Enapoint	Time	value		Organism		Not relevant for inorganic substances.
12.3. Bioaccumulative							Not to be
potential: 12.4. Mobility in soil:							expected Low
12.4. Mobility in soli: 12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
SECTION 13: Disposal considerations							

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation: Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

SECTION 14: Transport information

General statements
14.1. UN number:
Transport by road/by rail (ADR/RID)
14.2. UN proper shipping name:UN 1950 AEROSOLS14.3. Transport hazard class(es):

1950





Page	16 of 18	

(GB)-

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

14.4. Packing group:Classification code:LQ:14.5. Environmental hazards:Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
AEROSOLS (PENTANES)
14.3. Transport hazard class(es):
14.4. Packing group:
EmS:
Marine Pollutant:

14.5. Environmental hazards:

Transport by air (IATA)

14.2. UN proper shipping name: Aerosols, flammable
14.3. Transport hazard class(es):
14.4. Packing group:
14.5. Environmental hazards:

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

5F

1 L

D

2.1

Yes

2.1

Not applicable

F-D. S-U

environmentally hazardous

environmentally hazardous

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
E2		200	500
P3b	11.1, 11.2	5000 (netto)	50000 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

80,2 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

1, 2.3, 3, 5, 8, 11, 12, 15



Page 17 of 18

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025 Replacing version dated / version: 22.02.2019 / 0024 Valid from: 30.09.2020 PDF print date: 02.10.2020 Wartungsspray weiss

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Asp. Tox. — Aspiration hazard Flam. Liq. — Flammable liquid Skin Irrit. — Skin irritation Aquatic Acute — Hazardous to the aquatic environment - acute Carc. — Carcinogenicity

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds AOX approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances **European Norms** EN



Page 18 of 18 Safety data short according to Degulation (EC) No 1007/2006, Appay II
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.09.2020 / 0025
Replacing version dated / version: 22.02.2019 / 0024
Valid from: 30.09.2020
PDF print date: 02.10.2020
Wartungsspray weiss
Waltungsspray weiss
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,
Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List
Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International
Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight
The statements made here should describe the product with regard to the persecutive adatu pressuries at they are
The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

C by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.