

Page 1 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0007
Replacing version dated / version: 28.07.2014 / 0006
Valid from: 21.08.2015
PDF print date: 25.08.2015
Bremsflüssigkeit DOT 5.1. 250 mL
Art.: 3092

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Bremsflüssigkeit DOT 5.1. 250 mL
Art.: 3092

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Hydraulic fluid

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC16 - Heat transfer fluids

PC17 - Hydraulic fluids

Process category [PROC]:

PROC 1 - Use in closed process, no likelihood of exposure.

PROC 2 - Use in closed, continuous process with occasional controlled exposure

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC20 - Heat and pressure transfer fluids in dispersive, professional use but closed systems

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 9a - Wide dispersive indoor use of substances in closed systems

ERC 9b - Wide dispersive outdoor use of substances in closed systems

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

GB

Page 2 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

Glycol ether
 Polyglycols
 Corrosion inhibitor
 Glycol ether borate

3.1 Substance

n.a.

3.2 Mixture

2-(2-methoxyethoxy)ethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	--
Index	603-107-00-6
EINECS, ELINCS, NLP	203-906-6
CAS	111-77-3
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Repr. 2, H361d

2-[2-(2-butoxyethoxy)ethoxy]ethanol	
Registration number (REACH)	--
Index	603-183-00-0
EINECS, ELINCS, NLP	205-592-6
CAS	143-22-6
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Page 3 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0007
Replacing version dated / version: 28.07.2014 / 0006
Valid from: 21.08.2015
PDF print date: 25.08.2015
Bremsflüssigkeit DOT 5.1. 250 mL
Art.: 3092

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
Never pour anything into the mouth of an unconscious person!

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes
Product removes fat.
Dermatitis (skin inflammation)
In aerosol misting:
Irritation of the respiratory tract
Ingestion of large quantities:
Kidney damage
Coma
Death

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Indications for the physician:

Symptomatic treatment.

Antidote:

None known

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. sand, earth) and dispose of according to Section 13.

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid aerosol formation.
 Avoid contact with eyes.
 Avoid long lasting or intensive contact with skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect against moisture and store closed.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

(GB) Chemical Name	2-(2-methoxyethoxy)ethanol		Content %:1-<5
WEL-TWA: 10 ppm (50,1 mg/m ³) (WEL, EU)	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---	Other information: Sk (WEL, EU)		

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

2-(2-methoxyethoxy)ethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,53	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	50,1	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,27	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,5	mg/kg bw/day	
	Environment - freshwater		PNEC	12	mg/l	
	Environment - marine		PNEC	1,2	mg/l	

GB

Page 5 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

	Environment - water, sporadic (intermittent) release		PNEC	12	mg/l	
	Environment - sediment, freshwater		PNEC	44,4	mg/kg dw	
	Environment - sediment, marine		PNEC	0,44	mg/l	
	Environment - soil		PNEC	2,44	mg/kg dw	

2-[2-(2-butoxyethoxy)ethoxy]ethanol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	195	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	117	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	2,5	mg/kg bw/day	
	Environment - freshwater		PNEC	1,5	mg/l	
	Environment - marine		PNEC	0,15	mg/l	
	Environment - sediment, marine		PNEC	0,13	mg/kg dw	
	Environment - sediment, freshwater		PNEC	5,77	mg/kg dw	
	Environment - soil		PNEC	0,45	mg/kg dw	
	Environment - sewage treatment plant		PNEC	200	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	5	mg/l	

2-(2-(2-methoxyethoxy)ethoxy)ethanol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	156	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	93	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/d	
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	50	mg/l	
	Environment - sediment, freshwater		PNEC	36,6	mg/kg dw	
	Environment - marine		PNEC	0,8	mg/kg dw	
	Environment - soil		PNEC	1,73	mg/kg dw	
	Environment - sewage treatment plant		PNEC	200	mg/l	

GB

Page 6 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

	Environment - oral (animal feed)		PNEC	89	mg/kg feed	
--	----------------------------------	--	------	----	------------	--

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:
 Recommended
 Safety gloves made of natural rubber latex (EN 374).
 Safety gloves made of PE laminate (EN 374).
 Protective PVC gloves (EN 374)
 Protective nitrile gloves (EN 374)
 Minimum layer thickness in mm:
 >= 0,4
 Permeation time (penetration time) in minutes:
 >= 480
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If fumes build up, use suitable breathing mask.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Amber
Colour:	Colourless

Page 7 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

Odour:	Mild
Odour threshold:	Not determined
pH-value:	7-10,5 (SAE J 1703)
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	>260 °C
Flash point:	>100 °C (IP 35 (Pensky-Martens, open cup))
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	<2 mbar (20°C)
Vapour density (air = 1):	Vapours heavier than air.
Density:	1,04-1,09 g/ml (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Mixable
Partition coefficient (n-octanol/water):	<2 (OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method))
Auto-ignition temperature:	>300 °C (ASTM D 286)
Decomposition temperature:	Not determined
Viscosity:	~5-10 cSt (20°C, ASTM D 445)
Explosive properties:	Not determined
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.

Strong heat

Protect from humidity.

Product is hygroscopic.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Carefully avoid contamination of the product with foreign substances.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

Peroxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Bremsflüssigkeit DOT 5.1. 250 mL

Art.: 3092

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
	t					

GB

Page 8 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat		
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

2-(2-methoxyethoxy)ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	9210	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	6500	mg/kg	Rabbit		
Symptoms:						breathing difficulties, respiratory distress, heart/circulatory disorders, coughing, headaches, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea

2-[2-(2-butoxyethoxy)ethoxy]ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5100-6616	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000-6540	mg/kg	Rabbit		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						cornea opacity, mucous membrane irritation

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Bremsflüssigkeit DOT 5.1. 250 mL Art.: 3092							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	> 100	mg/l	Oncorhynchus mykiss		
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							Not accepted owing to the logP values of the components.

(GB)

Page 9 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

2-(2-methoxyethoxy)ethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	24h	>5000	mg/l	Leuciscus idus		
Toxicity to algae:	EC50	72h	>500	mg/l	Scenedesmus subspicatus		

2-[2-(2-butoxyethoxy)ethoxy]ethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	1305-4600	mg/l	Leuciscus idus		
Toxicity to fish:	LC50	96h	1350-2400	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50	48h	500-2802	mg/l	Daphnia magna		
Toxicity to algae:	EC50	72h	>500	mg/l	Scenedesmus subspicatus		
Persistence and degradability:		14d	88	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 01 13 brake fluids

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Classification code: n.a.

LQ (ADR 2015): n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

(GB)

Page 10 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Marine Pollutant: n.a.
 Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII

2-(2-methoxyethoxy)ethanol

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1 - 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child.

H318 Causes serious eye damage.

Repr. — Reproductive toxicity

Eye Dam. — Serious eye damage

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

Page 11 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0007
 Replacing version dated / version: 28.07.2014 / 0006
 Valid from: 21.08.2015
 PDF print date: 25.08.2015
 Bremsflüssigkeit DOT 5.1. 250 mL
 Art.: 3092

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available

Page 12 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0007
Replacing version dated / version: 28.07.2014 / 0006
Valid from: 21.08.2015
PDF print date: 25.08.2015
Bremsflüssigkeit DOT 5.1. 250 mL
Art.: 3092

NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.