

Page 1 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Auspuff-Montage-Paste 150 g

Art.: 3342

അ

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Seam sealant

Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC 1 - Adhesives, sealants Process category [PROC]: PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC10 - Roller application or brushing Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP) Not applicable

2.3 Other hazards

ആ

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	
Classification according to Regulation (EC) 1272/2008 (CLP)	

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Give copious water to drink - consult doctor immediately.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur:

Irritation of the eyes

with long-term contact: Product removes fat.

Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media



Page 3 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

Adapt to the nature and extent of fire. Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

ആ

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Irritating gases Oxides of carbon Oxides of nitrogen Toxic pyrolysis products.

5.3 Advice for firefighters

According to size of fire Protective respirator with independent air supply. Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

If leakage occurs, dam up. Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Or:

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Store separately from alkalis. Store separately from acids. Store in a dry place. Store in a well ventilated place.

Protect from direct sunlight and warming. Only store at temperatures from 15°C to 30°C.



Page 4 of 10

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	general dust limit			Content %:
WEL-TWA: 10 mg/m3 (inhal. dust)	, 4 mg/m3 (respir.	WEL-STEL:		
dust)				
Monitoring procedures:	-			
BMGV:			Other information:	
Chemical Name	China stone			Content %:
WEL-TWA: 2 mg/m3 (res. dust)		WEL-STEL:		
Monitoring procedures:	-			
BMGV:			Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). Recommended Protective nitrile gloves (EN 374).

Minimum layer thickness in mm: > 0.4

Permeation time (penetration time) in minutes:

> 30

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.



Page 5 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments). According to operation. Natural fibre or heat-resistant synthetic fibre

Respiratory protection: Normally not necessary.

Thermal hazards:

ആ

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	Grey
Odour:	Odourless
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	100 °C (water)
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	n.a.
Upper explosive limit:	n.a.
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	~1,71 g/cm3 (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	partially, Soluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined

SECTION 10: Stability and reactivity

0 % (Organic solvents)

10.1 Reactivity

Solvents content:

The product has not been tested.



Page 6 of 10

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from humidity.

10.5 Incompatible materials

Avoid contact with strong alkalis. Avoid contact with strong acids. Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

4	Auspuff-Montage-Paste 150 g

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

China stone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat		
Serious eye damage/irritation:						Mechanical
						irritation possible.
Aspiration hazard:						No

SECTION 12: Ecological information

Possibly more information	on environmen	tal effects, s	ee Section 2	.1 (classific	ation).		
Auspuff-Montage-Paste	150 g						
Art.: 3342							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.



Page 7 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

(GB)·

12.2. Persistence and degradability:	Inorganic products cannot be eliminated from water through biological purification
	methods.
12.3. Bioaccumulative	n.d.a.
potential:	
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	
Other information:	According to the
	recipe, contains
	no ÁOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT	•						No PBT
and vPvB assessment							substance, No
							vPvB substance
12.2. Persistence and							Inorganic
degradability:							products cannot
							be eliminated
							from water
							through
							biological
							purification
							methods.,
							Mechanical
							precipitation
							possible.
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l			
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	Analogous
					mykiss	Acute Toxicity Test)	conclusion
12.1. Toxicity to daphnia:	LC50	48h	>1100	mg/l	Daphnia magna		References
12.1. Toxicity to algae:	IC50		>1000	mg/l			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus	OECD 201 (Alga,	Analogous
					subspicatus	Growth Inhibition	conclusion
						Test)	
12.2. Persistence and							Not
degradability:							biodegradable
Water solubility:							Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.



Page 8 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

E.g. dispose at suitable refuse site. For contaminated packing material

ആ

Pay attention to local and national official regulations. 15 01 04 metallic packaging Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

14.1. UN number:	n.a.	
Transport by road/by rail (ADR/RID)		
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	n.a.	
14.4. Packing group:	n.a.	
Classification code:	n.a.	
_Q:	n.a.	
14.5. Environmental hazards:	Not applicable	
Funnel restriction code:		
Transport by sea (IMDG-code)		
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	n.a.	
14.4. Packing group:	n.a.	
Marine Pollutant:	n.a	
14.5. Environmental hazards:	Not applicable	
Transport by air (IATA)		
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	n.a.	
14.4. Packing group:	n.a.	
14.5. Environmental hazards:	Not applicable	
14.6. Special precautions for user		
Jnless specified otherwise, general measures for safe tra	insport must be followed	
14.7. Transport in bulk according to An	•	
Non-dangerous material according to Transport Regulation		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

0 %

Revised sections:

4, 8, 9, 10, 11, 14, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).



Page 9 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

ആ

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) The International Bromine Council BSEF body weight bw CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL **Derived Minimum Effect Level** DNEL Derived No Effect Level dw dry weight e.g. for example (abbreviation of Latin 'exempli gratia'), for instance European Community EC ECHA European Chemicals Agency European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances EN **European Norms** EPA United States Environmental Protection Agency (United States of America) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic persistent, bioaccumulative and toxic PBT Polyethylene PF PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)



Page 10 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.01.2020 / 0009 Replacing version dated / version: 21.08.2015 / 0008 Valid from: 09.01.2020 PDF print date: 09.01.2020 Auspuff-Montage-Paste 150 g Art.: 3342

SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.