

Œ

Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Use in closed process, no likelihood of exposure.

PROC 2 - Use in closed, continuous process with occasional controlled exposure

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC20 - Heat and pressure transfer fluids in dispersive, professional use but closed systems

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 9a - Wide dispersive indoor use of substances in closed systems

ERC 9b - Wide dispersive outdoor use of substances in closed systems

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0. Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains C14-18 alpha-olefin epoxide, reaction products with boric acid. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixture**

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP	276-738-4
CAS	72623-87-1
content %	60-90
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Baseoil - unspecified *	
Registration number (REACH)	-
Index	
EINECS, ELINCS, NLP	-
CAS	
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	
Registration number (REACH)	01-2119976351-35-XXXX
Index	
EINECS, ELINCS, NLP	293-927-7
CAS	91648-65-6
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

The contained militeral oil can be	The contained mineral on earlibe described by one of more of the following numbers.									
EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name								
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic								
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic								
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic								
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic								

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures



Œ

Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015

PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

4.1 Description of first aid measures

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Normally not irritating to skin.

Wash thoroughly with soap and water.

Remove contaminated clothing immediately.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Foam

Dry extinguisher

Large fire:

Alcohol resistant foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.



Œ

Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH) -	
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371)	
	- Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

With short-term contact:

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

Permeation time (penetration time) in minutes:

> 30

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

n.a.

9.1 Information on basic physical and chemical properties

Physical state: Colour: Light yellow Odour: Characteristic Odour threshold: Not determined pH-value:

Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined 204 °C Flash point:

Evaporation rate: Not determined Flammability (solid, gas): n.a.

Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 0,857 g/cm3

Bulk density: n.a. Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined

Decomposition temperature: Not determined Viscosity: 36,5 mm2/s (40°C) Viscosity: 7,34 mm2/s (100°C)



Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

Explosive properties: Product is not explosive. Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7. Protect from humidity.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Doppelkupplungsgetriebe-Oel 8100 1 L Art.: 3640 Value Organism Toxicity / effect Endpoin Unit Test method **Notes** Acute toxicity, by oral route: n.d.a. Acute toxicity, by dermal route: n.d.a. Acute toxicity, by inhalation: n.d.a. Skin corrosion/irritation: n.d.a. Serious eye damage/irritation: n.d.a. Respiratory or skin sensitisation: n.d.a. Germ cell mutagenicity: n.d.a. Carcinogenicity: n.d.a. Reproductive toxicity: n.d.a. Specific target organ toxicity n.d.a. single exposure (STOT-SE): Specific target organ toxicity n.d.a. repeated exposure (STOT-RE): Aspiration hazard: n.d.a. Symptoms: n.d.a. Other information: Classification according to calculation procedure.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based										
Toxicity / effect	Toxicity / effect Endpoin Value Unit Organism Test method									
	t			_						
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral					
					Toxicity)					
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute					
					Dermal Toxicity)					



Page 7 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L Art.: 3640

Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant, Repeated
Chin con color, in tation.					Dermal	exposure may cause skir
					Irritation/Corrosion)	dryness or cracking.
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant
Okin Gon Golon, intaktori.					Dermal	140t iiiitant
					Irritation/Corrosion)	
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant
conouc cyc damago, manon.					Irritation/Corrosion)	110t milan
Respiratory or skin sensitisation:					OECD 406 (Skin	Not sensitizising
respiratory of skin sensitisation.					Sensitisation)	Not sensitizising
Respiratory or skin sensitisation:					OECD 406 (Skin	No (skin contact)
respiratory of skin serisitisation.					Sensitisation)	140 (Skiil Contact)
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
Germ cen matagementy.					Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 451	Negative
Carcinogericity.					(Carcinogenicity	Negative
					Studies)	
Carcinogenicity:					OECD 453 (Combined	Negative
Carcinogenicity.					Chronic	Negative
					Toxicity/Carcinogenicity	
					Studies)	
Carcinogenicity:					OECD 451	Negative
Carcinogericity.					(Carcinogenicity	Negative
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative
reproductive toxicity.					Developmental	rvegative
					Toxicity Study)	
Reproductive toxicity:					OECD 421	Negative
reproductive toxicity.					(Reproduction/Develop	rvegative
					mental Toxicity	
					Screening Test)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative
Reproductive toxicity.					Developmental	Negative
					Toxicity Study)	
Reproductive toxicity:					OECD 421	Negative
reproductive toxicity.					(Reproduction/Develop	Nogalive
					mental Toxicity	
					Screening Test)	
Specific target organ toxicity -					Screening rest)	No indications of such ar
single exposure (STOT-SE):						effect.
Specific target organ toxicity -						No indications of such ar
repeated exposure (STOT-RE):						effect.
Aspiration hazard:						Asp. Tox. 1

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Doppelkupplungsgetriebe-Oel 8100 1 L										
Art.: 3640										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
Toxicity to fish:							n.d.a.			
Toxicity to daphnia:							n.d.a.			
Toxicity to algae:							n.d.a.			
Persistence and							n.d.a.			
degradability:										
Bioaccumulative							n.d.a.			
potential:										
Mobility in soil:							n.d.a.			
Results of PBT and							n.d.a.			
vPvB assessment										
Other adverse effects:							n.d.a.			



Page 8 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L Art.: 3640

Other information:				According to the recipe,
				contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	NOEC/NO	96h	>=100	mg/l	Pimephales	OECD 203 (Fish,	
Toxiony to non.	EL	00	7-100	,g, .	promelas	Acute Toxicity	
	- -				prometas	Test)	
Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales	OECD 203 (Fish,	
TOXICITY TO HISTI.	LLSU	9011	> 100	ilig/i	promelas	Acute Toxicity	
					promeias	Test)	
Taviakuta danbaia.	NOEC/NO	48h	. 40000	/I	Dambuia magua	OECD 202	
Toxicity to daphnia:	FI	4011	>10000	mg/l	Daphnia magna		
	EL					(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to daphnia:	NOEC/NO	21d	10	mg/l	Daphnia magna	OECD 211	
	EL					(Daphnia magna	
						Reproduction	
						Test)	
Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OEĆD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to algae:	NOEC/NO	72h	>=100	mg/l	Pseudokirchneriell	OECD 201	
, ,	EL				a subcapitata	(Alga, Growth	
						Inhibition Test)	
Persistence and						OECD 301 B	Not readily biodegradable
degradability:						(Ready	,
,						Biodegradability -	
						Co2 Evolution	
						Test)	
Persistence and		28d	46	%		OECD 301 B	
degradability:		===		"		(Ready	
acg.aaacy.						Biodegradability -	
						Co2 Evolution	
						Test)	
Bioaccumulative	Log Kow		>6			. 550,	A notable biological
potential:	209 11017						accumulation potential
p							has to be expected
							(LogPow > 3).
Results of PBT and							No PBT substance, No
vPvB assessment							vPvB substance
Toxicity to bacteria:	NOEC/NO	10min	>1,93	mg/l		DIN 38412 T.8	VI VD SUDStatice
TOAICITY TO DACTETIA.	EL	10111111	>1,93	ilig/i		DIN 30412 1.0	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 06 synthetic engine, gear and lubricating oils Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.



(GB)

Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Classification code:

n.a.

CARR 2045):

n.a.

LQ (ADR 2015): n.a.

Environmental hazards: Not applicable Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Marine Pollutant:

n.a.

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es):

Packing group:

n.a.

n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1 - 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard



(GB)

Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and

mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)



(GB)

Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007

Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640

Inhibitory concentration IC

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

lethal concentration LC

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

Limited Quantities IΩ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAFC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level

Ozone Depletion Potential ODP

OECD Organisation for Economic Co-operation and Development

organic org.

PAH polycyclic aromatic hydrocarbon **PBT** persistent, bioaccumulative and toxic Chemical product category PC

PΕ Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

mag parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Telephone Tel.

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) **UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF

Volatile organic compounds VOC

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:



Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0007 Replacing version dated / version: 03.06.2014 / 0006

Valid from: 21.08.2015 PDF print date: 25.08.2015

Doppelkupplungsgetriebe-Oel 8100 1 L

Art.: 3640 Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90 © by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.