

Page 1 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 13.04.2018 / 0011  
Replacing version dated / version: 21.08.2015 / 0010  
Valid from: 13.04.2018  
PDF print date: 06.06.2018  
Top Tec 4200 5W-30 5 L  
Art.: 3707

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Top Tec 4200 5W-30 5 L**  
**Art.: 3707**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Motor oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

## Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based |                       |
|--|-----------------------|
| Registration number (REACH)  | 01-2119474889-13-XXXX |
| Index  | 649-483-00-5          |
| EINECS, ELINCS, NLP  | 276-738-4             |
| CAS  | 72623-87-1            |
| content %  | 20-40                 |
| Classification according to Regulation (EC) 1272/2008 (CLP)          | Asp. Tox. 1, H304     |

| Baseoil - unspecified *                                     |                   |
|---|-------------------|
| Registration number (REACH)                                 | ---               |
| Index   | ---               |
| EINECS, ELINCS, NLP   | ---               |
| CAS   | ---               |
| content %   | 1-<10             |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Asp. Tox. 1, H304 |

| Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |                         |
|---|-------------------------|
| Registration number (REACH)   | 01-0000015551-76-XXXX   |
| Index   | 607-530-00-7            |
| EINECS, ELINCS, NLP   | 406-040-9               |
| CAS   | 125643-61-0             |
| content %   | 1-10                    |
| Classification according to Regulation (EC) 1272/2008 (CLP)                             | Aquatic Chronic 4, H413 |

| Distillates (petroleum), hydrotreated heavy paraffinic      |                       |
|---|-----------------------|
| Registration number (REACH)                                 | 01-2119484627-25-XXXX |
| Index   | 649-467-00-8          |
| EINECS, ELINCS, NLP   | 265-157-1             |
| CAS   | 64742-54-7            |
| content %   | 1-<10                 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Asp. Tox. 1, H304     |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

Page 3 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

\* The contained mineral oil can be described by one or more of the following numbers:

| EINECS, ELINCS, NLP | Registration number (REACH) | Chemical name   |
|---------------------|-----------------------------|---|
| 265-157-1           | 01-2119484627-25-XXXX       | Distillates (petroleum), hydrotreated heavy paraffinic    |
| 265-169-7           | 01-2119471299-27-XXXX       | Distillates (petroleum), solvent-dewaxed heavy paraffinic |
| 265-158-7           | 01-2119487077-29-XXXX       | Distillates (petroleum), hydrotreated light paraffinic    |
| 265-159-2           | 01-2119480132-48-XXXX       | Distillates (petroleum), solvent-dewaxed light paraffinic |

The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent  
 Thinners

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes  
 with long-term contact:  
 Drying of the skin.  
 Dermatitis (skin inflammation)  
 Oil acne  
 On vapour formation:  
 irritation of the respiratory tract  
 Ingestion:  
 Gastrointestinal disturbances  
 Nausea  
 Vomiting

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>  
 Foam  
 Dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 13.04.2018 / 0011  
Replacing version dated / version: 21.08.2015 / 0010  
Valid from: 13.04.2018  
PDF print date: 06.06.2018  
Top Tec 4200 5W-30 5 L  
Art.: 3707

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of sulphur  
Oxides of phosphorus  
Toxic pyrolysis products.  
Flammable vapour/air mixtures

## 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Oil binder

Do not wash away with water or watery cleaning agents.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

GB

Page 5 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

Impermeable floor.  
 Protect against moisture and store closed.  
 Protect from direct sunlight and warming.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

| Chemical Name            | Oil mist, mineral  | Content %: |
|--------------------------|--|------------|
| WEL-TWA: 5 mg/m3 (ACGIH) | WEL-STEL: 10 mg/m3 (ACGIH)   | ---        |
| Monitoring procedures:   | - Draeger - Oil 10/a-P (67 28 371)<br>- Draeger - Oil Mist 1/a (67 33 031) |            |
| BMGV: ---                | Other information: ---   |            |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

### 8.2 Exposure controls

| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based |  |                          |            |       |            |      |
|--|--|--------------------------|------------|-------|------------|------|
| Area of application  | Exposure route / Environmental compartment | Effect on health         | Descriptor | Value | Unit       | Note |
|  | Human - oral                               |                          | PNEC       | 9,33  | mg/kg feed |      |
| Consumer   | Human - inhalation                         | Long term, local effects | DNEL       | 1,2   | mg/m3      | 24h  |
| Workers / employees  | Human - inhalation                         | Long term, local effects | DNEL       | 5,4   | mg/m3      | 8h   |

| Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate |  |                             |            |         |        |      |
|---|--|-----------------------------|------------|---------|--------|------|
| Area of application   | Exposure route / Environmental compartment | Effect on health            | Descriptor | Value   | Unit   | Note |
|   | Environment - sewage treatment plant       |                             | PNEC       | 10      | mg/l   |      |
|   | Environment - sediment, freshwater         |                             | PNEC       | 233     | mg/kg  |      |
|   | Environment - sediment, marine             |                             | PNEC       | 23,3    | mg/kg  |      |
|   | Environment - soil                         |                             | PNEC       | 189     | mg/kg  |      |
|   | Environment - freshwater                   |                             | PNEC       | 0,0043  | mg/kg  |      |
|   | Environment - marine                       |                             | PNEC       | 0,00043 | mg/kg  |      |
| Consumer  | Human - dermal                             | Long term, systemic effects | DNEL       | 0,25    | mg/kg  |      |
| Consumer  | Human - oral                               | Long term, local effects    | DNEL       | 0,25    | mg/kg  |      |
| Workers / employees   | Human - dermal                             | Long term, systemic effects | DNEL       | 0,22    | mg/kg  |      |
| Workers / employees   | Human - inhalation                         | Long term, systemic effects | DNEL       | 3,5     | mg/m3  |      |
| Workers / employees   | Human - dermal                             | Short term, local effects   | DNEL       | 1       | mg/cm2 |      |
| Workers / employees   | Human - dermal                             | Long term, local effects    | DNEL       | 0,006   | mg/cm2 |      |

Page 6 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

|                     |                |                              |      |    |       |  |
|---------------------|----------------|------------------------------|------|----|-------|--|
| Workers / employees | Human - dermal | Short term, systemic effects | DNEL | 20 | mg/kg |  |
|---------------------|----------------|------------------------------|------|----|-------|--|

| <b>Distillates (petroleum), hydrotreated heavy paraffinic</b> |  |                          |            |       |                   |      |
|---|--|--------------------------|------------|-------|-------------------|------|
| Area of application   | Exposure route / Environmental compartment | Effect on health         | Descriptor | Value | Unit              | Note |
|   | Environment - oral (animal feed)           |                          | PNEC       | 9,33  | mg/kg feed        |      |
| Consumer  | Human - inhalation                         | Long term, local effects | DNEL       | 1,2   | mg/m <sup>3</sup> |      |
| Workers / employees   | Human - inhalation                         | Long term, local effects | DNEL       | 5,4   | mg/m <sup>3</sup> |      |

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

**Eye/face protection:**  
 Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

**Skin protection - Hand protection:**  
 Protective gloves, oil resistant (EN 374)  
 If applicable  
 Protective nitrile gloves (EN 374)  
 Permeation time (penetration time) in minutes:  
 >480  
 Minimum layer thickness in mm:  
 0,5  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

**Skin protection - Other:**  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

**Respiratory protection:**  
 Normally not necessary.  
 With oil mist formation:  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

**Thermal hazards:**  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

Page 7 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |                                 |
|--|---------------------------------|
| Physical state:                          | Liquid                          |
| Colour:                                  | Brown                           |
| Odour:                                   | Characteristic                  |
| Odour threshold:                         | Not determined                  |
| pH-value:                                | n.a.                            |
| Melting point/freezing point:            | Not determined                  |
| Initial boiling point and boiling range: | Not determined                  |
| Flash point:                             | 230 °C                          |
| Evaporation rate:                        | Not determined                  |
| Flammability (solid, gas):               | Not determined                  |
| Lower explosive limit:                   | Not determined                  |
| Upper explosive limit:                   | Not determined                  |
| Vapour pressure:                         | Not determined                  |
| Vapour density (air = 1):                | Not determined                  |
| Density:                                 | 0,855 g/ml                      |
| Bulk density:                            | n.a.                            |
| Solubility(ies):                         | Not determined                  |
| Water solubility:                        | Insoluble                       |
| Partition coefficient (n-octanol/water): | Not determined                  |
| Auto-ignition temperature:               | Not determined                  |
| Decomposition temperature:               | Not determined                  |
| Viscosity:                               | 71 mm <sup>2</sup> /s (40°C)    |
| Viscosity:                               | 12,3 mm <sup>2</sup> /s (100°C) |
| Explosive properties:                    | Not determined                  |
| Oxidising properties:                    | No                              |

### 9.2 Other information

|                           |                |
|---------------------------|----------------|
| Miscibility:              | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity:             | Not determined |
| Surface tension:          | Not determined |
| Solvents content:         | Not determined |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Protect from humidity.

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

Page 8 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Top Tec 4200 5W-30 5 L

##### Art.: 3707

| Toxicity / effect   | Endpoint | Value | Unit | Organism | Test method | Notes  |
|---|----------|-------|------|----------|-------------|--|
| Acute toxicity, by oral route:                                |          |       |      |          |             | n.d.a.   |
| Acute toxicity, by dermal route:                              |          |       |      |          |             | n.d.a.   |
| Acute toxicity, by inhalation:                                |          |       |      |          |             | n.d.a.   |
| Skin corrosion/irritation:                                    |          |       |      |          |             | n.d.a.   |
| Serious eye damage/irritation:                                |          |       |      |          |             | n.d.a.   |
| Respiratory or skin sensitisation:                            |          |       |      |          |             | n.d.a.   |
| Germ cell mutagenicity:                                       |          |       |      |          |             | n.d.a.   |
| Carcinogenicity:  |          |       |      |          |             | n.d.a.   |
| Reproductive toxicity:  |          |       |      |          |             | n.d.a.   |
| Specific target organ toxicity - single exposure (STOT-SE):   |          |       |      |          |             | n.d.a.   |
| Specific target organ toxicity - repeated exposure (STOT-RE): |          |       |      |          |             | n.d.a.   |
| Aspiration hazard:  |          |       |      |          |             | n.d.a.   |
| Symptoms:   |          |       |      |          |             | n.d.a.   |
| Other information:  |          |       |      |          |             | Classification according to calculation procedure. |

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

| Toxicity / effect                  | Endpoint | Value | Unit    | Organism | Test method   | Notes   |
|------------------------------------|----------|-------|---------|----------|---|---|
| Acute toxicity, by oral route:     | LD50     | >5000 | mg/kg   | Rat      | OECD 401 (Acute Oral Toxicity)                                |   |
| Acute toxicity, by dermal route:   | LD50     | >5000 | mg/kg   | Rabbit   | OECD 402 (Acute Dermal Toxicity)                              |   |
| Acute toxicity, by inhalation:     | LC50     | >5,53 | mg/l/4h | Rat      | OECD 403 (Acute Inhalation Toxicity)                          |   |
| Skin corrosion/irritation:         |          |       |         |          | OECD 404 (Acute Dermal Irritation/Corrosion)                  | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation:     |          |       |         |          | OECD 405 (Acute Eye Irritation/Corrosion)                     | Not irritant  |
| Respiratory or skin sensitisation: |          |       |         |          | OECD 406 (Skin Sensitisation)                                 | No (skin contact)   |
| Germ cell mutagenicity:            |          |       |         |          | OECD 471 (Bacterial Reverse Mutation Test)                    | Negative  |
| Carcinogenicity:                   |          |       |         |          | OECD 451 (Carcinogenicity Studies)                            | Negative  |
| Carcinogenicity:                   |          |       |         |          | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)  | Negative  |
| Reproductive toxicity:             |          |       |         |          | OECD 414 (Prenatal Developmental Toxicity Study)              | Negative  |
| Reproductive toxicity:             |          |       |         |          | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative  |





Page 10 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

|  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|
| 12.1. Toxicity to daphnia:               |  |  |  |  |  |  | n.d.a.   |
| 12.1. Toxicity to algae:                 |  |  |  |  |  |  | n.d.a.   |
| 12.2. Persistence and degradability:     |  |  |  |  |  |  | Isolate as much as possible with an oil separator. |
| 12.3. Bioaccumulative potential:         |  |  |  |  |  |  | n.d.a.   |
| 12.4. Mobility in soil:                  |  |  |  |  |  |  | n.d.a.   |
| 12.5. Results of PBT and vPvB assessment |  |  |  |  |  |  | n.d.a.   |
| 12.6. Other adverse effects:             |  |  |  |  |  |  | n.d.a.   |
| Other information:                       |  |  |  |  |  |  | According to the recipe, contains no AOX.          |

**Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based**

| Toxicity / effect                        | Endpoint  | Time  | Value  | Unit | Organism                        | Test method  | Notes  |
|--|-----------|-------|--------|------|---------------------------------|--|--|
| 12.1. Toxicity to fish:                  | NOEC/NOEL | 96h   | >=100  | mg/l | Pimephales promelas             | OECD 203 (Fish, Acute Toxicity Test)                     |  |
| 12.1. Toxicity to fish:                  | LL50      | 96h   | > 100  | mg/l | Pimephales promelas             | OECD 203 (Fish, Acute Toxicity Test)                     |  |
| 12.1. Toxicity to daphnia:               | EL50      | 48h   | >10000 | mg/l | Daphnia magna                   | OECD 202 (Daphnia sp. Acute Immobilisation Test)         |  |
| 12.1. Toxicity to daphnia:               | NOEC/NOEL | 21d   | 10     | mg/l | Daphnia magna                   | OECD 211 (Daphnia magna Reproduction Test)               |  |
| 12.1. Toxicity to algae:                 | NOEC/NOEL | 72h   | >=100  | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test)                  |  |
| 12.1. Toxicity to algae:                 | EL50      | 48h   | >100   | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test)                  |  |
| 12.2. Persistence and degradability:     |           | 28d   | 46     | %    |                                 | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) |  |
| 12.3. Bioaccumulative potential:         | Log Kow   |       | 4,1    |      |                                 |  | A notable biological accumulation potential has to be expected (LogPow > 3). |
| 12.5. Results of PBT and vPvB assessment |           |       |        |      |                                 |  | No PBT substance, No vPvB substance  |
| Toxicity to bacteria:                    | NOEC/NOEL | 10min | >1,93  | mg/l |                                 | DIN 38412 T.8  |  |

**Baseoil - unspecified**

| Toxicity / effect          | Endpoint  | Time | Value  | Unit | Organism                | Test method | Notes |
|----------------------------|-----------|------|--------|------|-------------------------|-------------|-------|
| 12.1. Toxicity to fish:    | LC50      | 96h  | >100   | mg/l | Pimephales promelas     |             |       |
| 12.1. Toxicity to daphnia: | EC50      | 48h  | >10000 | mg/l | Daphnia magna           |             |       |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d  | >10    | mg/l | Daphnia magna           |             |       |
| 12.1. Toxicity to algae:   | EC50      | 72h  | >100   | mg/l | Scenedesmus quadricauda |             |       |

Page 11 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

|                                      |  |     |    |   |  |  |                           |
|--------------------------------------|--|-----|----|---|--|--|---------------------------|
| 12.2. Persistence and degradability: |  | 28d | 31 | % |  | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Not readily biodegradable |
|--------------------------------------|--|-----|----|---|--|--|---------------------------|

**Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate**

| Toxicity / effect                    | Endpoint  | Time | Value | Unit | Organism                | Test method  | Notes                                |
|--------------------------------------|-----------|------|-------|------|-------------------------|--|--------------------------------------|
| 12.1. Toxicity to fish:              | LC50      | 96h  | >75   | mg/l | Brachydanio rerio       | OECD 203 (Fish, Acute Toxicity Test)                     |                                      |
| 12.1. Toxicity to daphnia:           | EC50      | 48h  | >100  | mg/l | Daphnia magna           | OECD 202 (Daphnia sp. Acute Immobilisation Test)         |                                      |
| 12.1. Toxicity to daphnia:           | NOEC/NOEL | 21d  | >=1   | mg/l | Daphnia magna           | OECD 202 (Daphnia sp. Acute Immobilisation Test)         |                                      |
| 12.1. Toxicity to algae:             | EC50      | 72h  | >3    | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test)                  |                                      |
| 12.2. Persistence and degradability: |           |      |       |      |                         | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Not readily biodegradable            |
| 12.3. Bioaccumulative potential:     | Log Pow   |      | 9,2   |      |                         |  | Low                                  |
| 12.3. Bioaccumulative potential:     | BCF       | 35d  | 260   |      |                         | OECD 305 (Bioconcentration - Flow-Through Fish Test)     | Concentration in organisms possible. |

**Distillates (petroleum), hydrotreated heavy paraffinic**

| Toxicity / effect                    | Endpoint  | Time | Value  | Unit | Organism                        | Test method  | Notes                     |
|--------------------------------------|-----------|------|--------|------|---------------------------------|--|---------------------------|
| 12.1. Toxicity to fish:              | NOEC/NOEL | 96h  | >100   | mg/l | Pimephales promelas             | OECD 203 (Fish, Acute Toxicity Test)                               |                           |
| 12.1. Toxicity to daphnia:           | LL50      | 96h  | >10000 | mg/l |                                 | OECD 202 (Daphnia sp. Acute Immobilisation Test)                   |                           |
| 12.1. Toxicity to daphnia:           | NOEC/NOEL | 21d  | 10     | mg/l | Daphnia magna                   |  |                           |
| 12.1. Toxicity to algae:             | NOEC/NOEL | 72h  | >=100  | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                           |
| 12.2. Persistence and degradability: |           | 28d  | 31     | %    |                                 | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Not readily biodegradable |

**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**
**For the substance / mixture / residual amounts**

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

Page 12 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

EC disposal code no.:  
 The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. dispose at suitable refuse site.  
 E.g. suitable incineration plant.  
**For contaminated packing material**  
 Pay attention to local and national official regulations.  
 15 01 01 paper and cardboard packaging  
 15 01 02 plastic packaging  
 15 01 04 metallic packaging  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Classification code: n.a.  
 LQ: n.a.  
 14.5. Environmental hazards: Not applicable  
 Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
 General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

## SECTION 16: Other information

Revised sections:

3, 4, 8, 11, 12, 15

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletory, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances

Page 14 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.04.2018 / 0011  
 Replacing version dated / version: 21.08.2015 / 0010  
 Valid from: 13.04.2018  
 PDF print date: 06.06.2018  
 Top Tec 4200 5W-30 5 L  
 Art.: 3707

EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemicals Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration  
 LD Lethal Dose of a chemical  
 LD50 Lethal Dose, 50% kill  
 LDLo Lethal Dose Low  
 LOAEL Lowest Observed Adverse Effect Level  
 LOEC Lowest Observed Effect Concentration  
 LOEL Lowest Observed Effect Level  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute of Occupational Safety and Health (United States of America)  
 NOAEC No Observed Adverse Effective Concentration  
 NOAEL No Observed Adverse Effect Level  
 NOEC No Observed Effect Concentration  
 NOEL No Observed Effect Level  
 ODP Ozone Depletion Potential  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 PAH polycyclic aromatic hydrocarbon  
 PBT persistent, bioaccumulative and toxic  
 PC Chemical product category  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 POCP Photochemical ozone creation potential  
 ppm parts per million  
 PROC Process category  
 PTFE Polytetrafluorethylene  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SADT Self-Accelerating Decomposition Temperature  
 SAR Structure Activity Relationship  
 SU Sector of use  
 SVHC Substances of Very High Concern

Page 15 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 13.04.2018 / 0011  
Replacing version dated / version: 21.08.2015 / 0010  
Valid from: 13.04.2018  
PDF print date: 06.06.2018  
Top Tec 4200 5W-30 5 L  
Art.: 3707

Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.