

Page 1 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.05.2020 / 0012  
Replacing version dated / version: 13.04.2018 / 0011  
Valid from: 12.05.2020  
PDF print date: 12.05.2020  
Top Tec 4200 5W-30 20 L  
Art.: 3708

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Top Tec 4200 5W-30 20 L**  
**Art.: 3708**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Motor oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH

Jerg-Wieland-Str. 4

89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

## 2.1 Classification of the substance or mixture

### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Alkyl alcohol triester with boric acid. May produce an allergic reaction.  
 EUH210-Safety data sheet available on request.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based</b>	
<b>Registration number (REACH)</b>	01-2119474889-13-XXXX
<b>Index</b>	649-483-00-5
<b>EINECS, ELINCS, NLP</b>	276-738-4
<b>CAS</b>	72623-87-1
<b>content %</b>	20-<40
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304

<b>Distillates (petroleum), hydrotreated heavy paraffinic</b>	
<b>Registration number (REACH)</b>	01-2119484627-25-XXXX
<b>Index</b>	649-467-00-8
<b>EINECS, ELINCS, NLP</b>	265-157-1
<b>CAS</b>	64742-54-7
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304

<b>Bis(nonylphenyl)amine</b>	
<b>Registration number (REACH)</b>	01-2119488911-28-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	253-249-4
<b>CAS</b>	36878-20-3
<b>content %</b>	1-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Chronic 4, H413

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.05.2020 / 0012  
Replacing version dated / version: 13.04.2018 / 0011  
Valid from: 12.05.2020  
PDF print date: 12.05.2020  
Top Tec 4200 5W-30 20 L  
Art.: 3708

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

##### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

##### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent  
Thinners

##### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

##### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes  
with long-term contact:  
Drying of the skin.  
Dermatitis (skin inflammation)  
Oil acne  
On vapour formation:  
irritation of the respiratory tract  
Ingestion:  
Gastrointestinal disturbances  
Nausea  
Vomiting

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

CO<sub>2</sub>  
Foam  
Dry extinguisher

##### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of sulphur  
Oxides of phosphorus  
Toxic pyrolysis products.  
Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire

Page 4 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.05.2020 / 0012  
Replacing version dated / version: 13.04.2018 / 0011  
Valid from: 12.05.2020  
PDF print date: 12.05.2020  
Top Tec 4200 5W-30 20 L  
Art.: 3708

Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.  
Avoid formation of oil mist.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.  
Oil binder  
Do not wash away with water or watery cleaning agents.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Avoid formation of oil mist.  
Ensure good ventilation.  
Keep away from sources of ignition - Do not smoke.  
Do not heat to temperatures close to flash point.  
Avoid contact with eyes.  
Avoid long lasting or intensive contact with skin.  
Do not carry cleaning cloths soaked in product in trouser pockets.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Impermeable floor.  
Protect against moisture and store closed.  
Protect from direct sunlight and warming.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Page 5 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---	

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m <sup>3</sup>	24h
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m <sup>3</sup>	8h

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m <sup>3</sup>	

Bis(nonylphenyl)amine						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	132000	mg/kg dw	
	Environment - sediment, marine		PNEC	13200	mg/kg dw	
	Environment - soil		DNEL	263000	mg/kg dw	
	Environment - periodic release		PNEC	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,09	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,62	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,37	mg/m <sup>3</sup>	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	

Page 6 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.05.2020 / 0012  
Replacing version dated / version: 13.04.2018 / 0011  
Valid from: 12.05.2020  
PDF print date: 12.05.2020  
Top Tec 4200 5W-30 20 L  
Art.: 3708

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).  
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. BS EN 14042.  
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
Protective gloves, oil resistant (EN 374).  
If applicable  
Protective nitrile gloves (EN 374).  
Permeation time (penetration time) in minutes:  
>480  
Minimum layer thickness in mm:  
0,5  
Protective hand cream recommended.  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
Normally not necessary.  
With oil mist formation:  
Filter A2 P2 (EN 14387), code colour brown, white  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Page 7 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	230 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,855 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	70,00 mm <sup>2</sup> /s (40°C)
Viscosity:	12,2 mm <sup>2</sup> /s (100°C)
Explosive properties:	Not determined
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Protect from humidity.

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

Page 8 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

See also section 5.2  
 No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Top Tec 4200 5W-30 20 L

Art.: 3708

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:					OECD 451 (Carcinogenicity Studies)	Negative



Page 9 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	Negative
Aspiration hazard:						Asp. Tox. 1

<b>Distillates (petroleum), hydrotreated heavy paraffinic</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Aspiration hazard:						Yes

Page 10 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

Symptoms:						coughing, respiratory distress, nausea and vomiting., diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	30	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion

<b>Bis(nonylphenyl)amine</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):	NOAEL	150	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<100	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

**Top Tec 4200 5W-30 20 L**  
**Art.: 3708**

<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.

Page 11 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

**Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>=100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	46	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Kow		>6				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	10min	>1,93	mg/l		DIN 38412 T.8	

**Distillates (petroleum), hydrotreated heavy paraffinic**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion

Page 12 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

12.1. Toxicity to daphnia:	LL50	96h	>10000	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
Water solubility:							Insoluble

Bis(nonylphenyl)amine							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>10	mg/l	Desmodesmus subspicatus		Analogous conclusion
12.2. Persistence and degradability:		28d	24	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	600	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>7,6				Concentration in organisms possible.
12.3. Bioaccumulative potential:	BCF		1730				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.05.2020 / 0012

Replacing version dated / version: 13.04.2018 / 0011

Valid from: 12.05.2020

PDF print date: 12.05.2020

Top Tec 4200 5W-30 20 L

Art.: 3708

### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.05.2020 / 0012  
 Replacing version dated / version: 13.04.2018 / 0011  
 Valid from: 12.05.2020  
 PDF print date: 12.05.2020  
 Top Tec 4200 5W-30 20 L  
 Art.: 3708

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive

Page 15 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.05.2020 / 0012  
Replacing version dated / version: 13.04.2018 / 0011  
Valid from: 12.05.2020  
PDF print date: 12.05.2020  
Top Tec 4200 5W-30 20 L  
Art.: 3708

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.