

Page 1 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC16 - Heat transfer fluids

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

(GB)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety

## 1.4 Emergency telephone number

#### Emergency information services / official advisory body:

#### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)



Œ

Page 2 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

Hazard class Hazard category Hazard statement

Acute Tox. 4 H302-Harmful if swallowed.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H302-Harmful if swallowed.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P270-Do not eat, drink or smoke when using this product.

P301+P312-IF SWALLOWED: Call a POISON CENTRE / doctor if you feel unwell. P330-Rinse mouth.

P501-Dispose of contents / container to special waste collection point.

Polyalkylene glycol

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

## n.a. 3.2 Mixture

•-= ··········	
Polyalkylene glycol	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	353291-27-7
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures Inhalation



Œ

Page 3 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Never pour anything into the mouth of an unconscious person!

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

With long-term contact:

Product removes fat.

Dermatitis (skin inflammation)

Irritation of the skin.

On vapour formation:

Irritant to mucosa of the nose and throat

Irritation of the respiratory tract

In aerosol misting:

Lung damage

Ingestion:

Irritation of the mouth and throat

Irritation of the stomach

Gastrointestinal disturbances

Vomiting

Diarrhoea

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Aldehydes

Toxic gases

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures



®

Page 4 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Protect against moisture and store closed.

Do not store with oxidizing agents.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Suitable material:

Steel

Stainless steel (alloy steel)

#### 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

\_\_\_

#### 8.2 Exposure controls

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.



Page 5 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

Applies only if maximum permissible exposure values are listed here.

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:

Protective PVC gloves (EN 374)

Permeation time (penetration time) in minutes:

>= 480

Minimum layer thickness in mm:

0.7

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If fumes build up, use suitable breathing mask.

In aerosol misting:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state:

Colour:
Colour:
Codour:
Codour:
Codour threshold:
Liquid
Light yellow
Characteristic
Not determined

pH-value: n.a.
Melting point/freezing point: Not determined

Initial boiling point and boiling range:

Not determined

Flash point: >200 °C (DIN 51376 (Cleveland, open cup))

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Not determined

Not determined

Not determined

Not determined

Not determined



Page 6 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

Vapour density (air = 1):

Density: Bulk density:

Solubility(ies):

Water solubility: Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Explosive properties:

Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent:

Conductivity:

Surface tension:

Solvents content:

Not determined

0,998 g/cm3 (20°C) Not determined

Not determined

partially, Soluble

Not determined Not determined

Not determined

154 mm2/s (40°C)

Product is not explosive.

No

Not determined Not determined

Not determined

Not determined Not determined

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

## 10.4 Conditions to avoid

See also section 7.

Strong heat

Decomposition: T > 150°C

#### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### PAG Klima-Anlagenoel 150 250 mL Art.: 4082 Endpoint Toxicity / effect Value Unit Organism Test method Notes Acute toxicity, by oral route: calculated value ATE 505 mg/kg Acute toxicity, by dermal route: n.d.a. Acute toxicity, by inhalation: n.d.a. Skin corrosion/irritation: n.d.a. Serious eye damage/irritation: n.d.a. Respiratory or skin n.d.a. sensitisation: Germ cell mutagenicity: n.d.a. Carcinogenicity: n.d.a. Reproductive toxicity: n.d.a. Specific target organ toxicity n.d.a. single exposure (STOT-SE):



Page 7 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL Art.: 4082

Specific target organ toxicity - repeated exposure (STOT-RE):			n.d.a.
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.
Other information:			Classification
			according to
			calculation
			procedure.

Polyalkylene glycol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	500	mg/kg	Rat		
Skin corrosion/irritation:						Mild irritant
Serious eye damage/irritation:						Mild irritant
Respiratory or skin						No indications of
sensitisation:						such an effect.
Germ cell mutagenicity:				Salmonella		Negative
•				typhimurium		

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to t recipe, contain no AOX.

Polyalkylene glycol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and							Not readily
degradability:							biodegradable
12.3. Bioaccumulative							Not to be
potential:							expected

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 13 02 06 synthetic engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.



Page 8 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Recommended cleaner:

Water

## **SECTION 14: Transport information**

**General statements** 

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

Observe youth employment law (German regulation).

Observe law on protection of expectant mothers (German regulation).

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections: 2,16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.



Page 9 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H302	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

Acute Tox. — Acute toxicity - oral

### Any abbreviations and acronyms used in this document:

AC **Article Categories** 

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no.

Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

Bioconcentration factor BCF

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

body weight bw

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EC **European Community** ECHA European Chemicals Agency EEA European Economic Area **EEC European Economic Community** 

**EINECS** European Inventory of Existing Commercial Chemical Substances

**ELINCS** European List of Notified Chemical Substances

FΝ European Norms

EPA United States Environmental Protection Agency (United States of America)



Page 10 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform ChemicaL Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAECNo Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon persistent, bioaccumulative and toxic PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand



Page 11 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0010

Replacing version dated / version: 21.08.2015 / 0009

Valid from: 07.03.2017 PDF print date: 18.03.2017 PAG Klima-Anlagenoel 150 250 mL

Art.: 4082

TOC Total organic carbon

TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) **UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

## Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.