

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Hydraulikoel HVLP 32 20 L

Art.: 4156

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Hydraulic oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

(GB)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

## Emergency information services / official advisory body:

---

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture



Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011 Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

## Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hydrocarbons can be harmful to water.

Endangerment of potable water possible.

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

## n.a. 3 2 Mixture

O.Z MIXTO	
Distillates (petroleum), solvent-dewaxed light paraffinic	
Registration number (REACH)	01-2119480132-48-XXXX
Index	649-469-00-9
EINECS, ELINCS, NLP	265-159-2
CAS	64742-56-9
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	64742-55-8
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

\* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

On vapour formation:

Irritation of the respiratory tract

Ingestion:

Nausea

Vomiting

Diarrhoea

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media Suitable extinguishing media

CO<sub>2</sub>

Foam

Dry extinguisher

Water jet spray

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

Toxic gases

Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.



(B)

Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Oil binder

Do not wash away with water or watery cleaning agents.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Do not heat to temperatures close to flash point.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store at room temperature.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Chemical Name	Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (ACGIH)		WEL-STEL: 10 mg/m3 (ACGIH)	
Monitoring procedures:	- D	raeger - Oil 10/a-P (67 28 371)	



(B)

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

_	Draeger - Oil Mist 1/a (67 33 031)
	Draeger - Oil Mist 1/a (07 33 031)
BMGV:	Other information:

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

#### 8.2 Exposure controls

Distillates (petroleum), hydrotreated light paraffinic								
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note		
	Environmental							
	compartment							
Workers / employees	Human - dermal	Long term, systemic	DNEL	1	mg/kg			
		effects			bw/day			
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2,7	mg/m3			
		effects						

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Protective PVC gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:



Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

Normally not necessary. With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

manufacturer

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Liquid Physical state: Colour: Yellow Odour: Characteristic Odour threshold: Not determined pH-value: n.a. 10 % Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined 200 °C Flash point: Not determined

Evaporation rate: Not determined lity (solid, gas): n.a.

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Density:

Not determined

Not determined

Not determined

Not determined

O,85 g/ml (20°C)

Bulk density: n.a.

Solubility(ies):

Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Not determined

Not determined

Not determined

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Viscosity:

Viscosity:

Explosive properties:

Not determined

30,5 mm2/s (40°C)

6,7 mm2/s (100°C)

Product is not explosive.

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.



Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Open flame, ignition sources

#### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

#### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Hydraulikoel HVLP 32 20 L						
Art.: 4156						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), solvent	-dewaxed ligh	nt paraffinic				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian	Negative
<u> </u>					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	



B.

Page 8 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L Art.: 4156

Carcinogenicity:				Mouse		Female, Negative
Reproductive toxicity:	NOAEL	>2000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity	
					Study)	
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	
Aspiration hazard:					·	Yes
Symptoms:						drying of the skin., vomiting, nausea

Distillates (petroleum), hydrotreated light paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:					•	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizisin

Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Aspiration hazard:						Yes

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Hydraulikoel HVLP 32 20	) L						
Art.: 4156							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:		1					

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LL50	48h	>1000	mg/l	Gammarus sp.	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inherent
12.3. Bioaccumulative potential:	Log Pow		>3				Low

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
2.1. Toxicity to algae:	EL50	72h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
2.2. Persistence and			31	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
0.0 5:						Test)	0000
2.3. Bioaccumulative ootential:	Log Pow		>6				@20°C
2.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 01 10 mineral based non-chlorinated hydraulic oils

Recommendation:



Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling. E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

#### **General statements**

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:

n.a.

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0,04 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections: 3, 8, 11, 12, 15



ദ

Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011 Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

## Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union



Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

**EWC** European Waste Catalogue

Fax. Fax number general aen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

**GWP** Global warming potential

Hen's Egg Test - Chorionallantoic Membrane HET-CAM

**HGWP Halocarbon Global Warming Potential** IARC International Agency for Research on Cancer International Air Transport Association Intermediate Bulk Container **IBC** 

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

**IUCLID** International Uniform Chemical Information Database

LC lethal concentration

lethal concentration 50 percent kill LC50 LCLo lowest published lethal concentration

Lethal Dose of a chemical LD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOFC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

**Limited Quantities** IΩ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. no data available n.d.a.

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAECNo Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon persistent, bioaccumulative and toxic PBT

PC Chemical product category

Polyethylene PΕ

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million Process category PROC PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

Structure Activity Relationship SAR

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))



Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.05.2018 / 0011

Replacing version dated / version: 16.03.2018 / 0010

Valid from: 24.05.2018 PDF print date: 24.05.2018 Hydraulikoel HVLP 32 20 L

Art.: 4156

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

## These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.