

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Rust remover

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

PC35 - Washing and cleaning products (including solvent based products)

Process category [PROC]:

PROC 1 - Use in closed process, no likelihood of exposure.

PROC 2 - Use in closed, continuous process with occasional controlled exposure

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 8a - Wide dispersive indoor use of processing aids in open systems ERC 8d - Wide dispersive outdoor use of processing aids in open systems

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(B)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Hazard class Hazard statement Hazard category

Aerosol H222-Extremely flammable aerosol. 1

Asp. Tox. H304-May be fatal if swallowed and enters airways. 1 Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixture**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	(64742-48-9)
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Carbon dioxide S	Substance for which an EU exposure limit value applies.
Registration number (REACH)	



Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Index	
EINECS, ELINCS, NLP	204-696-9
CAS	124-38-9
content %	1-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	

2-Butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP	203-905-0
CAS	111-76-2
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Eye Irrit. 2, H319
	Skin Irrit. 2, H315
	Acute Tox. 4, H312
	Acute Tox. 4, H332

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

with long-term contact:

Product removes fat.

Irritation of the skin.

Frostbite

Reddening

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media



Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Suitable extinguishing media

Adapt to the nature and extent of fire. Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Oxides of sulphur
Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store in a well-ventilated place.

Observe special regulations for aerosols!

Not to be stored in gangways or stair wells.



-®—

Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Do not store with oxidizing agents. Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hvdrocarbons, C	10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			Content %:50-70
WEL-TWA: 800 mg/m3	,	WEL-STEL:			
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03 581)			
	=	Draeger - Hydrocarbons 0,1%/c (81 03 571)			
	-	Compur - KITA-187 S (551 174)			
BMGV:		Other information EH40)	: (WE	EL acc. to	RCP-method,
Chemical Name	Carbon dioxide				Content %:1-<20
WEL-TWA: 5000 ppm (9150 mg/n ppm (9000 mg/m3) (EU)	n3) (WEL), 5000	WEL-STEL: 15000 ppm (27400 mg/m3) (WEL)			
Monitoring procedures:	-	Compur - KITA-126 B (549 475)			
	=	Compur - KITA-126 SA (549 467)			
	-	Compur - KITA-126 SB (548 816)			
	-	Compur - KITA-126 SF (549 491)			
	=	Compur - KITA-126 SG (550 210)			
	-	Compur - KITA-126 SH (549 509)			
	-	Compur - KITA-126 UH (549 517)			
	-	Draeger - Carbon Dioxide 100/a (81 01 811)			
	-	Draeger - Carbon Dioxide 0,1%/a (CH 23 501)			
	-	Draeger - Carbon Dioxide 0,5%/a (CH 31 401) Draeger - Carbon Dioxide 1%/a (CH 25 101)			
	_	Draeger - Carbon Dioxide 1767a (CH 20 301)			
	_	OSHA ID-172 (Carbon dioxide in workplace atmosphe	res) - 19	990	
	_	NIOSH 6603 (Carbon dioxide) - 1994	.00,	000	
BMGV:		Other information	:		
Chemical Name	2-Butoxyethanol				Content %:1-<10
WEL-TWA: 25 ppm (123 mg/m3) mg/m3) (EU)	(WEL), 20 ppm (98	WEL-STEL: 50 ppm (246 mg/m3) (WEL, EU)			
Monitoring procedures:	-	Compur - KITA-190 U(C) (548 873)			
		DFG (D) (Loesungsmittelgemische 3), DFG (E) (Solve	nt mixtu	ures 3) - 1	1998, 2002 - EU
	-	project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)			
BMGV: 240 mmol butoxyacetic ac	id/mol creatinine in	urine, post shift (BMGV) Other information	: Sk ((WEL)	
Chemical Name	Oil mist, mineral				Content %:
WEL-TWA: 5 mg/m3 (ACGIH)		WEL-STEL: 10 mg/m3 (ACGIH)			
Monitoring procedures:	-	Draeger - Oil 10/a-P (67 28 371)			
DMOV/	-	Draeger - Oil Mist 1/a (67 33 031)	_		
BMGV:		Other information	:		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

2-Butoxyethanol



Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	98	mg/m3	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,3

Permeation time (penetration time) in minutes:

> 120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.



Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P3 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol, Substance: Liquid

Colour: Colourless Odour: Characteristic Not determined Odour threshold:

pH-value: n.a.

Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: Not determined Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined

Density: 0,829-0,86 g/ml (20°C)

Bulk density: Solubility(ies):

Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Product is not explosive.

Oxidising properties: Nο

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

n.a.

10.1 Reactivity

In use, may form flammable/explosive vapour-air mixture.

This product is not reactive based on experiences.



Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line Schnell-Rostloeser 400 ml							
Art.: 7390							
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes	
-	t			_			
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value	
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value	
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours	
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol	
Skin corrosion/irritation:						n.d.a.	
Serious eye damage/irritation:						n.d.a.	
Respiratory or skin sensitisation:						n.d.a.	
Germ cell mutagenicity:						n.d.a.	
Carcinogenicity:						n.d.a.	
Reproductive toxicity:						n.d.a.	
Specific target organ toxicity -						n.d.a.	
single exposure (STOT-SE):							
Specific target organ toxicity -						n.d.a.	
repeated exposure (STOT-RE):							
Aspiration hazard:						n.d.a.	
Symptoms:						n.d.a.	

Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion



Page 9 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

Reproductive toxicity:	OECD 414 (Prenatal	Negative, Analogous
	Developmental	conclusion
	Toxicity Study)	
Reproductive toxicity:	OECD 421	Negative, Analogous
	(Reproduction/Develop	conclusion
	mental Toxicity	
	Screening Test)	
Specific target organ toxicity -		No indications of such an
single exposure (STOT-SE):		effect.
Specific target organ toxicity -	OECD 408 (Repeated	No indications of such an
repeated exposure (STOT-RE):	Dose 90-Day Oral	effect., Analogous
	Toxicity Study in	conclusion
	Rodents)	
Aspiration hazard:		Yes
Symptoms:		unconsciousness,
		headaches, dizziness

Carbon dioxide								
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes		
	t							
Symptoms:						unconsciousness, blisters by skin-contact, vomiting, frostbite, annoyance, palpitations, itching, headaches, cramps, ear noises, dizziness		

2-Butoxyethanol							
Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	1746	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Guinea pig	OECD 402 (Acute Dermal Toxicity)	Does not conform with EU classification.	
Acute toxicity, by inhalation:	LC50	2-20	mg/l	Rat			
Skin corrosion/irritation:				Rabbit		Irritant, Product removes fat.	
Serious eye damage/irritation:				Rabbit		Intensively irritant, Risk of serious damage to eyes.	
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising	
Specific target organ toxicity - repeated exposure (STOT-RE):							
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Pro-Line Schnell-Rostloeser 400 ml								
Art.: 7390								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	
12.1. Toxicity to daphnia:							n.d.a.	
12.1. Toxicity to algae:							n.d.a.	



Page 10 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.05.2016 / 0024
Replacing version dated / version: 05.04.2016 / 0023
Valid from: 18.05.2016

PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

12.2. Persistence and degradability:				The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative potential:				n.d.a.
12.4. Mobility in soil:				n.d.a.
12.5. Results of PBT				n.d.a.
and vPvB assessment				
12.6. Other adverse effects:				n.d.a.
Other information:	AOX			According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	80	%		OECD 301 F	
degradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry	
10.0 0			5.5.7.0			Test)	
12.3. Bioaccumulative	Log Pow		5,5-7,2				
potential:	1 1/						
12.4. Mobility in soil: 12.5. Results of PBT	Log Koc		>3				No DDT substance No
							No PBT substance, No
and vPvB assessment							vPvB substance No PBT substance. No
Other information:							vPvB substance
Water colubility:			~10	ma/l			
Water solubility: Water solubility:			~10	mg/l			Slight Insoluble
vvaler solubility.							irisoluble

Endpoint	Time	Value	Unit	Organism	Test method	Notes
LC50	96h	35	mg/l	Salmo gairdneri		
						Greenhouse effect
Log Kow		0,83				
	LC50	LC50 96h	LC50 96h 35	LC50 96h 35 mg/l	LC50 96h 35 mg/l Salmo gairdneri	LC50 96h 35 mg/l Salmo gairdneri



Page 11 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NO EL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.3. Bioaccumulative potential:	Log Pow		0,83			,	Negative
12.4. Mobility in soil:	H (Henry)		0,0000 016	atm*m3/ mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC0	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Return to manufacturer with residual pressure.

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information



Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name: UN 1950 AEROSOLS 14.3. Transport hazard class(es): 2.1 14.4. Packing group: Classification code: 5F LQ (ADR 2015): 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 14.4. Packing group:

F-D, S-U EmS: Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Observe youth employment law (German regulation).

Observe incident regulations.

Directive 2010/75/EU (VOC):

~ 58 %

Comply with trade association/occupational health regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):











(GB)

Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used			
Aerosol 1, H222	Classification according to calculation procedure.			
Asp. Tox. 1, H304	Classification according to calculation procedure.			
Aerosol 1, H229	Classification based on the form or physical state.			

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Aerosol - Aerosols

Asp. Tox. — Aspiration hazard

Acute Tox. — Acute toxicity - oral

Eve Irrit. — Eve irritation

Skin Irrit. — Skin irritation

Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

AC **Article Categories**

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

Bromine Science and Environmental Forum **BSEF**

body weight bw

CAS Chemical Abstracts Service

Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CFC

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level Derived No Effect Level DNEL

Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

DOC



(GB)

Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Ca

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential

ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.



(GB)

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2016 / 0024

Replacing version dated / version: 05.04.2016 / 0023

Valid from: 18.05.2016 PDF print date: 18.05.2016 Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.