

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Pro-Line Schnell-Rostloeser 400 ml

Art.: 7390

അ

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Rust remover

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) Hazard class Hazard category Hazard statement

Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3 2 Mixture**

ആ

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Registration number (REACH)		
Index		
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)	
CAS	(64742-48-9)	
content %	50-70	
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304	

Carbon dioxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	204-696-9
CAS	124-38-9
content %	1-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	

2-Butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	603-014-00-0
EINECS, ELINCS, NLP	203-905-0
CAS	111-76-2
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Eye Irrit. 2, H319
	Skin Irrit. 2, H315
	Acute Tox. 4, H312
	Acute Tox. 4, H332

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.



Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Irritation of the respiratory tract with long-term contact: Product removes fat. Irritation of the skin. Frostbite Reddening

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire. Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of sulphur Hydrocarbons Toxic pyrolysis products. Danger of explosion by prolonged heating. Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures



Page 4 of 16

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store in a well-ventilated place. Observe special regulations for aerosols! Not to be stored in gangways or stair wells. Do not store with oxidizing agents. Observe special storage conditions. Keep protected from direct sunlight and temperatures over 50°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:50-70
WEL-TWA: 800 mg/m3	WEL-STEL:	
Monitoring procedures:	 Draeger - Hydrocarbons 2/a (81 03 581) 	
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 	
	- Compur - KITA-187 S (551 174)	
BMGV:	Other information: (WEL acc. to RCP-method,
	EH40)	



Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

œ

Chemical Name	Carbon dioxide		Content %:1-<	<20
WEL-TWA: 5000 ppm (9150 mg/m	13) (WEL), 5000	WEL-STEL: 15000 ppm (27400 mg/m3) (WEL)		
ppm (9000 mg/m3) (EU)				
Monitoring procedures:	-	Compur - KITA-126 B (549 475)		
	-	Compur - KITA-126 SA (549 467)		
	-	Compur - KITA-126 SB (548 816)		
	-	Compur - KITA-126 SF (549 491)		
	-	Compur - KITA-126 SG (550 210)		
	-	Compur - KITA-126 SH (549 509)		
	-	Compur - KITA-126 UH (549 517)		
	-	Draeger - Carbon Dioxide 100/a (81 01 811)		
	-	Draeger - Carbon Dioxide 0,1%/a (CH 23 501)		
	-	Draeger - Carbon Dioxide 0,5%/a (CH 31 401)		
	-	Draeger - Carbon Dioxide 1%/a (CH 25 101)		
	-	Draeger - Carbon Dioxide 5%/A (CH 20 301)		
	-	OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 19	990	
	-	NIOSH 6603 (Carbon dioxide) - 1994		
BMGV:		Other information:		
Chemical Name	2-Butoxyethanol		Content %:1-<	<10
WEL-TWA: 25 ppm (123 mg/m3) (1			

WEL-TWA: 25 ppm (123 mg/m3)	(WEL), 20 ppm (98	WEL-STEL:	50 ppm (246 mg/m	13) (WEL, EU)		
mg/m3) (EU)						
Monitoring procedures:	-	Compur - KITA-	190 U(C) (548 873)			
		DFG (D) (Loesu	ngsmittelgemische 3	3), DFG (E) (Solvent	mixtures 3)	- 1998, 2002 - EU
	-	project BC/CEN	/ENTR/000/2002-16	card 32-2 (2004)		
BMGV: 240 mmol butoxyacetic ac	id/mol creatinine in	urine, post shift ((BMGV)	Other information:	Sk (WEL)	
Chemical Name	Oil mist, mineral					Content %:
WEL-TWA: 5 mg/m3 (ACGIH)		WEL-STEL:	10 mg/m3 (ACGIH)		
Monitoring procedures:	-	Draeger - Oil 10	/a-P (67 28 371)			
	-	Draeger - Oil Mi	st 1/a (67 33 031)			
BMGV:				Other information:		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment,		PNEC	34,6	mg/kg dw	
	freshwater					
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage		PNEC	463	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	3,46	mg/kg dw	
	marine					
	Environment - sporadic		PNEC	9,1	mg/l	
	(intermittent) release					
Consumer	Human - dermal	Short term, systemic	DNEL	44,5	mg/kg bw/d	
		effects				



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

ആ

Consumer	effects		DNEL	426	mg/m3
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective nitrile gloves (EN 374) Minimum layer thickness in mm: 0,3 Permeation time (penetration time) in minutes: > 120 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A P3 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.



Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Paste, liquid.	
Colour: Colourless	
Odour: Characteristic	
Odour threshold: Not determined	
pH-value: n.a.	
Melting point/freezing point: Not determined	
Initial boiling point and boiling range: Not determined	
Flash point: Not determined	
Evaporation rate: Not determined	
Flammability (solid, gas): Not determined	
Lower explosive limit: Not determined	
Upper explosive limit: Not determined	
Vapour pressure: Not determined	
Vapour density (air = 1): Not determined	
Density: 0,829-0,86 g/m	l (20°C)
Bulk density: n.a.	
Solubility(ies): Not determined	
Water solubility: Insoluble	
Partition coefficient (n-octanol/water): Not determined	
Auto-ignition temperature: Not determined	
Decomposition temperature: Not determined	
Viscosity: Not determined	
Explosive properties: Product is not e	explosive.
Oxidising properties: No	
9.2 Other information	
Miscibility: Not determined	
Fat solubility / solvent: Not determined	
Conductivity: Not determined	
Surface tension: Not determined	
Solvents content: Not determined	

SECTION 10: Stability and reactivity

10.1 Reactivity

In use, may form flammable/explosive vapour-air mixture. This product is not reactive based on experiences.

10.2 Chemical stability

Stable with proper storage and handling. **10.3 Possibility of hazardous reactions**Hazardous reactions will not occur during storage and handling under normal conditions. **10.4 Conditions to avoid**Pressure increase will result in danger of bursting.



Page 8 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

Heating, open flame, ignition sources **10.5 Incompatible materials**

œ)

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg	-		
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:					OECD 438 (Isolated Chicken Eye Test Method for Identifying Ocular Corrosives and Severe Irritants)	Non-caustic
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:		1				n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion



Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

œ.

Reproductive toxicity:	OECD 421	Negative,
	(Reproduction/Develo	pm Analogous
	ental Toxicity Screeni	ng conclusion
	Test)	-
Specific target organ toxicity -		No indications of
single exposure (STOT-SE):		such an effect.
Specific target organ toxicity -	OECD 408 (Repeated	No indications of
repeated exposure (STOT-RE):	Dose 90-Day Oral	such an effect.,
	Toxicity Study in	Analogous
	Rodents)	conclusion
Aspiration hazard:		Yes
Symptoms:		unconsciousness
		, headaches,
		dizziness,
		vomiting, fatigue,
		nausea

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1746	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	2-20	mg/l	Rat		
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSI ON)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Aspiration hazard:						No
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousnes , annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness



B Page 10 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)

		SECTI	ON 12: E	Ecologia	cal informatio	n	
Possibly more information Pro-Line Schnell-Rostloo							
Art.: 7390 Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	Lindpoint		- Fullo	0	organioni		n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,1	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

œ.

Water solubility:			~10	mg/l			Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Log Koc		>3				
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to fish:	LC50	96h	1490	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	
12.3. Bioaccumulative potential:	BCF		3,2				
12.3. Bioaccumulative potential:	Log Pow		0,83				Negative
12.4. Mobility in soil:	H (Henry)		0,00000 16	atm*m3/m ol			
12.4. Mobility in soil:	Koc		67				Expert judgen



Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390								
12.5. Results of PBT and vPvB assessment							No PBT substance, No	
Toxicity to bacteria:	EC0	16h	700	mg/l	Pseudomonas putida	DIN 38412 T.8	vPvB substance	
SECTION 13: Disposal considerations								
EC disposal code no.: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. Take full aerosol cans to problem waste collection. Take emptied aerosol cans to valuable material collection. For contaminated packing material Pay attention to local and national official regulations. Recommendation: Return to manufacturer with residual pressure.								
Do not perforate, cut up o				Transpo	ort information	1		
General statemen	Its			1950)			
Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name: UN 1950 AEROSOLS 14.3. Transport hazard class(es): 2.1 14.4. Packing group: - Classification code: 5F LQ: 1 L 14.5. Environmental hazards: Not applicable						•		
Tunnel restriction code: D Transport by sea (IMDG-code) 14.2. UN proper shipping name: AEROSOLS 14.3. Transport hazard class(es): 2.1 14.4. Packing group: - EmS: F-D, S-U Marine Pollutant: n.a								
14.5. Environmental hazards: Not applicable Transport by air (IATA) Not applicable 14.2. UN proper shipping name: Acrosols, flammable 14.3. Transport hazard class(es): 2.1 14.4. Packing group: -								
14.5. Environmental haza 14.6. Special prec Persons employed in tran All persons involved in tra Precautions must be take	autions for sporting dang	erous goods r st observe saf		ned.	applicable			



Page 13 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

ആ

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

4, 8, 15

~ 58 %

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.



Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

H319 Causes serious eye irritation. H332 Harmful if inhaled.

അ

Aerosol — Aerosols Asp. Tox. — Aspiration hazard Acute Tox. — Acute toxicity - oral Eye Irrit. — Eye irritation Skin Irrit. — Skin irritation Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

AC **Article Categories** acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) Biochemical oxygen demand BOD BSEF Bromine Science and Environmental Forum body weight bw CAS **Chemical Abstracts Service** Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CEC CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic Chemical oxygen demand COD CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEA European Economic Area EEC European Economic Community European Inventory of Existing Commercial Chemical Substances FINECS ELINCS European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA ERC **Environmental Release Categories** Exposure scenario ES et cetera etc. FU European Union EWC European Waste Catalogue Fax. Fax number



Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390 general gen. ĞHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential International Agency for Research on Cancer IARC International Air Transport Association IATA Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) Inhibitory concentration IC IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform ChemicaL Information Database lethal concentration LC LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration LD Lethal Dose of a chemical Lethal Dose, 50% kill LD50 Lethal Dose Low LDLo LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAECNo Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP **Ozone Depletion Potential** OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic PC Chemical product category PF Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) Volatile organic compounds VOC very persistent and very bioaccumulative vPvB

ആ



Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.06.2018 / 0026 Replacing version dated / version: 20.09.2017 / 0025 Valid from: 29.06.2018 PDF print date: 02.07.2018 Pro-Line Schnell-Rostloeser 400 ml Art.: 7390

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

œ

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.