

Page 1 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Pro-Line Haftschmier Spray 400 ml

Art.: 7388

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Aquatic Chronic 3 H412-Harmful to aquatic life with long lasting effects.

Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to special waste collection point.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	
content %	2,5-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Aguatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!



Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

With long-term contact:

Dermatitis (skin inflammation)

Drying of the skin.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Extinction powder

Sand

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Oxides of phosphorus

Oxides of nitrogen

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures



Page 4 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020 Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Do not keep the container sealed.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3





Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml Art.: 7388

Art.: 7388				
WEL-TWA: 1000 mg/m3	WEL-STEL:			
Monitoring procedures:	 Compur - KITA-187 S (551 174) 			
BMGV:		Other information: EH40)	(WEL acc.	to RCP-method,
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics	, <5% n-hexane		Content %:1-5
WEL-TWA: 600 mg/m3	WEL-STEL:			
Monitoring procedures:	- Compur - KITA-187 S (551 174)			
BMGV:		Other information: EH40)	(WEL acc.	to RCP-method,
Chemical Name	Oil mist, mineral			Content %:
© Chemical Name WEL-TWA: 5 mg/m3 (ACGIH)	Oil mist, mineral WEL-STEL: 10 mg/m3 (ACGII	H)		Content %:
	WEL-STEL: 10 mg/m3 (ACGII - Draeger - Oil 10/a-P (67 28 371)	H)		Content %:
WEL-TWA: 5 mg/m3 (ACGIH) Monitoring procedures:	WEL-STEL: 10 mg/m3 (ACGII	1)		Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGII - Draeger - Oil 10/a-P (67 28 371)	d) Other information:		Content %:
WEL-TWA: 5 mg/m3 (ACGIH) Monitoring procedures:	WEL-STEL: 10 mg/m3 (ACGII - Draeger - Oil 10/a-P (67 28 371)			Content %:
WEL-TWA: 5 mg/m3 (ACGIH) Monitoring procedures: BMGV: Chemical Name WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: 10 mg/m3 (ACGII - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	Other information:		
WEL-TWA: 5 mg/m3 (ACGIH) Monitoring procedures: BMGV: BMGV:	WEL-STEL: 10 mg/m3 (ACGIII - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031) Hydrocarbons, C3-4 WEL-STEL: 1250 ppm (2180 r	Other information:		

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit
- value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane											
Area of application	Exposure route / Environmental compartment	vironmental		Value	Unit	Note					
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d						
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d						
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3						
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3						
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d						

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	



Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

Workers / employees	Human - dermal	Long term, systemic	DNEL	300	mg/kg	
		effects			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2035	mg/m3	
		effects				

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,33

Permeation time (penetration time) in minutes:

480

Safety gloves made of butyl (EN 374)

Minimum layer thickness in mm:

0,8

Permeation time (penetration time) in minutes:

120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.



Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Characteristic Odour: Characteristic Odour threshold: Not determined

pH-value: n.a.

Melting point/freezing point: Not determined

Initial boiling point and boiling range: n.a. Flash point: n.a.

Not determined Evaporation rate:

Flammability (solid, gas):

Not determined Lower explosive limit: Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: ~0,62 g/ml Bulk density: n.a.

Not determined Solubility(ies): Water solubility: Insoluble Not determined Partition coefficient (n-octanol/water):

Auto-ignition temperature: Not determined Decomposition temperature: Not determined

Viscosity: n.a.

Explosive properties: Product is not explosive. Possible build up of explosive/highly

flammable vapour/air mixture. No

Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects



Page 8 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml Art.: 7388

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	25,2	mg/l/4h	Rat		
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Slightly irritant
Respiratory or skin						Not sensitizising
sensitisation:						
Aspiration hazard:						Yes
Symptoms:						may cause
						headaches and
						vertigo.

Hydrocarbons, C6-C7, n-alkane	es, isoalkanes	s, cyclics, <5%	% n-hexane			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Mild irritant
					Irritation/Corrosion)	(Analogous
						conclusion)
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Analogous
					Reverse Mutation Test)	conclusion,
						Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal	Analogous
					Developmental Toxicity	conclusion,
					Study)	Negative
Specific target organ toxicity -						May cause
single exposure (STOT-SE):						drowsiness or
						dizziness.
Specific target organ toxicity -						Negative
repeated exposure (STOT-RE):						



Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml Art.: 7388

Aspiration hazard:			Yes
Symptoms:			drowsiness,
			unconsciousness
			heart/circulatory
			disorders,
			headaches,
			cramps,
			drowsiness,
			mucous
			membrane
			irritation,
			dizziness,
			nausea and
			vomiting.
Specific target organ toxicity -			Not irritant
single exposure (STOT-SE),			(respiratory tract).
inhalative:			

Hydrocarbons, C3-4										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Symptoms:						malaise, nausea,				
						dizziness,				
						mucous				
						membrane				
						irritation,				
						drowsiness,				
						unconsciousness				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Pro-Line Haftschmier Sp	ray 400 ml						
Art.: 7388							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							
Other information:							According to the
							recipe, contains
							no AOX.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l			Goldforelle (Oncorhynchus aguabonita)
12.1. Toxicity to daphnia:	EL50	48h	3	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	30	mg/l	Pseudokirchneriell a subcapitata		

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane



Œ

Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish,	
•						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202	
12.11 Toxiony to daprima.	2000	1011		1119/1	Baprilla magna	(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211	
12.1. Toxicity to daprilla.	NOEC/NOEL	Ziu	'	mg/i	Dapilila iliagila		
						(Daphnia magna	
40.4 Tandakuta danbalar	NOTID	401-	0.4	/1	Danhair mana	Reproduction Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna	0505 004 (4)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	81	%			Analogous
degradability:							conclusion
12.3. Bioaccumulative	BCF		242-253				
potential:							
12.4. Mobility in soil:							Adsorption in
							ground., Produc
							is slightly volatile
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Other information:	AOX		0	%			1 = 1 = 1 = 1
		1		1 11		1	

Hydrocarbons, C3-4							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Biodegradable
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3)., Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:



Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations. Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

2.1 14.3. Transport hazard class(es): 14.4. Packing group: 5F Classification code: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

2.1 14.3. Transport hazard class(es): 14.4. Packing group: F-D. S-U FmS:

Marine Pollutant:

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):









Page 12 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
Tiazara categories	Notes to Affick 1	dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 84.3 % Directive 2010/75/EU (VOC): 522,7 g/l

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

8, 15

Revised sections: Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used		
(EC) No. 1272/2008 (CLP)			
Aquatic Chronic 3, H412	Classification according to calculation procedure.		
Aerosol 1, H222	Classification according to calculation procedure.		
Aerosol 1, H229	Classification based on the form or physical state.		

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

 ${\rm Skin\ Irrit.} - {\rm Skin\ irritation}$

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Any abbreviations and acronyms used in this document:

AC **Article Categories**

according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level Adsorbable organic halogen compounds



Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

approx. approximately

Art., Art. no. Article number

Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATF

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK)

Biochemical oxygen demand BOD

BSEF Bromine Science and Environmental Forum

body weight bw

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level Dissolved organic carbon DOC

Dwell Time - 50% reduction of start concentration DT50

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EC **European Community** ECHA European Chemicals Agency **EEA** European Economic Area European Economic Community **EEC**

European Inventory of Existing Commercial Chemical Substances **EINECS**

ELINCS European List of Notified Chemical Substances

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

FRC **Environmental Release Categories**

ES Exposure scenario

etc. et cetera FU European Union

EWC European Waste Catalogue

Fax. Fax number general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC: Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

LC lethal concentration

lethal concentration 50 percent kill LC50 LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill Lethal Dose Low LDLo

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration



Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2018 / 0020

Replacing version dated / version: 06.11.2017 / 0019

Valid from: 25.06.2018 PDF print date: 25.06.2018 Pro-Line Haftschmier Spray 400 ml

Art.: 7388

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAECNo Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.