

GB

Page 1 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SPEED BENZIN ZUSATZ 1 L
Art.: 5105

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
 Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|-----------------|-----------------|---|
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |
| Aquatic Chronic | 3 | H412-Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Page 2 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting.
 P405-Store locked up.
 P501-Dispose of contents / container to special waste collection point.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Hydrocarbons, C10, aromatics, >1% naphthalene
 Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | |
|--|-------------------------------|
| Registration number (REACH) | 01-2119457273-39-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 918-481-9 (REACH-IT List-No.) |
| CAS | --- |
| content % | 80-<100 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Asp. Tox. 1, H304 |

| Hydrocarbons, C10, aromatics, >1% naphthalene | |
|---|---|
| Registration number (REACH) | --- |
| Index | --- |
| EINECS, ELINCS, NLP | 919-284-0 (REACH-IT List-No.) |
| CAS | (64742-94-5) |
| content % | 1-<2,5 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 |

| Naphthalene | |
|---|---|
| Registration number (REACH) | --- |
| Index | 601-052-00-2 |
| EINECS, ELINCS, NLP | 202-049-5 |
| CAS | 91-20-3 |
| content % | 0,1-<0,25 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Carc. 2, H351 Acute Tox. 4, H302 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Page 3 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 17.04.2018 / 0025
Replacing version dated / version: 05.11.2015 / 0024
Valid from: 17.04.2018
PDF print date: 19.04.2018
SPEED BENZIN ZUSATZ 1 L
Art.: 5105

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."
Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.
Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.
Protective hand cream recommended.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
Danger of aspiration
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes
Irritation of the respiratory tract
Headaches
Dizziness
Effects/damages the central nervous system
Coordination disorders
Unconsciousness
Liver and kidney damage
Blood count modifications
Nausea
Vomiting
Danger of aspiration
Oedema of the lungs

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion:
Activated carbon
Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Exinction powder
Foam
Water jet spray

Unsuitable extinguishing media

Page 4 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 17.04.2018 / 0025
Replacing version dated / version: 05.11.2015 / 0024
Valid from: 17.04.2018
PDF print date: 19.04.2018
SPEED BENZIN ZUSATZ 1 L
Art.: 5105

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Ensure sufficient ventilation.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

GB

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

Solvent resistant floor
 Do not store with oxidizing agents.
 Store in a well ventilated place.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

| Chemical Name | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | Content %:80- <100 |
|--------------------------------|--|-----------------------|
| WEL-TWA: 800 mg/m ³ | WEL-STEL: --- | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: (WEL acc. to RCP-method, EH40) | |

| Chemical Name | Hydrocarbons, C10, aromatics, >1% naphthalene | Content %:1-<2,5 |
|--|--|------------------|
| WEL-TWA: 500 mg/m ³ (Aromatics) | WEL-STEL: --- | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: --- | |

| Chemical Name | Naphthalene | Content %:0,1- <0,25 |
|--|------------------------------------|-------------------------|
| WEL-TWA: 10 ppm (50 mg/m ³) (EU) | WEL-STEL: --- | --- |
| Monitoring procedures: | - Compur - KITA-153 U(C) (551 182) | |
| BMGV: --- | Other information: --- | |

| Chemical Name | Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | Content %: |
|--|--|------------|
| WEL-TWA: 1200 mg/m ³ (>=C7 normal and branched chain alkanes) | WEL-STEL: 2(II) (AGW) | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: --- | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

| Naphthalene | | | | | | |
|---------------------|--|------------------|------------|-------|------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 2,4 | µg/l | |
| | Environment - marine | | PNEC | 0,24 | µg/l | |

Page 6 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

| | | | | | | |
|---------------------|--------------------------------------|-----------------------------|------|--------|-------------------|--|
| | Environment - sewage treatment plant | | PNEC | 2,9 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,0672 | mg/kg dry weight | |
| | Environment - sediment, marine | | PNEC | 0,0672 | mg/kg dry weight | |
| | Environment - soil | | PNEC | 0,0533 | mg/kg dry weight | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 3,57 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 25 | mg/m ³ | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 25 | mg/m ³ | |

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective Viton® / fluoroelastomer gloves (EN 374)

Permeation time (penetration time) in minutes:

>480

Minimum layer thickness in mm:

0,4

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state: | Liquid |
| Colour: | Light yellow |
| Colour: | Clear |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | n.a. |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | 145 °C |
| Flash point: | >61 °C |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | n.a. |
| Lower explosive limit: | Not determined |
| Upper explosive limit: | Not determined |
| Vapour pressure: | Not determined |
| Vapour density (air = 1): | Vapours heavier than air. |
| Density: | 0,765 g/ml (20°C) |
| Bulk density: | n.a. |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | Not determined |
| Decomposition temperature: | Not determined |
| Viscosity: | <7 mm ² /s (40°C) |
| Explosive properties: | Product is not explosive. When using: development of explosive vapour/air mixture possible. |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | Not determined |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 17.04.2018 / 0025

Replacing version dated / version: 05.11.2015 / 0024

Valid from: 17.04.2018

PDF print date: 19.04.2018

SPEED BENZIN ZUSATZ 1 L

Art.: 5105

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

SPEED BENZIN ZUSATZ 1 L

Art.: 5105

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|------|----------|-------------|---|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | negative, the real Naphthalene content is <1% |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-------|-------|----------|-------------|---|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >3160 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LC50 | >4951 | mg/m3 | Rat | | |
| Skin corrosion/irritation: | | | | | | Vapours Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Respiratory or skin sensitisation: | | | | | | No (skin contact) |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | unconsciousness, headaches, dizziness |
| Other information: | | | | | | Repeated exposure may cause skin dryness or cracking. |

Hydrocarbons, C10, aromatics, >1% naphthalene

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-------|-------|------------|--------------------------------------|-----------------|
| Acute toxicity, by oral route: | LD50 | ~7093 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >4688 | mg/m3 | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitising |

Naphthalene

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|-------------------|----------|-------|------|----------|-------------|-------|
|-------------------|----------|-------|------|----------|-------------|-------|

Page 9 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

| | | | | | | |
|----------------------------------|------|-------|---------|-----|--|---|
| Acute toxicity, by oral route: | LD50 | 490 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >2500 | mg/kg | Rat | | |
| Acute toxicity, by inhalation: | LC50 | >110 | mg/l/4h | | | |
| Symptoms: | | | | | | lack of appetite, ataxia, breathing difficulties, unconsciousness , diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting. |

| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|--|----------|-------|-----------------------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5000 | mg/m ³ /8h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours |
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking. |
| Skin corrosion/irritation: | | | | | OECD 404 (Acute Dermal Irritation/Corrosion) | Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation) |
| Serious eye damage/irritation: | | | | | OECD 405 (Acute Eye Irritation/Corrosion) | Analogous conclusion, Slightly irritant |
| Respiratory or skin sensitisation: | | | | Rat | | Not sensitising |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | in vivo | Negative |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Analogous conclusion, Negative |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Analogous conclusion, Negative |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Analogous conclusion, No indications of such an effect. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Analogous conclusion, Not to be expected |
| Aspiration hazard: | | | | | | Yes |

Page 10 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

| | | | | | | | |
|-----------|--|--|--|--|--|--|---|
| Symptoms: | | | | | | | drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting |
|-----------|--|--|--|--|--|--|---|

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| SPEED BENZIN ZUSATZ 1 L | | | | | | | |
|--|----------|------|-------|------|----------|-------------|--|
| Art.: 5105 | | | | | | | |
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | Isolate as much as possible with an oil separator. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |
| Other information: | | | | | | | According to the recipe, contains no AOX. |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | | |
|--|----------|------|-------|------|---------------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.1. Toxicity to fish: | LL50 | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,101 | mg/l | Oncorhynchus mykiss | | |
| 12.1. Toxicity to daphnia: | EL50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 0,176 | mg/l | Daphnia magna | | |
| 12.2. Persistence and degradability: | | 28d | 80 | % | activated sludge | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.1. Toxicity to algae: | EL50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| Other organisms: | EL50 | 48h | >1000 | mg/l | Tetrahymen pyriformis | | |

| Hydrocarbons, C10, aromatics, >1% naphthalene | | | | | | | |
|---|----------|------|-------|------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |

Page 11 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

| | | | | | | | |
|----------------------------|------|-----|-------|------|--------------------------|--|--|
| 12.1. Toxicity to daphnia: | EL50 | 48h | 10 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 72h | >1-<3 | mg/l | Raphidocelis subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |

Naphthalene

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|----------------------------|----------|------|-------|------|---------------------------|-------------|-------|
| 12.1. Toxicity to fish: | LC50 | 96h | 0,51 | mg/l | | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 2,19 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to algae: | LC50 | 4h | 2,96 | mg/l | Selenastrum capricornutum | | |
| Other information: | COD | | 22 | % | | | |
| Other information: | Log Pow | | 3,3 | | | | |

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|---------------------------------|--|-------------------------------------|
| 12.1. Toxicity to fish: | NOELR | 28d | 0,17 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 1,22 | mg/l | Daphnia magna | QSAR | |
| 12.1. Toxicity to algae: | NOELR | 72h | 1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 69 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 6-8 | | | | High |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Implement substance recycling.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): ~ 96 %

Directive 2010/75/EU (VOC): ~ 764,1 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 4, 8, 15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |
| Aquatic Chronic 3, H412 | Classification according to calculation procedure. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Page 13 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Carc. — Carcinogenicity
 Acute Tox. — Acute toxicity - oral
 Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario

Page 14 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.04.2018 / 0025
 Replacing version dated / version: 05.11.2015 / 0024
 Valid from: 17.04.2018
 PDF print date: 19.04.2018
 SPEED BENZIN ZUSATZ 1 L
 Art.: 5105

etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 17.04.2018 / 0025

Replacing version dated / version: 05.11.2015 / 0024

Valid from: 17.04.2018

PDF print date: 19.04.2018

SPEED BENZIN ZUSATZ 1 L

Art.: 5105

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.