

Page 1 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Injection Reiniger 300 mL

Art.: 5110

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives

അ

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet $(\ensuremath{\mathbb{R}})$

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC)Hazard classHazard categoryHazard statementAsp. Tox.1H304-May be fatal if swallowed and enters airways.Aquatic Chronic3H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to special waste collection point.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10, aromatics, >1% naphthalene Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

ആ

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatic	CS
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	919-284-0 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411
Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP	202-049-5
CAS	91-20-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351
	Acute Tox. 4, H302
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.



Page 3 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Protective hand cream recommended.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur:

Irritation of the eyes Irritation of the respiratory tract Headaches Dizziness Effects/damages the central nervous system Coordination disorders Unconsciousness Liver and kidney damage Blood count modifications Nausea Vomiting Danger of aspiration Oedema of the lungs

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion: Activated carbon

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2 Extinction powder Foam Water jet spray Unsuitable extinguishing media



Page 4 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

High volume water jet 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Hydrocarbons Toxic pyrolysis products. Explosive vapour/air or gas/air mixtures. Dangerous vapours heavier than air. In case of spreading near the ground, flashback to distance sources of ignition is possible. **5.3 Advice for firefighters**

ആ

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Ensure sufficient ventilation. 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells.



Page 5 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Solvent resistant floor Do not store with oxidizing agents. Store in a well ventilated place. Protect from direct sunlight and warming.

7.3 Specific end use(s)

ആ

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C1	0-C13, n-alkanes, isoalkanes, cyclic	cs, <2% aromatics		Content %:80- <100
WEL-TWA: 800 mg/m3		WEL-STEL:			
Monitoring procedures:	- 1	Draeger - Hydrocarbons 2/a (81 03 Draeger - Hydrocarbons 0,1%/c (81 Compur - KITA-187 S (551 174)			
BMGV:			Other information: EH40)	(WEL acc.	to RCP-method,
Chemical Name	Hydrocarbons, C1	0, aromatics, >1% naphthalene			Content %:1-<2,5
WEL-TWA: 500 mg/m3 (Aromatics		WEL-STEL:			
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03 Draeger - Hydrocarbons 0,1%/c (81 Compur - KITA-187 S (551 174)			
BMGV:			Other information:		
⁽³⁸⁾ Chemical Name	Naphthalene				Content %:0,1- <0,25
WEL-TWA: 500 mg/m3 (Aromatics (50 mg/m3) (EU)		WEL-STEL:			
Monitoring procedures:	- (Compur - KITA-153 U(C) (551 182)			
BMGV:			Other information:		
Chemical Name		1-C14, n-alkanes, isoalkanes, cyclic	cs, <2% aromatics		Content %:
WEL-TWA: 1200 mg/m3 (>=C7 no chain alkanes)	ormal and branched	WEL-STEL: 2(II) (AGW)			
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 03	581)	·	
		Draeger - Hydrocarbons 0,1%/c (81 Compur - KITA-187 S (551 174)	03 571)		
BMGV:			Other information:		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Naphthalene						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	2,4	µg/l	



Page 6 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

	Environment - marine		PNEC	0,24	µg/l
	Environment - sewage		PNEC	2,9	mg/l
	treatment plant				
	Environment - sediment,		PNEC	0,0672	mg/kg dry
	freshwater				weight
	Environment - sediment,		PNEC	0,0672	mg/kg dry
	marine				weight
	Environment - soil		PNEC	0,0533	mg/kg dry
					weight
Workers / employees	Human - dermal	Long term, systemic	DNEL	3,57	mg/kg
		effects			bw/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

ആ

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective Viton® / fluoroelastomer gloves (EN 374) Permeation time (penetration time) in minutes: >480 Minimum layer thickness in mm: 0,4 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.



Page 7 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

ആ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Physical state: Liquid

Physical state: Colour: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties:

Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

Light yellow Clear Characteristic Not determined n.a. Not determined 145 °C >61 °C Not determined n.a. Not determined Not determined Not determined Vapours heavier than air. 0,765 g/ml (20°C) n.a. Not determined Insoluble Not determined Not determined Not determined <7 mm2/s (40°C) Product is not explosive. When using: development of explosive vapour/air mixture possible. No

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Heating, open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** No decomposition when used as directed.



œ Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

SECTION 11: Toxicological information

11.1 Information on toxicological effects Possibly more information on health effects, see Section 2.1 (classification). Injection Reiniger 300 mL

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the
						real
						Naphthalene
						content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alka	anes, isoalkan	es, cyclics, <	2% aromatics			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4951	mg/m3	Rat		Vapours
Skin corrosion/irritation:						Not irritant,
						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin						No (skin contact)
sensitisation:						
Aspiration hazard:						Yes
Symptoms:						unconsciousness
						, headaches,
						dizziness
Other information:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.

Hydrocarbons, C10, aromatics,	Hydrocarbons, C10, aromatics, >1% naphthalene								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	~7093	mg/kg	Rat	OECD 401 (Acute Oral				
					Toxicity)				
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute				
					Dermal Toxicity)				
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute				
					Inhalation Toxicity)				
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising			
sensitisation:					Sensitisation)				



B Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Naphthalene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h			
Symptoms:						lack of appetite, ataxia, breathing difficulties, unconsciousness , diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute	Vapours
			-		Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Skin corrosion/irritation:					OECD 404 (Acute	Analogous
					Dermal	conclusion,
					Irritation/Corrosion)	Drying of the
						skin., Dermatitis
						(skin
						inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye	Analogous
, ,					Irritation/Corrosion)	conclusion,
					,	Slightly irritant
Respiratory or skin				Rat		Not sensitizising
sensitisation:						
Germ cell mutagenicity:				Salmonella	in vivo	Negative
				typhimurium		_
Carcinogenicity:					OECD 453 (Combined	Analogous
					Chronic	conclusion,
					Toxicity/Carcinogenicity	Negative
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Analogous
					Developmental Toxicity	conclusion,
					Study)	Negative
Specific target organ toxicity -						Analogous
single exposure (STOT-SE):						conclusion, No
o						indications of
						such an effect.



B Page 10 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Specific target organ toxicity -		OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE):		Dose 90-Day Oral	conclusion, Not
		Toxicity Study in	to be expected
		Rodents)	
Aspiration hazard:			Yes
Symptoms:			drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

SECTION 12: Ecological information

Injection Reiniger 300 m	L						
Art.: 5110							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with
							an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.2. Persistence and		28d	80	%	activated sludge	OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	



Page 11 of 15 Safety data sheet accordir Revision date / version: 09 Replacing version dated / Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110	0.07.2018 / 002 version: 04.05.3	27		nex II			
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		
Hydrocarbons, C10, aror	natics, >1% na						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EL50	48h	10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>1-<3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,51	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	2,19	mg/l	Daphnia magna		
12.1. Toxicity to algae:	LC50	4h	2,96	mg/l	Selenastrum capricornutum		
Other information:	COD		22	%			
Other information:	Log Pow		3,3				
Hydrocarbons, C11-C14,	n-alkanos isc	alkanes cy	clice <2% a	romatics			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		6-8				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely. Uncontaminated packaging can be recycled.



Page 12 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

œ

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

8

~ 96 %

~ 764,1 g/l

Revised sections:

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.



Page 13 of 15

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic STOT SE — Specific target organ toxicity - single exposure - narcotic effects Carc. — Carcinogenicity Acute Tox. — Acute toxicity - oral Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC **Article Categories** acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight **Chemical Abstracts Service** CAS CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) carcinogenic, mutagenic, reproductive toxic CMR Chemical oxygen demand COD CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. ΕČ European Community ECHA European Chemicals Agency EEA European Economic Area European Economic Community FFC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances



-08					
Page 14 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II					
Revision date / version: 09.07.2018 / 0027					
Replacing version dated / version: 04.05.2018 / 0026					
Valid from: 09.07.2018					
PDF print date: 09.07.2018					
Injection Reiniger 300 mL					
Art.: 5110					
EN European Norms					
EN European Norms EPA United States Environmental Protection Agency (United States of America)					
ERC Environmental Release Categories					
ES Exposure scenario					
etc. et cetera					
EU European Union					
EWC European Waste Catalogue					
Fax. Fax number					
gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals					
GWP Global warming potential					
HET-CAM Hen's Egg Test - Chorionallantoic Membrane					
HGWP Halocarbon Global Warming Potential					
IARC International Agency for Research on Cancer					
IATA International Air Transport Association					
IBC Intermediate Bulk Container					
IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration					
IMDG-code International Maritime Code for Dangerous Goods					
incl. including, inclusive					
IUCLID International Uniform ChemicaL Information Database					
LC lethal concentration					
LC50 lethal concentration 50 percent kill					
LCLo lowest published lethal concentration					
LD Lethal Dose of a chemical					
LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low					
LOAEL Lowest Observed Adverse Effect Level					
LOEC Lowest Observed Effect Concentration					
LOEL Lowest Observed Effect Level					
LQ Limited Quantities					
MARPOL International Convention for the Prevention of Marine Pollution from Ships					
n.a. not applicable					
n.av. not available n.c. not checked					
n.d.a. no data available					
NIOSH National Institute of Occupational Safety and Health (United States of America)					
NOAECNo Observed Adverse Effective Concentration					
NOAEL No Observed Adverse Effect Level					
NOEC No Observed Effect Concentration					
NOEL No Observed Effect Level					
ODP Ozone Depletion Potential OECD Organisation for Economic Co-operation and Development					
org. organisation of Economic Co-operation and Development					
PAH polycyclic aromatic hydrocarbon					
PBT persistent, bioaccumulative and toxic					
PC Chemical product category					
PE Polyethylene					
PNEC Predicted No Effect Concentration					
POCP Photochemical ozone creation potential ppm parts per million					
ppm parts per million PROC Process category					
PTFE Polytetrafluorethylene					
REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,					
Evaluation, Authorisation and Restriction of Chemicals)					
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List					
Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.					
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International					
Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature					
SAR Structure Activity Relationship					
SU Sector of use					
SVHC Substances of Very High Concern					



Page 15 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.07.2018 / 0027 Replacing version dated / version: 04.05.2018 / 0026 Valid from: 09.07.2018 PDF print date: 09.07.2018 Injection Reiniger 300 mL Art.: 5110

Telephone Tel. ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) United Nations Recommendations on the Transport of Dangerous Goods UN RTDG Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

œ

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.