

GB

Page 1 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**ProLine Jet Clean Benzin System Reiniger K 500 mL**  
**Art.: 5152**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Additive

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
 Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Flam. Liq.	3	H226-Flammable liquid and vapour.
Eye Irrit.	2	H319-Causes serious eye irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Danger

Page 2 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

H226-Flammable liquid and vapour. H319-Causes serious eye irritation. H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273-Avoid release to the environment. P280-Wear eye protection / face protection.  
 P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. P337+P313-If eye irritation persists: Get medical advice / attention.  
 P405-Store locked up.  
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Xylene  
 Hydrocarbons, C10, aromatics, >1% naphthalene  
 Hydrocarbons, C9, aromatics  
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	---
content %	70-90
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	919-284-0 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Polyolefin alkylphenol alkylamine (Conf0621)	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	n.a.
CAS	n.a.
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315

Xylene	Substance for which an EU exposure limit value applies.
--------	---

GB

Page 3 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

<b>Registration number (REACH)</b>	01-2119488216-32-XXXX
<b>Index</b>	601-022-00-9
<b>EINECS, ELINCS, NLP</b>	215-535-7
<b>CAS</b>	1330-20-7
<b>content %</b>	1-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373

<b>Alkaryl polyether (ACC-HR410712-34)</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	n.a.
<b>CAS</b>	n.a.
<b>content %</b>	1-5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Chronic 3, H412

<b>2-methylpropan-1-ol</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-108-00-1
<b>EINECS, ELINCS, NLP</b>	201-148-0
<b>CAS</b>	78-83-1
<b>content %</b>	1-<3
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336

<b>Hydrocarbons, C9, aromatics</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	918-668-5 (REACH-IT List-No.)
<b>CAS</b>	(64742-95-6)
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411

<b>Diethylbenzene</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	246-874-9
<b>CAS</b>	25340-17-4
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

Page 4 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.07.2019 / 0017  
Replacing version dated / version: 22.02.2019 / 0016  
Valid from: 12.07.2019  
PDF print date: 12.07.2019  
ProLine Jet Clean Benzin System Reiniger K 500 mL  
Art.: 5152

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.  
Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."  
Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.  
If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
Danger of aspiration.  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Ingestion:

Oedema of the lungs

Lung damage

With long-term contact:

Product removes fat.

Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>

Extinguishing powder

Foam

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Page 5 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.07.2019 / 0017  
Replacing version dated / version: 22.02.2019 / 0016  
Valid from: 12.07.2019  
PDF print date: 12.07.2019  
ProLine Jet Clean Benzin System Reiniger K 500 mL  
Art.: 5152

According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep unprotected persons away.  
Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
Avoid inhalation, and contact with eyes or skin.  
If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Keep away from sources of ignition - Do not smoke.  
Take precautions against electrostatic charges.  
Avoid contact with eyes or skin.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Store product closed and only in original packing.  
Not to be stored in gangways or stair wells.  
Observe special storage conditions.  
Solvent resistant floor  
Do not store with oxidizing agents.  
Protect from direct sunlight and warming.  
Store in a well-ventilated place.  
Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

GB

Page 6 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:70-90
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Hydrocarbons, C10, aromatics, >1% naphthalene	Content %:1-10
WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: ---	

Chemical Name	Xylene	Content %:1-<5
WEL-TWA: 220 mg/m <sup>3</sup> (50 ppm) (WEL), 50 ppm (221 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 100 ppm (441 mg/m <sup>3</sup> (WEL), 100 ppm (442 mg/m <sup>3</sup> ) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-143 SA (550 325)</li> <li>- Compur - KITA-143 SB (505 998)</li> <li>- Draeger - Xylene 10/a (67 33 161)</li> <li>- MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004)</li> </ul>	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)	

Chemical Name	2-methylpropan-1-ol	Content %:1-<3
WEL-TWA: 50 ppm (154 mg/m <sup>3</sup> )	WEL-STEL: 75 ppm (231 mg/m <sup>3</sup> )	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-208 U (549 426)</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>	
BMGV: ---	Other information: ---	

Chemical Name	Hydrocarbons, C9, aromatics	Content %:1-<2,5
WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: ---	

Hydrocarbons, C10, aromatics, >1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m <sup>3</sup>	

**Xylene**

Page 7 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - periodic release		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	0,327	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	

2-methylpropan-1-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	
	Environment - marine		PNEC	0,04	mg/l	
	Environment - sediment, freshwater		PNEC	1,52	mg/kg	
	Environment - sediment, marine		PNEC	0,152	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,0699	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	11	mg/l	
Consumer	Human - oral	Long term, local effects	DNEL	25	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	25	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	55	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	55	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	310	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	310	mg/m <sup>3</sup>	



GB

Page 8 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Hydrocarbons, C9, aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m <sup>3</sup>	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN 374).  
 If applicable  
 Protective nitrile gloves (EN 374).  
 Minimum layer thickness in mm:  
 >= 0,4  
 Permeation time (penetration time) in minutes:  
 >= 480  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective Neoprene® / polychloroprene gloves (EN 374).  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).



Page 9 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

**Respiratory protection:**  
 If OES or MEL is exceeded.  
 Gas mask filter A (EN 14387), code colour brown  
 At high concentrations:  
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)  
 Observe wearing time limitations for respiratory protection equipment.

**Thermal hazards:**  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	145-200 °C
Flash point:	43 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,809 g/ml (15°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm <sup>2</sup> /s (40°C)
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No decomposition if used as intended.

## 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Electrostatic charge

## 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.  
 Avoid contact with strong acids.

## 10.6 Hazardous decomposition products

No decomposition when used as directed.

# SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

### ProLine Jet Clean Benzin System Reiniger K 500 mL

Art.: 5152

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the real Naphthalene content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion

Page 11 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness
Other information:						Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10, aromatics, >1% naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion

Page 12 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						drowsiness, headaches, drowsiness, dizziness

<b>Xylene</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LD50	27,6	mg/l/4h	Rat		Does not conform with EU classification., Vapours
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Irritant
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						Yes
Symptoms:						breathing difficulties, headaches, dizziness, Lung damage
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

<b>2-methylpropan-1-ol</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2460-3350	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000-2460	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

Page 13 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Acute toxicity, by inhalation:	LC50	19,2	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Symptoms:						respiratory distress, drowsiness, unconsciousness, vomiting, coughing, headaches, drowsiness, mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

Hydrocarbons, C9, aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative

Page 14 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H335, STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative
Aspiration hazard:						Yes
Symptoms:						respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness, fever, ear noises, drying of the skin.

Diethylbenzene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2050	mg/kg	Rat	U.S. EPA 81-1	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	U.S. EPA 81-2	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

ProLine Jet Clean Benzin System Reiniger K 500 mL Art.: 5152							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:	AOX						According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 15 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Product floats on the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

#### Hydrocarbons, C10, aromatics, >1% naphthalene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	57,95	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,8-6,5				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Xylene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		3,16				
12.4. Mobility in soil:	H (Henry)		665	Pa*m <sup>3</sup> /mol			

#### 2-methylpropan-1-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1430	mg/l	Pimephales promelas		References
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	20	mg/l			
12.1. Toxicity to daphnia:	EC50	24h	583	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to algae:	EC50	48h	1250	mg/l	Scenedesmus subspicatus		



Page 16 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

12.2. Persistence and degradability:	DOC	28d	99	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	100	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	
12.3. Bioaccumulative potential:							No
Other information:	COD		2600	mg/g			

#### Hydrocarbons, C9, aromatics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	54-56	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.2. Persistence and degradability:		28d	78	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	78	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		3,7 - 4,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Diethylbenzene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	4,7	%		Regulation (EC) 440/2008 C.4-C (DETERMINATION OF 'READY' BIODEGRADABILITY - CO2 EVOLUTION TEST)	
12.1. Toxicity to fish:	LC50	96h	0,673	mg/l	Salmo gairdneri	OECD 203 (Fish, Acute Toxicity Test)	

Page 17 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

12.1. Toxicity to daphnia:	EC50	48h	2,01	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	1	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: 1993

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:  
UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTANOL,XYLENES)

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Classification code: F1

LQ: 5 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D/E



#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
FLAMMABLE LIQUID, N.O.S. (ISOBUTANOL,XYLENES)

14.3. Transport hazard class(es): 3

14.4. Packing group: III

EmS: F-E, S-E

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



#### Transport by air (IATA)

14.2. UN proper shipping name:  
Flammable liquid, n.o.s. (ISOBUTANOL,XYLENES)

14.3. Transport hazard class(es): 3

14.4. Packing group: III

14.5. Environmental hazards: Not applicable



### 14.6. Special precautions for user

Page 18 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freight as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 92,7722 %

Observe incident regulations.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 8  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.

Page 19 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 12.07.2019 / 0017  
 Replacing version dated / version: 22.02.2019 / 0016  
 Valid from: 12.07.2019  
 PDF print date: 12.07.2019  
 ProLine Jet Clean Benzin System Reiniger K 500 mL  
 Art.: 5152

H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid  
 Eye Irrit. — Eye irritation  
 Asp. Tox. — Aspiration hazard  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Carc. — Carcinogenicity  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Skin Irrit. — Skin irritation  
 Acute Tox. — Acute toxicity - dermal  
 Acute Tox. — Acute toxicity - inhalation  
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation  
 STOT RE — Specific target organ toxicity - repeated exposure  
 Eye Dam. — Serious eye damage  
 Aquatic Acute — Hazardous to the aquatic environment - acute

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential

Page 20 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 12.07.2019 / 0017  
Replacing version dated / version: 22.02.2019 / 0016  
Valid from: 12.07.2019  
PDF print date: 12.07.2019  
ProLine Jet Clean Benzin System Reiniger K 500 mL  
Art.: 5152

IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.