

Page 1 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 29.06.2018 / 0017  
Replacing version dated / version: 18.04.2018 / 0016  
Valid from: 29.06.2018  
PDF print date: 29.06.2018  
Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
Art.: 3379

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Pro-Line Injektoren- und Gluehkerzenloeser 400 ml**  
**Art.: 3379**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

##### Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

##### Chemical product category [PC]:

PC13 - Fuels

PC35 - Washing and cleaning products

##### Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC11 - Non industrial spraying

PROC16 - Use of fuels

##### Article Categories [AC]:

AC99 - Not required.

##### Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal plant.

Without adequate ventilation, formation of explosive mixtures may be possible.

Benzyl alcohol  
 Xylene (mixture of isomers)  
 Acetone

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

When using: development of explosive vapour/air mixture possible.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

GB

Page 3 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

n.a.  
**3.2 Mixture**

Xylene (mixture of isomers)	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	601-022-00-9
EINECS, ELINCS, NLP	215-535-7
CAS	1330-20-7
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP	200-662-2
CAS	67-64-1
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Benzyl alcohol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119492630-38-XXXX
Index	603-057-00-5
EINECS, ELINCS, NLP	202-859-9
CAS	100-51-6
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Eye Irrit. 2, H319 Acute Tox. 4, H332

Carbon dioxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	204-696-9
CAS	124-38-9
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	---

Fatty alcohol ethoxylate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	78330-21-9
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.06.2018 / 0017

Replacing version dated / version: 18.04.2018 / 0016

Valid from: 29.06.2018

PDF print date: 29.06.2018

Pro-Line Injektoren- und Gluehkerzenloeser 400 ml

Art.: 3379

## Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Respiratory arrest - Artificial respiration apparatus necessary.

## Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

## Eye contact

Wash thoroughly for several minutes using copious water.

Consult medical specialist.

Keep Data Sheet available.

## Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Immediate admittance to a hospital.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Dermatitis (skin inflammation)

Product removes fat.

Skin resorption

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Water jet spray

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Explosive vapour/air or gas/air mixtures.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

### 5.3 Advice for firefighters

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

If leakage occurs, dam up.

GB

Page 5 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.  
 Active substance:  
 Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.  
 Only from a specialist.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Do not use on hot surfaces.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with oxidizing agents.  
 Observe special regulations for aerosols!  
 Store in a well ventilated place.  
 Keep protected from direct sunlight and temperatures over 50°C.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Xylene (mixture of isomers)	Content %:30-50
WEL-TWA: 50 ppm (220 mg/m <sup>3</sup> ) (WEL), 50 ppm (221 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 100 ppm (441 mg/m <sup>3</sup> ) (WEL), 100 ppm (442 mg/m <sup>3</sup> ) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-143 SA (550 325)</li> <li>- Compur - KITA-143 SB (505 998)</li> <li>- Draeger - Xylene 10/a (67 33 161)</li> <li>- MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004)</li> </ul>	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)	

Chemical Name	Acetone	Content %:20-30
WEL-TWA: 500 ppm (1210 mg/m <sup>3</sup> ) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m <sup>3</sup> ) (WEL)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-102 SA (548 534)</li> <li>- Compur - KITA-102 SC (548 550)</li> </ul>	

GB

Page 6 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

- Compur - KITA-102 SD (551 109)
- Draeger - Acetone 40/a (5) (81 03 381)
- Draeger - Acetone 100/b (CH 22 901)
- MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004)
- MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993

BMGV: ---

Other information: ---

**Chemical Name** Carbon dioxide **Content %:1-5**

WEL-TWA: 5000 ppm (9150 mg/m3) (WEL), 5000 ppm (9000 mg/m3) (EU) WEL-STEL: 15000 ppm (27400 mg/m3) (WEL) ---

Monitoring procedures:

- Compur - KITA-126 B (549 475)
- Compur - KITA-126 SA (549 467)
- Compur - KITA-126 SB (548 816)
- Compur - KITA-126 SF (549 491)
- Compur - KITA-126 SG (550 210)
- Compur - KITA-126 SH (549 509)
- Compur - KITA-126 UH (549 517)
- Draeger - Carbon Dioxide 100/a (81 01 811)
- Draeger - Carbon Dioxide 0,1%/a (CH 23 501)
- Draeger - Carbon Dioxide 0,5%/a (CH 31 401)
- Draeger - Carbon Dioxide 1%/a (CH 25 101)
- Draeger - Carbon Dioxide 5%/A (CH 20 301)
- OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990
- NIOSH 6603 (Carbon dioxide) - 1994

BMGV: ---

Other information: ---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

Xylene (mixture of isomers)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg	
	Environment - soil		PNEC	2,31	mg/kg	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, marine		PNEC	12,46	mg/kg	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	

Page 7 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg	

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assesment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assesment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/l	
	Environment - sediment, marine		PNEC	3,04	mg/l	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assesment factor 100
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m <sup>3</sup>	Overall assesment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m <sup>3</sup>	

Benzyl alcohol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	0,456	mg/kg	
	Environment - sewage treatment plant		PNEC	39	mg/l	
	Environment - sediment		PNEC	5,27	mg/kg	
	Environment - sediment, marine		PNEC	0,527	mg/kg	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - periodic release		PNEC	2,3	mg/l	
	Environment - freshwater		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	28,5	mg/kg bw/d	



Page 8 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

Consumer	Human - dermal	Long term, systemic effects	DNEL	5,7	mg/kg bw/d	
Consumer	Human - oral	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	95,5	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	19,1	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	47	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	450	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	90	mg/m3	

Dimethyl glutarate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - inhalation		DNEL	8,3	mg/m3	
	Environment - sediment, marine		PNEC	0,015	mg/kg	
	Environment - sediment, freshwater		PNEC	0,15	mg/kg	
	Environment - marine		PNEC	0,0031	mg/l	
	Environment - freshwater		PNEC	0,031	mg/l	
	Environment - soil		PNEC	0,113	mg/kg	
	Environment - sporadic (intermittent) release		PNEC	0,31	mg/l	

Dimethyl adipate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	0,0018	mg/l	
	Environment - soil		PNEC	0,09	mg/kg	
	Environment - sediment, marine		PNEC	0,016	mg/kg	
	Environment - sediment, freshwater		PNEC	0,16	mg/kg	
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - sporadic (intermittent) release		DNEL	0,18	mg/l	
Industrial	Human - inhalation	Long term	DNEL	8,3	mg/m3	
Consumer	Human - inhalation	Long term	DNEL	5	mg/m3	

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 29.06.2018 / 0017  
Replacing version dated / version: 18.04.2018 / 0016  
Valid from: 29.06.2018  
PDF print date: 29.06.2018  
Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
Art.: 3379

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Safety gloves made of butyl (EN 374)  
Minimum layer thickness in mm:  
0,5  
Permeation time (penetration time) in minutes:  
> 120 (Level 4)  
Protective hand cream recommended.  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
Oil resistant protective clothing (EN 13034)

Respiratory protection:  
Normally not necessary.  
If OES or MEL is exceeded.  
Filter A (EN 14387), code colour brown

Thermal hazards:  
If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	n.a.
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,1 Vol-%
Upper explosive limit:	13 Vol-%
Vapour pressure:	n.a.
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,87 g/ml (Active substance )
Bulk density:	Not determined

Page 10 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	435 °C (Ignition temperature )
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	82,6 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

See also Subsection 10.2 to 10.6.  
The product has not been tested.

### 10.2 Chemical stability

See also Subsection 10.1 to 10.6.  
Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

### 10.4 Conditions to avoid

See also section 7.  
Heating, open flame, ignition sources  
Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

See also section 7.  
Avoid contact with oxidizing agents.

### 10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.  
See also section 5.2

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line Injektoren- und Gluehkerzenloeser 400 ml Art.: 3379						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	3,3	mg/l/4h			calculated value, Aerosol
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.

Page 11 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>Xylene (mixture of isomers)</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	2840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>1700	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	21,7	mg/l/4h	Rat		Vapours, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Symptoms:						breathing difficulties, drying of the skin., drowsiness, unconsciousness , burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea

<b>Acetone</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	~76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Slightly irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative



Page 13 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Xylene (mixture of isomers)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	86	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	24h	75,5	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	10	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		>3				
12.3. Bioaccumulative potential:	BCF		0,6-15				

Acetone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex		
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriella subcapitata		
12.3. Bioaccumulative potential:	Log Pow		-0,24				
12.3. Bioaccumulative potential:	BCF		0,19				
12.4. Mobility in soil:							No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		
Other information:	BOD5		1760-1900	mg/g			
Other information:	COD		2100	mg/g			
Other information:	AOX		0	%			

Benzyl alcohol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 14 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

12.1. Toxicity to fish:	LC50	96h	460	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	230	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	51	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	770	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	310	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		21d	95-97	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	92-96	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,1				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Toxicity to bacteria:	EC10	16h	658	mg/l	Pseudomonas putida		

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

If applicable

Return to manufacturer with residual pressure.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

## SECTION 14: Transport information

### General statements

Page 15 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

14.1. UN number: 1950

**Transport by road/by rail (ADR/RID)**

14.2. UN proper shipping name:  
 UN 1950 AEROSOLS  
 14.3. Transport hazard class(es): 2.1  
 14.4. Packing group: -  
 Classification code: 5F  
 LQ: 1 L  
 14.5. Environmental hazards: Not applicable  
 Tunnel restriction code: D



**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:  
 AEROSOLS  
 14.3. Transport hazard class(es): 2.1  
 14.4. Packing group: -  
 EmS: F-D, S-U  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable



**Transport by air (IATA)**

14.2. UN proper shipping name:  
 Aerosols, flammable  
 14.3. Transport hazard class(es): 2.1  
 14.4. Packing group: -  
 14.5. Environmental hazards: Not applicable



**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 805 g/l  
 Directive 2010/75/EU (VOC): 98 %

Observe incident regulations.

**15.2 Chemical safety assessment**



Page 16 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 8  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

--- ---

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - dermal

Acute Tox. — Acute toxicity - oral

Eye Dam. — Serious eye damage

Aquatic Acute — Hazardous to the aquatic environment - acute

Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

Page 17 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 29.06.2018 / 0017  
 Replacing version dated / version: 18.04.2018 / 0016  
 Valid from: 29.06.2018  
 PDF print date: 29.06.2018  
 Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
 Art.: 3379

approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration  
 LD Lethal Dose of a chemical  
 LD50 Lethal Dose, 50% kill  
 LDLo Lethal Dose Low  
 LOAEL Lowest Observed Adverse Effect Level  
 LOEC Lowest Observed Effect Concentration

Page 18 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 29.06.2018 / 0017  
Replacing version dated / version: 18.04.2018 / 0016  
Valid from: 29.06.2018  
PDF print date: 29.06.2018  
Pro-Line Injektoren- und Gluehkerzenloeser 400 ml  
Art.: 3379

LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.