

Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)



Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The degradation products during combustion of fluorinated polymers may cause polymer fever with influenza-like symptoms in humans.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Mineral oil	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	64742-55-8
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Nonylphenol ethoxylate	SVHC-substance
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	500-209-1 (NLP)
CAS	68412-54-4
content %	0,01-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319
	Skin Irrit. 2, H315
	Aguatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures



(B)

Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Drying of the skin.

Dermatitis (skin inflammation)

Oil acne

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up



Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Mineral oil			Content %:1-5
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	- [Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information:	
@ at 1 111	Oili-ti			0
Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e		WEL-STEL:		 Content %:
		WEL-STEL:		 Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL: Draeger - Oil Mist 1/a (67 33 031)		 Content %:

Distillates (petroleum), hydrotreated light paraffinic									
Area of application	Exposure route / Environmental compartment	Effect on health Descripto		Value	Unit	Note			
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3				
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day				



(B)

Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

Workers / employees	Human - dermal	Long term, systemic	DNEL	0.97	mg/kg	
' ' ' ' ' ' ' '		effects		- , -		
		enecis			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2,7	mg/m3	
Trainers / cimple / cos	Trainian initialation	, ,		_,.	1119,1110	
		effects				

Distillates (petroleum), hydrotreated heavy paraffinic										
Area of application	Exposure route /	xposure route / Effect on health Descriptor Value Unit Note								
	Environmental									
	compartment									
	Environment - oral (animal		PNEC	9,33	mg/kg					
	feed)									

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).



Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

Respiratory protection: Normally not necessary. With oil mist formation:

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Green Odour: Characteristic Odour threshold: Not determined pH-value: Not determined Not determined Melting point/freezing point: Initial boiling point and boiling range: Not determined Flash point: 230 °C Evaporation rate: Not determined

Flammability (solid, gas): n.a.

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Density:

Bulk density:

Not determined

not dete

Solubility(ies):

Not determined
Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Not determined
Not determined
Not determined
Oetermined
Not determined

Viscosity: 10,7 mm2/s (100°C)
Explosive properties: Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Not to be expected



(B)

Page 7 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Marine 4T Motor Oil 10W-30 1 L	•	,	,			
Art.: 25022						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Mineral oil						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin						No (inhalation
sensitisation:						and skin contact)
Aspiration hazard:						Yes

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion



Page 8 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L Art.: 25022

	1	1		T		
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Carcinogenicity:				Mouse	OECD 451	Negative,
					(Carcinogenicity Studies)	Analogous
						conclusion
Reproductive toxicity:				Rat	OECD 421	Negative,
					(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusion
					Test)	
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):					Developmental Toxicity	Analogous
					Study)	conclusion
Aspiration hazard:						Yes
Specific target organ toxicity -	NOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose Dermal Toxicity -	conclusion
dermal:					90-Day)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Marine 4T Motor Oil 10W	/-30 1 L						
Art.: 25022							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Mineral oil							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna STRAUS		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna STRAUS		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		



GB)

Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

12.2. Persistence and	28d	31	%	OECD 301 B
degradability:				(Ready
				Biodegradability -
				Co2 Evolution
				Test)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>6				@20°C
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Nonylphenol ethoxylate								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	0,218	mg/l	Pimephales			
-					promelas			
12.1. Toxicity to daphnia:	EC50	48h	0,148	mg/l	Daphnia magna			
12.2. Persistence and	DOC	28d	28,7	%				
degradability:								
12.3. Bioaccumulative	Log Kow		5,58				extrapolated	
potential:	_						data of other	
							substances	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be



Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site. E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Classification code: n.a. LQ: n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII

Nonylphenol ethoxylate

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 8, 11, 12, 15



Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard

Eye Irrit. — Eye irritation Skin Irrit. — Skin irritation

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

dry weight dw

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EC **European Community** ECHA European Chemicals Agency EEC **European Economic Community**

EINECS European Inventory of Existing Commercial Chemical Substances

European List of Notified Chemical Substances **ELINCS**

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera European Union EU

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number general gen.

Globally Harmonized System of Classification and Labelling of Chemicals GHS

Global warming potential **GWP**

International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

LQ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships



Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2020 / 0002

Replacing version dated / version: 02.11.2015 / 0001

Valid from: 26.05.2020 PDF print date: 27.05.2020 Marine 4T Motor Oil 10W-30 1 L

Art.: 25022

not applicable n.a. n.av. not available not checked n.c. no data available n.d.a.

OECD Organisation for Economic Co-operation and Development

org. organic

persistent, bioaccumulative and toxic PBT

Polyethylene PF

PNEC Predicted No Effect Concentration

ppm parts per million **PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Tel. Telephone

United Nations Recommendations on the Transport of Dangerous Goods **UN RTDG**

Volatile organic compounds VOC

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.