

Page 1 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0014  
Replacing version dated / version: 26.01.2016 / 0013  
Valid from: 07.03.2017  
PDF print date: 18.03.2017  
Karosserie-Klebespray 400 mL  
Art.: 6192

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Karosserie-Klebespray 400 mL**  
**Art.: 6192**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Adhesive

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
--------------	-----------------	------------------

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves and eye protection / face protection.  
 P312-Call a POISON CENTRE / doctor if you feel unwell.  
 P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
 P501-Dispose of contents / container to special waste collection point.

Without adequate ventilation, formation of explosive mixtures may be possible.

Methyl acetate

Ethyl acetate

Hydrocarbons, C6, isoalkanes, < 5% n-hexane

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Methyl acetate</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	607-021-00-X
<b>EINECS, ELINCS, NLP</b>	201-185-2
<b>CAS</b>	79-20-9
<b>content %</b>	20-40

GB

Page 3 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
--	---

<b>Hydrocarbons, C6, isoalkanes, &lt; 5% n-hexane</b>	
<b>Registration number (REACH)</b>	01-2119484651-34-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	931-254-9 (REACH-IT List-No.)
<b>CAS</b>	(64742-49-0)
<b>content %</b>	10-20
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

<b>Ethyl acetate</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119475103-46-XXXX
<b>Index</b>	607-022-00-5
<b>EINECS, ELINCS, NLP</b>	205-500-4
<b>CAS</b>	141-78-6
<b>content %</b>	1-5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

<b>n-Hexane</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	---
<b>Index</b>	601-037-00-0
<b>EINECS, ELINCS, NLP</b>	203-777-6
<b>CAS</b>	110-54-3
<b>content %</b>	0,25-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

<b>2,6-di-tert-butyl-p-cresol</b>	
<b>Registration number (REACH)</b>	01-2119555270-46-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	204-881-4
<b>CAS</b>	128-37-0
<b>content %</b>	0,01-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0014

Replacing version dated / version: 26.01.2016 / 0013

Valid from: 07.03.2017

PDF print date: 18.03.2017

Karosserie-Klebespray 400 mL

Art.: 6192

## Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

## Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Nausea

Effects/damages the central nervous system

Narcotic effect.

With long-term contact:

Dermatitis (skin inflammation)

Drying of the skin.

Irritation of the skin.

Other dangerous properties cannot be ruled out.

## 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

In case of spreading near the ground, flashback to distance sources of ignition is possible.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

GB

Page 5 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Prevent surface and ground-water infiltration, as well as ground penetration.  
 Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.  
 If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.  
 Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Only from a specialist.

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
 Do not wash away with water or watery cleaning agents.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Avoid inhalation of the vapours.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Do not use on hot surfaces.  
 Avoid contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with oxidizing agents.  
 Observe special regulations for aerosols!  
 Observe special storage conditions.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

<b>Chemical Name</b>	Methyl acetate	Content %:20-40	
WEL-TWA: 200 ppm (616 mg/m <sup>3</sup> )	WEL-STEL: 250 ppm (770 mg/m <sup>3</sup> )	---	
Monitoring procedures:	- Compur - KITA-111 SA(C) (549 160)		
BMGV: ---	Other information: ---		
<b>Chemical Name</b>	Hydrocarbons, C <sub>6</sub> , isoalkanes, < 5% n-hexane	Content %:10-20	
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	

GB

Page 6 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)

Chemical Name	Ethyl acetate	Content %:1-5
WEL-TWA: 200 ppm (WEL-TWA), 200 ppm (734 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 400 ppm (WEL-STEL), 400 ppm (1468 mg/m <sup>3</sup> ) (EU)	---
Monitoring procedures:	- Compur - KITA-111 SA (549 160) - Compur - KITA-111 U(C) (549 178) - Draeger - Ethyl Acetate 200/a (CH 20 201) - DFG (D) (Loesungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1998, 2002 - DFG (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 1998, 2002 - DFG (D) (Loesungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 1998, 2002 - DFG (D) (Loesungsmittelgemische 5), DFG (E) (Solvent mixtures 5) - 1998, 2002	
BMGV: ---	Other information: ---	

Chemical Name	n-Hexane	Content %:0,25-<1
WEL-TWA: 20 ppm (72 mg/m <sup>3</sup> ) (WEL, EU)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SA (549 350) - Compur - KITA-113 SB (549 368) - Compur - KITA-113 SC (503 787) - Draeger - Hexane 100/a (67 28 391) MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, n-heptane, n-octane, n-nonane) in air) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 26-1 (2004) - DFG Meth. Nr. 1 (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 1) - 1998, 2002	
BMGV: ---	Other information: ---	

Chemical Name	2,6-di-tert-butyl-p-cresol	Content %:0,01-<1
WEL-TWA: 10 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )	WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> )	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
BMGV: ---	Other information: ---	

Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
BMGV: ---	Other information: ---	

Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Ethyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,26	mg/l	

Page 7 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

	Environment - marine		PNEC	0,026	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,65	mg/l	
	Environment - sediment, freshwater		PNEC	0,34	mg/kg	
	Environment - sediment, marine		PNEC	0,125	mg/kg	
	Environment - soil		PNEC	0,22	mg/kg	
	Environment - sewage treatment plant		PNEC	650	mg/l	
	Environment - oral (animal feed)		PNEC	200	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,5	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	37	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	367	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	367	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	734	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	734	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	63	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	734	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	734	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m <sup>3</sup>	

Hydrocarbons, C6, isoalkanes, < 5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1137	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m <sup>3</sup>	

2,6-di-tert-butyl-p-cresol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	1,04	mg/kg wwt	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment		PNEC	1,29	mg/kg wwt	
	Environment - marine		PNEC	0,4	µg/l	
	Environment - periodic release		PNEC	4	µg/l	
	Environment - freshwater		PNEC	4	µg/l	

Page 8 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

	Environment - oral (animal feed)		PNEC	16,7	mg/kg	
	Environment - soil		PNEC	1,23	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,74	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5,8	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/day	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves made of polyvinyl alcohol (EN 374)

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.



Page 9 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Alcoholic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	-60 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	1,4 Vol-%
Upper explosive limit:	32 Vol-%
Vapour pressure:	3500 hPa
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,71 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	510 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Karosserie-Klebespray 400 mL Art.: 6192						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Methyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>6970	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3705	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>48	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Germ cell mutagenicity:					bacterial	Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	350	ppm			
Symptoms:						acidosis, respiratory distress, drowsiness, unconsciousness, burning of the membranes of the nose and throat, headaches, stomach pain, drowsiness, dizziness, watering eyes, nausea and vomiting.

Hydrocarbons, C6, isoalkanes, < 5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

Page 11 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Acute toxicity, by inhalation:	LC50	259354	mg/m <sup>3</sup>	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Irritant
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Ethyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	6100	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4h	Rat		Vapours
Acute toxicity, by inhalation:	LC50	>28,6	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LCLo	>6000	ppm/6h	Rat		Multi-Substance Rule for the Testing of Neurotoxicity 40 CFR Part 799 (58 FR 40262)
Skin corrosion/irritation:		24	h	Rabbit		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative

Page 12 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Symptoms:						lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,002	mg/kg	Rat	Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS))	

n-Hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	25000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	171,6	mg/l/1h	Rat		
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, blisters, cornea opacity, coughing, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, watering eyes, nausea

2,6-di-tert-butyl-p-cresol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>2930	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	

GB

Page 13 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:						Slightly irritant
Serious eye damage/irritation:				Rabbit	(Draize-Test)	Slightly irritant
Respiratory or skin sensitisation:				Human being		Not sensitizing
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mammalian		Negative
Reproductive toxicity:	NOAEL	100	mg/kg	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	25	mg/kg	Rat		(28 d)
Symptoms:						mucous membrane irritation
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	25	mg/kg	Rat		

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

Page 14 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

### Karosserie-Klebespray 400 mL Art.: 6192

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

### Methyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	250-300	mg/l	Brachydanio rerio		
12.1. Toxicity to daphnia:	EC50	48h	1027	mg/l			
12.1. Toxicity to algae:	IC50	72h	>20	mg/l			
12.2. Persistence and degradability:		28d	>70	%			Readily biodegradable
12.3. Bioaccumulative potential:							No

### Hydrocarbons, C6, isoalkanes, < 5% n-hexane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	48h	>1	mg/l	Oryzias latipes		Analogous conclusion
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	55	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	30	mg/l	Raphidocelis subcapitata		
12.2. Persistence and degradability:		28d	98	%			Readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential:	Log Kow		4				

Page 15 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	-------------------------------------

Ethyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	230	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	NOEC/NOEL	32d	>9,65	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	610	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to algae:	EC50	48h	5600	mg/l	Desmodesmus subspicatus	DIN 38412 T.9	
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	2000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			100	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.2. Persistence and degradability:		20d	79	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	72h	30				(Fish)
12.3. Bioaccumulative potential:	Log Kow		0,6			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Bioaccumulation is unlikely (LogPow < 1).
12.4. Mobility in soil:	H (Henry)		0,00012	atm*m3/mol			
12.4. Mobility in soil:	Koc		3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	15min	5870	mg/l	Photobacterium phosphoreum		
Toxicity to bacteria:	EC10	16h	2900	mg/l	Escherichia coli		

n-Hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2,5	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	2,1	mg/l			
12.3. Bioaccumulative potential:							Not to be expected

2,6-di-tert-butyl-p-cresol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>0,57	mg/l		QSAR	
12.1. Toxicity to fish:	NOEC/NOEL	42d	0,053	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	

Page 16 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

12.1. Toxicity to daphnia:	LC50	48h	0,61	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,07	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,5	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	1	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4,5	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.3. Bioaccumulative potential:			230-2500		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	56d
12.3. Bioaccumulative potential:	BCF		330-1800				
12.3. Bioaccumulative potential:	Log Pow		4,17-5,1				
12.3. Bioaccumulative potential:	Log Pow		5,1				
12.5. Results of PBT and vPvB assessment							No PBT substance
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Water solubility:			0,00076	g/l			

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance



GB

Page 17 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

## SECTION 14: Transport information

### General statements

14.1. UN number: 1950

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D



#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS (CYCLOHEXANE)

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



#### Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -



GB

Page 18 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 72 %

Observe incident regulations.

Observe youth employment law (German regulation).

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

Revised sections: 2, 3, 8, 16

These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.  
 Employee training in handling dangerous goods is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H361f Suspected of damaging fertility.
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Page 19 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Eye Irrit. — Eye irritation  
 Skin Irrit. — Skin irritation  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Aerosol — Aerosols  
 Flam. Liq. — Flammable liquid  
 Asp. Tox. — Aspiration hazard  
 Repr. — Reproductive toxicity  
 STOT RE — Specific target organ toxicity - repeated exposure  
 Aquatic Acute — Hazardous to the aquatic environment - acute

### Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue

Page 20 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0014  
 Replacing version dated / version: 26.01.2016 / 0013  
 Valid from: 07.03.2017  
 PDF print date: 18.03.2017  
 Karosserie-Klebespray 400 mL  
 Art.: 6192

Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration  
 LD Lethal Dose of a chemical  
 LD50 Lethal Dose, 50% kill  
 LDLo Lethal Dose Low  
 LOAEL Lowest Observed Adverse Effect Level  
 LOEC Lowest Observed Effect Concentration  
 LOEL Lowest Observed Effect Level  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute of Occupational Safety and Health (United States of America)  
 NOAEC No Observed Adverse Effective Concentration  
 NOAEL No Observed Adverse Effect Level  
 NOEC No Observed Effect Concentration  
 NOEL No Observed Effect Level  
 ODP Ozone Depletion Potential  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 PAH polycyclic aromatic hydrocarbon  
 PBT persistent, bioaccumulative and toxic  
 PC Chemical product category  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 POCP Photochemical ozone creation potential  
 ppm parts per million  
 PROC Process category  
 PTFE Polytetrafluorethylene  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SADT Self-Accelerating Decomposition Temperature  
 SAR Structure Activity Relationship  
 SU Sector of use  
 SVHC Substances of Very High Concern  
 Tel. Telephone  
 ThOD Theoretical oxygen demand  
 TOC Total organic carbon  
 TRGS Technische Regeln für Gefahrstoffe (= Technical Regulations for Hazardous Substances)  
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
 VOC Volatile organic compounds

Page 21 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0014  
Replacing version dated / version: 26.01.2016 / 0013  
Valid from: 07.03.2017  
PDF print date: 18.03.2017  
Karosserie-Klebespray 400 mL  
Art.: 6192

---

vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.