

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Special Tec AA 5W-20 1 L

Art.: 20792

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

(GB)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

#### Emergency information services / official advisory body:

---

#### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture



Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

#### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Alkyl alcohol triester with boric acid. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

## n.a. 3.2 Mixture

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP	265-157-1
CAS	64742-54-7
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Bis(nonylphenyl)amine	
Registration number (REACH)	01-2119488911-28-XXXX
Index	
EINECS, ELINCS, NLP	253-249-4
CAS	36878-20-3
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

\* The contained mineral oil can be described by one or more of the following numbers:

EINECS	S, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157	7-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169	9-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158	8-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159	9-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

Oil acne

On vapour formation:

Irritation of the respiratory tract

Ingestion:

Gastrointestinal disturbances

Nausea

Vomiting

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

CO2

Foam

Dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrogen sulphide

Oxides of nitrogen

Oxides of sulphur

Oxides of phosphorus

Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.



Œ

Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid formation of oil mist.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Oil binder

Do not wash away with water or watery cleaning agents.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Impermeable floor.

Protect against moisture and store closed.

Protect from direct sunlight and warming.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters



(B)-

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, ex	cluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	-	Draeger - Oil 10/a-P (67 28 371)		
	-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information: -	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

#### 8.2 Exposure controls

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application Exposure route / Effect on health Descriptor Value Unit Note									
	Environmental								
	compartment								
	Environment - oral (animal		PNEC	9,33	mg/kg				
	feed)								
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m3	8h			

Bis(nonylphenyl)amine Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
, a ca c. application	Environmental compartment		2000ptg.	raido	J	11010
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	132000	mg/kg dry weight	
	Environment - sediment, marine		PNEC	13200	mg/kg dry weight	
	Environment - soil		DNEL	263000	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,09	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,62	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,37	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic							
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note	



Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

Environment - oral (animal	PNEC	9,33	mg/kg	
feed)				

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective nitrile gloves (EN 374)

Protective PVC gloves (EN 374)

Minimum layer thickness in mm:

0,35

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**



Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

#### 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Brown Characteristic Odour: Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined 220 °C Flash point: Evaporation rate: Not determined Flammability (solid, gas): n.a.

Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined 0,850 g/ml Density:

Bulk density: n.a. Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined Viscosity: 45 mm2/s (40°C) Viscosity: 8,2 mm2/s (100°C) Explosive properties: Not determined

9.2 Other information

Oxidising properties:

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

#### **SECTION 10: Stability and reactivity**

Not determined

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

#### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

#### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Special Tec AA 5W-20 1 L						
Art.: 20792						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 8 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L Art.: 20792

Acute toxicity, by oral route:	n.d.a.
Acute toxicity, by dermal route:	n.d.a.
Acute toxicity, by inhalation:	n.d.a.
Skin corrosion/irritation:	n.d.a.
Serious eye damage/irritation:	n.d.a.
Respiratory or skin	n.d.a.
sensitisation:	
Germ cell mutagenicity:	n.d.a.
Carcinogenicity:	n.d.a.
Reproductive toxicity:	n.d.a.
Specific target organ toxicity -	n.d.a.
single exposure (STOT-SE):	
Specific target organ toxicity -	n.d.a.
repeated exposure (STOT-RE):	
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral		
					toxicity - Fixe Dose		
					Procedure)		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute		
					Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol	
					Inhalation Toxicity)		
Skin corrosion/irritation:						Not irritant	
Serious eye damage/irritation:						Slightly irritant	
Respiratory or skin						Not sensitizising	
sensitisation:							
Aspiration hazard:						Yes	

Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin						Not sensitizising
sensitisation:						
Aspiration hazard:						Yes

Bis(nonylphenyl)amine								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral			
					Toxicity)			
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute			
					Dermal Toxicity)			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant		
					Dermal			
					Irritation/Corrosion)			
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant		
					Irritation/Corrosion)			
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising		
sensitisation:					Sensitisation)			

#### **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Ш	Special rec AA 5W-20 1	L						
	Art.: 20792							
	Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
	12.1. Toxicity to fish:							n.d.a.
	12.1. Toxicity to daphnia:							n.d.a.
	12.1. Toxicity to algae:							n.d.a.



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L Art.: 20792

12.2. Persistence and degradability:			n.d.a.
12.3. Bioaccumulative			n.d.a.
potential:			II.u.a.
12.4. Mobility in soil:			n.d.a.
12.5. Results of PBT			n.d.a.
and vPvB assessment			
12.6. Other adverse			n.d.a.
effects:			

Distillates (petroleum), hydrotreated heavy paraffinic									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)			
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSÁR			
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR			
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)			
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)			
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)			
Other information:	AOX		0	%					

Baseoil - unspecified								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas			
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna			
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda			
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish,	
					-	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	600	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	



Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

12.2. Persistence and degradability:		28d	1	%	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		7,7			Concentration in organisms possible.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

#### **General statements**

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards:

Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:
n.a.

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.



(B)

Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007 Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

0,118 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

2, 3, 8, 9, 11, 12, 15

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

#### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)



Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera EU European l

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform ChemicaL Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAECNo Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category



Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.09.2018 / 0007

Replacing version dated / version: 09.03.2018 / 0006

Valid from: 24.09.2018 PDF print date: 25.09.2018 Special Tec AA 5W-20 1 L

Art.: 20792

Polyethylene PΕ

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WÉL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL

reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

### These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.