

GB

Page 1 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 09.07.2018 / 0016
Replacing version dated / version: 20.09.2017 / 0015
Valid from: 09.07.2018
PDF print date: 10.07.2018
Motor Oil Saver 300 mL
Art.: 7143

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Motor Oil Saver 300 mL
Art.: 7143

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Dam.	1	H318-Causes serious eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H318-Causes serious eye damage.

Page 2 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P280-Wear eye protection.
 P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

Isotridecanol, ethoxylated

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

2-Butoxyethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475112-47-XXXX
Index	607-038-00-2
EINECS, ELINCS, NLP	203-933-3
CAS	112-07-2
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332

Isotridecanol, ethoxylated	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	69011-36-5
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Page 3 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 09.07.2018 / 0016
Replacing version dated / version: 20.09.2017 / 0015
Valid from: 09.07.2018
PDF print date: 10.07.2018
Motor Oil Saver 300 mL
Art.: 7143

Remove contact lenses.
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.
Protect uninjured eye.
Follow-up examination by an ophthalmologist

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes
Product removes fat.
Drying of the skin.
Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Foam
Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Hydrocarbons
Toxic pyrolysis products.
Hot product gives off combustible vapours.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
Remove possible causes of ignition - do not smoke.
Avoid formation of oil mist.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

GB

Page 4 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid contact with eyes or skin.
 Do not heat to temperatures close to flash point.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Do not carry cleaning cloths soaked in product in trouser pockets.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Solvent resistant floor
 Do not store with oxidizing agents.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	2-Butoxyethyl acetate		Content %:1-10
WEL-TWA: 20 ppm (133 mg/m3) (WEL, EU)	WEL-STEL: 50 ppm (333 mg/m3) (WEL, EU)	---	
Monitoring procedures:	- DFG (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 33-3 (2004)		
BMGV: ---	Other information: Sk (WEL)		
Chemical Name	Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---	
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

2-Butoxyethyl acetate

Page 5 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	4,3	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	36	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	67	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	102	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	133	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	333	mg/m ³	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 If applicable
 Protective nitrile gloves (EN 374)
 Permeation time (penetration time) in minutes:
 >480
 Minimum layer thickness in mm:
 0,4
 Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.

Page 6 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Pastelike, Liquid
Colour:	Yellow, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,896 g/ml (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	1299 mPas (20°C)
Explosive properties:	Not determined
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

Page 8 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

2-Butoxyethyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	28	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	37	mg/l	Daphnia pulex	DIN 38412 T.11	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata	ISO/DIS 8692	References
12.2. Persistence and degradability:		28d	88	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.2. Persistence and degradability:		28d	>70	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		1,51			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
Toxicity to bacteria:	EC50	17h	720	mg/l	Pseudomonas putida	DIN 38412 T.8	

Isotridecanol, ethoxylated

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Readily biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Classification code: n.a.
 LQ: n.a.
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 9 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 4, 8, 15
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H412 Harmful to aquatic life with long lasting effects.

Eye Dam. — Serious eye damage
 Acute Tox. — Acute toxicity - oral
 Acute Tox. — Acute toxicity - dermal
 Acute Tox. — Acute toxicity - inhalation
 Skin Irrit. — Skin irritation
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency

Page 11 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.07.2018 / 0016
 Replacing version dated / version: 20.09.2017 / 0015
 Valid from: 09.07.2018
 PDF print date: 10.07.2018
 Motor Oil Saver 300 mL
 Art.: 7143

EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 12 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 09.07.2018 / 0016
Replacing version dated / version: 20.09.2017 / 0015
Valid from: 09.07.2018
PDF print date: 10.07.2018
Motor Oil Saver 300 mL
Art.: 7143

SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.