

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Anti-Bacterial Diesel Additive 125 ml**  
**Art.: 20940**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Biocide

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Acute Tox.	4	H302-Harmful if swallowed.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.06.2019 / 0005

Replacing version dated / version: 22.02.2019 / 0004

Valid from: 18.06.2019

PDF print date: 20.09.2019

Anti-Bacterial Diesel Additive 125 ml

Art.: 20940



Danger

H332-Harmful if inhaled. H302-Harmful if swallowed. H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P315-Get immediate medical advice / attention. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement.

2-Ethylhexylnitrate

1,2-benzisothiazol-3(2H)-one

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics

Methyl salicylate

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	---
content %	40-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

2-Ethylhexylnitrate	
Registration number (REACH)	01-2119539586-27-XXXX
Index	---
EINECS, ELINCS, NLP	248-363-6
CAS	27247-96-7
content %	25-30

Page 3 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Chronic 2, H411
--	---

<b>Methyl salicylate</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	204-317-7
<b>CAS</b>	119-36-8
<b>content %</b>	10-<20
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

<b>2-Ethylhexanol</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119487289-20-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	203-234-3
<b>CAS</b>	104-76-7
<b>content %</b>	1-5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335

<b>Ethanediol</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119456816-28-XXXX
<b>Index</b>	603-027-00-1
<b>EINECS, ELINCS, NLP</b>	203-473-3
<b>CAS</b>	107-21-1
<b>content %</b>	1-5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 STOT RE 2, H373 (kidneys) (oral)

<b>1,2-benzisothiazol-3(2H)-one</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	613-088-00-6
<b>EINECS, ELINCS, NLP</b>	220-120-9
<b>CAS</b>	2634-33-5
<b>content %</b>	3,2
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Page 4 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.06.2019 / 0005  
Replacing version dated / version: 22.02.2019 / 0004  
Valid from: 18.06.2019  
PDF print date: 20.09.2019  
Anti-Bacterial Diesel Additive 125 ml  
Art.: 20940

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

### **Inhalation**

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

### **Skin contact**

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### **Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.  
Protect uninjured eye.  
Follow-up examination by an ophthalmologist.

### **Ingestion**

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.  
Danger of aspiration.  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Ingestion:

Nausea  
Vomiting  
Danger of aspiration.  
Oedema of the lungs  
Chemical pneumonitis (condition similar to pneumonia)

### **4.3 Indication of any immediate medical attention and special treatment needed**

Gastric lavage (stomach washing) only under endotracheal intubation.  
Subsequent observation for pneumonia and pulmonary oedema.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Water jet spray/foam/CO2/dry extinguisher

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen  
Toxic gases  
Danger of bursting (explosion) when heated

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Keep unprotected persons away.  
Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.

GB

Page 5 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

Avoid inhalation, and contact with eyes or skin.  
 If applicable, - caution - risk of slipping.

## 6.2 Environmental precautions

Resolve leaks if this possible without risk.  
 If leakage occurs, dam up.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 Prevent from entering drainage system.  
 If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.  
 Fill the absorbed material into lockable containers.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Avoid contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Under all circumstances prevent penetration into the soil.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		Content %:40-50
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name	2-Ethylhexanol		Content %:1-5
WEL-TWA: 1 ppm (5,4 mg/m <sup>3</sup> ) (WEL, EU)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Alcohol 100/a (CH 29 701)		

GB

Page 6 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

BMGV: ---	Other information: ---
-----------	------------------------

Chemical Name	Ethanediol	Content %:1-5
WEL-TWA: 10 mg/m3 (particulate), 52 mg/m3 (vapour) (WEL), 20 ppm (52 mg/m3) (EU)	WEL-STEL: 104 mg/m3 (vapour) (WEL), 40 ppm (104 mg/m3) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-232 SA (502 342)</li> <li>- Compur - KITA-232 SB (550 267)</li> <li>- Draeger - Ethylene Glycol 10 (5) (81 01 351)</li> <li>- NIOSH 5523 (Glycols) - 1996</li> <li>- OSHA PV2024 (Ethylene glycol) - 1999 - EU project BC/CEN/ENTR/000/2002-16 card</li> <li>- 11-2 (2004)</li> </ul>	

BMGV: ---	Other information: Sk (particulate, vapour)
-----------	---

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Oil 10/a-P (67 28 371)</li> <li>- Draeger - Oil Mist 1/a (67 33 031)</li> </ul>	

BMGV: ---	Other information: ---
-----------	------------------------

2-Ethylhexylnitrate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,8	µg/l	
	Environment - marine		PNEC	0,08	µg/l	
	Environment - sediment		PNEC	0,00074	mg/kg dw	
	Environment - soil		PNEC	0,00019	mg/kg dw	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm2	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,044	mg/cm2	

2-Ethylhexanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - marine		PNEC	0,0017	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,17	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,28	mg/kg dw	
	Environment - sediment, marine		PNEC	0,028	mg/kg dw	
	Environment - soil		PNEC	0,047	mg/kg dw	
	Environment - oral (animal feed)		PNEC	55	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,1	mg/kg body weight/day	

Page 7 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

Consumer	Human - inhalation	Short term, local effects	DNEL	53,2	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11,4	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,3	mg/m <sup>3</sup>	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	26,6	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	12,8	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	23	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	53,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	53,2	mg/m <sup>3</sup>	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	12,8	mg/m <sup>3</sup>	

Ethanediol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sediment		PNEC	20,9	mg/kg	
	Environment - soil		PNEC	1,53	mg/kg	
	Environment - sewage treatment plant		PNEC	199,5	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	37	mg/kg dry weight	
	Environment - sediment, marine		PNEC	3,7	mg/kg dry weight	
Consumer	Human - inhalation	Long term, local effects	DNEL	7	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	53	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	35	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	106	mg/kg	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m <sup>3</sup>	

06 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 8 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.06.2019 / 0005  
Replacing version dated / version: 22.02.2019 / 0004  
Valid from: 18.06.2019  
PDF print date: 20.09.2019  
Anti-Bacterial Diesel Additive 125 ml  
Art.: 20940

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374).

Safety gloves made of fluorocarbon rubber (EN 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties



Page 9 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

Physical state:	Liquid
Colour:	Brown, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>63-<100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,923 g/ml (15°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm <sup>2</sup> /s (40°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Risk of explosion if heated under confinement.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

**Anti-Bacterial Diesel Additive 125 ml**  
**Art.: 20940**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1208-1296,4	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	11,32	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	3,95	mg/l/4h			calculated value, Aerosol, Mist

GB

Page 10 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness
Other information:						Repeated exposure may cause skin dryness or cracking.

**2-Ethylhexylnitrate**

Page 11 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:						Experiences on persons., Harmful
Acute toxicity, by inhalation:						Experiences on persons., Harmful
Acute toxicity, by inhalation:	LCLo	>4,6	mg/l/1h	Rat		Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	100	mg/kg bw/d		OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Symptoms:						drying of the skin., may cause headaches and vertigo., nausea, drop in blood pressure, diarrhoea, unconsciousness

### 2-Ethylhexanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2047	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	2,7	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig		No (skin contact) literature
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	750	mg/kg bw/d	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	3000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Reproductive toxicity (Developmental toxicity):				Mouse	OECD 414 (Prenatal Developmental Toxicity Study)	Negative

Page 12 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract, STOT SE 3, H335
Symptoms:						unconsciousness, drop in blood pressure, vomiting, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg bw/d	Mouse		
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,6384	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours

Ethanediol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1600	mg/kg	Human being		
Acute toxicity, by dermal route:	LD50	9530	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>3500	mg/kg	Mouse		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Human being	(Patch-Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	in vivo	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat		
Symptoms:						ataxia, breathing difficulties, unconsciousness, cramps, fatigue

1,2-benzisothiazol-3(2H)-one						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1020	mg/kg	Rat		
Acute toxicity, by dermal route:	LC50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	0,4	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

**Anti-Bacterial Diesel Additive 125 ml**  
**Art.: 20940**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 13 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Product floats on the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

2-Ethylhexylnitrate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,88	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>12,6	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	>12,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	0	%		OECD 310 (Ready Biodegradability - CO <sub>2</sub> in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		1332				

Page 14 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

12.3. Bioaccumulative potential:	Log Pow		3,74-5,24				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Log Koc		3,75			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	
Other information:	AOX		0	%			No
Water solubility:							Slight

#### 2-Ethylhexanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	17,1	mg/l	Leuciscus idus	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	39	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	EC50	72h	11,5	mg/l	Scenedesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	COD	14d	100	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,3-3,2				Low
12.3. Bioaccumulative potential:	BCF		25,33				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Ethanediol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC20	30min	>1995	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales promelas	IUCLID Chem. Data Sheet (ESIS)	

Page 15 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

12.1. Toxicity to fish:	NOEC/NOEL	7d	15380	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL		8590	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	96h	6500-7500	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	56	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.2. Persistence and degradability:		10h	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-1,36				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	>10000	mg/l	Pseudomonas putida	IUCLID Chem. Data Sheet (ESIS)	
Other information:	BOD5		0,78	g/g			IUCLID

**1,2-benzisothiazol-3(2H)-one**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,6	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,21	mg/l	Oncorhynchus mykiss	OECD 215 (Fish, Juvenile Growth Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,27	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1,2	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,11	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			90	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	
12.2. Persistence and degradability:	DOC		80	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	



Page 16 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

12.3. Bioaccumulative potential:	BCF		6,95			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.3. Bioaccumulative potential:	Log Kow		0,7			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	
Toxicity to bacteria:	EC50	3h	13	mg/l	activated sludge	ISO 10712	
Toxicity to bacteria:	EC20	3h	3,3	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 07 03 other fuels (including mixtures)

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: 3082

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Classification code:

M6

LQ:

5 L

14.5. Environmental hazards:

environmentally hazardous

Tunnel restriction code:

-

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

EmS:

F-A, S-F

Marine Pollutant:

Yes



Page 17 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

14.5. Environmental hazards: environmentally hazardous

**Transport by air (IATA)**

14.2. UN proper shipping name:  
 Environmentally hazardous substance, liquid, n.o.s. (2-ETHYLHEXYL NITRATE,1,2-BENZISOTHIAZOL-3(2H)-ONE)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

14.5. Environmental hazards: environmentally hazardous



**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
21	Propylene oxide		5	50

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 75 %

**REGULATION (EC) No 648/2004**

30 % and more  
 aliphatic hydrocarbons

perfumes  
 disinfectants

Observe Regulation (EU) No 528/2012 concerning the placing of biocidal products on the market.

Additional data acc. to Art. 69 (2), Regulation (EU) No 528/2012 (Biocide products):

The identity of every active substance and its concentration in metric units:

1,2-benzisothiazol-3(2H)-one  
 3,2 g/100 g

Page 18 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.06.2019 / 0005  
 Replacing version dated / version: 22.02.2019 / 0004  
 Valid from: 18.06.2019  
 PDF print date: 20.09.2019  
 Anti-Bacterial Diesel Additive 125 ml  
 Art.: 20940

The uses:  
 Preservation  
 Biocidal product authorisation number (Regulation (EU) No. 528/2012):  
 n.d.a.

Observe incident regulations.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 3, 8, 11, 12  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Acute Tox. 4, H302	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.  
 H373 May cause damage to organs through prolonged or repeated exposure if swallowed.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - inhalation  
 Acute Tox. — Acute toxicity - oral  
 Skin Irrit. — Skin irritation  
 Eye Dam. — Serious eye damage  
 Skin Sens. — Skin sensitization  
 Asp. Tox. — Aspiration hazard  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Acute Tox. — Acute toxicity - dermal  
 Eye Irrit. — Eye irritation  
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation  
 STOT RE — Specific target organ toxicity - repeated exposure  
 Aquatic Acute — Hazardous to the aquatic environment - acute

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.06.2019 / 0005

Replacing version dated / version: 22.02.2019 / 0004

Valid from: 18.06.2019

PDF print date: 20.09.2019

Anti-Bacterial Diesel Additive 125 ml

Art.: 20940

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 20 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.06.2019 / 0005  
Replacing version dated / version: 22.02.2019 / 0004  
Valid from: 18.06.2019  
PDF print date: 20.09.2019  
Anti-Bacterial Diesel Additive 125 ml  
Art.: 20940

---

SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.