

Page 1 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

അ

Truck Series Oil Treatment 500 ml Art.: 20998

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0, 1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients



Page 2 of 10

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

3.1 Substance

n.a. **3.2 Mixture**

-

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

With long-term contact: Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Dry extinguisher Foam Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Oxides of sulphur Toxic gases 5.3 Advice for firefighters In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply.



Page 3 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid formation of oil mist. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

അ

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets. Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

 $\label{eq:keep} \ensuremath{\mathsf{Keep}}\xspace \ensuremath{\mathsf{away}}\xspace \ensuremath{\mathsf{from}}\xspace \ensuremath{\mathsf{form}}\xspace \ensuremath{\mathsf{from}}\xspace \ensuremath{$

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing. Not to be stored in gangways or stair wells. Solvent resistant floor

Do not store with oxidizing agents.

Protect from direct sunlight and warming. Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Molybdenum disulp	hide			Content %:
WEL-TWA: 10 mg/m3 (molybdenu	m insoluble	WEL-STEL:	20 mg/m3 (molybdenum insoluble		
compounds, as Mo) compounds, as Mo)					
Monitoring procedures:					



Page 4 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

BMGV:			Other information: -	
Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information: -	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

= The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166). If there is a risk of contact with the eyes or while decanting:

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Protective Neoprene® / polychloroprene gloves (EN 374). Minimum layer thickness in mm:

0.5 Permeation time (penetration time) in minutes:

480

ആ

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation:



Page 5 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

on monadon on saolo physical and choing	
Physical state:	Liquid
Colour:	Grey, Silver
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	180 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,89 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	92 mm2/s (40°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity



Page 6 of 10

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

10.4 Conditions to avoid

See also section 7. Strong heat

10.5 Incompatible materials

See also section 7. Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Truck Series Oil Treatment 500	· · · ·	0000011211	olacomoatorij.			
Art.: 20998	,					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Molybdenum disulphide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>2820	mg/m3/4h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Mild irritant
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Respiratory or skin						No (skin contact)
sensitisation:						
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Symptoms:						mucous
						membrane
						irritation

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Truck Series Oil Treatment 500 ml

Art.: 20998
Toxicity / effect
Endpoint
Time
Value
Unit
Organism
Test method
Notes

12.1. Toxicity to fish:
Image: Colspan="5">Image: Colspan="5">Value

12.1. Toxicity to fish:
Image: Colspan="5">Image: Colspan="5" Colspan="5">Image: Colspan="5" Colspa="5" Colspan="5" Colspan="5" Colspan="5" Colspa



Page 7 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

GB

12.1. Toxicity to algae:	n.d.a.
12.2. Persistence and	Mechanical
degradability:	precipitation
	possible.
12.3. Bioaccumulative	n.d.a.
potential:	
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	781- 1339	mg/l	Oncorhynchus mykiss		Analogous conclusion(mg Mo/L)
12.1. Toxicity to daphnia:	LC50	48h	1680,4- 1776,6	mg/l	Daphnia magna		Analogous conclusion(mg Mo/L)
12.1. Toxicity to daphnia:	LC50	48h	2729,4	mg/l	Daphnia magna		Analogous conclusion(mg Mo/L)
12.1. Toxicity to daphnia:	LC50	48h	2847,5	mg/l	Daphnia magna		Analogous conclusion(mg Mo/L)
12.1. Toxicity to daphnia:	LC50	48h	130,9	mg/l	Daphnia magna		Analogous conclusion(mg Mo/L)
12.1. Toxicity to daphnia:	LC50	48h	1005,5- 1024,6	mg/l	Ceriodaphnia spec.		Analogous conclusion(mg Mo/L)
12.1. Toxicity to algae:	ErC50	72h	289,2- 390,9	mg/l	Pseudokirchneriell a subcapitata		Analogous conclusion(mg Mo/L)
12.1. Toxicity to fish:	LC50	96h	609- 681,4	mg/l	Pimephales promelas		Analogous conclusion(mg Mo/L)
12.1. Toxicity to fish:	LC50	96h	7600	mg/l	Oncorhynchus mykiss		Analogous conclusion(mg Mo/L)
Water solubility:			<0,1	mg/l			@20°C

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.



Page 8 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

ആ

14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

1

Revised sections:

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Any abbreviations and acronyms used in this document:



ആ Page 9 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998 acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds AOX approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency European Economic Community EEC **EINECS** European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association International Bulk Chemical (Code) IBC (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLID** International Uniform Chemical Information Database LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC



Page 10 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0013 Replacing version dated / version: 17.04.2020 / 0012 Valid from: 29.04.2020 PDF print date: 29.04.2020 Truck Series Oil Treatment 500 ml Art.: 20998

vPvB very persistent and very bioaccumulative wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.