

Page 1 of 10  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 26.07.2019 / 0013  
Replacing version dated / version: 07.01.2019 / 0012  
Valid from: 26.07.2019  
PDF print date: 29.07.2019  
Oil Smoke Stop 300 mL  
Art.: 8901

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Oil Smoke Stop 300 mL**  
**Art.: 8901**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Additives

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

## Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Isotridecanol, ethoxylated</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	500-241-6 (NLP)
<b>CAS</b>	69011-36-5
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Irritation of the eyes

Page 3 of 10  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 26.07.2019 / 0013  
Replacing version dated / version: 07.01.2019 / 0012  
Valid from: 26.07.2019  
PDF print date: 29.07.2019  
Oil Smoke Stop 300 mL  
Art.: 8901

Product removes fat.  
with long-term contact:  
Dermatitis (skin inflammation)  
With oil mist formation:  
Irritation of the respiratory tract  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>  
Extinction powder  
Foam

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Toxic gases

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
Do not carry cleaning cloths soaked in product in trouser pockets.  
If applicable, caution - risk of slipping.

### **6.2 Environmental precautions**

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.  
Avoid formation of oil mist.  
Keep away from sources of ignition - Do not smoke.  
Do not heat to temperatures close to flash point.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Solvent resistant floor  
 Do not store with oxidizing agents.  
 Store in a well ventilated place.  
 Protect from direct sunlight and warming.  
 Store cool.

## 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Page 5 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Protective gloves, oil resistant (EN 374)  
 If applicable  
 Protective nitrile gloves (EN 374).  
 Minimum layer thickness in mm:  
 0,33  
 Permeation time (penetration time) in minutes:  
 > 480  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.  
 With oil mist formation:  
 Filter A2 P2 (EN 14387), code colour brown, white  
 If applicable  
 Filter A (EN 14387), code colour brown

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid, Viscous
Colour:	Yellow, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	120 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,852 g/ml (20°C)

Page 6 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	1493 mm <sup>2</sup> /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Reducing agent

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

**Oil Smoke Stop 300 mL**

**Art.: 8901**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

GB

Page 7 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

Isotridecanol, ethoxylated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Oil Smoke Stop 300 mL Art.: 8901							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Supporting documents that confirm this are kept available for the competent authorities and will be provided by a detergent manufacturer upon inquiry or demand.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Isotridecanol, ethoxylated							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 8 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

12.1. Toxicity to fish:	LC50	96h	5,18	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	2,5	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	1,5	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to daphnia:	EC20	21d	0,74	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	EC50	72h	2,5	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
Toxicity to bacteria:	EC50	3h	140	mg/l	activated sludge		EC 88/302

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

16 07 08 wastes containing oil

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Classification code:

LQ:

14.5. Environmental hazards:

Tunnel restriction code:

#### Transport by sea (IMDG-code)

n.a.

n.a.

n.a.

n.a.

n.a.

Not applicable



GB

Page 9 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 26.07.2019 / 0013  
 Replacing version dated / version: 07.01.2019 / 0012  
 Valid from: 26.07.2019  
 PDF print date: 29.07.2019  
 Oil Smoke Stop 300 mL  
 Art.: 8901

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
 General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2, 3, 4, 7, 11, 12, 16

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H412 Harmful to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

## Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic

Page 10 of 10  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 26.07.2019 / 0013  
Replacing version dated / version: 07.01.2019 / 0012  
Valid from: 26.07.2019  
PDF print date: 29.07.2019  
Oil Smoke Stop 300 mL  
Art.: 8901

DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.