

Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Top Tec 4605 5W-30 5 L

Art.: 8937

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

No information available at present.

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Use in closed process, no likelihood of exposure.

PROC 2 - Use in closed, continuous process with occasional controlled exposure

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC20 - Heat and pressure transfer fluids in dispersive, professional use but closed systems

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 9a - Wide dispersive indoor use of substances in closed systems ERC 9b - Wide dispersive outdoor use of substances in closed systems

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).



Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP	276-738-4
CAS	72623-87-1
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP	265-157-1
CAS	64742-54-7
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Baseoil - unspecified *	
Registration number (REACH)	-
Index	
EINECS, ELINCS, NLP	-
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures



Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Drying of the skin.

Irritation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed

n.c

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Foam

Dry extinguisher

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up



Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371)	
	 Draeger - Oil Mist 1/a (67 33 031) 	
BMGV:	Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Distillates (petroleum), hydrotreated heavy paraffinic								
Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note		
	compartment							
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3			
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3			
	Environment - oral (animal		PNEC	9,33	mg/kg feed			
	feed)							

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.



(GB)

Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection: Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0.5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Brown Odour: Characteristic Odour threshold: Not determined pH-value: n.a. Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: 234 °C Not determined Evaporation rate: Flammability (solid, gas): n.a.

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Not determined

Not determined

Not determined

Vapour pressure: Not determined Vapour density (air = 1): Not determined



(GB

Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

Density: 0,852 g/ml Bulk density: n.a.

Solubility(ies):

Not determined
Water solubility:

Partition coefficient (n-octanol/water):

Not determined
Not determined

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Viscosity:

Viscosity:

Explosive properties:

Not determined

Not determined

Not determined

Not determined

12,03 mm2/s (40°C)

Product is not explosive.

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Open flame, ignition sources

Protect from humidity.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Top Tec 4605 5W-30 5 L Art.: 8937						
Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.



Page 7 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0008
Replacing version dated / version: 10.02.2015 / 0007
Valid from: 21.08.2015

PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L Art.: 8937

Other information:			Classification according	ĺ
			to calculation procedure.	Ĺ

Lubricating oils (petroleum), C2					Toot weath ad	Notes
Toxicity / effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	
Skin corrosion/irritation:					Inhalation Toxicity) OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizising
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Carcinogenicity:					OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 421 (Reproduction/Develop mental Toxicity Screening Test)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 421 (Reproduction/Develop mental Toxicity Screening Test)	Negative
Specific target organ toxicity - single exposure (STOT-SE):					<u> </u>	No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						Asp. Tox. 1

Distillates (petroleum), hydrotreated heavy paraffinic								
Toxicity / effect	Endpoin	Value	Unit	Organism	Test method	Notes		
	t							
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat				
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous conclusion		
					Toxicity)			
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	Analogous conclusion		
					Dermal Toxicity)			



Page 8 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L Art.: 8937

Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol, Analogous
					Inhalation Toxicity)	conclusion
Skin corrosion/irritation:						Not irritant
Skin corrosion/irritation:						Mild irritant, Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizising
Aspiration hazard:						Yes
Aspiration hazard:						Yes, Analogous
						conclusion
Aspiration hazard:						Yes
Symptoms:						coughing, respiratory
						distress, nausea and
						vomiting., diarrhoea

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and							Inherent
degradability:							
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT and							n.d.a.
vPvB assessment							
Other adverse effects:							n.d.a.
Other information:							According to the recipe,
							contains no AOX.

Lubricating oils (petro Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
							Notes
Toxicity to fish:	NOEC/NO	96h	>=100	mg/l	Pimephales	OECD 203 (Fish,	
	EL				promelas	Acute Toxicity	
						Test)	
Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales	OECD 203 (Fish,	
					promelas	Acute Toxicity	
						Test)	
Toxicity to daphnia:	NOEC/NO	48h	>10000	mg/l	Daphnia magna	OECD 202	
	EL					(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to daphnia:	NOEC/NO	21d	10	mg/l	Daphnia magna	OEĆD 211	
	EL				'	(Daphnia magna	
						Reproduction	
						Test)	
Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202	
					'	(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to algae:	NOEC/NO	72h	>=100	mg/l	Pseudokirchneriell	OECD 201	
	EL	' -			a subcapitata	(Alga, Growth	
					a cascapitata	Inhibition Test)	



Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

				,	
Persistence and					OECD 301 B Not readily biodegradable
degradability:					(Ready
,					Biodegradability -
					Co2 Evolution
					Test)
Persistence and		28d	46	%	OECD 301 B
degradability:					(Ready
					Biodegradability -
					Co2 Evolution
					Test)
Bioaccumulative	Log Kow		>6		A notable biological
potential:					accumulation potential
					has to be expected
					(LogPow > 3).
Results of PBT and					No PBT substance, No
vPvB assessment					vPvB substance
Toxicity to bacteria:	NOEC/NO EL	10min	>1,93	mg/l	DIN 38412 T.8

Distillates (petroleum), hydrotreated heavy paraffinic								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Toxicity to fish:	NOEC/NO	96h	>100	mg/l	Pimephales	OECD 203 (Fish,		
	EL				promelas	Acute Toxicity		
						Test)		
Toxicity to daphnia:	LL50	96h	>10000	mg/l		OECD 202		
				_		(Daphnia sp.		
						Acute		
						Immobilisation		
						Test)		
Toxicity to algae:	NOEC/NO	72h	>=100	mg/l	Pseudokirchneriell	OECD 201		
	EL				a subcapitata	(Alga, Growth		
						Inhibition Test)		
Persistence and							Not readily biodegradable	
degradability:								
Water solubility:							Insoluble	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

20 01 26 oil and fat other than those mentioned in 20 01 25

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information



Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name: Transport hazard class(es): n.a. Packing group: n.a. Classification code: n.a. LQ (ADR 2015): n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name: Transport hazard class(es):

n.a. Packing group: n.a. Marine Pollutant: n.a

Not applicable Environmental hazards:

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es): n.a. Packing group: n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

For classification and labelling see Section 2.

Observe restrictions: General hygiene measures for the handling of chemicals are applicable. 0 %

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to



(GB)

Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

ACGIH American Conference of Governmental Industrial Hygienists

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

Adsorbable organic halogen compounds AOX

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BGV

Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and

mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

Dwell Time - 50% reduction of start concentration DT50

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EC **European Community** ECHA European Chemicals Agency EEA European Economic Area

European Economic Community EEC

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC **Environmental Release Categories**

FS Exposure scenario

etc. et cetera EU **European Union**

EWC European Waste Catalogue

Fax number Fax. general aen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

Global warming potential **GWP**

Hen's Egg Test - Chorionallantoic Membrane HET-CAM

HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer

International Air Transport Association IATA

IBC Intermediate Bulk Container International Bulk Chemical (Code) IBC (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill **LCLo** lowest published lethal concentration

Lethal Dose of a chemical LD



(GB)

Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.08.2015 / 0008

Replacing version dated / version: 10.02.2015 / 0007

Valid from: 21.08.2015 PDF print date: 27.08.2015 Top Tec 4605 5W-30 5 L

Art.: 8937

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

IΩ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

organic org.

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

parts per million ppm PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Telephone Tel.

ThOD Theoretical oxygen demand

Total organic carbon TOC

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

United Nations Recommendations on the Transport of Dangerous Goods **UN RTDG** VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.