

GB

Page 1 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.07.2016 / 0010
Replacing version dated / version: 10.04.2015 / 0009
Valid from: 29.07.2016
PDF print date: 29.07.2016
Kupfergleitpaste 500 g
Art.: 735698

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Kupfergleitpaste 500 g
Art.: 735698

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC10 - Roller application or brushing

PROC19 - Manual activities involving hand contact

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC99 - Not required.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

Albert Berner Deutschland GmbH, Bernerstrasse 4, 74653 Künzelsau, Germany
Phone: +49 79 40 12 10, Fax: +49 79 40 12 13 00
info@berner.de, www.berner.de

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please
DO NOT use for requesting Safety Data Sheets.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Benzene, mono-C10-13-alkyl derivs., distn. residues	
Registration number (REACH)	01-2119485843-26-XXXX
Index	---
EINECS, ELINCS, NLP	284-660-7
CAS	84961-70-6
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Copper	
Registration number (REACH)	01-2119480154-42-XXXX
Index	---
EINECS, ELINCS, NLP	231-159-6

GB

Page 3 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

CAS	7440-50-8
content %	5-15
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Acute 1, H400 (M=1)

Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts	Substance with specific conc. limit(s) acc. to REACH-registration
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	939-603-7 (REACH-IT List-No.)
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly with soap and water.
 Remove contaminated clothing immediately.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting. Consult doctor immediately.
 Keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.07.2016 / 0010

Replacing version dated / version: 10.04.2015 / 0009

Valid from: 29.07.2016

PDF print date: 29.07.2016

Kupfergleitpaste 500 g

Art.: 735698

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Water jet spray

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of sulphur

Oxides of phosphorus

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Ⓢ

Page 5 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Store in a dry place.

Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ⓢ	Chemical Name	Copper	Content %:5-15
	WEL-TWA: 1 mg/m3 (dusts and mists, as Cu)	WEL-STEL: 2 mg/m3 (dusts and mists, as Cu)	---
	Monitoring procedures:	ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2000(Part 1), 2001(Part 2), 2004 (Part 3) - EU project - BC/CEN/ENTR/000/2002-16 card 84-1 (2004) MDHS 91 (Metals and metalloids in workplace air by X-ray fluorescence spectrometry) - 1998 - EU project - BC/CEN/ENTR/000/2002-16 card 84-2 (2004) - NIOSH 7029 (Copper (dust and fume)) - 1994 - NIOSH 7300 (Elements by ICP (nitric/perchloric ashing)) - 2003 - NIOSH 7301 (Elements by ICP (aqua regia ashing)) - 2003 NIOSH 7303 (Elements by ICP (Hot block HCl/HNO3 digestion)) - 2003 - 2003 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project - BC/CEN/ENTR/000/2002-16 card 84-10 (2004) OSHA ID-125G (Metal and metalloid particulates in workplace atmospheres (ICP)) - 2002 OSHA ID-206 (ICP analysis of metal/metalloid particulates from solder operations) - 1991	
	BMGV: ---	Other information: ---	
Ⓢ	Chemical Name	China stone	Content %:
	WEL-TWA: 2 mg/m3 (res. dust)	WEL-STEL: ---	---
	Monitoring procedures:	---	
	BMGV: ---	Other information: ---	
Ⓢ	Chemical Name	Silica, amorphous	Content %:
	WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---
	Monitoring procedures:	---	
	BMGV: ---	Other information: ---	

Ⓢ

GB

Page 6 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Benzene, mono-C10-13-alkyl derivs., distn. residues						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,000 075	mg/l	
	Environment - marine		PNEC	0,007 5	µg/l	
	Environment - sporadic (intermittent) release		PNEC	0,001	mg/l	
	Environment - sewage treatment plant		PNEC	2	mg/l	
	Environment - sediment, freshwater		PNEC	1761	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1761	mg/kg dry weight	
Industrial / commercial	Human - inhalation	Long term, systemic effects	DNEL	96	mg/kg bw/day	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 With danger of contact with eyes.
 Tight fitting protective goggles with side protection (EN 166).

Page 7 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.07.2016 / 0010

Replacing version dated / version: 10.04.2015 / 0009

Valid from: 29.07.2016

PDF print date: 29.07.2016

Kupfergleitpaste 500 g

Art.: 735698

Skin protection - Hand protection:

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,35

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, Liquid
Colour:	Copper
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined

Page 8 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,14 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

See also section 7.

None known

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Kupfergleitpaste 500 g

Art.: 735698

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

GB

Page 9 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Benzene, mono-C10-13-alkyl derivs., distn. residues

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3600	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Aspiration hazard:						Yes

Copper

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

GB

Page 10 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

Acute toxicity, by dermal route:						n.d.a.
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing
Symptoms:						abdominal pain, vomiting, weight loss, headaches, metal fume fever

Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg			
Acute toxicity, by inhalation:	LC0	>1,9	mg/l/4 h	Rat		Maximum achievable concentration., Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Skin Sens. 1
Germ cell mutagenicity:					(Ames-Test)	Negative

China stone

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Serious eye damage/irritation:						Mechanical irritation possible.
Respiratory or skin sensitisation:						No indications of such an effect.

SECTION 12: Ecological information

GB

Page 11 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupferleitpaste 500 g
 Art.: 735698

Possibly more information on environmental effects, see Section 2.1 (classification).

Kupferleitpaste 500 g
Art.: 735698

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Benzene, mono-C10-13-alkyl derivs., distn. residues

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	14d	>10	µg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.2. Persistence and degradability:		28d	28	%			
12.2. Persistence and degradability:							Hardly biodegradable
12.3. Bioaccumulative potential:	Log Pow		6,6 - 9,9				A notable biological accumulation potential has to be expected (LogPow > 3).

GB

Page 12 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.5. Results of PBT and vPvB assessment							n.a.
Toxicity to bacteria:	EC10	30min	>100 00	mg/l	activated sludge		
Water solubility:							Insoluble

Copper

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,665	mg/l			
12.1. Toxicity to fish:	LOEC/LOEL	96h	0,022	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50		0,44	mg/l	Daphnia magna		

Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	EC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			8	%			Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		70,8				Biological accumulation potential: , Not to be expected
12.3. Bioaccumulative potential:	Log Pow		8				@20°C
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

GB

Page 13 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.07.2016 / 0010
 Replacing version dated / version: 10.04.2015 / 0009
 Valid from: 29.07.2016
 PDF print date: 29.07.2016
 Kupfergleitpaste 500 g
 Art.: 735698

Toxicity to bacteria:	EC50		>100 00	mg/l		OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Water solubility:			0,000 1	g/l			@25°C

China stone

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	LC50	96h	>100 0	mg/l			
12.1. Toxicity to daphnia:	LC50	48h	>110 0	mg/l	Daphnia magna		References
12.1. Toxicity to daphnia:	EC50		>100 0	mg/l			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	IC50		>100 0	mg/l			
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.2. Persistence and degradability:							Not biodegradable
Water solubility:							Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

12 01 12 spent waxes and fats

Recommendation:

Sewage disposal shall be discouraged.

Page 14 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.07.2016 / 0010
Replacing version dated / version: 10.04.2015 / 0009
Valid from: 29.07.2016
PDF print date: 29.07.2016
Kupfergleitpaste 500 g
Art.: 735698

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ (ADR 2015): n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

15.2 Chemical safety assessment



Page 15 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.07.2016 / 0010
Replacing version dated / version: 10.04.2015 / 0009
Valid from: 29.07.2016
PDF print date: 29.07.2016
Kupfergleitpaste 500 g
Art.: 735698

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1 - 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

Asp. Tox. — Aspiration hazard

Aquatic Acute — Hazardous to the aquatic environment - acute

Skin Sens. — Skin sensitization

Albert Berner Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
Fax +49 79 40 12 13 00
info@berner.de
www.berner.de

Berner Gesellschaft m.b.H.
Industriezeile 36
A - 5280 Braunau / Inn
Tel +43 77 22 800 508
Fax +43 77 22 800 184
berner@berner.co.at
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
B - 3620 Lanaken
Tel +31 45 533 93 133(8.00h-16.00h)
Tel +31 6 290 27 464 (16.00h-8.00h)
Fax +31 455 33 92 43
info@berner.be
www.berner.be

Montagetechnik Berner AG
Kägenstraße 8
CH - 4153 Reinach / Bl. 1
Tel +41 61 71 59 222
Fax +41 61 71 59 333
berner-ag@berner-ag.ch
www.berner-ag.ch

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
Fax +45 98 19 24 14
info@berner.dk
www.berner.dk

Berner Montaje y Fijación, S.L.
P.I. "La Rosa VI"
C/Albert Berner, 2
E - 18330 Chauchina-Granada-España
Tel +34 90 21 03 504
Fax +34 90 21 13 190
berner-spain@berner.es
www.berner.es

Page 16 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.07.2016 / 0010

Replacing version dated / version: 10.04.2015 / 0009

Valid from: 29.07.2016

PDF print date: 29.07.2016

Kupfergleitpaste 500 g

Art.: 735698

Berner Kft.
Táblás u. 34
H - 1097 Budapest
Tel +36 (1) 347 1059
Fax +36 (1) 347 1045
info@berner.hu
www.berner.hu

Frimann-Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 76 55 80
Fax +47 66 76 55 81
info@berner.no
www.berner.no

Berner Succ. Luxembourg
105, Rue des Bruyères
L - 1274 Howald
Tel +31 45 533 93 133 (8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.lu
www.berner.lu

Berner spol. s r.o.
Jinonická 80
CZ - 158 00 Praha 5
Tel +420 225 390 666
Fax +420 225 390 660
berner@berner.cz
www.berner.cz

Berner, S.A.
Av. Amália Rodrigues, 3510
Manique de Baixo
P - 2785-738 São Domingos de Rana
Tel ++351 21 448 90 60
Fax ++351 21 448 90 69
marketing.pt@berner.pt
www.berner.pt

Berner Polska Sp. z o.o.
Ul. Puzkarska 7J
30-644 Kraków
Tel +48 12 297 62 40
Fax +48 12 297 62 02
office@berner.pl
www.berner.pl

Albert Berner UAB
Kalvarijø 29B, LT09313,
Vilnius, Lithuania
Tel +370-52104355
Fax +370-52350020
info@berner.lt

Berner SK
Berner s r.o.
Jesenského 1
SK - 962 12 Detva
Tel (+421) 45 5410 245
Fax (+421) 45 5410 255
berner@berner.sk
www.berner.sk

Albert Berner Montagetechnik AB
Elektravägen 53
S - 126 30 Hägersten
Tel +46 85 78 77 800
Fax +46 85 78 77 805
info@berner.se
www.berner.se

Berner Pultti Oy
Volltikatu 6
FI - 70700 Kuopio
Tel +358-207-590 220
Fax +358-207-590 221
kuopio@berner-pultti.com
www.berner-pultti.com

Mitras d.o.o
Brdnikova ulica 34e
SL-1000 Ljubljana
Tel +386-1-256-62-46
Fax +386-1-256-62-45
mitras@siol.com

BERNER d.o.o
CPM Savčca Šanci
Trgovačka 2
HR - 10000 Zagreb
Tel +38512 499 470
Fax +38512 499 480
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler
Sanayi ve Ticaret A.Ş.
Ferhatpaşa Mah. G 7 Sok. 31/2
TR - 34858 Kartal-Samandıra /
ÝSTANBUL
Tel +90 (0) 216-4713077
Fax +90 (0) 216-4719625
info@berner.com.tr
www.berner.com.tr

Berner S.p.A.
Via dell' Elettronica 15
I - 37139 Verona
Tel +39 04 58 67 01 11
Fax +39 04 58 67 01 34
info@berner.it
www.berner.it

Albert Berner srl
Str. Vrancei Nr. 51 - 55
RO - 310315 Arad
Tel +40 257 212291
Fax +40 257 250460
office@berner-romania.ro
www.berner-romania.ro

Page 17 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.07.2016 / 0010
Replacing version dated / version: 10.04.2015 / 0009
Valid from: 29.07.2016
PDF print date: 29.07.2016
Kupfergleitpaste 500 g
Art.: 735698

Berner Produkten b.v.
Vogelzankweg 175
NL - 6374 AC Landgraaf
+31 45 53 39 133 (8.00h-
16.00h)
+31 6 290 27 464 (16.00h-

Berner s.a.r.l.
ZI Les Manteaux
F - 89331 Saint-Julien-du-Sault
Cedex
Tel +33 38 69 94 400
Fax +33 38 69 94 444

Albert Berner SIA
Liliju 20, Marupe, Mārupes
novads,
LV-2167, Latvija
Tel +37167840007
Fax +371678440008

(c) COPYRIGHT 1987 - 2050 ALL
RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration

Page 18 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.07.2016 / 0010
Replacing version dated / version: 10.04.2015 / 0009
Valid from: 29.07.2016
PDF print date: 29.07.2016
Kupfergleitpaste 500 g
Art.: 735698

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

Page 19 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.07.2016 / 0010

Replacing version dated / version: 10.04.2015 / 0009

Valid from: 29.07.2016

PDF print date: 29.07.2016

Kupfergleitpaste 500 g

Art.: 735698

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.