

GB

Page 1 of 31
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.03.2019 / 0016
Replacing version dated / version: 25.04.2018 / 0015
Valid from: 28.03.2019
PDF print date: 28.03.2019
U-FLOOR PROT. 1001 BITUM 500 ml
Art.: 145195

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

U-FLOOR PROT. 1001 BITUM 500 ml
Art.: 145195

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Paint

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 9a - Coatings and paints, thinners, paint removers

Process category [PROC]:

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC99 - Not required.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

Albert Berner Deutschland GmbH, Bernerstrasse 4, 74653 Künzelsau, Germany
Phone: +49 79 40 12 10, Fax: +49 79 40 12 13 00
info@berner.de, www.berner.de

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.
 P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.
 P312-Call a POISON CENTRE / doctor if you feel unwell.

GB

Page 3 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.
 Naphtha (petroleum), hydrotreated light
 Butanone
 Hydrocarbons, C9, aromatics
 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	---
EINECS, ELINCS, NLP	920-750-0 (REACH-IT List-No.)
CAS	---
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411

Butanone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	606-002-00-3
EINECS, ELINCS, NLP	201-159-0
CAS	78-93-3
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Naphtha (petroleum), hydrotreated light	
Registration number (REACH)	---
Index	649-328-00-1
EINECS, ELINCS, NLP	265-151-9
CAS	64742-49-0
content %	10-<20

GB

Page 4 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336
Butane	
Registration number (REACH)	01-2119474691-32-XXXX
Index	601-004-00-0
EINECS, ELINCS, NLP	203-448-7
CAS	106-97-8
content %	1-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1, H220
Isobutane	
Registration number (REACH)	01-2119485395-27-XXXX
Index	601-004-00-0
EINECS, ELINCS, NLP	200-857-2
CAS	75-28-5
content %	1-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1, H220
Propane	
Registration number (REACH)	01-2119486944-21-XXXX
Index	601-003-00-5
EINECS, ELINCS, NLP	200-827-9
CAS	74-98-6
content %	1-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1, H220
Hydrocarbons, C9, aromatics	
Registration number (REACH)	01-2119455851-35-XXXX
Index	---
EINECS, ELINCS, NLP	918-668-5 (REACH-IT List-No.)
CAS	(64742-95-6)
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

Page 5 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Headaches

Dizziness

Effect on the central nervous system

Coordination disorders

Unconsciousness

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinguishing powder

Water jet spray

Large fire:

Page 6 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid inhalation of the vapours.

Ensure good ventilation.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

GB

Page 7 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Observe special regulations for aerosols!

Do not keep the container sealed.

Store cool.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

800 mg/m³

Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Content %: 10-<25
WEL-TWA: 1200 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Butanone	Content %: 10-<20
WEL-TWA: 200 ppm (600 mg/m ³) (WEL, EU)	WEL-STEL: 300 ppm (899 mg/m ³) (WEL), 300 ppm (900 mg/m ³) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-139 SB (549 731) - Compur - KITA-139 U (549 749) - MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project - BC/CEN/ENTR/000/2002-16 card 105-1 (2004) 	

GB

Page 8 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

- MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993
 - DFG (D) (Lösungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1998, 2002
 - DFG (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 1998, 2002
 - DFG (D) (Lösungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 1998, 2002
 - DFG (D) (Lösungsmittelgemische 5), DFG (E) (Solvent mixtures 5) - 1998, 2002
 - DFG (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 1998, 2002

BMGV: 70 µmol butan-2-one/l in urine, post shift (BMGV) Other information: Sk

Chemical Name	Naphtha (petroleum), hydrotreated light		Content %: 10-<20
WEL-TWA:	800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-187 S (551 174)		
BMGV:	---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Butane		Content %: 1-20
WEL-TWA:	600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)		
BMGV:	---	Other information: ---	

Chemical Name	Isobutane		Content %: 1-20
WEL-TWA:	1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)		
BMGV:	---	Other information: ---	

Chemical Name	Propane		Content %: 1-20
WEL-TWA:	1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)		
BMGV:	---	Other information: ---	

Chemical Name	Hydrocarbons, C9, aromatics		Content %: 1-5
WEL-TWA:	500 mg/m ³ (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)		
BMGV:	---	Other information: ---	

Chemical Name	Calcium carbonate		Content %:
WEL-TWA:	4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures:	---		
BMGV:	---	Other information: ---	

Chemical Name	Bitumen		Content %:
---------------	---------	--	------------

GB

Page 9 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

WEL-TWA: 5 mg/m ³ (Asphalt, petroleum fumes)	WEL-STEL: 10 mg/m ³ (Asphalt, petroleum fumes)	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m ³	

Butanone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	55,8	mg/l	
	Environment - marine		PNEC	55,8	mg/l	
	Environment - sediment, freshwater		PNEC	284,74	mg/kg	
	Environment - sediment, marine		PNEC	287,7	mg/kg	
	Environment - soil		PNEC	22,5	mg/kg	
	Environment - sewage treatment plant		PNEC	709	mg/l	
	Environment - sporadic (intermittent) release		PNEC	55,8	mg/l	
	Environment - oral (animal feed)		PNEC	1000	mg/kg	
Consumer	Human - dermal	Long term	DNEL	412	mg/kg	
Consumer	Human - inhalation	Long term	DNEL	106	mg/m ³	
Consumer	Human - oral	Long term	DNEL	31	mg/kg	
Workers / employees	Human - dermal	Long term	DNEL	1161	mg/kg	
Workers / employees	Human - inhalation	Long term	DNEL	600	mg/m ³	

Hydrocarbons, C9, aromatics

GB

Page 10 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m ³	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Page 11 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Protective nitrile gloves (EN 374).

Protective Neoprene® / polychloroprene gloves (EN 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 120

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	<0 °C

GB

Page 12 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	1,1 Vol-%
Upper explosive limit:	11,5 Vol-%
Vapour pressure:	3500 hPa (20°C)
Vapour density (air = 1):	Not determined
Density:	0,764 g/cm ³ (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	365 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	63,3 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

Electrostatic charge

10.5 Incompatible materials

See also section 7.

No dangerous reactions are known.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

GB

Page 13 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Possibly more information on health effects, see Section 2.1 (classification).

U-FLOOR PROT. 1001 BITUM 500 ml
Art.: 145195

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	2800	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

GB

Page 14 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Butanone

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	34,5	mg/l/4 h	Rat		

GB

Page 15 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Skin corrosion/irritation:						Mild irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, coughing, headaches, cramps, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting, mental confusion

Butane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

GB

Page 16 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

GB

Page 17 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Hydrocarbons, C9, aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative

GB

Page 18 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H335, STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative
Aspiration hazard:						Yes
Symptoms:						respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness, fever, ear noises, drying of the skin.

Calcium carbonate

GB

Page 20 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:	AOX						According to the recipe, contains no AOX.
Other information:	DOC						DOC-elimination degree (complexing organic substance) > = 80%/28d: n.a.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50		1 -10	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EbL50	72h	10-30		Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Completely biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

GB

Page 21 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value
-----------------------	------	-----	-------	------	--	--	------------------

Butanone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1690	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	2993	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	308	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	LC50	72h	1972	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,29			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	Bioaccumulation is unlikely (LogPow < 1).
12.4. Mobility in soil:	H (Henry)		0,000 0244	atm*m ³ /mol			25°C
Other information:	DOC		>70	%			
Other information:	BOD/COD		>50	%			

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).

GB

Page 22 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	-------------------------------------

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Hydrocarbons, C9, aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

GB

Page 23 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	54-56	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.2. Persistence and degradability:		28d	78	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	78	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		3,7 - 4,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Calcium carbonate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	

GB

Page 24 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Toxicity to bacteria:	EC50	3h	>100 0	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
Water solubility:			0,014	g/l			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Do not dispose of with household waste.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L



Page 25 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

14.5. Environmental hazards: environmentally hazardous
 Tunnel restriction code: D
Transport by sea (IMDG-code)
 14.2. UN proper shipping name: AEROSOLS (NAPHTHA (PETROLEUM))
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 EmS: F-D, S-U
 Marine Pollutant: Yes
 14.5. Environmental hazards: environmentally hazardous



Transport by air (IATA)
 14.2. UN proper shipping name: Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

GB

Page 26 of 31
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.03.2019 / 0016
 Replacing version dated / version: 25.04.2018 / 0015
 Valid from: 28.03.2019
 PDF print date: 28.03.2019
 U-FLOOR PROT. 1001 BITUM 500 ml
 Art.: 145195

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 71,53 %
 Directive 2010/75/EU (VOC): 546,5 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 16
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Aerosol 1, H229**Classification based on test data.**

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H220 Extremely flammable gas.

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Flam. Gas — Flammable gases (including chemically unstable gases)

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Albert Berner Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
Fax +49 79 40 12 13 00
info@berner.de
www.berner.de

Berner Gesellschaft m.b.H.
Industriezeile 36
A - 5280 Braunau / Inn
Tel +43 77 22 800 508
Fax +43 77 22 800 184
berner@berner.co.at
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
B - 3620 Lanaken
Tel +31 45 533 93 133(8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.be
www.berner.be

Montagetechnik Berner AG
Kägenstraße 8
CH - 4153 Reinach / Bl. 1
Tel +41 61 71 59 222
Fax +41 61 71 59 333
berner-ag@berner-ag.ch
www.berner-ag.ch

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
Fax +45 98 19 24 14
info@berner.dk
www.berner.dk

Berner Montaje y Fijación, S.L.
P.I. "La Rosa VI"
C/Albert Berner, 2
E - 18330 Chauchina-Granada-
España
Tel +34 90 21 03 504
Fax +34 90 21 13 190
berner-spain@berner.es
www.berner.es

Page 28 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Berner Kft.
Gubacsi út 6/b
H - 1097 Budapest
Tel +36 (1) 347 1059
Fax +36 (1) 347 1045
info@berner.hu
www.berner.hu

Frimann-Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 76 55 80
Fax +47 66 76 55 81
info@berner.no
www.berner.no

Berner Succ. Luxembourg
105, Rue des Bruyères
L - 1274 Howald
Tel +31 45 533 93 133 (8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.lu
www.berner.lu

Berner spol. s r.o.
Jinonická 80
CZ - 158 00 Praha 5
Tel +420 225 390 666
Fax +420 225 390 660
berner@berner.cz
www.berner.cz

Berner,S.A.
Av. Amália Rodrigues,3510
Manique de Baixo
P - 2785-738 São Domingos de Rana
Tel ++351 21 448 90 60
Fax ++351 21 448 90 69
marketing@berner.pt
www.berner.pt

Berner Polska Sp. z o.o.
Ul. Puzkarska 7J
30-644 Kraków
Tel +48 12 297 62 40
Fax +48 12 297 62 02
office@berner.pl
www.berner.pl

Albert Berner UAB
Kalvarijø 29B, LT09313,
Vilnius, Lithuania
Tel +370-52104355
Fax +370-52350020
info@berner.lt

Berner SK
Berner s r.o.
Jesenského 1
SK - 962 12 Detva
Tel (+421) 45 5410 245
Fax (+421) 45 5410 255
berner@berner.sk
www.berner.sk

Albert Berner Montagetechnik AB
Elektravägen 53
S - 126 30 Hägersten
Tel +46 85 78 77 800
Fax +46 85 78 77 805
info@berner.se
www.berner.se

Berner Pultti Oy
Volltikatu 6
FI - 70700 Kuopio
Tel +358-207-590 220
Fax +358-207-590 221
kuopio@berner-pultti.com
www.berner-pultti.com

Mitras d.o.o
Brdnikova ulica 34e
SL-1000 Ljubljana
Tel +386-1-256-62-46
Fax +386-1-256-62-45
mitras@siol.com

BERNER d.o.o
CPM Savëca Šanci
Trgovačka 2
HR - 10000 Zagreb
Tel +38512 499 470
Fax +38512 499 480
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler
Sanayi ve Ticaret A.Ş.
Ferhatpaşa Mah. G 7 Sok. 31/2
TR - 34858 Kartal-Samandıra /
ÝSTANBUL
Tel +90 (0) 216-4713077
Fax +90 (0) 216-4719625
info@berner.com.tr
www.berner.com.tr

Berner S.p.A.
Via dell 'Elettronica 15
I - 37139 Verona
Tel +39 04 58 67 01 11
Fax +39 04 58 67 01 34
info@berner.it
www.berner.it

Albert Berner srl
Str. Vrancei Nr. 51 - 55
RO - 310315 Arad
Tel +40 257 212291
Fax +40 257 250460
office@berner-romania.ro
www.berner-romania.ro

Page 29 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

Berner Produkten b.v.

Vogelzankweg 175

NL - 6374 AC Landgraaf

+31 45 53 39 133 (8.00h-16.00h)

+31 6 290 27 464 (16.00h-8.00h)

info@berner.nl

Berner s.a.r.l.

ZI Les Manteaux

F - 89331 Saint-Julien-du-Sault

Cedex

Tel +33 38 69 94 400

Fax +33 38 69 94 444

Albert Berner SIA

Liliju 20, Marupe, Mārupes

novads,

LV-2167, Latvija

Tel +37167840007

Fax +371678440008

(c) COPYRIGHT 1987 - 2050 ALL RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration



Page 30 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

Page 31 of 31

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.03.2019 / 0016

Replacing version dated / version: 25.04.2018 / 0015

Valid from: 28.03.2019

PDF print date: 28.03.2019

U-FLOOR PROT. 1001 BITUM 500 ml

Art.: 145195

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.