

GB

Page 1 of 24
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.06.2017 / 0016
Replacing version dated / version: 05.07.2016 / 0015
Valid from: 23.06.2017
PDF print date: 19.09.2017
Contact spray 400 ml
Art.: 147618

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Contact spray 400 ml
Art.: 147618

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC35 - Washing and cleaning products

Process category [PROC]:

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC99 - Not required.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

Albert Berner Deutschland GmbH, Bernerstrasse 4, 74653 Künzelsau, Germany
Phone: +49 79 40 12 10, Fax: +49 79 40 12 13 00
info@berner.de, www.berner.de

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H315-Causes skin irritation. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.
 P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.
 P314-Get medical advice / attention if you feel unwell.
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH208-Contains Turpentine, oil. May produce an allergic reaction.

GB

Page 3 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Without adequate ventilation, formation of explosive mixtures may be possible.
 Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	01-2119458869-15-XXXX
Index	---
EINECS, ELINCS, NLP	925-653-7 (REACH-IT List-No.)
CAS	(64742-81-0)
content %	70-90
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Carbon dioxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	204-696-9
CAS	124-38-9
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	---

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	202-414-9
CAS	95-38-5
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10) Skin Corr. 1C, H314 STOT RE 2, H373 (gastrointestinal tract, thymus) (oral) Eye Dam. 1, H318

Turpentine, oil	
------------------------	--

GB

Page 4 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Registration number (REACH)	---
Index	650-002-00-6
EINECS, ELINCS, NLP	232-350-7
CAS	8006-64-2
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting. Consult doctor immediately.
 Danger of aspiration
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

With long-term contact:
 Dermatitis (skin inflammation)
 Drying of the skin.
 Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Page 5 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray

CO₂

Extinction powder

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid inhalation of the vapours.

Ensure good ventilation.

GB

Page 6 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Do not store with flammable or self-igniting materials.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %: 70-90
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)	

Chemical Name	Carbon dioxide	Content %: 1-5
WEL-TWA: 5000 ppm (9150 mg/m ³) (WEL), 5000 ppm (9000 mg/m ³) (EU)	WEL-STEL: 15000 ppm (27400 mg/m ³) (WEL)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-126 B (549 475) - Compur - KITA-126 SA (549 467) - Compur - KITA-126 SB (548 816) - Compur - KITA-126 SF (549 491) - Compur - KITA-126 SG (550 210) - Compur - KITA-126 SH (549 509) - Compur - KITA-126 UH (549 517) - Draeger - Carbon Dioxide 100/a (81 01 811) 	

GB

Page 7 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

- Draeger - Carbon Dioxide 0,1%/a (CH 23 501)
- Draeger - Carbon Dioxide 0,5%/a (CH 31 401)
- Draeger - Carbon Dioxide 1%/a (CH 25 101)
- Draeger - Carbon Dioxide 5%/A (CH 20 301)
- OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990
- NIOSH 6603 (Carbon dioxide) - 1994

BMGV: --- Other information: ---

Chemical Name	4-methylpentan-2-ol		Content %:1-5
WEL-TWA:	25 ppm (106 mg/m3)	WEL-STEL:	40 ppm (170 mg/m3) ---
Monitoring procedures:	- Draeger - Alcohol 100/a (CH 29 701)		
BMGV:	---	Other information:	Sk

Chemical Name	Turpentine, oil		Content %:0,1-<1
WEL-TWA:	100 ppm (566 mg/m3)	WEL-STEL:	150 ppm (850 mg/m3) ---
Monitoring procedures:	---		
BMGV:	---	Other information:	---

Chemical Name	Oil mist, mineral		Content %:
WEL-TWA:	5 mg/m3 (ACGIH)	WEL-STEL:	10 mg/m3 (ACGIH) ---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)		
BMGV:	---	Other information:	---

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Turpentine, oil						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	µg/l	
	Environment - marine		PNEC	0,88	µg/l	
	Environment - sediment, freshwater		PNEC	2,27	mg/kg	
	Environment - sediment, marine		PNEC	0,227	mg/kg	
	Environment - soil		PNEC	0,45	mg/kg	
	Environment - sewage treatment plant		PNEC	6,6	mg/l	

Page 8 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

	Environment - oral (animal feed)		PNEC	1,35	mg/kg	
Consumer	Human - dermal	Short term	DNEL	0,081	mg/cm2	
Consumer	Human - oral	Long term	DNEL	0,31	mg/kg bw/d	
Consumer	Human - inhalation	Long term	DNEL	1,06	mg/m3	
Workers / employees	Human - dermal	Short term	DNEL	0,161	mg/cm2	
Workers / employees	Human - inhalation	Long term	DNEL	5,98	mg/m3	

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,46	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,06	mg/kg bw/day	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

With long-term contact:

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

Page 9 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	65 °C (DIN 51755 (Abel-Pensky, closed cup))
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-%
Upper explosive limit:	6,5 Vol-%
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,81 g/cm ³ (20°C, DIN 51757)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined

GB

Page 10 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	3,9 cSt (20°C)
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Contact spray 400 ml

Art.: 147618

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.

GB

Page 11 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5060	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	~3400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	13,1	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Acute toxicity, by inhalation:	LC50	>13,1	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEC	>=300	ppm	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Aspiration hazard:						Yes

GB

Page 12 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Symptoms:						Oedema of the lungs, Chemical pneumonitis (condition similar to pneumonia), drowsiness, unconsciousness, headaches, dizziness, drying of the skin., Gastrointestinal disturbances, Irritation of the mouth and throat
-----------	--	--	--	--	--	---

Carbon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						unconsciousness, blisters by skin-contact, vomiting, frostbite, annoyance, palpitations, itching, headaches, cramps, ear noises, dizziness

4-methylpentan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2590	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	3560	mg/kg	Rabbit		

GB

Page 13 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

Symptoms:						respiratory distress, unconsciousness, vomiting, coughing, headaches, fatigue, mucous membrane irritation, dizziness, nausea
-----------	--	--	--	--	--	--

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1265	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Corrosive
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing

Turpentine, oil						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3956	mg/kg	Rat		Does not conform with EU classification
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		Does not conform with EU classification
Acute toxicity, by inhalation:	LC50	>13,7	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Does not conform with EU classification
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Irritant

GB

Page 16 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Other adverse effects:							Product floats on the water surface.
Other information:							Isolate as much as possible with an oil separator.
Water solubility:							Insoluble

Carbon dioxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	35	mg/l	Salmo gairdneri		
12.6. Other adverse effects:							Greenhouse effect
Other information:	Log Kow		0,83				
Global warming potential (GWP):			1				

4-methylpentan-2-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	100-1000	mg/l			
12.1. Toxicity to daphnia:	EC50	96h	200	mg/l	Daphnia magna		

Turpentine, oil

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	29	mg/l		OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	8,8-14,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	16,4-17,1	mg/l		OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:						OECD 301 (Ready Biodegradability)	Readily biodegradable

GB

Page 17 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	736	mg/l		OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

07 06 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: D

Transport by sea (IMDG-code)



GB

Page 18 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

14.2. UN proper shipping name:
 AEROSOLS (2-(2-HEPTADEC-8-ENYL-2-IMIDAZOLIN-1-YL) ETHANOL)
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 EmS: F-D, S-U
 Marine Pollutant: Yes
 14.5. Environmental hazards: environmentally hazardous



Transport by air (IATA)

14.2. UN proper shipping name:
 Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection and the protection of young people at work!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 83,1 %
 REGULATION (EC) No 648/2004

GB

Page 19 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0016
 Replacing version dated / version: 05.07.2016 / 0015
 Valid from: 23.06.2017
 PDF print date: 19.09.2017
 Contact spray 400 ml
 Art.: 147618

30 % and more
 aliphatic hydrocarbons
 15 % or over but less than 30 %
 aromatic hydrocarbons

perfumes
 LIMONENE

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15, 16
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H226 Flammable liquid and vapour.

--- ---

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

Page 20 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Acute Tox. — Acute toxicity - oral

Aquatic Acute — Hazardous to the aquatic environment - acute

Skin Corr. — Skin corrosion

STOT RE — Specific target organ toxicity - repeated exposure

Eye Dam. — Serious eye damage

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Acute Tox. — Acute toxicity - dermal

Skin Sens. — Skin sensitization

Albert Berner Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
Fax +49 79 40 12 13 00
info@berner.de
www.berner.de

Berner Gesellschaft m.b.H.
Industriezeile 36
A - 5280 Braunau / Inn
Tel +43 77 22 800 508
Fax +43 77 22 800 184
berner@berner.co.at
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
B - 3620 Lanaken
Tel +31 45 533 93 133(8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.be
www.berner.be

Montagetechnik Berner AG
Kägenstraße 8
CH - 4153 Reinach / Bl. 1
Tel +41 61 71 59 222
Fax +41 61 71 59 333
berner-ag@berner-ag.ch
www.berner-ag.ch

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
Fax +45 98 19 24 14
info@berner.dk
www.berner.dk

Berner Montaje y Fijación, S.L.
P.I. "La Rosa VI"
C/Albert Berner, 2
E - 18330 Chauchina-Granada-
España
Tel +34 90 21 03 504
Fax +34 90 21 13 190
berner-spain@berner.es
www.berner.es

Page 21 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

Berner Kft.
Táblás u. 34
H - 1097 Budapest
Tel +36 (1) 347 1059
Fax +36 (1) 347 1045
info@berner.hu
www.berner.hu

Frimann-Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 76 55 80
Fax +47 66 76 55 81
info@berner.no
www.berner.no

Berner Succ. Luxembourg
105, Rue des Bruyères
L - 1274 Howald
Tel +31 45 533 93 133 (8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.lu
www.berner.lu

Berner spol. s r.o.
Jinonická 80
CZ - 158 00 Praha 5
Tel +420 225 390 666
Fax +420 225 390 660
berner@berner.cz
www.berner.cz

Berner,S.A.
Av. Amália Rodrigues,3510
Manique de Baixo
P - 2785-738 São Domingos de Rana
Tel ++351 21 448 90 60
Fax ++351 21 448 90 69
marketing.pt@berner.pt
www.berner.pt

Berner Polska Sp. z o.o.
Ul. Puzkarska 7J
30-644 Kraków
Tel +48 12 297 62 40
Fax +48 12 297 62 02
office@berner.pl
www.berner.pl

Albert Berner UAB
Kalvarijø 29B, LT09313,
Vilnius, Lithuania
Tel +370-52104355
Fax +370-52350020
info@berner.lt

Berner SK
Berner s r.o.
Jesenského 1
SK - 962 12 Detva
Tel (+421) 45 5410 245
Fax (+421) 45 5410 255
berner@berner.sk
www.berner.sk

Albert Berner Montagetechnik AB
Elektravägen 53
S - 126 30 Hägersten
Tel +46 85 78 77 800
Fax +46 85 78 77 805
info@berner.se
www.berner.se

Berner Pultti Oy
Volltikatu 6
FI - 70700 Kuopio
Tel +358-207-590 220
Fax +358-207-590 221
kuopio@berner-pultti.com
www.berner-pultti.com

Mitras d.o.o
Brdnikova ulica 34e
SL-1000 Ljubljana
Tel +386-1-256-62-46
Fax +386-1-256-62-45
mitras@siol.com

BERNER d.o.o
CPM Savëca Šanci
Trgovačka 2
HR - 10000 Zagreb
Tel +38512 499 470
Fax +38512 499 480
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler
Sanayi ve Ticaret A.Ş.
Ferhatpaşa Mah. G 7 Sok. 31/2
TR - 34858 Kartal-Samandıra /
ÝSTANBUL
Tel +90 (0) 216-4713077
Fax +90 (0) 216-4719625
info@berner.com.tr
www.berner.com.tr

Berner S.p.A.
Via dell 'Elettronica 15
I - 37139 Verona
Tel +39 04 58 67 01 11
Fax +39 04 58 67 01 34
info@berner.it
www.berner.it

Albert Berner srl
Str. Vrancei Nr. 51 - 55
RO - 310315 Arad
Tel +40 257 212291
Fax +40 257 250460
office@berner-romania.ro
www.berner-romania.ro

Page 22 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

Berner Produkten b.v.

Vogelzankweg 175

NL - 6374 AC Landgraaf

+31 45 53 39 133 (8.00h-16.00h)

+31 6 290 27 464 (16.00h-8.00h)

info@berner.nl

Berner s.a.r.l.

ZI Les Manteaux

F - 89331 Saint-Julien-du-Sault

Cedex

Tel +33 38 69 94 400

Fax +33 38 69 94 444

Albert Berner SIA

Liliju 20, Marupe, Mārupes

novads,

LV-2167, Latvija

Tel +37167840007

Fax +371678440008

(c) COPYRIGHT 1987 - 2050 ALL
RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

Page 23 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

Page 24 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0016

Replacing version dated / version: 05.07.2016 / 0015

Valid from: 23.06.2017

PDF print date: 19.09.2017

Contact spray 400 ml

Art.: 147618

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.