

GB

Page 1 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Tyre Foam 500 ml**

**Art.: 365877**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cleaner

Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

Albert Berner Deutschland GmbH, Bernerstrasse 4, 74653 Künzelsau, Germany

Phone: +49 79 40 12 10, Fax: +49 79 40 12 13 00

info@berner.de, www.berner.de

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.  
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH208-Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Ammonia</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	007-001-01-2

GB

Page 3 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

<b>EINECS, ELINCS, NLP</b>	215-647-6
<b>CAS</b>	1336-21-6
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 Eye Dam. 1, H318

<b>(R)-p-mentha-1,8-diene</b>	
<b>Registration number (REACH)</b>	01-2119529223-47-XXXX
<b>Index</b>	601-029-00-7
<b>EINECS, ELINCS, NLP</b>	227-813-5
<b>CAS</b>	5989-27-5
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

<b>Bronopol (INN)</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-085-00-8
<b>EINECS, ELINCS, NLP</b>	200-143-0
<b>CAS</b>	52-51-7
<b>content %</b>	0,01-<0,1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Page 4 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO<sub>2</sub> / dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

GB

Page 5 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well-ventilated place.

Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

GB

**Chemical Name**

Ammonia

Content  
%: 0,1-<1

Ⓢ

Page 6 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

WEL-TWA: NH3 25 ppm (18 mg/m <sup>3</sup> ) (WEL), 20 ppm (14 mg/m <sup>3</sup> ) (EU)	WEL-STEL: NH3 35 ppm (25 mg/m <sup>3</sup> ) (WEL), 50 ppm (36 mg/m <sup>3</sup> ) (EU)	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	
<b>Ⓢ Chemical Name</b> Butane	<b>Content %:</b>	
WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )	WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> )	---
Monitoring procedures: - Compur - KITA-221 SA (549 459)		
BMGV: ---	Other information: ---	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

Ammonia						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,001 1	mg/l	
	Environment - marine		PNEC	0,001 1	mg/l	
	Environment - periodic release		PNEC	0,006 8	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	2,8	mg/m <sup>3</sup>	
Consumer	Human - dermal	Short term, local effects	DNEL	68	mg/kg body weight/d ay	
Consumer	Human - dermal	Short term, systemic effects	DNEL	68	mg/kg body weight/d ay	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	23,8	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	23,8	mg/m <sup>3</sup>	

GB

Page 7 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Consumer	Human - oral	Short term, systemic effects	DNEL	6,8	mg/kg body weight/d ay	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,8	mg/kg body weight/d ay	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	6,8	mg/kg body weight/d ay	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	6,8	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	47,6	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	36	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	47,6	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	14	mg/m3	

**Bronopol (INN)**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,01	mg/l	
	Environment - marine		PNEC	0,0008	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,0025	mg/l	
	Environment - sewage treatment plant		PNEC	0,43	mg/l	
	Environment - sediment, freshwater		PNEC	0,041	mg/l	
	Environment - sediment, marine		PNEC	0,00328	mg/l	
	Environment - soil		PNEC	0,5	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,4	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,35	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4,2	mg/kg	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,1	mg/kg	

Page 8 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Consumer	Human - dermal	Long term, local effects	DNEL	0,008	mg/cm <sup>2</sup>	
Consumer	Human - dermal	Short term, local effects	DNEL	0,008	mg/cm <sup>2</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,3	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	1,3	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	3,7	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,3	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,1	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	12,3	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	4,2	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	7	mg/kg	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,013	mg/cm <sup>2</sup>	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,013	mg/cm <sup>2</sup>	

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 If applicable  
 Protective gloves in butyl rubber (EN 374).  
 Protective Neoprene® / polychloroprene gloves (EN 374).



Page 9 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Usual protective working garments

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Foam aerosol
Colour:	White
Odour:	Lemon
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined

GB

Page 10 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Density:	0,930 g/ml
Density:	0,995 g/cm <sup>3</sup> (Active substance )
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	100 % (Soluble )
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No

**9.2 Other information**

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

**Tyre Foam 500 ml**  
**Art.: 365877**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.

GB

Page 11 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

**Ammonia**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	350	mg/kg	Rat		
Acute toxicity, by oral route:	LDLo	550	mg/kg	Cat		
Acute toxicity, by oral route:	LDLo	43	mg/kg	Human being		
Acute toxicity, by inhalation:	LCLo	5000	ppm	Human being		
Skin corrosion/irritation:						Corrosive
Serious eye damage/irritation:				Rabbit		Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Germ cell mutagenicity:						None
Carcinogenicity:						None
Reproductive toxicity:						None

GB

Page 12 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Symptoms:						asthmatic symptoms, respiratory distress, unconsciousness, burning of the membranes of the nose and throat, vomiting, cornea opacity, coughing, cramps, circulatory collapse, shock, nausea
-----------	--	--	--	--	--	---

<b>(R)-p-mentha-1,8-diene</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1
Symptoms:						diarrhoea, rash, itching, gastrointestinal disturbances, mucous membrane irritation, nausea and vomiting.

<b>Bronopol (INN)</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	305	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	data of a diluted aqueous solution
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	



GB

Page 14 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

GB

Page 15 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Other information:							DOC-elimination degree(comp lexing organic substance) > = 80%/28d: n.a.
Other information:	AOX		0	%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

**Ammonia**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,42	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOEC/NOEL	27d	0,06	mg/l	Ictalurus punctatus		
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	0,53	mg/l	Oncorhynchus mykiss		Anhydrous substance
12.1. Toxicity to daphnia:	EC50	48h	0,66	mg/l	Daphnia pulex		
12.1. Toxicity to daphnia:	EC50	48h	1,16	mg/l	Daphnia pulicaria		Anhydrous substance
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:							Not to be expected
Toxicity to bacteria:	EC50	5min	1,16	mg/l	Photobacterium phosphoreum		Anhydrous substance
Water solubility:							Soluble

**(R)-p-mentha-1,8-diene**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,70	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	

GB

Page 16 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

12.1. Toxicity to daphnia:	EC50	48h	0,42	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	4	mg/l			
12.2. Persistence and degradability:		28d	92	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	

**Bronopol (INN)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	41,2	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	49d	39,1		Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,27	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,4 - 2,8	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:			>70	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.2. Persistence and degradability:	DOC		50	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	Biodegradable
12.3. Bioaccumulative potential:	Log Kow		0,22			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	



GB

Page 17 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Toxicity to bacteria:	LC0	3h	43	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	LC50	14d	>500	mg/l	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other information:	COD		600	mg/g			
Other information:	Koc		5				

#### Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

**For contaminated packing material**

Pay attention to local and national official regulations.  
 Recommendation:  
 Do not perforate, cut up or weld uncleaned container.  
 Recycling  
 15 01 04 metallic packaging

**SECTION 14: Transport information**

**General statements**

14.1. UN number: 1950

**Transport by road/by rail (ADR/RID)**

14.2. UN proper shipping name:  
 UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D



**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:  
 AEROSOLS (ISOHEXANES)

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



**Transport by air (IATA)**

14.2. UN proper shipping name:  
 Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

GB

Page 19 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 24.04.2018 / 0002  
 Replacing version dated / version: 05.02.2018 / 0001  
 Valid from: 24.04.2018  
 PDF print date: 05.07.2018  
 Tyre Foam 500 ml  
 Art.: 365877

Observe restrictions:  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 11 %  
**REGULATION (EC) No 648/2004**  
 5 % or over but less than 15 %  
 aliphatic hydrocarbons  
 less than 5 %  
 non-ionic surfactants

perfumes  
 CITRAL  
 LIMONENE  
 2-BROMO-2-NITROPROPANE-1,3-DIOL  
 OCTYLISOTHIAZOLINONE

Observe incident regulations.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 15  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

**Classification in accordance with regulation (EC) No. 1272/2008 (CLP)**

**Evaluation method used**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Skin Corr. — Skin corrosion

Aquatic Acute — Hazardous to the aquatic environment - acute

Eye Dam. — Serious eye damage

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Albert Berner Deutschland GmbH

Bernerstrasse 4

D - 74653 Künzelsau

Tel +49 79 40 12 10

Fax +49 79 40 12 13 00

info@berner.de

www.berner.de

Berner Gesellschaft m.b.H.

Industriezeile 36

A - 5280 Braunau / Inn

Tel +43 77 22 800 508

Fax +43 77 22 800 184

berner@berner.co.at

www.berner.co.at

Berner Belgien NV/SA

Bernerstraat 1

B - 3620 Lanaken

Tel +31 45 533 93 133(8.00h-

16.00h)

Tel +31 6 290 27 464 (16.00h-

8.00h)

Fax +31 455 33 92 43

info@berner.be

www.berner.be

Page 21 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Montagetechnik Berner AG  
Kägenstraße 8  
CH - 4153 Reinach / Bl. 1  
Tel +41 61 71 59 222  
Fax +41 61 71 59 333  
berner-ag@berner-ag.ch  
www.berner-ag.ch

Berner A/S  
Stenholm 2  
DK - 9400 Nørresundby  
Tel +45 99 36 15 00  
Fax +45 98 19 24 14  
info@berner.dk  
www.berner.dk

Berner Montaje y Fijación, S.L.  
P.I. "La Rosa VI"  
C/Albert Berner, 2  
E - 18330 Chauchina-Granada-  
España  
Tel +34 90 21 03 504  
Fax +34 90 21 13 190  
berner-spain@berner.es  
www.berner.es

Berner Kft.  
Táblás u. 34  
H - 1097 Budapest  
Tel +36 (1) 347 1059  
Fax +36 (1) 347 1045  
info@berner.hu  
www.berner.hu

Frimann-Berner AS  
Holmaveien 25  
N - 1339 Vøyenenga  
Tel +47 66 76 55 80  
Fax +47 66 76 55 81  
info@berner.no  
www.berner.no

Berner Succ. Luxembourg  
105, Rue des Bruyères  
L - 1274 Howald  
Tel +31 45 533 93 133 (8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.lu  
www.berner.lu

Berner spol. s r.o.  
Jinonická 80  
CZ - 158 00 Praha 5  
Tel +420 225 390 666  
Fax +420 225 390 660  
berner@berner.cz  
www.berner.cz

Berner, S.A.  
Av. Amália Rodrigues, 3510  
Manique de Baixo  
P - 2785-738 São Domingos de Rana  
Tel ++351 21 448 90 60  
Fax ++351 21 448 90 69  
marketing.pt@berner.pt  
www.berner.pt

Berner Polska Sp. z o.o.  
Ul. Puzkarska 7J  
30-644 Kraków  
Tel +48 12 297 62 40  
Fax +48 12 297 62 02  
office@berner.pl  
www.berner.pl

Albert Berner UAB  
Kalvarijø 29B, LT09313,  
Vilnius, Lithuania  
Tel +370-52104355  
Fax +370-52350020  
info@berner.lt

Berner SK  
Berner s r.o.  
Jesenského 1  
SK - 962 12 Detva  
Tel (+421) 45 5410 245  
Fax (+421) 45 5410 255  
berner@berner.sk  
www.berner.sk

Albert Berner Montagetechnik AB  
Elektravägen 53  
S - 126 30 Hägersten  
Tel +46 85 78 77 800  
Fax +46 85 78 77 805  
info@berner.se  
www.berner.se

Berner Pultti Oy  
Volltikatu 6  
FI - 70700 Kuopio  
Tel +358-207-590 220  
Fax +358-207-590 221  
kuopio@berner-pultti.com  
www.berner-pultti.com

Mitras d.o.o  
Brdnikova ulica 34e  
SL-1000 Ljubljana  
Tel +386-1-256-62-46  
Fax +386-1-256-62-45  
mitras@siol.com

BERNER d.o.o  
CPM Savčica Šanci  
Trgovačka 2  
HR - 10000 Zagreb  
Tel +38512 499 470  
Fax +38512 499 480  
e-mail: safetydata-hr@berner.co.at

Page 22 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

Berner Endüstriyel Ürünler  
Sanayi ve Ticaret A.Ş.  
Ferhatpaşa Mah. G 7 Sok. 31/2  
TR - 34858 Kartal-Samandıra /  
YİSTANBUL  
Tel +90 (0) 216-4713077  
Fax +90 (0) 216-4719625  
info@berner.com.tr

Berner S.p.A.  
Via dell 'Elettronica 15  
I - 37139 Verona  
Tel +39 04 58 67 01 11  
Fax +39 04 58 67 01 34  
info@berner.it  
www.berner.it

Albert Berner srl  
Str. Vrancei Nr. 51 - 55  
RO - 310315 Arad  
Tel +40 257 212291  
Fax +40 257 250460  
office@berner-romania.ro  
www.berner-romania.ro

Berner Produkten b.v.  
Vogelzankweg 175  
NL - 6374 AC Landgraaf  
+31 45 53 39 133 (8.00h-16.00h)  
+31 6 290 27 464 (16.00h-8.00h)  
info@berner.nl  
www.berner.nl

Berner s.a.r.l.  
ZI Les Manteaux  
F - 89331 Saint-Julien-du-Sault Cedex  
Tel +33 38 69 94 400  
Fax +33 38 69 94 444  
contact@berner.fr  
www.berner.fr

Albert Berner SIA  
Liliju 20, Marupe, Mārupes novads,  
LV-2167, Latvija  
Tel +37167840007  
Fax +371678440008  
info@berner.lv

(c) COPYRIGHT 1987 - 2050 ALL  
RIGHTS RESERVED

### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

Page 23 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

Page 24 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.04.2018 / 0002

Replacing version dated / version: 05.02.2018 / 0001

Valid from: 24.04.2018

PDF print date: 05.07.2018

Tyre Foam 500 ml

Art.: 365877

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.