

GB

Page 1 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0006  
Replacing version dated / version: 05.08.2016 / 0005  
Valid from: 07.03.2017  
PDF print date: 15.04.2017  
Hardener for Polyester Filler 40 g  
Art.: 100015

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Hardener for Polyester Filler 40 g**  
**Art.: 100015**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Hardener

Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

NL

Berner Produkten b.v., Vogelzankweg 175, 6374 AC Landgraaf, Netherlands  
Phone: +31 45 53 39 133, Fax: +31 45 53 14 588  
info@berner.nl, www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

**Hazard class   Hazard category   Hazard statement**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Acute	1	H400-Very toxic to aquatic life.
Org. Perox.	Type E	H242-Heating may cause a fire.
Aquatic Chronic	1	H410-Very toxic to aquatic life with long lasting effects.

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



### Warning

H319-Causes serious eye irritation. H317-May cause an allergic skin reaction. H242-Heating may cause a fire. H410-Very toxic to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234-Keep only in original packaging. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.

P314-Get medical advice / attention if you feel unwell.

P235-Keep cool. P403-Store in a well-ventilated place. P411-Store at temperatures not exceeding 30 °C.

Dibenzoyl peroxide

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Dibenzoyl peroxide</b>	
<b>Registration number (REACH)</b>	01-2119511472-50-XXXX

GB

Page 3 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

<b>Index</b>	617-008-00-0
<b>EINECS, ELINCS, NLP</b>	202-327-6
<b>CAS</b>	94-36-0
<b>content %</b>	40-60
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Org. Perox. Type B, H241 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

<b>Ethanediol</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119456816-28-XXXX
<b>Index</b>	603-027-00-1
<b>EINECS, ELINCS, NLP</b>	203-473-3
<b>CAS</b>	107-21-1
<b>content %</b>	1-10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 STOT RE 2, H373

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting. Consult doctor immediately.  
 Keep Data Sheet available.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

Page 4 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Water jet spray

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Benzoic acid

Benzene

Toxic gases

Can have a fire-promoting (oxidizing) effect due to oxygen release.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Use no flammable substances.

Fill the absorbed material into lockable containers.

Keep moist.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

GB

Page 5 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Take precautions against electrostatic charges.  
 Electrical equipment must be suitable for temperature class T 3 (Germany).  
 Avoid inhalation, and contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Once product has been withdrawn it must under no circumstances be poured back into the vessel.  
 Do not pour remainders back into the storage vessels.  
 Keep away from dirt, rust, alkalis, acids and accelerators.  
 Carefully avoid contamination of the product with foreign substances.  
 Avoid drying.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Do not store with highly flammable, flammable, or self-igniting materials.  
 Store upright.  
 Observe regulations for keeping separated.  
 Observe the special regulations for organic peroxides.  
 Protect against moisture and store closed.  
 Only store at temperatures from 5°C to 25°C.  
 Protect from direct sunlight and warming.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Dibenzoyl peroxide		Content %: 40-60
WEL-TWA: 5 mg/m <sup>3</sup>	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

Chemical Name	Ethanediol		Content %: 1-10
WEL-TWA: 10 mg/m <sup>3</sup> (particulate), 52 mg/m <sup>3</sup> (vapour) (WEL), 20 ppm (52 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 104 mg/m <sup>3</sup> (vapour) (WEL), 40 ppm (104 mg/m <sup>3</sup> ) (EU)	---	
Monitoring procedures:	- Compur - KITA-232 SA (502 342)		

GB

Page 6 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

- Compur - KITA-232 SB (550 267)
- Draeger - Ethylene Glycol 10 (5) (81 01 351)
- NIOSH 5523 (Glycols) - 1996
- OSHA PV2024 (Ethylene glycol) - 1999 - EU project
- BC/CEN/ENTR/000/2002-16 card 11-2 (2004)
- Draeger - Alcohol 100/a (CH 29 701)

BMGV: ---

Other information: Sk (particulate, vapour)

Chemical Name	Dimethyl phthalate		Content %:
WEL-TWA:	5 mg/m <sup>3</sup>	WEL-STEL:	10 mg/m <sup>3</sup>
Monitoring procedures:		---	
BMGV:	---		Other information: ---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Ethanediol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	199,5	mg/l	
	Environment - sediment, freshwater		PNEC	20,9	mg/kg	
	Environment - soil		PNEC	1,53	mg/kg	
Industrial	Human - inhalation	Long term, local effects	DNEL	35	mg/m <sup>3</sup>	
Industrial	Human - dermal	Long term, systemic effects	DNEL	106	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	7	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	53	mg/m <sup>3</sup>	

**Dimethyl phthalate**

Page 7 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,192	mg/l	
	Environment - marine		PNEC	0,0192	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,39	mg/l	
	Environment - sewage treatment plant		PNEC	4	mg/l	
	Environment - sediment, freshwater		PNEC	1,403	mg/kg	
	Environment - soil		PNEC	3,16	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	60	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	86,96	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	25	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	100	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	293,86	mg/m <sup>3</sup>	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Page 8 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Protective Neoprene® / polychloroprene gloves (EN 374).

Minimum layer thickness in mm:

>= 0,5

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Paste, Solid, Thixotrope
Colour:	Red
Odour:	Slightly
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>50 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined



Page 9 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	~1,1-1,2 g/cm <sup>3</sup> (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble 20°C
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	50 °C (SADT )
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	Not determined

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

May cause fire.

### 10.2 Chemical stability

Degradation from a temperature of 50°C.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur during storage and handling under normal conditions.

### 10.4 Conditions to avoid

Protect from humidity.

Heating, open flame, ignition sources

Decomposition:

SADT = 50°C

### 10.5 Incompatible materials

Contact with incompatible substances can result in decomposition at or below the SADT (Self-Accelerating Decomposition Temperature).

Bases

Acids

Accelerators

Heavy metal salts

Rust

Amines

Iron

Copper

Reducing agent

### 10.6 Hazardous decomposition products

Benzoic acid

Benzene

## SECTION 11: Toxicological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

### Hardener for Polyester Filler 40 g

Art.: 100015

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

### Dibenzoyl peroxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>24,3	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)

GB

Page 11 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

Germ cell mutagenicity:						Negative
Carcinogenicity:	NOAEL	1000	mg/kg			Negative <sup>29d</sup>
Symptoms:						cornea opacity, mucous membrane irritation

**Ethanediol**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7712	mg/kg	Rat	IUCLID Chem. Data Sheet (ESIS)	Does not conform with EU classification
Acute toxicity, by dermal route:	LD50	9530	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>2,5	mg/l/6 h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:				Human being	(Patch-Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, unconsciousness, cramps, fatigue

**Dimethyl phthalate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	6800	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>10000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	9300	mg/m <sup>3</sup>			6,5 h
Skin corrosion/irritation:						Slightly irritant
Serious eye damage/irritation:						Slightly irritant

GB

Page 12 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

Symptoms:							abdominal pain, burning of the membranes of the nose and throat, diarrhoea, coughing, itching, salivation, watering eyes, nausea and vomiting.
-----------	--	--	--	--	--	--	--

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Hardener for Polyester Filler 40 g Art.: 100015							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Page 13 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Other information:								DOC-elimination degree (complexing organic substance) > = 80%/28d: n.a.
--------------------	--	--	--	--	--	--	--	---

Dibenzoyl peroxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,0602	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	0,0316	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,11	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	72h	0,02	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,0711	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,02	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			>60	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		66,6			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.3. Bioaccumulative potential:	Log Pow		3,2			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	

GB

Page 14 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

12.4. Mobility in soil:	Log Koc		3,8			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	
Toxicity to bacteria:	EC50	30min	35	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

**Ethanediol**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales promelas	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to daphnia:	EC50	48h	41100	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	6500-7500	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	IC5	7d	>10000	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-1,36				Not to be expected
Toxicity to bacteria:	EC20	30min	>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

**Dimethyl phthalate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

GB

Page 15 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

12.1. Toxicity to fish:	LC50	96h	>100- <200	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	56	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	330	mg/l			
12.1. Toxicity to algae:	EC50	72h	204	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			>70	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		5,4				
Toxicity to bacteria:	EC50	17h	>300 0	mg/l	Pseudomonas putida		

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number:

3108

Transport by road/by rail (ADR/RID)

GB

Page 16 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

14.2. UN proper shipping name:

UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

Classification code: P1

LQ: 500 g

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: D

**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:

ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

EmS: F-J, S-R

Marine Pollutant: Yes

14.5. Environmental hazards: environmentally hazardous

**Transport by air (IATA)**

14.2. UN proper shipping name:

Organic peroxide type E, solid (DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

Observe incident regulations.

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**



GB

Page 17 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0006  
 Replacing version dated / version: 05.08.2016 / 0005  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 Hardener for Polyester Filler 40 g  
 Art.: 100015

Revised sections: 2, 3, 8, 9, 11, 12, 16

These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.  
 Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Acute 1, H400	Classification according to calculation procedure.
Org. Perox. Type E, H242	Classification according to calculation procedure.
Aquatic Chronic 1, H410	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H241 Heating may cause a fire or explosion.
- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

- Eye Irrit. — Eye irritation
- Skin Sens. — Skin sensitization
- Aquatic Acute — Hazardous to the aquatic environment - acute
- Org. Perox. — Organic peroxide
- Aquatic Chronic — Hazardous to the aquatic environment - chronic
- Acute Tox. — Acute toxicity - oral
- STOT RE — Specific target organ toxicity - repeated exposure

Page 18 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Albert Berner Deutschland GmbH  
Bernerstrasse 4  
D - 74653 Künzelsau  
Tel +49 79 40 12 10  
Fax +49 79 40 12 13 00  
info@berner.de  
www.berner.de

Berner Gesellschaft m.b.H.  
Industriezeile 36  
A - 5280 Braunau / Inn  
Tel +43 77 22 800 508  
Fax +43 77 22 800 184  
berner@berner.co.at  
www.berner.co.at

Berner Belgien NV/SA  
Bernerstraat 1  
B - 3620 Lanaken  
Tel +31 45 533 93 133(8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.be  
www.berner.be

Montagetechnik Berner AG  
Kägenstraße 8  
CH - 4153 Reinach / Bl. 1  
Tel +41 61 71 59 222  
Fax +41 61 71 59 333  
berner-ag@berner-ag.ch  
www.berner-ag.ch

Berner A/S  
Stenholm 2  
DK - 9400 Nørresundby  
Tel +45 99 36 15 00  
Fax +45 98 19 24 14  
info@berner.dk  
www.berner.dk

Berner Montaje y Fijación, S.L.  
P.I. "La Rosa VI"  
C/Albert Berner, 2  
E - 18330 Chauchina-Granada-  
España  
Tel +34 90 21 03 504  
Fax +34 90 21 13 190  
berner-spain@berner.es  
www.berner.es

Berner Kft.  
Táblás u. 34  
H - 1097 Budapest  
Tel +36 (1) 347 1059  
Fax +36 (1) 347 1045  
info@berner.hu  
www.berner.hu

Frimann-Berner AS  
Holmaveien 25  
N - 1339 Vøyenenga  
Tel +47 66 76 55 80  
Fax +47 66 76 55 81  
info@berner.no  
www.berner.no

Berner Succ. Luxembourg  
105, Rue des Bruyères  
L - 1274 Howald  
Tel +31 45 533 93 133 (8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.lu  
www.berner.lu

Berner spol. s r.o.  
Jinonická 80  
CZ - 158 00 Praha 5  
Tel +420 225 390 666  
Fax +420 225 390 660  
berner@berner.cz  
www.berner.cz

Berner,S.A.  
Av. Amália Rodrigues,3510  
Manique de Baixo  
P - 2785-738 São Domingos de Rana  
Tel ++351 21 448 90 60  
Fax ++351 21 448 90 69  
marketing.pt@berner.pt  
www.berner.pt

Berner Polska Sp. z o.o.  
Ul. Puzkarska 7J  
30-644 Kraków  
Tel +48 12 297 62 40  
Fax +48 12 297 62 02  
office@berner.pl  
www.berner.pl

Albert Berner UAB  
Kalvarijø 29B, LT09313,  
Vilnius, Lithuania  
Tel +370-52104355  
Fax +370-52350020  
info@berner.lt

Berner SK  
Berner s r.o.  
Jesenského 1  
SK - 962 12 Detva  
Tel (+421) 45 5410 245  
Fax (+421) 45 5410 255  
berner@berner.sk  
www.berner.sk

Albert Berner Montagetechnik AB  
Elektravägen 53  
S - 126 30 Hägersten  
Tel +46 85 78 77 800  
Fax +46 85 78 77 805  
info@berner.se  
www.berner.se

Page 19 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

Berner Pultti Oy  
Volltikatu 6  
FI - 70700 Kuopio  
Tel +358-207-590 220  
Fax +358-207-590 221  
kuopio@berner-pultti.com  
www.berner-pultti.com

Mitras d.o.o  
Brdnikova ulica 34e  
SL-1000 Ljubljana  
Tel +386-1-256-62-46  
Fax +386-1-256-62-45  
mitras@siol.com

BERNER d.o.o  
CPM Savčica Šanci  
Trgovačka 2  
HR - 10000 Zagreb  
Tel +38512 499 470  
Fax +38512 499 480  
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler  
Sanayi ve Ticaret A.Ş.  
Ferhatpaşa Mah. G 7 Sok. 31/2  
TR - 34858 Kartal-Samandıra /  
İSTANBUL  
Tel +90 (0) 216-4713077  
Fax +90 (0) 216-4719625  
info@berner.com.tr  
www.berner.com.tr

Berner S.p.A.  
Via dell 'Elettronica 15  
I - 37139 Verona  
Tel +39 04 58 67 01 11  
Fax +39 04 58 67 01 34  
info@berner.it  
www.berner.it

Albert Berner srl  
Str. Vrancei Nr. 51 - 55  
RO - 310315 Arad  
Tel +40 257 212291  
Fax +40 257 250460  
office@berner-romania.ro  
www.berner-romania.ro

Berner Produkten b.v.  
Vogelzankweg 175  
NL - 6374 AC Landgraaf  
+31 45 53 39 133 (8.00h-16.00h)  
+31 6 290 27 464 (16.00h-8.00h)  
info@berner.nl  
www.berner.nl

Berner s.a.r.l.  
ZI Les Manteaux  
F - 89331 Saint-Julien-du-Sault Cedex  
Tel +33 38 69 94 400  
Fax +33 38 69 94 444  
contact@berner.fr  
www.berner.fr

Albert Berner SIA  
Liliju 20, Marupe, Mārupes novads,  
LV-2167, Latvija  
Tel +37167840007  
Fax +371678440008  
info@berner.lv

(c) COPYRIGHT 1987 - 2050 ALL  
RIGHTS RESERVED

### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

Page 20 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)  
BMGV Biological monitoring guidance value (EH40, UK)  
BOD Biochemical oxygen demand  
BSEF Bromine Science and Environmental Forum  
bw body weight  
CAS Chemical Abstracts Service  
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
CIPAC Collaborative International Pesticides Analytical Council  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
COD Chemical oxygen demand  
CTFA Cosmetic, Toiletry, and Fragrance Association  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
DT50 Dwell Time - 50% reduction of start concentration  
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEA European Economic Area  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ERC Environmental Release Categories  
ES Exposure scenario  
etc. et cetera  
EU European Union  
EWC European Waste Catalogue  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
HGWP Halocarbon Global Warming Potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC Intermediate Bulk Container  
IBC (Code) International Bulk Chemical (Code)  
IC Inhibitory concentration  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LC lethal concentration  
LC50 lethal concentration 50 percent kill

Page 21 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

GB

Page 22 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0006

Replacing version dated / version: 05.08.2016 / 0005

Valid from: 07.03.2017

PDF print date: 15.04.2017

Hardener for Polyester Filler 40 g

Art.: 100015

---

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.