

GB

Page 1 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 05.09.2019 / 0005  
Replacing version dated / version: 16.07.2019 / 0004  
Valid from: 05.09.2019  
PDF print date: 06.09.2019  
Adhesive grease spray 400 ml  
Art.: 143656

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Adhesive grease spray 400 ml**  
**Art.: 143656**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

Berner Produkten b.v., Vogelzankweg 175, 6374 AC Landgraaf, Netherlands  
Phone: +31 45 53 39 133, Fax: +31 45 53 14 588  
info@berner.nl, www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

**Hazard class   Hazard category   Hazard statement**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.  
 P273-Avoid release to the environment. P280-Wear protective gloves.  
 P332+P313-If skin irritation occurs: Get medical advice / attention.  
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C6, isoalkanes, <5% n-hexane  
 Paraffin oils (petroleum), catalytic dewaxed heavy

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>	
<b>Registration number (REACH)</b>	01-2119484651-34-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	931-254-9 (REACH-IT List-No.)
<b>CAS</b>	(64742-49-0)
<b>content %</b>	10-<20
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

<b>Paraffin oils (petroleum), catalytic dewaxed heavy</b>	
<b>Registration number (REACH)</b>	01-2119487080-42-XXXX
<b>Index</b>	649-477-00-2
<b>EINECS, ELINCS, NLP</b>	265-174-4
<b>CAS</b>	64742-70-7
<b>content %</b>	1-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

Thinners

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Page 4 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Inhalation:

Irritation of the respiratory tract

Headaches

Dizziness

Nausea

Effects/damages the central nervous system

Unconsciousness

Liver and kidney damage

Skin contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Skin resorption

Ingestion:

Irritation of the mouth and throat

Gastrointestinal disturbances

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Foam

Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Oxides of phosphorus

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Page 5 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Use no flammable substances.

Unsuitable cleaning product:

Solvents

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Avoid inhalation of the vapours.

Ensure good ventilation.

Do not use the product in enclosed spaces.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Take explosion-prevention measures if applicable.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

GB

Page 6 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Observe special regulations for aerosols!  
 Do not store with flammable or self-igniting materials.  
 Solvent resistant floor  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Observe special storage conditions.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane		Content %: 10-<20
WEL-TWA:	800 mg/m <sup>3</sup>	WEL-STEL:	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>		
BMGV:	---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Butane		Content %:
WEL-TWA:	600 ppm (1450 mg/m <sup>3</sup> )	WEL-STEL:	750 ppm (1810 mg/m <sup>3</sup> )
Monitoring procedures:	- Compur - KITA-221 SA (549 459)		
BMGV:	---	Other information: ---	

Chemical Name	Propane		Content %:
WEL-TWA:	1000 ppm (ACGIH)	WEL-STEL:	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)		
BMGV:	---	Other information: ---	

Chemical Name	Dimethoxymethane		Content %:
WEL-TWA:	1000 ppm (3160 mg/m <sup>3</sup> )	WEL-STEL:	1250 ppm (3950 mg/m <sup>3</sup> )
Monitoring procedures:	---		
BMGV:	---	Other information: ---	

Chemical Name	Isobutane		Content %:
WEL-TWA:	1000 ppm (EX) (ACGIH)	WEL-STEL:	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)		
BMGV:	---	Other information: ---	

**Hydrocarbons, C<sub>6</sub>, isoalkanes, <5% n-hexane**

GB

Page 7 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

Dimethoxymethane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - water		PNEC	14,577	mg/l	
	Environment - sediment, marine		PNEC	1,4577	mg/l	
	Environment - sediment, freshwater		PNEC	13,135	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1,3135	mg/kg dry weight	
	Environment - soil		PNEC	4,6538	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	10000	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	9,6	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	39	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,7	mg/kg body weight/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	22	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	132	mg/m3	

GB

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted

Page 8 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

Protective gloves made of polyvinyl alcohol (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

240

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:



Page 9 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	55 °C
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	<1 (relative density )
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	200 °C
Decomposition temperature:	200 °C
Viscosity:	Not determined
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

Electrostatic charge

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Adhesive grease spray 400 ml

Art.: 143656

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.

GB

Page 11 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

**Hydrocarbons, C6, isoalkanes, <5% n-hexane**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

**Butane**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

GB

Page 12 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

GB

Page 13 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Dimethoxymethane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	6423	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	57	mg/l	Mouse	OECD 403 (Acute Inhalation Toxicity)	
Acute toxicity, by inhalation:	LOAEL	1000	mg/l/6 h	Rat		Vapours
Acute toxicity, by inhalation:	NOAEL	2000	mg/l/6 h	Rat		Vapours
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No
Symptoms:						acidosis, respiratory distress, drowsiness, unconsciousness, diarrhoea, coughing, headaches, drowsiness, mucous membrane irritation, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

GB

Page 14 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Aspiration hazard:							No
Symptoms:							unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

### SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

#### Adhesive grease spray 400 ml Art.: 143656

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

#### Hydrocarbons, C6, isoalkanes, <5% n-hexane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	48h	>1	mg/l	Oryzias latipes		Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	31,9	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	30	mg/l	Raphidocelis subcapitata		

GB

Page 15 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

12.1. Toxicity to algae:	ErC50	72h	55	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchneriella subcapitata	QSAR	
12.2. Persistence and degradability:		28d	98	%			Readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential:	Log Kow		4				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Butane**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Propane**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

GB

Page 16 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

Dimethoxymethane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	6990	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC10	96h	>500	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:			>80	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0				
Toxicity to bacteria:	EC10	17h	3000	mg/l	Pseudomonas putida		
Water solubility:			32,3	%			

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be



Page 17 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

allocated under certain circumstances. (2014/955/EU)  
 16 05 04 gases in pressure containers (including halons) containing hazardous substances  
 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Take full aerosol cans to problem waste collection.  
 Take emptied aerosol cans to valuable material collection.  
**For contaminated packing material**  
 Pay attention to local and national official regulations.  
 Recommendation:  
 Do not perforate, cut up or weld uncleaned container.  
 15 01 04 metallic packaging

## SECTION 14: Transport information


### General statements

14.1. UN number: 1950

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U


Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

Page 18 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 05.09.2019 / 0005  
 Replacing version dated / version: 16.07.2019 / 0004  
 Valid from: 05.09.2019  
 PDF print date: 06.09.2019  
 Adhesive grease spray 400 ml  
 Art.: 143656

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 73,02 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Albert Berner Deutschland GmbH  
Bernerstrasse 4  
D - 74653 Künzelsau  
Tel +49 79 40 12 10  
Fax +49 79 40 12 13 00  
info@berner.de  
www.berner.de

Berner Gesellschaft m.b.H.  
Industriezeile 36  
A - 5280 Braunau / Inn  
Tel +43 77 22 800 508  
Fax +43 77 22 800 184  
berner@berner.co.at  
www.berner.co.at

Berner Belgien NV/SA  
Bernerstraat 1  
B - 3620 Lanaken  
Tel +31 45 533 93 133(8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.be  
www.berner.be

Page 20 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

Montageteknik Berner AG  
Kägenstraße 8  
CH - 4153 Reinach / Bl. 1  
Tel +41 61 71 59 222  
Fax +41 61 71 59 333  
berner-ag@berner-ag.ch  
www.berner-ag.ch

Berner A/S  
Stenholm 2  
DK - 9400 Nørresundby  
Tel +45 99 36 15 00  
Fax +45 98 19 24 14  
info@berner.dk  
www.berner.dk

Berner Montaje y Fijación, S.L.  
P.I. "La Rosa VI"  
C/Albert Berner, 2  
E - 18330 Chauchina-Granada-  
España  
Tel +34 90 21 03 504  
Fax +34 90 21 13 190  
berner-spain@berner.es  
www.berner.es

Berner Kft.  
Gubacsi út 6/b  
H - 1097 Budapest  
Tel +36 (1) 347 1059  
Fax +36 (1) 347 1045  
info@berner.hu  
www.berner.hu

Frimann-Berner AS  
Holmaveien 25  
N - 1339 Vøyenenga  
Tel +47 66 76 55 80  
Fax +47 66 76 55 81  
info@berner.no  
www.berner.no

Berner Succ. Luxembourg  
105, Rue des Bruyères  
L - 1274 Howald  
Tel +31 45 533 93 133 (8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.lu  
www.berner.lu

Berner spol. s r.o.  
Jinonická 80  
CZ - 158 00 Praha 5  
Tel +420 225 390 666  
Fax +420 225 390 660  
berner@berner.cz  
www.berner.cz

Berner, S.A.  
Av. Amália Rodrigues, 3510  
Manique de Baixo  
P - 2785-738 São Domingos de Rana  
Tel ++351 21 448 90 60  
Fax ++351 21 448 90 69  
marketing@berner.pt  
www.berner.pt

Berner Polska Sp. z o.o.  
Ul. Puzkarska 7J  
30-644 Kraków  
Tel +48 12 297 62 40  
Fax +48 12 297 62 02  
office@berner.pl  
www.berner.pl

Albert Berner UAB  
Kalvarijø 29B, LT09313,  
Vilnius, Lithuania  
Tel +370-52104355  
Fax +370-52350020  
info@berner.lt

Berner SK  
Berner s r.o.  
Jesenského 1  
SK - 962 12 Detva  
Tel (+421) 45 5410 245  
Fax (+421) 45 5410 255  
berner@berner.sk  
www.berner.sk

Albert Berner Montageteknik AB  
Elektravägen 53  
S - 126 30 Hägersten  
Tel +46 85 78 77 800  
Fax +46 85 78 77 805  
info@berner.se  
www.berner.se

Tarfi Oy  
Äyritie 8D  
01510 Vantaa, Suomi  
Tel: 0207 590  
220/Asiakaspalvelukeskus  
asiakaspalvelu@tarfi.fi  
www.tarfi.fi

Mitras d.o.o  
Brdnikova ulica 34e  
SL-1000 Ljubljana  
Tel +386-1-256-62-46  
Fax +386-1-256-62-45  
mitras@siol.com

BERNER d.o.o  
CPM Savčica Šanci  
Trgovačka 2  
HR - 10000 Zagreb  
Tel +38512 499 470  
Fax +38512 499 480  
e-mail: safetydata-hr@berner.co.at

Page 21 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

Berner Endüstriyel Ürünler  
Sanayi ve Ticaret A.Ş.  
Ferhatpaşa Mah. G 7 Sok. 31/2  
TR - 34858 Kartal-Samandıra /  
İSTANBUL  
Tel +90 (0) 216-4713077  
Fax +90 (0) 216-4719625  
info@berner.com.tr

Berner S.p.A.  
Via dell 'Elettronica 15  
I - 37139 Verona  
Tel +39 04 58 67 01 11  
Fax +39 04 58 67 01 34  
info@berner.it  
www.berner.it

Albert Berner srl  
Str. Vrancei Nr. 51 - 55  
RO - 310315 Arad  
Tel +40 257 212291  
Fax +40 257 250460  
office@berner-romania.ro  
www.berner-romania.ro

Berner Produkten b.v.  
Vogelzankweg 175  
NL - 6374 AC Landgraaf  
+31 45 53 39 133 (8.00h-16.00h)  
+31 6 290 27 464 (16.00h-8.00h)  
info@berner.nl  
www.berner.nl

Berner s.a.r.l.  
ZI Les Manteaux  
F - 89331 Saint-Julien-du-Sault Cedex  
Tel +33 38 69 94 400  
Fax +33 38 69 94 444  
contact@berner.fr  
www.berner.fr

Albert Berner SIA  
Liliju 20, Marupe, Mārupes novads,  
LV-2167, Latvija  
Tel +37167840007  
Fax +371678440008  
info@berner.lv

(c) COPYRIGHT 1987 - 2050 ALL  
RIGHTS RESERVED

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

Page 22 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.09.2019 / 0005

Replacing version dated / version: 16.07.2019 / 0004

Valid from: 05.09.2019

PDF print date: 06.09.2019

Adhesive grease spray 400 ml

Art.: 143656

EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.