

GB

Page 1 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0003  
Replacing version dated / version: 05.08.2016 / 0002  
Valid from: 07.03.2017  
PDF print date: 15.04.2017  
SUPERGLUE GEL 20 g  
Art.: 243426

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**SUPERGLUE GEL 20 g**  
**Art.: 243426**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC10 - Roller application or brushing

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC99 - Not required.

Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

NL

Berner Produkten b.v., Vogelzankweg 175, 6374 AC Landgraaf, Netherlands  
Phone: +31 45 53 39 133, Fax: +31 45 53 14 588  
info@berner.nl, www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

Emergency information services / official advisory body:

---

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

**Hazard class**    **Hazard category**    **Hazard statement**

Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.

### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Warning

H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation.

P261-Avoid breathing vapours or spray. P280-Wear protective gloves and eye protection / face protection.  
P312-Call a POISON CENTRE / doctor if you feel unwell.

EUH202-Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Ethyl 2-cyanoacrylate

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 05.08.2016 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 SUPERGLUE GEL 20 g  
 Art.: 243426

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Ethyl 2-cyanoacrylate</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	607-236-00-9
<b>EINECS, ELINCS, NLP</b>	230-391-5
<b>CAS</b>	7085-85-0
<b>content %</b>	80-100
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap. Call a doctor immediately, keep datasheet at hand  
 If the skin is glued:  
 Do not attempt to force glued areas of skin apart.

#### Eye contact

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting.  
 Call doctor immediately - have Data Sheet available.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:  
 Allergic reaction possible.

Asthmatic symptoms  
 May cause sensitisation by inhalation.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

Page 4 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0003  
Replacing version dated / version: 05.08.2016 / 0002  
Valid from: 07.03.2017  
PDF print date: 15.04.2017  
SUPERGLUE GEL 20 g  
Art.: 243426

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>

Water jet spray

Extinction powder

Foam

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Toxic gases

Oxides of carbon

Oxides of nitrogen

Toxic pyrolysis products.

Traces possible:

Hydrogen cyanide

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Flush residue using copious water.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

GB

Page 5 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 05.08.2016 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 SUPERGLUE GEL 20 g  
 Art.: 243426

Keep away from sources of ignition - Do not smoke.  
 Handle and open container with care.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.  
 During processing:

Ambient humidity should be increased to at least 50-60% relative humidity.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with alkalis.

Do not store with acids.

Do not store with oxidizing agents.

Protect from direct sunlight and warming.

Recommended storage temperature:

2 - 8°C

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Ethyl 2-cyanoacrylate	Content %:	80-100
WEL-TWA: ---	WEL-STEL: 0,3 ppm (1,5 mg/m3)	---	
Monitoring procedures: ---			
BMGV: ---	Other information: ---		

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Ethyl 2-cyanoacrylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	9,25	mg/m3	

GB

Page 6 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 05.08.2016 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 SUPERGLUE GEL 20 g  
 Art.: 243426

Consumer	Human - inhalation	Long term, local effects	DNEL	9,25	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	9,25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	9,25	mg/m3	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Polyethylene

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

GB

Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless, Transparent
Odour:	Penetrating
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	-31 °C
Initial boiling point and boiling range:	>200 °C
Flash point:	82-83 °C (closed cup)
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	≤21 Pa
Vapour density (air = 1):	Not determined
Density:	1,04-1,07 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Acetone
Water solubility:	reacts with water, Insoluble
Partition coefficient (n-octanol/water):	0,776
Auto-ignition temperature:	480 °C
Decomposition temperature:	75 °C
Viscosity:	2,6 mPas (20°C, Not determined )
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

In case of contact with water:

Polymerisation possible

### 10.4 Conditions to avoid

See also section 7.

Protect from humidity.

Heating, open flame, ignition sources

### 10.5 Incompatible materials

See also section 7.

Do not bring into contact with water.

Polymerisation possible

Violent reaction with:

Water

Bases

Acids

Oxidizing agents

Amines

Alcohols

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### SUPERGLUE GEL 20 g

Art.: 243426

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.



GB

Page 9 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 05.08.2016 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 SUPERGLUE GEL 20 g  
 Art.: 243426

Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

<b>Ethyl 2-cyanoacrylate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Mild irritant
Skin corrosion/irritation:		24	h	Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Serious eye damage/irritation:		72	h	Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Symptoms:						respiratory distress, coughing, mucous membrane irritation, watering eyes

GB

Page 10 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 05.08.2016 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 15.04.2017  
 SUPERGLUE GEL 20 g  
 Art.: 243426

Specific target organ toxicity - single exposure (STOT-SE), inhalative:							STOT SE 3, H335
---	--	--	--	--	--	--	-----------------

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

<b>SUPERGLUE GEL 20 g</b>							
<b>Art.: 243426</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Page 11 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2,16

These details refer to the product as it is delivered.

Page 12 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0003  
Replacing version dated / version: 05.08.2016 / 0002  
Valid from: 07.03.2017  
PDF print date: 15.04.2017  
SUPERGLUE GEL 20 g  
Art.: 243426

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

<b>Classification in accordance with regulation (EC) No. 1272/2008 (CLP)</b>	<b>Evaluation method used</b>
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Albert Berner Deutschland GmbH  
Bernerstrasse 4  
D - 74653 Künzelsau  
Tel +49 79 40 12 10  
Fax +49 79 40 12 13 00  
info@berner.de  
www.berner.de

Berner Gesellschaft m.b.H.  
Industriezeile 36  
A - 5280 Braunau / Inn  
Tel +43 77 22 800 508  
Fax +43 77 22 800 184  
berner@berner.co.at  
www.berner.co.at

Berner Belgien NV/SA  
Bernerstraat 1  
B - 3620 Lanaken  
Tel +31 45 533 93 133(8.00h-16.00h)  
Tel +31 6 290 27 464 (16.00h-8.00h)  
Fax +31 455 33 92 43  
info@berner.be  
www.berner.be

Montagetechnik Berner AG  
Kägenstraße 8  
CH - 4153 Reinach / Bl. 1  
Tel +41 61 71 59 222  
Fax +41 61 71 59 333  
berner-ag@berner-ag.ch  
www.berner-ag.ch

Berner A/S  
Stenholm 2  
DK - 9400 Nørresundby  
Tel +45 99 36 15 00  
Fax +45 98 19 24 14  
info@berner.dk  
www.berner.dk

Berner Montaje y Fijación, S.L.  
P.I. "La Rosa VI"  
C/Albert Berner, 2  
E - 18330 Chauchina-Granada-España  
Tel +34 90 21 03 504  
Fax +34 90 21 13 190  
berner-spain@berner.es  
www.berner.es

Page 13 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

Berner Kft.  
Táblás u. 34  
H - 1097 Budapest  
Tel +36 (1) 347 1059  
Fax +36 (1) 347 1045  
info@berner.hu  
www.berner.hu

Frimann-Berner AS  
Holmaveien 25  
N - 1339 Vøyenenga  
Tel +47 66 76 55 80  
Fax +47 66 76 55 81  
info@berner.no  
www.berner.no

Berner Succ. Luxembourg  
105, Rue des Bruyères  
L - 1274 Howald  
Tel +31 45 533 93 133 (8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.lu  
www.berner.lu

Berner spol. s r.o.  
Jinonická 80  
CZ - 158 00 Praha 5  
Tel +420 225 390 666  
Fax +420 225 390 660  
berner@berner.cz  
www.berner.cz

Berner,S.A.  
Av. Amália Rodrigues,3510  
Manique de Baixo  
P - 2785-738 São Domingos de Rana  
Tel ++351 21 448 90 60  
Fax ++351 21 448 90 69  
marketing.pt@berner.pt  
www.berner.pt

Berner Polska Sp. z o.o.  
Ul. Puzkarska 7J  
30-644 Kraków  
Tel +48 12 297 62 40  
Fax +48 12 297 62 02  
office@berner.pl  
www.berner.pl

Albert Berner UAB  
Kalvarijø 29B, LT09313,  
Vilnius, Lithuania  
Tel +370-52104355  
Fax +370-52350020  
info@berner.lt

Berner SK  
Berner s r.o.  
Jesenského 1  
SK - 962 12 Detva  
Tel (+421) 45 5410 245  
Fax (+421) 45 5410 255  
berner@berner.sk  
www.berner.sk

Albert Berner Montagetechnik AB  
Elektravägen 53  
S - 126 30 Hägersten  
Tel +46 85 78 77 800  
Fax +46 85 78 77 805  
info@berner.se  
www.berner.se

Berner Pultti Oy  
Volltikatu 6  
FI - 70700 Kuopio  
Tel +358-207-590 220  
Fax +358-207-590 221  
kuopio@berner-pultti.com  
www.berner-pultti.com

Mitras d.o.o  
Brdnikova ulica 34e  
SL-1000 Ljubljana  
Tel +386-1-256-62-46  
Fax +386-1-256-62-45  
mitras@siol.com

BERNER d.o.o  
CPM Savëca Šanci  
Trgovačka 2  
HR - 10000 Zagreb  
Tel +38512 499 470  
Fax +38512 499 480  
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler  
Sanayi ve Ticaret A.Ş.  
Ferhatpaşa Mah. G 7 Sok. 31/2  
TR - 34858 Kartal-Samandıra /  
ÝSTANBUL  
Tel +90 (0) 216-4713077  
Fax +90 (0) 216-4719625  
info@berner.com.tr  
www.berner.com.tr

Berner S.p.A.  
Via dell 'Elettronica 15  
I - 37139 Verona  
Tel +39 04 58 67 01 11  
Fax +39 04 58 67 01 34  
info@berner.it  
www.berner.it

Albert Berner srl  
Str. Vrancei Nr. 51 - 55  
RO - 310315 Arad  
Tel +40 257 212291  
Fax +40 257 250460  
office@berner-romania.ro  
www.berner-romania.ro

Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

Berner Produkten b.v.

Vogelzankweg 175

NL - 6374 AC Landgraaf

+31 45 53 39 133 (8.00h-16.00h)

+31 6 290 27 464 (16.00h-8.00h)

info@berner.nl

Berner s.a.r.l.

ZI Les Manteaux

F - 89331 Saint-Julien-du-Sault

Cedex

Tel +33 38 69 94 400

Fax +33 38 69 94 444

Albert Berner SIA

Liliju 20, Marupe, Mārupes

novads,

LV-2167, Latvija

Tel +37167840007

Fax +371678440008

(c) COPYRIGHT 1987 - 2050 ALL RIGHTS RESERVED

### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

Page 15 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 05.08.2016 / 0002

Valid from: 07.03.2017

PDF print date: 15.04.2017

SUPERGLUE GEL 20 g

Art.: 243426

org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.