

GB

Page 1 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 16.01.2018 / 0001  
Replacing version dated / version: 16.01.2018 / 0001  
Valid from: 16.01.2018  
PDF print date: 18.01.2018  
WINDSCREEN ADHESIVE SAFE 400 ml  
Art.: 358546

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**WINDSCREEN ADHESIVE SAFE 400 ml**  
**Art.: 358546**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

Berner Produkten b.v., Vogelzankweg 175, 6374 AC Landgraaf, Netherlands  
Phone: +31 45 53 39 133, Fax: +31 45 53 14 588  
info@berner.nl, www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

**Hazard class    Hazard category    Hazard statement**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Resp. Sens. 1 H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.

P261-Avoid breathing vapours or spray. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342+P311-If experiencing respiratory symptoms: Call a POISON CENTER / doctor.

EUH204-Contains isocyanates. May produce an allergic reaction.

4,4'-methylenediphenyl diisocyanate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

**SECTION 3: Composition/information on ingredients**

3.1 Substance

n.a.

3.2 Mixture

<b>4,4'-methylenediphenyl diisocyanate</b>	
<b>Registration number (REACH)</b>	01-2119457014-47-XXXX
<b>Index</b>	615-005-00-9
<b>EINECS, ELINCS, NLP</b>	202-966-0
<b>CAS</b>	101-68-8
<b>content %</b>	0,1-<1

Page 3 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 16.01.2018 / 0001  
Replacing version dated / version: 16.01.2018 / 0001  
Valid from: 16.01.2018  
PDF print date: 18.01.2018  
WINDSCREEN ADHESIVE SAFE 400 ml  
Art.: 358546

**Classification according to Regulation (EC)  
1272/2008 (CLP)**

Carc. 2, H351  
Acute Tox. 4, H332  
STOT RE 2, H373  
Eye Irrit. 2, H319  
STOT SE 3, H335  
Skin Irrit. 2, H315  
Resp. Sens. 1, H334  
Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Consult doctor immediately - keep Data Sheet available.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Adapt to the nature and extent of fire.  
Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

GB

Page 4 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

None known

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

## 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

GB

Page 5 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Only store at temperatures from > 0°C to < 35°C.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	4,4'-methylenediphenyl diisocyanate		Content %: 0,1-<1
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	
Monitoring procedures:	ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2001 - MDHS 25/3 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1- methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 1999 - EU project BC/CEN/ENTR/000/2002-16 card 7-4 (2004)		
BMGV: 1 µmol urinary diamine/mol creatinine in urine (Isocyanate, post task)	Other information: Sen (Isocyanates, all (as -NCO))		
Chemical Name	Carbon black		Content %:
WEL-TWA: 3,5 mg/m3	WEL-STEL: 7 mg/m3	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	Diisononyl phthalate		Content %:
WEL-TWA: 5 mg/m3	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

### 8.2 Exposure controls

4,4'-methylenediphenyl diisocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note

GB

Page 6 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

**Diisononyl phthalate**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	

Page 7 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m3	

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 With danger of contact with eyes.  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 Recommended  
 Protective nitrile gloves (EN 374)  
 Minimum layer thickness in mm:  
 >=0,4  
 Permeation time (penetration time) in minutes:  
 >480  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Gas mask filter A (EN 14387), code colour brown  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.

Page 8 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	Black
Odour:	Not determined
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	270 °C
Flash point:	164 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	0,4 Vol-%
Upper explosive limit:	2,9 Vol-%
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,14 g/cm <sup>3</sup> (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	>300 °C (Ignition temperature )
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	0,0 % (Organic solvents )

## SECTION 10: Stability and reactivity



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

None known

### 10.5 Incompatible materials

See also section 7.

None known

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

GB

Page 10 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

**4,4'-methylenediphenyl diisocyanate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>2,24	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	0,368	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Does not conform with EU classification
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (inhalation and skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.

GB

Page 11 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Symptoms:						respiratory distress, coughing, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract, Target organ(s): respiratory system

**Carbon black**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3000	mg/kg			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Mouse		Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	0,0011	mg/l			References, Target organ(s): lung90d
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	137	mg/kg	Mouse		

GB

Page 12 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	52	mg/kg	Rat		
---	-------	----	-------	-----	--	--

<b>Diisononyl phthalate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4 h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:				Mammalian		No indications of such an effect.
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:						No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Symptoms:						diarrhoea, nausea and vomiting.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

**WINDSCREEN ADHESIVE SAFE 400 ml**  
**Art.: 358546**

<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
--------------------------	-----------------	-------------	--------------	-------------	-----------------	--------------------	--------------

GB

Page 13 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							DOC-elimination degree(comp lexing organic substance) > = 80%/28d: n.a.
Other information:							According to the recipe, contains no AOX.

**4,4'-methylenediphenyl diisocyanate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100 0	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC0	96h	>100 0	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>100 0	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	1,5	mg/l		OECD 201 (Alga, Growth Inhibition Test)	

GB

Page 14 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

12.1. Toxicity to algae:	EC50	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO <sub>2</sub> into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and non-degradable.

Page 15 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

12.2. Persistence and degradability:	BOD	28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO <sub>2</sub> into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and non-degradable.
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	Log Pow		5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

GB

Page 16 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

**Carbon black**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>5600	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	3d	10000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not biodegradable, Insoluble
12.3. Bioaccumulative potential:							Not to be expected



GB

Page 17 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Toxicity to bacteria:	EC0	3h	>=80 0	mg/l	activated sludge	Regulation (EC) 440/2008 C.22 (SOIL MICROORGANISMS - CARBON TRANSFORMATION TEST)	
-----------------------	-----	----	-----------	------	------------------	--	--

**Diisononyl phthalate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>102	mg/l	Brachydanio rerio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>74	mg/l	Daphnia magna	92/69/EC	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>101	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	88	mg/l	Scenedesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	>88	mg/l	Scenedesmus subspicatus	84/449/EEC C.3	
12.2. Persistence and degradability:		28d	81	%	activated sludge	Regulation (EC) 440/2008 C.4-C (DETERMINATION OF 'READY' BIODEGRADABILITY - CO2 EVOLUTION TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		8,8-10,7				calculated value
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,00000149	atm*m <sup>3</sup> /mol			

GB

Page 18 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	56d	>982,4	mg/kg	Eisenia foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

##### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

### SECTION 14: Transport information

#### General statements

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 16.01.2018 / 0001  
 Replacing version dated / version: 16.01.2018 / 0001  
 Valid from: 16.01.2018  
 PDF print date: 18.01.2018  
 WINDSCREEN ADHESIVE SAFE 400 ml  
 Art.: 358546

**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

**Transport by air (IATA)**

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**  
 Non-dangerous material according to Transport Regulations.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Regulation (EC) No 1907/2006, Annex XVII  
 4,4'-methylenediphenyl diisocyanate  
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0,00 %

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

Revised sections: n.a.

These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

**Classification in accordance with regulation (EC) No. 1272/2008 (CLP)**

**Evaluation method used**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

Resp. Sens. 1, H334

Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Resp. Sens. — Respiratory sensitization

Carc. — Carcinogenicity

Acute Tox. — Acute toxicity - inhalation

STOT RE — Specific target organ toxicity - repeated exposure

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Albert Berner Deutschland GmbH  
Bernerstrasse 4  
D - 74653 Künzelsau  
Tel +49 79 40 12 10  
Fax +49 79 40 12 13 00  
info@berner.de  
www.berner.de

Berner Gesellschaft m.b.H.  
Industriezeile 36  
A - 5280 Braunau / Inn  
Tel +43 77 22 800 508  
Fax +43 77 22 800 184  
berner@berner.co.at  
www.berner.co.at

Berner Belgien NV/SA  
Bernerstraat 1  
B - 3620 Lanaken  
Tel +31 45 533 93 133(8.00h-16.00h)  
Tel +31 6 290 27 464 (16.00h-8.00h)  
Fax +31 455 33 92 43  
info@berner.be  
www.berner.be

Montagetechnik Berner AG  
Kägenstraße 8  
CH - 4153 Reinach / Bl. 1  
Tel +41 61 71 59 222  
Fax +41 61 71 59 333  
berner-ag@berner-ag.ch  
www.berner-ag.ch

Berner A/S  
Stenholm 2  
DK - 9400 Nørresundby  
Tel +45 99 36 15 00  
Fax +45 98 19 24 14  
info@berner.dk  
www.berner.dk

Berner Montaje y Fijación, S.L.  
P.I. "La Rosa VI"  
C/Albert Berner, 2  
E - 18330 Chauchina-Granada-España  
Tel +34 90 21 03 504  
Fax +34 90 21 13 190  
berner-spain@berner.es  
www.berner.es

Page 21 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

Berner Kft.  
Táblás u. 34  
H - 1097 Budapest  
Tel +36 (1) 347 1059  
Fax +36 (1) 347 1045  
info@berner.hu  
www.berner.hu

Frimann-Berner AS  
Holmaveien 25  
N - 1339 Vøyenenga  
Tel +47 66 76 55 80  
Fax +47 66 76 55 81  
info@berner.no  
www.berner.no

Berner Succ. Luxembourg  
105, Rue des Bruyères  
L - 1274 Howald  
Tel +31 45 533 93 133 (8.00h-  
16.00h)  
Tel +31 6 290 27 464 (16.00h-  
8.00h)  
Fax +31 455 33 92 43  
info@berner.lu  
www.berner.lu

Berner spol. s r.o.  
Jinonická 80  
CZ - 158 00 Praha 5  
Tel +420 225 390 666  
Fax +420 225 390 660  
berner@berner.cz  
www.berner.cz

Berner,S.A.  
Av. Amália Rodrigues,3510  
Manique de Baixo  
P - 2785-738 São Domingos de Rana  
Tel ++351 21 448 90 60  
Fax ++351 21 448 90 69  
marketing.pt@berner.pt  
www.berner.pt

Berner Polska Sp. z o.o.  
Ul. Puzkarska 7J  
30-644 Kraków  
Tel +48 12 297 62 40  
Fax +48 12 297 62 02  
office@berner.pl  
www.berner.pl

Albert Berner UAB  
Kalvarijø 29B, LT09313,  
Vilnius, Lithuania  
Tel +370-52104355  
Fax +370-52350020  
info@berner.lt

Berner SK  
Berner s r.o.  
Jesenského 1  
SK - 962 12 Detva  
Tel (+421) 45 5410 245  
Fax (+421) 45 5410 255  
berner@berner.sk  
www.berner.sk

Albert Berner Montagetechnik AB  
Elektravägen 53  
S - 126 30 Hägersten  
Tel +46 85 78 77 800  
Fax +46 85 78 77 805  
info@berner.se  
www.berner.se

Berner Pultti Oy  
Volltikatu 6  
FI - 70700 Kuopio  
Tel +358-207-590 220  
Fax +358-207-590 221  
kuopio@berner-pultti.com  
www.berner-pultti.com

Mitras d.o.o  
Brdnikova ulica 34e  
SL-1000 Ljubljana  
Tel +386-1-256-62-46  
Fax +386-1-256-62-45  
mitras@siol.com

BERNER d.o.o  
CPM Savëca Šanci  
Trgovačka 2  
HR - 10000 Zagreb  
Tel +38512 499 470  
Fax +38512 499 480  
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler  
Sanayi ve Ticaret A.Ş.  
Ferhatpaşa Mah. G 7 Sok. 31/2  
TR - 34858 Kartal-Samandıra /  
ÝSTANBUL  
Tel +90 (0) 216-4713077  
Fax +90 (0) 216-4719625  
info@berner.com.tr  
www.berner.com.tr

Berner S.p.A.  
Via dell 'Elettronica 15  
I - 37139 Verona  
Tel +39 04 58 67 01 11  
Fax +39 04 58 67 01 34  
info@berner.it  
www.berner.it

Albert Berner srl  
Str. Vrancei Nr. 51 - 55  
RO - 310315 Arad  
Tel +40 257 212291  
Fax +40 257 250460  
office@berner-romania.ro  
www.berner-romania.ro

Page 22 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

Berner Produkten b.v.

Vogelzankweg 175

NL - 6374 AC Landgraaf

+31 45 53 39 133 (8.00h-16.00h)

+31 6 290 27 464 (16.00h-8.00h)

info@berner.nl

Berner s.a.r.l.

ZI Les Manteaux

F - 89331 Saint-Julien-du-Sault

Cedex

Tel +33 38 69 94 400

Fax +33 38 69 94 444

Albert Berner SIA

Liliju 20, Marupe, Mārupes

novads,

LV-2167, Latvija

Tel +37167840007

Fax +371678440008

(c) COPYRIGHT 1987 - 2050 ALL RIGHTS RESERVED

### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

Page 23 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

Page 24 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.01.2018 / 0001

Replacing version dated / version: 16.01.2018 / 0001

Valid from: 16.01.2018

PDF print date: 18.01.2018

WINDSCREEN ADHESIVE SAFE 400 ml

Art.: 358546

org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.