

GB

Page 1 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.05.2018 / 0001
Replacing version dated / version: 16.05.2018 / 0001
Valid from: 16.05.2018
PDF print date: 17.05.2018
Vaseline 450 ml
Art.: 368058

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Vaseline 450 ml
Art.: 368058

Petrolatum
Registration number (ECHA): 01-2119490412-42-XXXX
Index: 649-254-00-X
EINECS, ELINCS, NLP: 232-373-2
CAS: 8009-03-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

Berner Produkten b.v., Vogelzankweg 175, 6374 AC Landgraaf, Netherlands
Phone: +31 45 53 39 133, Fax: +31 45 53 14 588
info@berner.nl, www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

Page 2 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.05.2018 / 0001
Replacing version dated / version: 16.05.2018 / 0001
Valid from: 16.05.2018
PDF print date: 17.05.2018
Vaseline 450 ml
Art.: 368058

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

No vPvB substance

No PBT substance

SECTION 3: Composition/information on ingredients

3.1 Substance

Petrolatum	
Registration number (REACH)	01-2119490412-42-XXXX
Index	649-254-00-X
EINECS, ELINCS, NLP	232-373-2
CAS	8009-03-8
content %	
Classification according to Regulation (EC) 1272/2008 (CLP)	---

3.2 Mixture

n.a.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Normally not irritating to skin.

Wash thoroughly with soap and water.

Eye contact

Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Sand

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

GB

Page 4 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.05.2018 / 0001
 Replacing version dated / version: 16.05.2018 / 0001
 Valid from: 16.05.2018
 PDF print date: 17.05.2018
 Vaseline 450 ml
 Art.: 368058

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Protect from direct sunlight and warming.

Store in a well-ventilated place.

Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB	Chemical Name	Paraffin wax, fume	Content %:
	WEL-TWA: 2 mg/m ³	WEL-STEL: 6 mg/m ³	---
	Monitoring procedures: ---		
	BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)

Protective PVC gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

GB

Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, solid.
Colour:	White
Odour:	Odourless
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	45-65 °C (ISO 2207, Setting point)
Initial boiling point and boiling range:	Not determined
Flash point:	210 °C (ISO 2592 (Cleveland, open cup))
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	<0,01 hPa (20°C, DIN 51754)
Vapour density (air = 1):	Not determined
Density:	~780-880 kg/m ³ (70°C, DIN 51757)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble 20°C, (OECD 105 (Water Solubility))
Partition coefficient (n-octanol/water):	n.a.
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	5-15 mm ² /s (100°C, DIN 51562)
Explosive properties:	Not determined
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Not to be expected

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Petrolatum

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg			
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1000	mg/kg	Rat		
Aspiration hazard:						No
Symptoms:						mucous membrane irritation

Paraffin wax, fume

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						diarrhoea

GB

Page 8 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.05.2018 / 0001
 Replacing version dated / version: 16.05.2018 / 0001
 Valid from: 16.05.2018
 PDF print date: 17.05.2018
 Vaseline 450 ml
 Art.: 368058

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Petrolatum							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	10	mg/l	Daphnia magna		
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Other adverse effects:							n.d.a.
Other information:	DOC						DOC-elimination degree (complexing organic substance) > = 80%/28d; , n.a.
Water solubility:							Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

12 01 12 spent waxes and fats

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

No chemical safety assessment was carried out.

SECTION 16: Other information

Revised sections: n.a.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Albert Berner Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
Fax +49 79 40 12 13 00
info@berner.de
www.berner.de

Berner Gesellschaft m.b.H.
Industriezeile 36
A - 5280 Braunau / Inn
Tel +43 77 22 800 508
Fax +43 77 22 800 184
berner@berner.co.at
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
B - 3620 Lanaken
Tel +31 45 533 93 133(8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.be
www.berner.be

Montagetechnik Berner AG
Kägenstraße 8
CH - 4153 Reinach / Bl. 1
Tel +41 61 71 59 222
Fax +41 61 71 59 333
berner-ag@berner-ag.ch
www.berner-ag.ch

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
Fax +45 98 19 24 14
info@berner.dk
www.berner.dk

Berner Montaje y Fijación, S.L.
P.I. "La Rosa VI"
C/Albert Berner, 2
E - 18330 Chauchina-Granada-
España
Tel +34 90 21 03 504
Fax +34 90 21 13 190
berner-spain@berner.es
www.berner.es

Berner Kft.
Táblás u. 34
H - 1097 Budapest
Tel +36 (1) 347 1059
Fax +36 (1) 347 1045
info@berner.hu
www.berner.hu

Frimann-Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 76 55 80
Fax +47 66 76 55 81
info@berner.no
www.berner.no

Berner Succ. Luxembourg
105, Rue des Bruyères
L - 1274 Howald
Tel +31 45 533 93 133 (8.00h-
16.00h)
Tel +31 6 290 27 464 (16.00h-
8.00h)
Fax +31 455 33 92 43
info@berner.lu
www.berner.lu

Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

Berner spol. s r.o.
Jinonická 80
CZ - 158 00 Praha 5
Tel +420 225 390 666
Fax +420 225 390 660
berner@berner.cz
www.berner.cz

Berner, S.A.
Av. Amália Rodrigues, 3510
Manique de Baixo
P - 2785-738 São Domingos de
Rana
Tel ++351 21 448 90 60
Fax ++351 21 448 90 69

Berner Polska Sp. z o.o.
Ul. Puzkarska 7J
30-644 Kraków
Tel +48 12 297 62 40
Fax +48 12 297 62 02
office@berner.pl
www.berner.pl

Albert Berner UAB
Kalvarijø 29B, LT09313,
Vilnius, Lithuania
Tel +370-52104355
Fax +370-52350020
info@berner.lt

Berner SK
Berner s r.o.
Jesenského 1
SK - 962 12 Detva
Tel (+421) 45 5410 245
Fax (+421) 45 5410 255
berner@berner.sk
www.berner.sk

Albert Berner Montagetechnik AB
Elektravägen 53
S - 126 30 Hägersten
Tel +46 85 78 77 800
Fax +46 85 78 77 805
info@berner.se
www.berner.se

Berner Pultti Oy
Volltikatu 6
FI - 70700 Kuopio
Tel +358-207-590 220
Fax +358-207-590 221
kuopio@berner-pultti.com
www.berner-pultti.com

Mitras d.o.o
Brdnikova ulica 34e
SL-1000 Ljubljana
Tel +386-1-256-62-46
Fax +386-1-256-62-45
mitras@siol.com

BERNER d.o.o
CPM Savëca Šanci
Trgovačka 2
HR - 10000 Zagreb
Tel +38512 499 470
Fax +38512 499 480
e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler
Sanayi ve Ticaret A.Ş.
Ferhatpaşa Mah. G 7 Sok. 31/2
TR - 34858 Kartal-Samandıra /
ÝSTANBUL
Tel +90 (0) 216-4713077
Fax +90 (0) 216-4719625
info@berner.com.tr
www.berner.com.tr

Berner S.p.A.
Via dell 'Elettronica 15
I - 37139 Verona
Tel +39 04 58 67 01 11
Fax +39 04 58 67 01 34
info@berner.it
www.berner.it

Albert Berner srl
Str. Vrancei Nr. 51 - 55
RO - 310315 Arad
Tel +40 257 212291
Fax +40 257 250460
office@berner-romania.ro
www.berner-romania.ro

Berner Produkten b.v.
Vogelzankweg 175
NL - 6374 AC Landgraaf
+31 45 53 39 133 (8.00h-16.00h)
+31 6 290 27 464 (16.00h-8.00h)
info@berner.nl
www.berner.nl

Berner s.a.r.l.
ZI Les Manteaux
F - 89331 Saint-Julien-du-Sault Cedex
Tel +33 38 69 94 400
Fax +33 38 69 94 444
contact@berner.fr
www.berner.fr

Albert Berner SIA
Liliju 20, Marupe, Mārupes novads,
LV-2167, Latvija
Tel +37167840007
Fax +371678440008
info@berner.lv

(c) COPYRIGHT 1987 - 2050 ALL
RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.05.2018 / 0001

Replacing version dated / version: 16.05.2018 / 0001

Valid from: 16.05.2018

PDF print date: 17.05.2018

Vaseline 450 ml

Art.: 368058

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.