

Page 1 of 49
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 19.01.2021 / 0009
Replacing version dated / version: 29.03.2019 / 0008
Valid from: 19.01.2021
PDF print date: 20.01.2021
Paintspray Case red 400 ml
Art.: 147521

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Paintspray Case red 400 ml
Art.: 147521

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lacquer spray

Sector of use [SU]:

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 9a - Coatings and paints, thinners, paint removers

Process category [PROC]:

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC99 - Not required.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Berner Produkten b.v.

Steenbergstraat 25

6465 AB Kerkrade

Tel.: +31 45 53 39 133

Web: www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 221 80260 889 (9:00h - 17:00h)

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class **Hazard category** **Hazard statement**

Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P261-Avoid breathing vapours or spray. P280-Wear eye protection.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Without adequate ventilation, formation of explosive mixtures may be possible.

n-butyl acetate

Acetone

Page 3 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP	200-662-2
CAS	67-64-1
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

n-butyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	607-025-00-1
EINECS, ELINCS, NLP	204-658-1
CAS	123-86-4
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 STOT SE 3, H336

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119488216-32-XXXX
Index	601-022-00-9
EINECS, ELINCS, NLP	215-535-7
CAS	1330-20-7
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373

GB

Page 4 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

2-methoxy-1-methylethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475791-29-XXXX
Index	607-195-00-7
EINECS, ELINCS, NLP	203-603-9
CAS	108-65-6
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226

Ethanol	Substance with specific conc. limit(s) acc. to REACH-registration
Registration number (REACH)	01-2119457610-43-XXXX
Index	603-002-00-5
EINECS, ELINCS, NLP	200-578-6
CAS	64-17-5
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319

Isobutyl methyl ketone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	606-004-00-4
EINECS, ELINCS, NLP	203-550-1
CAS	108-10-1
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H335

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP	236-675-5
CAS	13463-67-7
content %	<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351 (as inhalation)

Glycolic acid n-butyl ester	
Registration number (REACH)	01-2119514685-36-XXXX
Index	---
EINECS, ELINCS, NLP	230-991-7
CAS	7397-62-8
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318 Repr. 2, H361

GB

Page 5 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	
Registration number (REACH)	01-2119974119-29-XXXX
Index	---
EINECS, ELINCS, NLP	251-846-4
CAS	34140-91-5
content %	<0,05
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 2, H411

Amines, C12-18-alkyldimethyl	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	269-923-6
CAS	68391-04-8
content %	<0,025
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=1) Eye Dam. 1, H318

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Product removes fat.

Headaches

Dizziness

Inhalation of fumes may have narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Dry extinguisher

Foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

GB

Page 7 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Take precautions against electrostatic charges.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Solvent resistant floor

Observe special regulations for aerosols!

Protect from direct sunlight.

Store in a dry place.

Only store at temperatures from 5°C to 35°C.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Acetone	Content %: 20-40
WEL-TWA: 500 ppm (1210 mg/m3) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Acetone 100/b (CH 22 901) - Draeger - Acetone 40/a (5) (81 03 381) - Compur - KITA-102 SA (548 534) - Compur - KITA-102 SC (548 550) 	

GB

Page 8 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

- Compur - KITA-102 SD (551 109)
INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project
- BC/CEN/ENTR/000/2002-16 card 67-1 (2004)
MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993
- NIOSH 1300 (KETONES I) - 1994
NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- NIOSH 2555 (KETONES I) - 2003
NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016
- OSHA 69 (Acetone) - 1988

BMGV: ---

Other information: ---

GB

Chemical Name

n-butyl acetate

Content
%: 1-10

WEL-TWA: 150 ppm (724 mg/m³)
(WEL), 50 ppm (241 mg/m³) (EU)

WEL-STEL: 200 ppm (966 mg/m³)
(WEL), 150 ppm (723 mg/m³) (EU)

Monitoring procedures:

- Compur - KITA-138 U (548 857)
- Compur - KITA-139 SB(C) (549 731)
- NIOSH 1450 (ESTERS 1) - 2003
NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007

BMGV: ---

Other information: ---

GB

Chemical Name

Xylene

Content
%: 1-<10

WEL-TWA: 220 mg/m³ (50 ppm)
(WEL), 50 ppm (221 mg/m³) (EU)

WEL-STEL: 100 ppm (441 mg/m³)
(WEL), 100 ppm (442 mg/m³) (EU)

Monitoring procedures:

- Draeger - Xylene 10/a (67 33 161)
- Compur - KITA-143 SA (550 325)
- Compur - KITA-143 SB (505 998)
INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004)
- NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003
NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999

BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)

Other information: Sk (WEL)

GB

Chemical Name

2-methoxy-1-methylethyl acetate

Content
%: 1-5

WEL-TWA: 50 ppm (274 mg/m³)
(WEL), 50 ppm (275 mg/m³) (EU)

WEL-STEL: 100 ppm (548 mg/m³)
(WEL), 100 ppm (550 mg/m³) (EU)

Page 9 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Monitoring procedures:	INSHT MTA/MA-024/A92 (Determination of esters II (1-methoxy-2-propyl acetate, 2-ethoxyethyl acetate) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project - BC/CEN/ENTR/000/2002-16 card 15-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993
BMGV: ---	Other information: Sk (WEL)

Chemical Name	Ethanol	Content %:1-5
WEL-TWA: 1000 ppm (1920 mg/m3)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Alcohol 25/a Ethanol (81 01 631) - Compur - KITA-104 SA (549 210) DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project - BC/CEN/ENTR/000/2002-16 card 63-2 (2004) DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)	
BMGV: ---	Other information: ---	

Chemical Name	Isobutyl methyl ketone	Content %:1-5
WEL-TWA: 50 ppm (208 mg/m3) (WEL), 20 ppm (83 mg/m3) (EU)	WEL-STEL: 100 ppm (416 mg/m3) (WEL), 50 ppm (208 mg/m3) (EU)	---
Monitoring procedures:	- Compur - KITA-122 SA(C) (549 277) - Compur - KITA-155 U (554 640) INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project - BC/CEN/ENTR/000/2002-16 card 13-1 (2004) MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 MDHS 80 (Volatile organic compounds in air – Laboratory method using diffusive solid sorbent tubes, thermal desorption and gas chromatography) - 1995 - NIOSH 1300 (KETONES I) - 1994 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - NIOSH 2555 (KETONES I) - 2003	
BMGV: 20 µmol 4-methylpentan-2one/l in Urine, post shift (BMGV)	Other information: Sk (WEL)	

Chemical Name	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	Content %:<5
WEL-TWA: 10 mg/m3 (total inhalable dust), 4 mg/m3 (respirable dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	

Page 10 of 49 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.01.2021 / 0009 Replacing version dated / version: 29.03.2019 / 0008 Valid from: 19.01.2021 PDF print date: 20.01.2021 Paintspray Case red 400 ml Art.: 147521		
- OSHA PV2010 (n-Butane) - 1993		
BMGV: ---	Other information: ---	
Chemical Name	Quartz	Content %:
WEL-TWA: 0,1 mg/m ³ (silica, respirable, crystalline)	WEL-STEL: ---	---
Monitoring procedures:	INSHT MTA/MA-036/A00 (Determination of Quartz in Air – Membrane Filter Method/ Xray Diffraction) - 2000, 2004 MDHS 101/2 (Crystalline silica in respirable airborne dust – Direct on-filter analysis by infrared spectroscopy and X-ray diffraction) - 2015 - EU project BC/CEN/ENTR/000/2002-16 card 52-1 (2004) NIOSH 7500 (Crystalline Silica, by XRD (filter redeposition)) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 52-6 (2004) NIOSH 7601 (SILICA, CRYSTALLINE, by VIS) - 2003 NIOSH 7602 (Crystalline Silica, by IR (KBr pellet)) - 2003 NIOSH 7603 (QUARTZ in coal mine dust, by IR (redeposition)) - 2017 OSHA ID-142 (Quartz and Cristobalite in Workplace Atmospheres) - 2016	
BMGV: ---	Other information: ---	
Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990	
BMGV: ---	Other information: ---	
Chemical Name	Aluminium powder (stabilised)	Content %:
WEL-TWA: 10 mg/m ³ (total inh. dust), 4 mg/m ³ (resp. dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
Chemical Name	Carbon black	Content %:
WEL-TWA: 3,5 mg/m ³	WEL-STEL: 7 mg/m ³	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
Chemical Name	Iron(III)oxide	Content %:
WEL-TWA: 5 mg/m ³ (fume, as Fe) / Rouge: 4 mg/m ³ (resp. dust), 10 mg/m ³ (total inh. dust)	WEL-STEL: 10 mg/m ³ (fume, as Fe)	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
Chemical Name	Copper compounds	Content %:
WEL-TWA: 1 mg/m ³ (Copper and compounds - dust and mists (as Cu))	WEL-STEL: 2 mg/m ³ (Copper and compounds - dust and mists (as Cu))	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
Acetone		

GB

Page 11 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assessment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assessment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/l	
	Environment - sediment, marine		PNEC	3,04	mg/l	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assessment factor 100
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m ³	Overall assessment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m ³	

n-butyl acetate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
---------------------	--	------------------	------------	-------	------	------

GB

Page 12 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

	Environment - freshwater		PNEC	0,18	mg/l	
	Environment - marine		PNEC	0,018	mg/l	
	Environment - periodic release		PNEC	0,36	mg/l	
	Environment - sediment, freshwater		PNEC	0,981	mg/kg	
	Environment - sediment, marine		PNEC	0,0981	mg/kg	
	Environment - soil		PNEC	0,0903	mg/kg	
	Environment - sewage treatment plant		PNEC	35,6	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	6	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	300	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	35,7	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	300	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	35,7	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	6	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	600	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	300	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	600	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	300	mg/m3	

Xylene

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - periodic release		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	

GB

Page 13 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	0,327	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	

2-methoxy-1-methylethyl acetate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,635	mg/l	
	Environment - sediment, freshwater		PNEC	3,29	mg/kg	
	Environment - sediment, marine		PNEC	0,329	mg/kg	
	Environment - soil		PNEC	0,29	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - marine		PNEC	0,0635	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	6,35	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	33	mg/m3	

GB

Page 14 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Consumer	Human - dermal	Long term, systemic effects	DNEL	54,8	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,67	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	153,5	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	275	mg/m3	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Ethanol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	

GB

Page 15 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

	Environment - sediment, freshwater		PNEC	3,6	mg/kg	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3	

Isobutyl methyl ketone

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - water, sporadic (intermittent) release		PNEC	1,5	mg/l	
	Environment - freshwater		PNEC	0,6	mg/l	
	Environment - marine		PNEC	0,06	mg/l	
	Environment - sediment, freshwater		PNEC	8,27	mg/kg	
	Environment - sediment, marine		PNEC	0,83	mg/kg	
	Environment - soil		PNEC	1,3	mg/kg	
	Environment - sewage treatment plant		PNEC	27,5	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	14,7	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	155,2	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	155,2	mg/m3	

GB

Page 16 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Consumer	Human - dermal	Long term, systemic effects	DNEL	4,2	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	208	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	208	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11,8	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	83	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	83	mg/m3	

Glycolic acid n-butyl ester

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - water		PNEC	0,05	mg/l	
	Environment - soil		PNEC	0,0112	mg/kg dw	
	Environment - sediment		PNEC	0,203	mg/kg dw	
	Environment - sewage treatment plant		PNEC	232	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	20,8	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,5	mg/m3	
Consumer	Human - dermal	Long term, local effects	DNEL	0,28	mg/cm2	
Consumer	Human - inhalation	Long term, local effects	DNEL	43,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	34	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	21,2	mg/m3	

Aluminium powder (stabilised)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0749	mg/l	
	Environment - sewage treatment plant		PNEC	20	mg/l	

GB

Page 17 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Consumer	Human - oral	Long term, systemic effects	DNEL	3,95	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	3,72	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3,72	mg/m ³	

Carbon black						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,06	mg/m ³	

Iron(III)oxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m ³	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

Page 18 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

With short-term contact:

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

max. 15

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

Page 19 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	<0 °C (Active substance)
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,5 Vol-%
Upper explosive limit:	13 Vol-%
Vapour pressure:	3600 hPa (20°C)
Vapour density (air = 1):	Not determined
Density:	0,75-0,825 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	365 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	82,7 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

GB

Page 20 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Pressure increase will result in danger of bursting.
 Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong acids.
 Avoid contact with strong alkalis.
 Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Paintspray Case red 400 ml Art.: 147521

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4 h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4 h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Acetone

GB

Page 21 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4 h	Rat		
Skin corrosion/irritation:				Guinea pig		Repeated exposure may cause skin dryness or cracking., Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness

GB

Page 22 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
---	-------	-----	------------	-----	--	--

n-butyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10760	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>14112	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	21,1	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEC	9640	mg/m3		OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative

GB

Page 23 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Symptoms:						drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	500	ppm	Rat		
Other information:						Repeated exposure may cause skin dryness or cracking.

Xylene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification
Acute toxicity, by inhalation:	LD50	27,6	mg/l/4 h	Rat		Does not conform with EU classification ., Vapours
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						Yes

GB

Page 24 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Symptoms:						breathing difficulties, headaches, dizziness
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

2-methoxy-1-methylethyl acetate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>23,8	mg/l/6 h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit		Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	No indications of such an effect.
Symptoms:						respiratory distress, drowsiness, unconsciousness, vomiting, headaches, mucous membrane irritation, dizziness, nausea

Ethanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	124,7	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours

GB

Page 25 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Aspiration hazard:				Human being		No indications of such an effect.
Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea

GB

Page 26 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Other information:						Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption., Experiences on persons.
--------------------	--	--	--	--	--	---

Isobutyl methyl ketone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2100	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	16000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	8,3-16,6	mg/l/4 h	Rat		Vapours
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Eye Irrit. 2
Respiratory or skin sensitisation:						Not sensitizing

GB

Page 27 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Symptoms:						respiratory distress, unconsciousness, coughing, headaches, cramps, paralysis, gastrointestinal disturbances, mucous membrane irritation, dizziness
-----------	--	--	--	--	--	---

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4 h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

GB

Page 28 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract).
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		90d
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		90d

Glycolic acid n-butyl ester

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4595	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LC50	> 6,2	mg/l/4 h	Rat		
Acute toxicity, by inhalation:	LC50	> 6,2	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing

GB

Page 29 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	250	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Reproductive toxicity (Developmental toxicity):	NOAEL	1250	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Female
Aspiration hazard:						No

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						eyes, reddened, watering eyes

Amines, C12-18-alkyldimethyl

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1015		Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit		Skin Corr. 1B, Analogous conclusion

GB

Page 30 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Serious eye damage/irritation:					OECD 437 (Bovine Corneal Opacity + Permeability Test for Identif. Ocular Corros. + Severe Irritants)	Eye Irrit. 2, Does not conform with EU classification., Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):	NOEL	100	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Analogous conclusion
Reproductive toxicity (Effects on fertility):	NOAEL	25	mg/kg bw/d	Rat		Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	40	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Analogous conclusion

Butane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

GB

Page 31 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Quartz						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						respiratory distress, coughing, mucous membrane irritation

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No

GB

Page 32 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Aluminium powder (stabilised)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	>5	mg/l/4 h	Rat		Dust, Mist
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Symptoms:						mucous membrane irritation

Carbon black						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3000	mg/kg			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Mouse		Negative

GB

Page 33 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	0,0011	mg/l			References, Target organ(s): lung90d
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	137	mg/kg	Mouse		
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	52	mg/kg	Rat		

Iron(III)oxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		Analogous conclusion
Acute toxicity, by inhalation:	LC50	>210	mg/m3	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant, Analogous conclusion, Mechanical irritation possible.
Serious eye damage/irritation:				Rabbit		Not irritant, Analogous conclusion, Mechanical irritation possible.
Germ cell mutagenicity:						No indications of such an effect.
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:						No indications of such an effect.
Aspiration hazard:						No
Symptoms:						respiratory distress, coughing, mucous membrane irritation

GB

Page 34 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Paintspray Case red 400 ml Art.: 147521

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							Contains organically bound halogens, which may contribute to the AOX value in wastewater.

Acetone

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		30d	81-92	%		Regulation (EC) 440/2008 C.4-E (DETERMINATION OF 'READY' BIODEGRADABILITY - CLOSED BOTTLE TEST)	Readily biodegradable

GB

Page 35 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		0,19				
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriella subcapitata		
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	BOD5		1760-1900	mg/g			
Other information:	AOX		0	%			

GB

Page 36 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:							No adsorption in soil.

n-butyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.6. Other adverse effects:							Product floats on the water surface.
12.1. Toxicity to fish:	LC50	96h	18	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	44	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	23	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	397	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		28d	98	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,85-2,3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		959	mg/l	Pseudomonas putida		

Xylene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

GB

Page 37 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

12.1. Toxicity to algae:	IC50	72h	4,36	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		3,16				
12.3. Bioaccumulative potential:	BCF		25,9				
12.4. Mobility in soil:	H (Henry)		665	Pa*m ³ /mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

2-methoxy-1-methylethyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	100-180	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

GB

Page 38 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Toxicity to bacteria:	EC20	30min	>100 0	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	-------	-----------	------	------------------	--	--

Ethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short-term Toxicity Test on Embryo and Sac-fry Stages)	
12.1. Toxicity to daphnia:	LC50	48h	12340	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,32				Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.4. Mobility in soil:	H (Henry)		0,000 138				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

GB

Page 39 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Toxicity to bacteria:	IC50	3h	>100 0	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	

Isobutyl methyl ketone

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	505-540	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	170	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	78	mg/l	Daphnia magna		
12.1. Toxicity to algae:	LC50	96h	400	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		7d	>99	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,31-1,38				
Toxicity to bacteria:	EC50	16h	275	mg/l	Pseudomonas putida		

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriella subcapitata	U.S. EPA-600/9-78-018	

GB

Page 40 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble 20°C

Glycolic acid n-butyl ester

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	24h	280	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to algae:	EC50	7d	>87,44	mg/l		OECD 221 (Lemna sp. Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	82	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Pow		0,38				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC20	18h	2320	mg/l	Pseudomonas putida	DIN 38412 T.8	

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

GB

Page 41 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

12.2. Persistence and degradability:		28d	66	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.1. Toxicity to fish:	LC50	96h	0,95	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	21d	1,41	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	

Amines, C12-18-alkyldimethyl

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,620	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	0,188	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	0,0099	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		23d	>99	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Analogous conclusion

Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).

GB

Page 42 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	-------------------------------------

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Carbon black							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							Insoluble, Product floats on the water surface.
12.1. Toxicity to fish:	LC50	96h	>100 0	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>560 0	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

GB

Page 43 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

12.1. Toxicity to algae:	NOEC/NOEL	3d	10000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not biodegradable
12.3. Bioaccumulative potential:							Not to be expected
Toxicity to bacteria:	EC0	3h	>=800	mg/l	activated sludge	Regulation (EC) 440/2008 C.22 (SOIL MICROORGANISMS - CARBON TRANSFORMATION TEST)	

Iron(III)oxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Leuciscus idus		Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	ISO 8192	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

GB

Page 44 of 49
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

allocated under certain circumstances. (2014/955/EU)
 08 01 11 waste paint and varnish containing organic solvents or other hazardous substances
 16 05 04 gases in pressure containers (including halons) containing hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.
For contaminated packing material
 Pay attention to local and national official regulations.
 Do not perforate, cut up or weld uncleaned container.
 15 01 04 metallic packaging

SECTION 14: Transport information


General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U


Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3b	11.1, 11.2	5000 (netto)	50000 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 82,66 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 19.01.2021 / 0009
 Replacing version dated / version: 29.03.2019 / 0008
 Valid from: 19.01.2021
 PDF print date: 20.01.2021
 Paintspray Case red 400 ml
 Art.: 147521

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H351 Suspected of causing cancer by inhalation.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

- Eye Irrit. — Eye irritation
- STOT SE — Specific target organ toxicity - single exposure - narcotic effects
- Aerosol — Aerosols
- Flam. Liq. — Flammable liquid
- Asp. Tox. — Aspiration hazard
- Acute Tox. — Acute toxicity - dermal
- Skin Irrit. — Skin irritation
- Acute Tox. — Acute toxicity - inhalation
- STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
- STOT RE — Specific target organ toxicity - repeated exposure
- Carc. — Carcinogenicity

Page 47 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

Eye Dam. — Serious eye damage

Repr. — Reproductive toxicity

Aquatic Acute — Hazardous to the aquatic environment - acute

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Skin Corr. — Skin corrosion

Albert Berner Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
www.berner.de

Berner Gesellschaft m.b.H.
Industriezeile 36
A - 5280 Braunau am Inn
Tel +43 77 22 80 00
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
3620 Lanaken
Zweigniederlassung:
105B, Rue des Bruyères
1274 Howald
Luxembourg

Montagetechnik Berner AG
Kägenstraße 8
4153 Reinach BL 1

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
www.berner.dk

Berner, Montaje y Fijación, S.L.
Poligono Industrial "La Rosa" VI
C/Albert Berner, núm. 2
E-18330 Chauchina-Granada
Tel +34 (0) 958 060-200
www.berner.es

Berner KFT
Gubacsi út 6/B
1097 Budapest

Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 7655-80
www.berner.no

Berner spol. s r.o.
Jinonická 80
CZ - 15800 Praha 5 Košiče

Berner S.A., Edificio Berner
Av. Amália Rodrigues,3510
Manique de Baixo
P-2785-738 São Domingos de Rana
Tel +35 12 14 48 90 60
www.berner.pt

UAB Albert Berner
K. Ladygos str. 1
LT-08235 Vilnius
Tel +370 (0) 52 10 43 55
www.berner.lt

Berner s.r.o.
Jesenského 1
96212 Detva

Albert Berner Montagetechnik AB
Elektravägen 53
S-126 30 Hägersten
Tel +46 (0) 85 78 77 800
www.berner.se

BERNER d.o.o
CPM Savica Sanc
Majstorska 9
10000 Zagreb

Berner S.p.A.
Via dell 'Elettronica, 15
I - 37139 Verona
Tel +39 04 58 67 01 11
www.berner.it

Albert Berner S.R.L.
Str. Vrancei Nr. 51 - 55
310315 Arad

Berner Produkten b.v.
Steenbergstraat 25
6654 AB Kerkrade
+31 45 53 39 133
www.berner.nl

Berner Logistics Kerkrade B.V.
Steenbergstraat 25
6465 AB Kerkrade

GB

Page 48 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

Berner s.a.r.l.
14, rue Albert Berner
Z.I. Les Manteaux
F - 89331 Saint-Julien-du-Sault
Cedex
Tel +33 38 69 94 400
www.berner.fr

Berner Holding France SAS
37, rue de Liège
75008 Paris

Berner Industry Services
37, rue de Liège
75008 Paris

SIA Albert Berner
Liliju iela 20
LV-2167 Marupe, Rigas raj.
Tel +371 (0) 67 84 00 07
www.berner.lv

Berner Polska Spółka z o.o.
Ul. Puzkarska 7j
PL-30-644 Kraków
Tel +48 12 297 62 00
www.berner.pl

(c) COPYRIGHT 1987 - 2050 ALL
RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

Page 49 of 49

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2021 / 0009

Replacing version dated / version: 29.03.2019 / 0008

Valid from: 19.01.2021

PDF print date: 20.01.2021

Paintspray Case red 400 ml

Art.: 147521

EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.