



Page 1 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Silicone sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

EUH208-Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

012 11211101 05	
Distillates (petroleum), hydrotreated middle	
Registration number (REACH)	01-2119552497-29-XXXX
Index	649-221-00-X
EINECS, ELINCS, NLP, REACH-IT List-No.	265-148-2
CAS	64742-46-7
content %	1-5
Classification according to Regulation (EC) 1272/2008	Asp. Tox. 1, H304
(CLP), M-factors	

3-Aminopropyl(methyl)silsesquioxane, ethoxy	
terminated	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	128446-60-6
content %	<3
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 3, H226
(CLP), M-factors	Eye Irrit. 2, H319
	Skin Irrit. 2, H315

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation





Page 3 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Silicon dioxide

Oxides of nitrogen

Formaldehyde

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.





Page 4 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Flush residue using copious water.

Or:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

An combustible atmosphere can develop in closed vessels.

Remove possible causes of ignition - do not smoke.

Take measures against electrostatic charging, if appropriate.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store in a well ventilated place.

Store cool.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

1200 mg/m3



Œ

Page 5 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Chemical Name	Distillates (pe	troleum), hydrotreated mid	dle		Content %:1-
WEL-TWA: 1200 mg/m3 (>=C7 normal	WEL-STEL:			
and branched chain alkanes)					
Monitoring procedures:		Draeger - Hydrocarbons 0,			
		Draeger - Hydrocarbons 2/a	,		
	=	Compur - KITA-187 S (55)			
BMGV:			Other information	:	
© Chemical Name	Silica, amorph	hous			Content %:
WEL-TWA: 6 mg/m3 (total	inh. dust),	WEL-STEL:			
2,4 mg/m3 (resp. dust)					
Monitoring procedures:					
BMGV:			Other information	:	
© Chemical Name	Ethanol				Content %:
WEL-TWA: 1000 ppm (192		WEL-STEL:			
Monitoring procedures:		Draeger - Alcohol 25/a Eth			
		Compur - KITA-104 SA (5	,		
		DFG (D) (Loesungsmittelg		Nr. 6 D	FG (E)
		(Solvent mixtures) - 2013, 2			
		BC/CEN/ENTR/000/2002-	, ,		
		DFG Meth. Nr. 2 (D) (Loes			3 - EU project
		BC/CEN/ENTR/000/2002-	, ,		
		DFG Meth. Nr. 3 (D) (Loes	0	,	3 - EU project
	-	BC/CEN/ENTR/000/2002-	` '		
BMGV:			Other information	:	

Silica, amorphous									
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note			
	Environmental		or						
	compartment								
	Environment - oral		PNEC	60000	mg/kg				
	(animal feed)				feed				
Workers / employees	Human - inhalation	Long term, local	DNEL	4	mg/m3				
		effects							

Ethanol						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,96	mg/l	
	freshwater					
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water,		PNEC	2,75	mg/l	
	sporadic					
	(intermittent) release					
	Environment -		PNEC	580	mg/l	
	sewage treatment					
	plant					





Page 6 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

	Environment - sediment, freshwater		PNEC	3,6	mg/kg
	Environment - soil		PNEC	0,63	mg/kg dry weight
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- $(8) = Inhalable\ fraction\ (2017/164/EU,\ 2017/2398/EU).\ (9) = Respirable\ fraction\ (2017/164/EU,\ 2017/2398/EU).$ $(10) = Short\text{-term}\ exposure\ limit\ value\ in\ relation\ to\ a\ reference\ period\ of\ 1\ minute\ (2017/164/EU).\ |\ BMGV=Biological\ monitoring\ guidance\ value\ EH40.\ BGW="Biologischer\ Grenzwert"\ (biological\ limit\ value,\ Germany)\ |\ Other\ information:\ Sen=Capable\ of\ causing\ occupational\ asthma.\ Sk=Can\ be\ absorbed\ through\ skin.\ Carc=Capable\ of\ causing\ cancer\ and/or\ heritable\ genetic\ damage.$
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.





Page 7 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

> 0.1

Permeation time (penetration time) in minutes:

> 480

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

> 0.3

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter ABEK (EN 14387), code colour brown, grey, yellow, green

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.





Page 8 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Paste, liquid.

Colour: According to specification

Odour: Alcoholic
Odour threshold: Not determined
pH-value: Not determined
Melting point/freezing point: Not determined
Initial boiling point and boiling range: Not determined
Flash point: Not determined
Evaporation rate: Not determined

Flammability (solid, gas): n.a.

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Not determined

Not determined

Not determined

Not determined

Not determined

Not determined

Density: 1,02-1,03 g/cm3 (23°C, ISO 1183)

Bulk density: n.a.

Solubility(ies):

Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Not determined

>400 °C (DIN 51794)

Not determined

Viscosity: ~800000 mPas (23°C, Brookfield)

Explosive properties: Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined
Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity





Page 9 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Moisture Strong heat T > 150°C

10.5 Incompatible materials

Water Bases Acids

10.6 Hazardous decomposition products

In case of contact with water:

Ethanol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Silicone Alcoxy plus trai	sparent 3	10 ml	`			
Art.: 9096574	_					
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat		Analogous
route:						conclusion
Acute toxicity, by	LD50	>2000	mg/kg	Rat		Analogous
dermal route:						conclusion
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:				Rabbit		Not irritant,
						Analogous
						conclusion
Serious eye				Rabbit		Not irritant,
damage/irritation:						Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						





Page 10 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Silica, amorphous						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	Analogous
route:					Oral Toxicity)	conclusion
Acute toxicity, by	LD50	>5000	mg/kg	Rabbit		References
dermal route:						
Acute toxicity, by	LC50	>0,139	mg/l/4h	Rat		References,
inhalation:						Maximum
						achievable
						concentration
Skin corrosion/irritation:				Rabbit		Not irritant,
Skiii Colfosion/Ilittation.				Kabbit		References
Serious eye				Rabbit		Not irritant,
damage/irritation:				Rabbit		Mechanical
damage/irration.						irritation
						possible.,
						References
Respiratory or skin				Guinea pig		Not
sensitisation:				1 0		sensitizising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No
						indications
						of such an
						effect.
Reproductive toxicity						No
(Developmental						indications
toxicity):						of such an
						effect.
Symptoms:						eyes,
						reddened

Ethanol						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt			_		
Acute toxicity, by oral	LD50	10470	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	124,7	mg/l/4h	Rat	OECD 403 (Acute	Vapours
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	





Page 11 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Serious eye damage/irritation:	Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Irritant
Respiratory or skin sensitisation:	Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:	Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:	Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:		OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:		OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Aspiration hazard:	Human being		No indications of such an effect.
Symptoms:			respiratory distress, drowsiness, unconsciousn ess, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea





Page 12 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Other information:		Excessive
		alcohol
		consumption
		during
		pregnancy
		induces the
		foetus
		alcohol
		syndrome
		(reduced
		weight at
		birth,
		physical and
		mental
		disorders).,
		There is no
		sign that this
		syndrome is
		also caused
		by dermal or
		inhalative
		absorption.,
		Experiences
		on persons.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Silicone Alcoxy plus transparent 310 ml									
Art.: 9096574									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to							n.d.a.		
fish:									
12.1. Toxicity to							n.d.a.		
daphnia:									
12.1. Toxicity to							n.d.a.		
algae:									
12.2. Persistence							n.d.a.		
and degradability:									
12.3.							n.d.a.		
Bioaccumulative									
potential:									
12.4. Mobility in							n.d.a.		
soil:									
12.5. Results of							n.d.a.		
PBT and vPvB									
assessment									
12.6. Other							n.d.a.		
adverse effects:									





Page 13 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Other information:			According
			to the recipe,
			contains no
			AOX.
Other information:			DOC-
			elimination
			degree(comp
			lexing
			organic
			substance)>=
			80%/28d:
			n.a.

Silica, amorphous								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203		
fish:			0	_	rerio	(Fish, Acute		
						Toxicity Test)		
12.1. Toxicity to	EC50	24h	>1000	mg/l	Daphnia	OECD 202		
daphnia:			0		magna	(Daphnia sp.		
						Acute		
						Immobilisatio		
						n Test)		
12.1. Toxicity to	EL50	72h	>1000	mg/l		OECD 201		
algae:			0			(Alga,		
						Growth		
						Inhibition		
						Test)		
12.2. Persistence							Abiotically	
and degradability:							degradable.	
12.3.							Not to be	
Bioaccumulative							expected	
potential:								
12.4. Mobility in							Not to be	
soil:							expected	
12.5. Results of							No PBT	
PBT and vPvB							substance,	
assessment							No vPvB	
							substance	

Ethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	13000	mg/l	Oncorhynchus	OECD 203	
fish:					mykiss	(Fish, Acute	
						Toxicity Test)	





Page 14 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

12.1. Toxicity to	NOEC/NO	120h	250	mg/l	Brachydanio	OECD 212	
fish:	EL	12011	250	IIIg/1	rerio	(Fish, Short-	
11011.					10110	term Toxicity	
						Test on	
						Embryo and	
						Sac-fry	
						Stages)	
12.1. Toxicity to	EC50	48h	5414	mg/l	Daphnia	OECD 202	
daphnia:	ECSO	4011	3414	IIIg/1		(Daphnia sp.	
чарина.					magna	Acute	
						Immobilisatio	
10.1 Taviaity to	NOEC/NO	10d	0.6	m ~ /1	Comin dombnin	n Test)	References
12.1. Toxicity to daphnia:	EL	100	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to	EC50	72h	275	mg/l	Chlorella	OECD 201	
algae:					vulgaris	(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence		28d	97	%		OECD 301 B	Readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Co2	-
						Evolution	
						Test)	
12.3.	Log Pow		-0,32				Bioaccumula
Bioaccumulative							tion is
potential:							unlikely
							(LogPow <
							1).
12.3.	BCF		0,66 -				,
Bioaccumulative			3,2				
potential:							
12.4. Mobility in	H (Henry)		0,000				
soil:			138				
12.4. Mobility in	Koc		1,0				Highestimate
soil:							d
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
Toxicity to	IC50	3h	>1000	mg/l	activated	OECD 209	Analogous
bacteria:					sludge	(Activated	conclusion
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
	1			L	1		





Page 15 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

Other organisms:	NOEC/NO	280	mg/l	Lemna gibba	OECD 201	
	EL				(Alga,	
					Growth	
					Inhibition	
					Test)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 02 17 waste containing silicones other than those mentioned in 07 02 16

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.





Page 16 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): < 1 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 9, 11

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Asp. Tox. — Aspiration hazard

Flam. Liq. — Flammable liquid

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number



(GB

Page 17 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million





Page 18 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.11.2020 / 0002

Replacing version dated / version: 16.04.2020 / 0001

Valid from: 27.11.2020 PDF print date: 02.06.2021

Silicone Alcoxy plus transparent 310 ml

Art.: 9096574

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.