



Page 1 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

EUH208-Contains Dioctylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Titanium dioxide (in powder form containing 1 % or	
more of particles with aerodynamic diameter <= 10 μm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP	236-675-5
CAS	13463-67-7
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008	Carc. 2, H351 (as inhalation)
(CLP)	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.





Page 3 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Calcium oxide

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.





Page 4 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid contact with eyes.

Prevent long-term skin contact.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

Suitable container:

Plastic

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

©B Chemical Name	Titanium diox	ide (in powder f	form conta	ining 1 % or more of	f	Content %:1-		
Chemical Name	particles with	aerodynamic dia	nerodynamic diameter <= 10 μm)					
WEL-TWA: 10 mg/m3 (to	tal inhalable	WEL-STEL:						
dust), 4 mg/m3 (respirable du	ust)							
Monitoring procedures:								
BMGV:	:							
© Chemical Name	Calcium carbo	onate				Content %:		
WEL-TWA: 4 mg/m3 (resp	pirable dust),	WEL-STEL:						
10 mg/m3 (total inhalable du	st)							
Monitoring procedures:								
BMGV:				Other information	:			

Titanium dioxide (in p	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10										
μm)											
Area of application	Exposure route / Effect on health Descript Value Unit Note										
	Environmental	Environmental or									
	compartment										
	Environment -		PNEC	0,184	mg/l						
	freshwater										





Page 5 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

	Environment - marine		PNEC	0,018	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

 $(8) = Inhalable\ fraction\ (2017/164/EU,\ 2017/2398/EU).\ (9) = Respirable\ fraction\ (2017/164/EU,\ 2017/2398/EU).$ $(10) = Short\text{-term}\ exposure\ limit\ value\ in\ relation\ to\ a\ reference\ period\ of\ 1\ minute\ (2017/164/EU).\ |\ BMGV=Biological\ monitoring\ guidance\ value\ EH40.\ BGW="Biologischer\ Grenzwert"\ (biological\ limit\ value,\ Germany)\ |\ Other\ information:\ Sen=Capable\ of\ causing\ occupational\ asthma.\ Sk=Can\ be\ absorbed\ through$





Page 6 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Rubber gloves (EN 374).

Protective gloves made of butyl (EN 374).

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0.4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.





Page 7 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Paste, liquid. Colour: Grey Odour: Slightly Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined >200 °C Flash point: Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 1455 kg/m3 Bulk density: Not determined Solubility(ies): Organic solvents Water solubility: Insoluble Not determined Partition coefficient (n-octanol/water): Auto-ignition temperature: Not determined

Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined





Page 8 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Water

Moisture

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

4W-Window- and Facade Sealant grey 290 ml								
Art.: 9097281								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral						n.d.a.		
route:								
Acute toxicity, by						n.d.a.		
dermal route:								
Acute toxicity, by						n.d.a.		
inhalation:								
Skin corrosion/irritation:						n.d.a.		
Serious eye						n.d.a.		
damage/irritation:								
Respiratory or skin						n.d.a.		
sensitisation:								
Germ cell mutagenicity:						n.d.a.		
Carcinogenicity:						n.d.a.		
Reproductive toxicity:						n.d.a.		
Specific target organ						n.d.a.		
toxicity - single								
exposure (STOT-SE):								





Page 9 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Specific target organ toxicity - repeated exposure (STOT-RE):			n.d.a.
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

μm) Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
2011010, 7 011000	nt	, 44244		019	1000 111001100	11000
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 425 (Acute	
route:					Oral Toxicity -	
					Up-and-Down	
					Procedure)	
Acute toxicity, by	LD50	>5000	mg/kg	Rabbit	,	
dermal route:						
Acute toxicity, by	LD50	>6,8	mg/l/4h	Rat		
inhalation:						
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Mechanical
					Irritation/Corrosio	irritation
					n)	possible.
Respiratory or skin				Mouse	OECD 429 (Skin	Not
sensitisation:					Sensitisation -	sensitizising
					Local Lymph	"""
					Node Assay)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Mouse	OECD 474	Negative
com con management,				1110000	(Mammalian	1 (oguil / o
					Erythrocyte	
					Micronucleus	
					Test)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
Germ cen matagementy.				typhimuri	(7 mes Test)	riogative
				um		
Germ cell mutagenicity:				A111	OECD 473 (In	Negative
commonly.					Vitro Mammalian	110541110
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In	Negative
common managementy.					Vitro Mammalian	110541110
					Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 471	Negative
Germ cen mutagementy.					(Bacterial Reverse	ricgative
					· `	
					Mutation Test)	





Page 10 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Reproductive toxicity				Rat	OECD 414	No
(Developmental					(Prenatal	indications
toxicity):					Developmental	of such an
					Toxicity Study)	effect.
Specific target organ						Not irritant
toxicity - single						(respiratory
exposure (STOT-SE):						tract).
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/	Rat		90d
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		90d

Calcium carbonate						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 420 (Acute	
route:					Oral toxicity -	
					Fixe Dose	
					Procedure)	
Acute toxicity, by	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation -	contact)
					Local Lymph	
					Node Assay)	
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	





Page 11 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):					•	No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard: Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

4W-Window- and 1 Art.: 9097281	Facade Sealar	nt grey 2	90 ml		·		
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes





Page 12 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

12.1. Toxicity to		n.d.a.
		II.u.a.
fish:		
12.1. Toxicity to		n.d.a.
daphnia:		
12.1. Toxicity to		n.d.a.
algae:		
12.2. Persistence		n.d.a.
and degradability:		
12.3.		n.d.a.
Bioaccumulative		
potential:		
12.4. Mobility in		n.d.a.
soil:		
12.5. Results of		n.d.a.
PBT and vPvB		
assessment		
12.6. Other		n.d.a.
adverse effects:		

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10									
μm)									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203			
fish:					mykiss	(Fish, Acute			
						Toxicity Test)			
12.1. Toxicity to	LC50	48h	>100	mg/l	Daphnia	OECD 202			
daphnia:					magna	(Daphnia sp.			
						Acute			
						Immobilisatio			
						n Test)			
12.1. Toxicity to	EC50	72h	16	mg/l	Pseudokirchne	U.S. EPA-			
algae:					riella	600/9-78-018			
10.0 D : 4					subcapitata		NT (1)		
12.2. Persistence							Not relevant		
and degradability:							for inorganic substances.		
12.3.	BCF	42d	9.6				Not to be		
Bioaccumulative	BCI	42u	9,0				expected		
potential:							cxpected		
12.3.	BCF	14d	19-				Oncorhynchu		
Bioaccumulative		1.0	352				s mykiss		
potential:							<i>j</i>		
12.4. Mobility in							Negative		
soil:									
12.5. Results of							No PBT		
PBT and vPvB							substance,		
assessment							No vPvB		
							substance		
Toxicity to			>5000	mg/l	Escherichia				
bacteria:					coli				





Page 13 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Toxicity to	LC0	24h	>1000	mg/l	Pseudomonas	
bacteria:			0		fluorescens	
Toxicity to	NOEC/NO		>1000	mg/kg	Eisenia	
annelids:	EL				foetida	
Water solubility:						Insoluble20°
						C

Calcium carbonate									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.		
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	No observation with saturated solution of test material.		
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)			
12.1. Toxicity to algae:	NOEC/NO EL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)			
12.2. Persistence and degradability:							Not relevant for inorganic substances.		
12.3. Bioaccumulative potential:							Not to be expected		
12.4. Mobility in soil:							n.a.		
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance		





Page 14 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Toxicity to	EC50	3h	>1000	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Toxicity to	NOEC/NO	3h	1000	mg/l	activated	OECD 209	
bacteria:	EL	311	1000	1115/1	sludge	(Activated	
bacteria.					studge	Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Glycine max
				dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Lycopersicon
				dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Avena sativa
				dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Glycine max
o unor organisms.	EL		1000	dw		(Terrestrial	
				G 1,1		Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Lycopersicon
Other organisms.	EL	210	1000	dw		(Terrestrial	esculentum
	LL			uw		Plants,	esculentum
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	ma/1-~		OECD 208	Ayono satires
Other organisms:		21 u	1000	mg/kg			Avena sativa
	EL			dw		(Terrestrial	
						Plants,	
	PG50	111	1000	M	T: :	Growth Test)	
Other organisms:	EC50	14d	>1000	mg/kg	Eisenia	OECD 207	
				dw	foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	





Page 15 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Other organisms:	NOEC/NO	14d	1000	mg/kg	Eisenia	OECD 207	
8	EL			dw	foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	
Other organisms:	EC50	28d	>1000	mg/kg		OECD 216	
				dw		(Soil	
						Microorganis	
						ms - Nitrogen	
						Transformatio	
						n Test)	
Other organisms:	NOEC/NO	28d	1000	mg/kg		OECD 216	
	EL			dw		(Soil	
						Microorganis	
						ms - Nitrogen	
						Transformatio	
						n Test)	
Water solubility:			0,016	g/l		OECD 105	20°C
			6			(Water	
						Solubility)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

SECTION 14: Transport information

General statements

14.1. UN number:

n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:





Page 16 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LO:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 1,4434 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: n.a.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H351 Suspected of causing cancer by inhalation.

Carc. — Carcinogenicity



(GB

Page 17 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European

Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and

Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European CommunityECHA European Chemicals AgencyEEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable





Page 18 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.10.2020 / 0001

Replacing version dated / version: 22.10.2020 / 0001

Valid from: 22.10.2020 PDF print date: 22.10.2020

4W-Window- and Facade Sealant grey 290 ml

Art.: 9097281

n.av. not availablen.c. not checkedn.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.