



Page 1 of 37
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 09.05.2022 / 0001
Replacing version dated / version: 09.05.2022 / 0001
Valid from: 09.05.2022
PDF print date: 09.05.2022
Montagefix Construction 800 ml
Art.: 9101828

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Montagefix Construction 800 ml
Art.: 9101828

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG
Salzstr. 51
74653 Ingelfingen
Tel.: +49 7940 141 141
Fax: +49 7940 141 9141
Email: info@bti.de
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)
+1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens.	1	H317-May cause an allergic skin reaction.
Repr.	Lact.	H362-May cause harm to breast-fed children.
Carc.	2	H351-Suspected of causing cancer.
Aquatic Chronic	4	H413-May cause long lasting harmful effects to aquatic life.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H362-May cause harm to breast-fed children. H351-Suspected of causing cancer. H413-May cause long lasting harmful effects to aquatic life. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P263-Avoid contact during pregnancy and while nursing. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH204-Contains isocyanates. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

As from 24 August 2023 adequate training is required before industrial or professional use.

Alkanes, C14-17, chloro

Diphenylmethanediisocyanate, isomeres and homologues

2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 3 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	9016-87-9
content %	25-<75
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 % ATE (as inhalation): 1,5 mg/l/4h

Reaction products of phosphoryl trichloride and 2-methyloxirane	
Registration number (REACH)	01-2119486772-26-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	807-935-0
CAS	1244733-77-4
content %	<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302

Dimethyl ether	
	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119472128-37-XXXX
Index	603-019-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-065-8
CAS	115-10-6
content %	<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Gas 1A, H220

Alkanes, C14-17, chloro	
	PBT-substance
	vPvB-substance
	SVHC-substance
Registration number (REACH)	01-2119519269-33-XXXX



Page 4 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Index	602-095-00-X
EINECS, ELINCS, NLP, REACH-IT List-No.	287-477-0
CAS	85535-85-9
content %	0,3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Repr. Lact., H362 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)

Polyether polyol, halogenated	
Registration number (REACH)	01-2119972940-30-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	617-903-6
CAS	86675-46-9
content %	<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302

2,2'-Dimorpholinyl diethyl ether	
Registration number (REACH)	01-2119969278-20-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	229-194-7
CAS	6425-39-4
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Irrit. 2, H319

Octamethylcyclotetrasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119529238-36-XXXX
Index	014-018-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	209-136-7
CAS	556-67-2
content %	<0,025
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Medical supervision necessary due to possibility of delayed reaction.

First-aiders should ensure they are protected!



Page 5 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Coughing

Irritation of the respiratory tract

Irritant to mucosa of the nose and throat

Respiratory distress

Oedema of the lungs

Dizziness

Headaches

Drying of the skin.

Dermatitis (skin inflammation)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Hydrocyanic acid (hydrogen cyanide)

Oxides of carbon

Oxides of nitrogen

Isocyanates

Hydrogen chloride

Oxides of phosphorus

Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters



Page 6 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

Recommended cleaner:

Acetone

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Take precautions against electrostatic charges.

Avoid contact with eyes or skin.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.



Page 7 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well-ventilated place.

Store cool.






Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

	Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues	
	WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as -NCO))	---
	Monitoring procedures: ---		
	BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))	
	Chemical Name	Dimethyl ether	
	WEL-TWA: 400 ppm (766 mg/m ³) (WEL), 1000 ppm (1920 mg/m ³) (EU)	WEL-STEL: 500 ppm (958 mg/m ³) (WEL)	---
	Monitoring procedures: - Compur - KITA-123 S (549 129)		
	BMGV: ---	Other information: ---	
	Chemical Name	Butane	
	WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
	Monitoring procedures: - Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993		
	BMGV: ---	Other information: ---	
	Chemical Name	Propane	
	WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures: - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990		
	BMGV: ---	Other information: ---	
	Chemical Name	Isobutane	
	WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures: - Compur - KITA-113 SB(C) (549 368)		
	BMGV: ---	Other information: ---	

Reaction products of phosphoryl trichloride and 2-methyloxirane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sediment, marine		PNEC	1,15	mg/kg dw	
	Environment - freshwater		PNEC	0,32	mg/l	
	Environment - soil		PNEC	0,34	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,1	mg/l	
	Environment - marine		PNEC	0,032	mg/l	
	Environment - sediment, freshwater		PNEC	11,5	mg/kg dw	
	Environment - oral (animal feed)		PNEC	11,6	g/kg feed	
Consumer	Human - oral	Short term, systemic effects	DNEL	2	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,45	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	5,6	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,04	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,52	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,91	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	22,6	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,2	mg/m3	

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	
	Environment - sewage treatment plant		PNEC	160	mg/l	
	Environment - marine		PNEC	0,016	mg/l	



Page 9 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	
	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m ³	

Alkanes, C14-17, chloro						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	11,9	mg/kg dw	
	Environment - sediment, freshwater		PNEC	13	mg/kg dw	
	Environment - sediment, marine		PNEC	2,6	mg/kg dw	
	Environment - freshwater		PNEC	1	µg/l	
	Environment - marine		PNEC	0,2	µg/l	
	Environment - sewage treatment plant		PNEC	80	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	28,72	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,58	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,7	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	47,9	mg/kg bw/day	

Polyether polyol, halogenated						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	37,5	mg/kg	



Page 10 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

	Environment - sediment, marine		PNEC	3,75	mg/kg	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	6,92	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	4,5	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	1,3	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,5	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,44	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,87	mg/kg	

2,2'-Dimorpholinyl diethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	8,2	mg/kg	
	Environment - sediment, marine		PNEC	0,82	mg/kg	
	Environment - soil		PNEC	1,58	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,8	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	7,28	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/d	

Octamethylcyclotetrasiloxane



Page 11 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,44	µg/l	
	Environment - marine		PNEC	0,044	µg/l	
	Environment - sediment, freshwater		PNEC	0,59	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,059	mg/kg dry weight	
	Environment - soil		PNEC	0,15	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	41	mg/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,7	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	73	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	73	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	73	mg/m ³	



WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).

(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value,



Page 12 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14)

= The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective gloves in butyl rubber (EN ISO 374).

Protective gloves made of fluorocarbon rubber (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:



Page 13 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid. 23°C
Colour:	Yellow
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.a.
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	There is no information available on this parameter.
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,2 g/ml (Active substance)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity



Page 14 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Polymerisation possible with:

Amines

Alcohols

Bases

Acids

Water

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Montagefix Construction 800 ml Art.: 9101828						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	2,5-<5				calculated value
Acute toxicity, by inhalation:	ATE	18,34-36,7				calculated value
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.



Page 15 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Expert judgement.
Acute toxicity, by inhalation:	LC50	0,31-0,49	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Respiratory or skin sensitisation:				Rat		Yes (inhalation)
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Negative

Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Limited evidence of a carcinogenic effect.
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, May cause respiratory irritation.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system
Symptoms:						breathing difficulties
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	1	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,2	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion

Reaction products of phosphoryl trichloride and 2-methyloxirane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>500-2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>7	mg/l	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing

®

Page 17 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 472 (Genetic Toxicology - Escherichia coli, Reverse Assay)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	500	mg/kg bw/d	Rabbit	OECD 414 (Prenatal Developmental Toxicity Study)	
Reproductive toxicity (Effects on fertility):	NOAEL	85	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Symptoms:						ataxia, cramps

Dimethyl ether						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

®

Page 18 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophila melanogaster)	Negative
Carcinogenicity:	NOAEC	47000	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No
Symptoms:						unconsciousness, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestinal disturbances, respiratory distress, circulatory collapse

Alkanes, C14-17, chloro						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:	LD50	4000	mg/kg	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant



Page 19 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:					(Ames-Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	500	mg/kg bw/d		OECD 414 (Prenatal Developmental Toxicity Study)	Positive, Analogous conclusion

Polyether polyol, halogenated

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	917	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Reproductive toxicity:	NOAEL	940	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	

2,2'-Dimorpholinyl diethyl ether

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2025	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3038	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	3038	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising



Page 20 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Effects on fertility):	NOAEL	300	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	Negative
Symptoms:						watering eyes, eyes, reddened

Octamethylcyclotetrasiloxane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>4800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Male
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	36	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rat	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:						Negative
Reproductive toxicity:						Repr. 2
Symptoms:						mucous membrane irritation

Butane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		



Page 21 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion

®

Page 22 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	

Isobutane



Page 23 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	

11.2. Information on other hazards

Montagefix Construction 800 ml Art.: 9101828						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).



Page 24 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Montagefix Construction 800 ml							
Art.: 9101828							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(comp lexing organic substance)>= 80%/28d: n.a.
Other information:	AOX		22	%			Contains organically bound halogens, which may contribute to the AOX value in wastewater.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 25 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	
12.1. Toxicity to fish:	LC0	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, According to experience available to date, polycarbamide is inert and non-degradable., With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide).



Page 26 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus carpio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.5. Results of PBT and vPvB assessment							No vPvB substance, No PBT substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	
Toxicity to annelids:	NOEC/NOEL	14d	>1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	

Reaction products of phosphoryl trichloride and 2-methyloxirane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,68				
12.1. Toxicity to fish:	LC50	96h	51	mg/l	Pimephales promelas		
12.2. Persistence and degradability:		>60d	95	%		OECD 302 A (Inherent Biodegradability - Modified SCAS Test)	Not readily but inherent biodegradable.
12.3. Bioaccumulative potential:	BCF		0,8-1,4				
Toxicity to bacteria:	EC50	3h	784	mg/l			
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	32	mg/l	Daphnia magna		
12.1. Toxicity to algae:	NOEC/NOEL	72h	13	mg/l	Pseudokirchneriella subcapitata		



Page 27 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

12.1. Toxicity to daphnia:	EC50	13d	32	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	82	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	14	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Not readily biodegradable

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	Poecilia reticulata		
12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m ³ /mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	Pseudomonas putida		



Page 28 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.DIN EN 1485
Water solubility:			45,60	mg/l			25°C

Alkanes, C14-17, chloro

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>5000	mg/l	Alburnus alburnus		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,01	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:							Hardly biodegradable
12.4. Mobility in soil:							Adsorption in ground., Sediment
12.5. Results of PBT and vPvB assessment							PBT-substance, vPvB-substance
Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge		

Polyether polyol, halogenated

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Poecilia reticulata	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	



Page 29 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

12.1. Toxicity to algae:	NOEC/NOEL	72h	500	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.2. Persistence and degradability:		28d	10	%			Not readily biodegradable

2,2'-Dimorpholinyl diethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	100	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	>2150	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	4	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable



Page 30 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

12.3. Bioaccumulative potential:	Log Pow		0,5			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	
12.3. Bioaccumulative potential:	BCF	56d	3				
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Octamethylcyclotetrasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	BCF	28d	12400		Pimephales promelas		
12.1. Toxicity to fish:	NOEC/NOEL	14d	0,0068	mg/l			
12.1. Toxicity to fish:	LC50	96h	>500	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,0079	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC10	96h	0,022	mg/l			
12.2. Persistence and degradability:			3,7	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	29d
12.3. Bioaccumulative potential:	Log Pow		5,1				
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge		

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 31 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable



Page 32 of 37
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.05.2022 / 0001
 Replacing version dated / version: 09.05.2022 / 0001
 Valid from: 09.05.2022
 PDF print date: 09.05.2022
 Montagefix Construction 800 ml
 Art.: 9101828

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

08 05 01 waste isocyanates

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 04 metallic packaging

SECTION 14: Transport information


General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



Page 33 of 37
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.05.2022 / 0001
 Replacing version dated / version: 09.05.2022 / 0001
 Valid from: 09.05.2022
 PDF print date: 09.05.2022
 Montagefix Construction 800 ml
 Art.: 9101828

Transport by air (IATA)

14.2. UN proper shipping name:
 Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC!)
 Regulation (EC) No 1907/2006, Annex XVII
 Diphenylmethanediisocyanate, isomeres and homologues
 Octamethylcyclotetrasiloxane
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC!)
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements



Page 34 of 37
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.05.2022 / 0001
 Replacing version dated / version: 09.05.2022 / 0001
 Valid from: 09.05.2022
 PDF print date: 09.05.2022
 Montagefix Construction 800 ml
 Art.: 9101828

18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200
----	--	----	----	-----

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 174 g/l

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: n.a.
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Repr. Lact., H362	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aquatic Chronic 4, H413	Classification based on test data.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361f Suspected of damaging fertility.
 H373 May cause damage to organs through prolonged or repeated exposure by inhalation.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.



Page 35 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H220 Extremely flammable gas.

EUH066 Repeated exposure may cause skin dryness or cracking.

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Repr. — Reproductive toxicity

Carc. — Carcinogenicity

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

STOT RE — Specific target organ toxicity - repeated exposure

Acute Tox. — Acute toxicity - oral

Flam. Gas — Flammable gases - Flammable gas

Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate



Page 36 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available



Page 37 of 37

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.05.2022 / 0001

Replacing version dated / version: 09.05.2022 / 0001

Valid from: 09.05.2022

PDF print date: 09.05.2022

Montagefix Construction 800 ml

Art.: 9101828

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.