

Page 1 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Acrylic Sealant Plus grey 310 ml Art.: 9075874 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Seam sealant Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC) +1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

EUH208-Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

- n.a.
- 3.2 Mixtures

Titanium dioxide (in powder form containing 1 % or	
more of particles with aerodynamic diameter <= 10 μm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008	Carc. 2, H351 (as inhalation)
(CLP), M-factors	

1,2-benzisothiazol-3(2H)-one	
Registration number (REACH)	
Index	613-088-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	220-120-9
CAS	2634-33-5
content %	0,005-<0,05
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP), M-factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Skin Sens. 1, H317
	Aquatic Acute 1, H400 (M=10)
Specific Concentration Limits and ATE	Skin Sens. 1, H317: >=0,05 %

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one	
and 2-methyl-2H-isothiazol-3-one (3:1)	
Registration number (REACH)	
Index	613-167-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	55965-84-9
content %	0,00015-<0,0015



Page 3 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Classification according to Regulation (EC) 1272/2008	EUH071
(CLP), M-factors	Acute Tox. 2, H310
	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Skin Corr. 1C, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 1, H410 (M=100)
Specific Concentration Limits and ATE	Skin Corr. 1C, H314: >=0,6 %
	Skin Irrit. 2, H315: >=0,06 %
	Eye Dam. 1, H318: >=0,6 %
	Eye Irrit. 2, H319: >=0,06 %
	Skin Sens. 1A, H317: >=0,0015 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person! Inhalation Remove person from danger area. Supply person with fresh air and consult doctor according to symptoms. Skin contact Wipe off residual product carefully with a soft, dry cloth. Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor. Eve contact Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Ingestion Rinse the mouth thoroughly with water. Do not induce vomiting - give copious water to drink. Consult doctor immediately. 4.2 Most important symptoms and effects, both acute and delayed If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Water jet spray/foam/CO2/dry extinguisher



Page 4 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Unsuitable extinguishing media

High volume water jet **5.2 Special hazards arising from the substance or mixture**In case of fire the following can develop:
Oxides of carbon
Toxic gases **5.3 Advice for firefighters**For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Or:

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.



Page 5 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed. **7.2 Conditions for safe storage, including any incompatibilities**Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Store at room temperature.
Protect from frost. **7.3 Specific end use(s)**No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB Chemical Name	Name Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu$ m)				f	Content %:0,1-<1
WEL-TWA: 10 mg/m3 (to		WEL-STEL:		- 10 μm)		70.0,1-<1
		WEL-SIEL.				
dust), 4 mg/m3 (respirable du	ist)					
Monitoring procedures:	-					
BMGV:				Other information		
Chemical Name	Diisononyl ph	thalate				Content %:
WEL-TWA: 5 mg/m3		WEL-STEL:				
Monitoring procedures:	-					
BMGV:				Other information	:	

Titanium dioxide (in p	owder form containing	1 % or more of par	ticles with a	aerodyna	mic diame	eter <= 10
μ m)						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,184	mg/l	
	freshwater					
	Environment - marine		PNEC	0,018	mg/l	
				4		
	Environment - water,		PNEC	0,193	mg/l	
	sporadic					
	(intermittent) release					
	Environment -		PNEC	100	mg/l	
	sewage treatment					
	plant					
	Environment -		PNEC	1000	mg/kg	
	sediment, freshwater				dw	
	Environment -		PNEC	100	mg/kg	
	sediment, marine				dw	
	Environment - soil		PNEC	100	mg/kg	
					dw	
	Environment - oral		PNEC	1667	mg/kg	
	(animal feed)				feed	



Page 6 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Area of application	lloro-2-methyl-2H-isothia Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - freshwater		PNEC	0,003 39	mg/l	
	Environment - marine		PNEC	0,003 39	mg/l	
	Environment - sediment, freshwater		PNEC	0,027	mg/kg dw	
	Environment - sediment, marine		PNEC	0,027	mg/kg dw	
	Environment - soil		PNEC	0,01	mg/kg dw	
	Environment - sewage treatment plant		PNEC	0,23	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,003 39	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,02	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,04	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,09	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,02	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,04	mg/m3	

Diisononyl phthalate						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral		PNEC	150	mg/kg	
	(animal feed)					
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	



Page 7 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m3	

Dolomite						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
Workers / employees	Human - inhalation	Long term,	DNEL	10	mg/m3	
		systemic effects				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include

metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:



Page 8 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

If there is a risk of contact with the eyes or while decanting: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective gloves made of natural rubber latex (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: >=0,4 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, solid.
Colour:	According to specification
Odour:	Characteristic
Melting point/freezing point:	0 °C



Page 9 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: 9.2 Other information Explosives: Oxidizing solids:

100 °C Not combustible. Does not apply to solids. There is no information available on this parameter. n.a. >21 mm2/s Mixable Does not apply to mixtures. There is no information available on this parameter. 1,71 g/ml Does not apply to solids.

There is no information available on this parameter. There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity
Not to be expected
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
See also section 7.
None known
10.5 Incompatible materials
See also section 7.
None known
10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Acrylic Sealant Plus grey 310 ml								
Art.: 9075874								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt			_				
Acute toxicity, by oral						n.d.a.		
route:								
Acute toxicity, by						n.d.a.		
dermal route:								



Page 10 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Acute toxicity, by			n.d.a.
inhalation:			
Skin corrosion/irritation:			n.d.a.
Serious eye			n.d.a.
damage/irritation:			
Respiratory or skin			n.d.a.
sensitisation:			
Germ cell mutagenicity:			n.d.a.
Carcinogenicity:			n.d.a.
Reproductive toxicity:			n.d.a.
Specific target organ			n.d.a.
toxicity - single			
exposure (STOT-SE):			
Specific target organ			n.d.a.
toxicity - repeated			
exposure (STOT-RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Titanium dioxide (in pov	wder form	containing	1 % or more	e of particles	with aerodynamic di	ameter <= 10
μm)						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative



Page 11 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Germ cell mutagenicity:				Mammalia	OECD 473 (In	Negative
				n	Vitro Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
				typhimuri		-
				um		
Germ cell mutagenicity:					OECD 476 (In	Negative
					Vitro Mammalian	-
					Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	-
					Mutation Test)	
Reproductive toxicity				Rat	OECD 414	No
(Developmental					(Prenatal	indications
toxicity):					Developmental	of such an
•					Toxicity Study)	effect.
Specific target organ						Not irritant
toxicity - single						(respiratory
exposure (STOT-SE):						tract).
Symptoms:						mucous
						membrane
						irritation,
						coughing,
						respiratory
						distress,
						drying of the
						skin.
Specific target organ	NOAEL	3500	mg/kg/	Rat		90d
toxicity - repeated			d			
exposure (STOT-RE),						
oral:						
Specific target organ	NOAEC	10	mg/m3	Rat		90d
toxicity - repeated						
exposure (STOT-RE),						
inhalat.:						

1,2-benzisothiazol-3(2H)-one								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral	LD50	375	mg/kg	Rat				
route:								
Acute toxicity, by	LD50	4115	mg/kg	Rat				
dermal route:								
Skin corrosion/irritation:						Skin Irrit. 2		
Serious eye						Eye Dam. 1		
damage/irritation:								
Respiratory or skin				Guinea pig		Yes (skin		
sensitisation:						contact)		
Germ cell mutagenicity:						Negative		



Page 12 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Symptoms:			vomiting, headaches, gastrointestin al
			disturbances,
			nausea

Reaction mass of 5-chlor	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)									
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes				
	nt									
Acute toxicity, by oral	LD50	53	mg/kg	Rat						
route:										
Acute toxicity, by	LD50	660	mg/kg	Rabbit						
dermal route:										
Skin corrosion/irritation:				Rabbit		Corrosive				
Serious eye				Rabbit		Corrosive				
damage/irritation:										
Respiratory or skin				Guinea pig	OECD 406 (Skin	Yes (skin				
sensitisation:					Sensitisation)	contact)				
Aspiration hazard:						No				
Symptoms:						diarrhoea,				
						mucous				
						membrane				
						irritation,				
						watering				
						eyes, eyes,				
						reddened				

Diisononyl phthalate									
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes			
	nt								
Acute toxicity, by oral	LD50	>10000	mg/kg	Rat	OECD 401 (Acute				
route:					Oral Toxicity)				
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit					
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant			
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant			
Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	No (skin contact)			
Germ cell mutagenicity:					(Ames-Test)	Negative			



Page 13 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Symptoms:			diarrhoea,
			nausea and
			vomiting.

11.2. Information on other hazards

Acrylic Sealant Plus grey 310 ml									
Art.: 9075874									
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes			
	nt								
Endocrine disrupting						Does not			
properties:						apply to			
						mixtures.			
Other information:						No other			
						relevant			
						information			
						available on			
						adverse			
						effects on			
						health.			

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Acrylic Sealant Plus grey 310 ml								
Art.: 9075874								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to							n.d.a.	
fish:								
12.1. Toxicity to							n.d.a.	
daphnia:								
12.1. Toxicity to							n.d.a.	
algae:								
12.2. Persistence							n.d.a.	
and degradability:								
12.3.							n.d.a.	
Bioaccumulative								
potential:								
12.4. Mobility in							n.d.a.	
soil:								
12.5. Results of							n.d.a.	
PBT and vPvB								
assessment								
12.6. Endocrine							Does not	
disrupting							apply to	
properties:							mixtures.	



Page 14 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

12.7. Other			No
adverse effects:			information
			available on
			other
			adverse
			effects on
			the
			environment.
Other information:			DOC-
			elimination
			degree(comp
			lexing
			organic
			substance)>=
			80%/28d:
			n.a.

	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)		
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)		
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchne riella subcapitata	U.S. EPA- 600/9-78-018		
12.2. Persistence and degradability:							Not relevant for inorganic substances.	
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected	
12.3. Bioaccumulative potential:	BCF	14d	19- 352				Oncorhynchu s mykiss	
12.4. Mobility in soil:							Negative	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance	
Toxicity to bacteria:			>5000	mg/l	Escherichia coli			
Toxicity to bacteria:	LC0	24h	>1000 0	mg/l	Pseudomonas fluorescens			



Page 15 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Toxicity to annelids:	NOEC/NO EL	>1000	mg/kg	Eisenia foetida	
Water solubility:					Insoluble20° C

1,2-benzisothiazol-	3(2H)-one						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	0,8-	mg/l	Oncorhynchus	OECD 203	
fish:			2,18		mykiss	(Fish, Acute	
	7.070	4.01				Toxicity Test)	
12.1. Toxicity to	EC50	48h	1,1-	mg/l	Daphnia	OECD 202	
daphnia:			4,4		magna	(Daphnia sp.	
						Acute Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	96h	0,055	mg/l	Pseudokirchne		
algae:	Leso	2011	0,055	1115/1	riella		
anguer					subcapitata		
12.1. Toxicity to	ErC50	72h	0,11	mg/l	Pseudokirchne	OECD 201	
algae:					riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
12.2. Persistence						OECD 303	Hardly
and degradability:						(Simulation	biodegradabl
						Test - Aerobic	e
						Sewage	
						Treatment)	
12.3.	Log Pow		1,11			Treatment)	A notable
Bioaccumulative							biological
potential:							accumulation
							potential is
							not to be
							expected
							(LogPow 1-
— • • •	EG50	1.0	0.1	/1			3).
Toxicity to	EC50	16h	0,4	mg/l	Pseudomonas		
bacteria:					putida		

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to	LC50	96h	0,28	mg/l	Lepomis			
fish:					macrochirus			
12.1. Toxicity to	LC50	96h	0,19-	mg/l	Oncorhynchus	OECD 203		
fish:			0,22		mykiss	(Fish, Acute		
						Toxicity Test)		
12.1. Toxicity to	NOEC/NO	28d	0,098	mg/l	Oncorhynchus	OECD 210		
fish:	EL				mykiss	(Fish, Early-		
						Life Stage		
						Toxicity Test)		



Page 16 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

12.1. Toxicity to daphnia:	NOEC/NO EL	21d	0,004	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,16	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	0,048	mg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NO EL	72h	0,001 2	mg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			>60	%	activated sludge	OECD 301 D (Ready Biodegradabil ity - Closed Bottle Test)	Does not conform with EU classification
12.3. Bioaccumulative potential:	BCF		3,6			· · · · · ·	calculated value
12.3. Bioaccumulative potential:	Log Pow		0,401- 0,486				Does not conform with EU classification
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	7,92	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Diisononyl phthalate								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to	LC50	96h	>102	mg/l	Brachydanio	92/69/EC		
fish:					rerio			
12.1. Toxicity to	EC50	48h	>=74	mg/l	Daphnia	84/449/EEC		
daphnia:				_	magna	C.2		



Page 17 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

10.1 Taniaitas ta	NOEC/NO	214	> 100		Daularia	OECD 202	
12.1. Toxicity to daphnia:	NOEC/NO EL	21d	>=100	mg/l	Daphnia magna	OECD 202 (Daphnia sp.	
uapinna.					magna	Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	72h	88	mg/l	Scenedesmus		
algae:	EL	/ 211		1115/1	subspicatus		
12.1. Toxicity to	EC50	72h	>88	mg/l	Scenedesmus	84/449/EEC	
algae:	2000	/	100	<u>B</u> , 1	subspicatus	C.3	
12.2. Persistence		28d	81	%	activated	Regulation	Readily
and degradability:					sludge	(EČ)	biodegradabl
					C	440/2008 C.4-	e
						C	
						(DETERMIN	
						ATION OF	
						'READY'	
						BIODEGRAD	
						ABILITY -	
						CO2	
						EVOLUTION	
10.2	T TZ		0.0			TEST)	A 1
12.3. Bioaccumulative	Log Kow		8,8-			OECD 117 Destition	Analogous conclusion
potential:			9,7			(Partition Coefficient (n-	conclusion
potentiai.						octanol/water)	
						- HPLC	
						method)	
12.3.	BCF	14d	<3				Analogous
Bioaccumulative							conclusion
potential:							
12.4. Mobility in	Koc		>5000				
soil:							
12.4. Mobility in	H (Henry)		0,000	atm*m			
soil: Toxicity to	EC50	30min	00149	3/mol	activated	OECD 209	
bacteria:	EC30	Somm	>85,9	mg/l	sludge	(Activated	
Dacterra.					sludge	Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Other organisms:	NOEC/NO	56d	>982,	mg/kg	Eisenia		
	EL		4		foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia	OECD 207	
					foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	



Page 18 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts EC disposal code no .: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. E.g. dispose at suitable refuse site. For contaminated packing material Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements								
14.1. UN number or ID number:	n.a.							
Transport by road/by rail (ADR/RID)								
14.2. UN proper shipping name:								
14.3. Transport hazard class(es):	n.a.							
14.4. Packing group:	n.a.							
Classification code:	n.a.							
LQ:	n.a.							
14.5. Environmental hazards:	Not applicable							
Tunnel restriction code:								
Transport by sea (IMDG-code)								
14.2. UN proper shipping name:								
14.3. Transport hazard class(es):	n.a.							
14.4. Packing group:	n.a.							
Marine Pollutant:	n.a							
14.5. Environmental hazards:	Not applicable							
Transport by air (IATA)								
14.2. UN proper shipping name:								
14.3. Transport hazard class(es):	n.a.							
14.4. Packing group:	n.a.							
14.5. Environmental hazards:	Not applicable							
14.6. Special precautions for user								
Unless specified otherwise, general measures for safe transport must be followed.								
14.7. Maritime transport in bulk according to IMO instruments								
Non-dangerous material according to Transport Regulations.								



Page 19 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label. Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012. Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.

These are indicated in the approval of the active substance.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1-16

0.99 %

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H351 Suspected of causing cancer by inhalation.

- H317 May cause an allergic skin reaction.
- H301 Toxic if swallowed.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Carc. — Carcinogenicity Acute Tox. — Acute toxicity - oral Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage Skin Sens. — Skin sensitization Aquatic Acute — Hazardous to the aquatic environment - acute Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation Skin Corr. — Skin corrosion Aquatic Chronic — Hazardous to the aquatic environment - chronic



œ

Page 20 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

- BSEF The International Bromine Council
- bw body weight
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
- CMR carcinogenic, mutagenic, reproductive toxic
- DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

- DOC Dissolved organic carbon
- dw dry weight
- e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
- EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
- EC European Community
- ECHA European Chemicals Agency
- ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

- EINECS European Inventory of Existing Commercial Chemical Substances
- ELINCS European List of Notified Chemical Substances



œ

Page 21 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

EN European Norms EPA United States Environmental Protection Agency (United States of America) ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive International Uniform Chemical Information Database IUCLID **IUPACInternational Union for Pure Applied Chemistry** LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LO Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic Polyethylene PE PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No REACH 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation RID

concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon



Page 22 of 22 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 23.03.2020 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 Acrylic Sealant Plus grey 310 ml Art.: 9075874

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.